



Microsemi Corp.

The diode experts

SCOTTSDALE, AZ
For more information call:
(602) 941-6300

**1N6267 thru
1N6303A
and 1.5KE6.8 thru
1.5KE400A**

FEATURES

- ECONOMICAL
- 1500 WATTS PEAK PULSE POWER DISSIPATION
- STAND OFF VOLTAGES FROM 5.5V - 171V
- UNIPOLAR OR BIPOLAR
- AVAILABLE IN CHIP FORM FOR HYBRID APPLICATION
- MULTI-CHIP BIDIRECTIONAL CELLS AVAILABLE

DESCRIPTION

This defines a series of silicon Transient Suppressors designed to protect voltage sensitive components from high energy voltage transients. TAZ devices have become very important as a consequence of their high surge capability, extremely fast response time, and low incremental surge resistance (R_s).

To characterize TAZ, a minimum voltage at low current conditions (V_{BR}), and a maximum clamping voltage (V_C), at a maximum peak pulse current are specified. In addition, a maximum clamping ratio is indicated. The maximum leakage current at the rated stand-off voltage is also provided to assure low power consumption under normal conditions.

APPLICATION

This TAZ series has a peak pulse power rating of 1500 watts for one millisecond. It can protect integrated circuits, hybrids, CMOS, MOS, and other voltage sensitive components in a broad range of applications such as telecommunications, power supplies, computers, automotive, and industrial equipment.

MAXIMUM RATINGS

1500 Watts of Peak Pulse Power Dissipation at 25°C.

$t_{clamping}$ (0 Volts to $V_{(BR)}$ Min.):

Unidirectional $< 1 \times 10^{-12}$ Seconds; Bidirectional $< 5 \times 10^{-9}$ Seconds.

Operating and Storage Temperature -65°C to +175°C.

Forward Surge Rating 200 Amps, 1/20 Second at 25°C.

Steady State Power Dissipation 5.0 W @ $T_1 = 75^\circ\text{C}$.

(Not Applicable in Chip Form).

ELECTRICAL CHARACTERISTICS


Clamping Factor: 1.33 @ full rated power

1.20 @ 50% rated power

The Clamping Factor is defined as: The ratio of the actual V_C (Clamping Voltage) to the actual $V_{(BR)}$ (Breakdown Voltage) as measured on a specific device.

**TRANSIENT
ABSORPTION ZENER**

**UNIDIRECTIONAL
AND
BIDIRECTIONAL**



All dimensions in INCH
m. m.

MECHANICAL CHARACTERISTICS

CASE: Molded

WEIGHT: 1.5 Grams (Approx.)

POLARITY: Positive Terminal
Marked with Band

1N6267 thru 1N6303A and 1.5KE6.8 thru 1.5KE400A

ELECTRICAL CHARACTERISTICS @ 25°C

Industry Type Number	JEDC Type Number	Rated Stand-off Voltage V_{WM} VOLTS	Breakdown Voltage V_{BR} VOLTS	Maximum Clamping Voltage V_C VOLTS	Maximum Reverse Leakage I_R μA	Maximum Peak Pulse Current I_{PP} A	Maximum Temperature Coefficient α_V %/°C
1.5KE6.8	1N5908	5.0	6.0	10	7.6	300	.057
1.5KE6.8A	1N6267	5.0	6.12	7.48	10.8	1000	.057
1.5KE7.5	1N6268	5.80	6.45	7.14	10	1000	.057
1.5KE7.5A	1N6269	6.05	6.75	8.25	10	1100	.057
1.5KE8.0	1N6270	6.45	7.13	7.88	10	1100	.061
1.5KE8.0A	1N6271	6.63	7.36	9.02	10	1200	.065
1.5KE8.5	1N6272	7.02	7.79	8.61	10	1200	.065
1.5KE9.1	1N6273	7.37	8.19	10.00	10	1300	.068
1.5KE9.1A	1N6274	7.76	8.55	10.50	10	1400	.068
1.5KE10	1N6275	8.10	9.00	11.00	10	1500	.073
1.5KE10A	1N6276	8.55	9.50	10.50	10	1600	.073
1.5KE11	1N6277	8.92	9.90	12.10	10	1600	.075
1.5KE11A	1N6278	9.40	10.50	11.60	10	1700	.075
1.5KE12	1N6279	9.72	10.80	13.70	10	17.3	.078
1.5KE12A	1N6280	10.20	11.40	12.60	10	18.7	.078
1.5KE13	1N6281	10.50	11.70	14.30	10	19.0	.081
1.5KE13A	1N6282	11.10	12.40	14.70	10	20.2	.081
1.5KE15	1N6275	12.10	13.50	16.50	10	22.0	.084
1.5KE15A	1N6276	12.80	14.30	15.80	10	21.2	.084
1.5KE16	1N6276	12.90	14.40	17.60	10	23.5	.086
1.5KE16A	1N6276A	13.60	15.20	16.80	10	22.5	.086
1.5KE18	1N6277	14.50	16.20	19.80	10	26.5	.088
1.5KE18A	1N6277A	15.30	17.10	18.90	10	25.2	.088
1.5KE20	1N6278	16.20	18.00	22.00	10	31.5	.090
1.5KE20A	1N6278A	17.10	19.00	21.00	10	27.7	.090
1.5KE22	1N6279	17.80	19.80	24.20	10	31.9	.092
1.5KE22A	1N6279A	18.80	20.90	23.10	10	30.6	.092
1.5KE24	1N6280	19.40	21.60	26.40	10	34.7	.094
1.5KE24A	1N6280A	20.50	22.80	25.20	10	33.2	.094
1.5KE27	1N6281	21.80	24.30	29.70	10	39.1	.096
1.5KE27A	1N6281A	23.10	25.70	28.40	10	37.5	.096
1.5KE30	1N6282	24.30	27.00	33.00	10	43.5	.097
1.5KE30A	1N6282A	25.60	28.50	31.50	10	41.4	.097
1.5KE33	1N6283	26.80	29.70	36.30	10	47.7	.098
1.5KE33A	1N6283A	28.20	31.40	34.70	10	45.7	.098
1.5KE36	1N6284	29.10	32.40	39.60	10	52.0	.099
1.5KE36A	1N6284A	30.80	34.20	37.80	10	49.9	.099
1.5KE39	1N6285	31.60	35.10	42.90	10	58.4	.100
1.5KE39A	1N6285A	33.30	37.10	41.00	10	53.9	.100
1.5KE43	1N6286	34.80	38.70	47.30	10	61.9	.101
1.5KE43A	1N6286A	36.80	40.90	45.00	10	59.3	.101
1.5KE47	1N6287	38.10	42.30	51.70	10	67.8	.101
1.5KE47A	1N6287A	40.20	44.70	49.40	10	64.8	.102
1.5KE51	1N6288	41.30	45.90	56.10	10	73.5	.102
1.5KE51A	1N6288A	43.60	48.50	53.60	10	70.1	.102
1.5KE56	1N6289	45.80	50.40	61.40	10	80.5	.103
1.5KE56A	1N6289A	47.80	53.20	58.80	10	77.0	.103
1.5KE62	1N6290	50.70	55.80	68.20	10	89.0	.104
1.5KE62A	1N6290A	53.00	58.90	65.10	10	85.0	.104
1.5KE66	1N6291	55.10	61.20	74.80	10	98.0	.104
1.5KE66A	1N6291A	58.10	64.60	71.40	10	92.0	.104
1.5KE75	1N6292	60.70	67.50	82.50	10	108.0	.105
1.5KE75A	1N6292A	64.10	71.30	78.00	10	103.0	.105
1.5KE80	1N6293	66.40	73.80	90.20	10	118.0	.105
1.5KE80A	1N6293A	70.10	77.90	86.10	10	113.0	.105
1.5KE91	1N6294	73.70	81.90	100.00	10	131.0	.106
1.5KE91A	1N6294A	77.80	86.50	116.00	10	125.0	.106
1.5KE100	1N6295	81.00	90.00	110.00	10	144.0	.106
1.5KE100A	1N6295A	85.50	95.00	105.00	10	137.0	.106
1.5KE110	1N6296	89.20	99.00	121.00	10	158.0	.107
1.5KE110A	1N6296A	94.00	105.00	116.00	10	152.0	.107
1.5KE120	1N6297	97.20	108.00	132.00	10	173.0	.107
1.5KE120A	1N6297A	102.00	114.00	126.00	10	165.0	.107
1.5KE130	1N6298	105.00	117.00	143.00	10	187.0	.107
1.5KE130A	1N6298A	111.00	124.00	137.00	10	179.0	.107
1.5KE150	1N6299	121.00	135.00	165.00	10	215.0	.108
1.5KE150A	1N6299A	128.00	143.00	158.00	10	207.0	.108
1.5KE160	1N6300	131.00	148.00	176.00	10	230.0	.108
1.5KE160A	1N6300A	136.00	152.00	168.00	10	219.0	.108
1.5KE170	1N6301	138.00	153.00	187.00	10	244.0	.108
1.5KE170A	1N6301A	145.00	162.00	179.00	10	234.0	.108
1.5KE180	1N6302	146.00	162.00	198.00	10	258.0	.108
1.5KE180A	1N6302A	154.00	171.00	189.00	10	246.0	.108
1.5KE200	1N6303	162.00	180.00	220.00	10	287.0	.108
1.5KE200A	1N6303A	171.00	190.00	210.00	10	274.0	.108
1.5KE220	175.00	198.00	242.00	344.0	5	4.3	0.110
1.5KE220A	185.00	209.00	231.00	328.0	5	4.6	0.110
1.5KE250	202.00	225.00	275.00	360.0	5	5.0	0.110
1.5KE250A	214.00	237.00	263.00	344.0	5	5.0	0.110
1.5KE300	243.00	270.00	330.00	430.0	5	5.0	0.111
1.5KE300A	256.00	285.00	315.00	414.0	5	5.0	0.111
1.5KE350	284.00	315.00	385.00	504.0	5	4.0	0.111
1.5KE350A	300.00	332.00	368.00	482.0	5	4.0	0.111
1.5KE400	324.00	360.00	440.00	574.0	5	4.0	0.111
1.5KE400A	342.00	380.00	420.00	548.0	5	4.0	0.111

V_F at 100 amps peak, 8.3 ms sine wave equals 3.5 volts max. (unidirectional only). For Bidirectional part number add C or CA as suffix (e.g., 1.5KE33C or 1.5KE33CA). For Bidirectional types having V_{WM} of 8 volts and under, the I_D leakage current is doubled. 1N62XX or 1N5908 not available as bidirectional. For bipolar capacitance will be .5 that shown in Fig. 2 for zero bias.

SYMBOLS AND ABBREVIATIONS

V_{WM} = Rated Stand-off Voltage	V_{BR} = Breakdown Voltage
I_{PP} = Peak Pulse Current	t_T = Test Current
P_{PP} = Peak Pulse Power	I_D = Reverse Leakage
$V_C(MAX)$ = Maximum Clamping Voltage	

NOTE 1: Normal selection criteria for TAZ devices is by rated stand-off voltage (V_{WM}) and should be equal or greater than DC or continuous peak operating voltage.
NOTE 2: TAZ devices are tested to maximum peak pulse current (I_{PP}) with clamping voltage monitored. This surge capability is one of the most significant electrical characteristics of the device and should be considered as part of customer quality inspections.





FIGURE 1
PEAK PULSE POWER VS. PULSE TIME (T_w) IN μs



BV: Breakdown Voltage in Volts

FIGURE 2
TYPICAL CAPACITANCE VS. BREAKDOWN VOLTAGE




FIGURE 3 PULSE WAVE FORM




FIGURE 4 DERATING CURVE



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.