

DB2F43100L

For rectification

Features

- Low forward voltage VF
- Forward current (Average) IF(AV) ≤ 5.0 A rectification is possible
- RoHS compliant
- (EU RoHS / MSL:Level 1 compliant)

Marking Symbol: E6



Packaging

Embossed type (Thermo-compression sealing) : 10 000 pcs / reel (standard)

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Reverse Voltage ^{*1}	VR	-	40	V
Maximum Peak Reverse Voltage ^{*1}	VRM	-	40	V
Average Forward Current ^{*2,3}	IF(AV)	-	5.0	A
Non-repetitive Peak Surge Forward Current ^{*1,4}	IFSM	-	40	A
Operating Junction Temperature ^{*5}	Tj	-	150	°C
Ambient Temperature	Ta	-40	+150	°C
Storage Temperature	Tstg	-55	+150	°C

- Note) *1: Ta = Tj = 25°C
*2: Square wave : σ = 0.5
*3: Solder Point Temperature : Tsp ≤ 122°C
*4: Square wave : Tp = 5 ms
*5: Power derating is necessary so that Tj < 150°C.




Electrical Characteristics Ta = 25 °C ± 3 °C


Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward Voltage	VF	IF = 5.0 A	-	0.51	0.6	V
Reverse Current	IR	VR = 40 V	-	15	100	μA
Terminal Capacitance	Ct	VR = 10 V, f = 1 MHz	-	140	-	pF
Reverse Recovery Time ^{*1}	trr	IF = IR = 100 mA, Irr = 10 mA	-	45	-	ns

- Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7031 measuring methods for diodes.
2. This product is sensitive to electric shock (static electricity, etc.).
Due attention must be paid on the charge of a human body and the leakage of current from the operating equipment.
3. *1: Measurement circuit, input pulse, output pulse for Reverse recovery time


(Measurement circuit)



(Input pulse)




(Output pulse)






Electrical Characteristics Technical Data (Reference)


IF - VF / Typical Data



Ct - VR / Typical Data



IR - VR / Typical Data




(Graph legends)

(1)	Ta = 150 °C
(2)	Ta = 125 °C
(3)	Ta = 85 °C
(4)	Ta = 25 °C
(5)	Ta = -40 °C




Electrical Characteristics Technical Data (Reference)

PF(AV) - IF(AV) / Typical Data




(Waveform definition)




Duty Cycle : $\sigma = \frac{T_p}{T}$

PR(AV) - VR / Typical Data



(Waveform definition)




Duty Cycle : $\sigma = \frac{T_p}{T}$




Electrical Characteristics Technical Data (Reference)

PF(AV) - IF(AV) / Typical Data



(Waveform definition)




Duty Cycle : $\sigma = \frac{T_p}{T}$


(Graph legends)

(1)	$\sigma=1.0$
(2)	$\sigma=0.8$
(3)	$\sigma=0.5$
(4)	$\sigma=0.3$

PR(AV) - VR / Typical Data



(Waveform definition)



Duty Cycle : $\sigma = \frac{T_p}{T}$

(Graph legends)


(1)	$\sigma=1.0$
(2)	$\sigma=0.7$
(3)	$\sigma=0.5$
(4)	$\sigma=0.2$

Thermal Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Thermal Resistance, Junction to Solder Point	$R_{th(j-sp)}$	$T_a = 25^{\circ}\text{C}$, in free air	-	8	-	$^{\circ}\text{C/W}$
Thermal Resistance, Junction to Ambient ^{*1}	$R_{th(j-a)}$	$T_a = 25^{\circ}\text{C}$, in free air	-	43	-	$^{\circ}\text{C/W}$
Thermal Resistance, Junction to Ambient ^{*2}	$R_{th(j-a)}$	$T_a = 25^{\circ}\text{C}$, in free air	-	250	-	$^{\circ}\text{C/W}$


Note) ^{*1}: Device mounted on Ceramic substrate (70mm×70mm×t1.0mm).
^{*2}: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (50.7mm² area, 36μm thick).

(Evaluation board outline)




Thermal Characteristics Technical Data (Reference)

$R_{th} - T^{*1}$ / Typical Data



Note) ^{*1}: Single pulse measurement (Waveform definition)




(Graph legends)

(1)	Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (50.7mm ² area, 36μm thick).
(2)	Device mounted on Ceramic substrate (70mm×70mm×t1.0mm).




Thermal Characteristics Technical Data (Reference)


Effective Transient Thermal Resistance - T_p^{*1} / Typical Data



(Evaluation board outline)



(Waveform definition)




$$\text{Duty Cycle : } \sigma = \frac{T_p}{T}$$


(Graph legends)

(1)	$\sigma = 0.5$
(2)	$\sigma = 0.2$
(3)	$\sigma = 0.1$
(4)	$\sigma = 0.05$
(5)	$\sigma = 0.02$
(6)	$\sigma = 0$


Effective Transient Thermal Resistance - T_p^{*2} / Typical Data



(Evaluation board outline)



(Waveform definition)



$$\text{Duty Cycle : } \sigma = \frac{T_p}{T}$$

(Graph legends)


(1)	$\sigma = 0.5$
(2)	$\sigma = 0.2$
(3)	$\sigma = 0.1$
(4)	$\sigma = 0.05$
(5)	$\sigma = 0.02$
(6)	$\sigma = 0$

Note) *1: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (50.7mm² area, 36μm thick).


*2: Device mounted on Ceramic substrate (70mm×70mm×t1.0mm).

Power Derating Technical Data (Reference)


IF(AV) - Ta^{*1} / Typical Data



IF(AV) - Ta^{*2} / Typical Data




IF(AV) - Tsp / Typical Data



(Graph legends)

(1)	$\sigma = 1.0$
(2)	$\sigma = 0.8$
(3)	$\sigma = 0.5$
(4)	$\sigma = 0.3$


(Waveform definition)



Note)

*1: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (50.7mm² area, 36μm thick).

(Evaluation board outline)



*2: Device mounted on Ceramic substrate (70mm×70mm×t1.0mm).

(Evaluation board outline)






Schottky Barrier Diode
DB2F43100L


DCSP1616010-N1

Unit: mm



■ Land Pattern (Reference)

Unit: mm



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information de-scribed in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
Please consult with our sales staff in advance for information on the following applications, moreover please exchange documents separately on terms of use etc.: Special applications (such as for in-vehicle equipment, airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, medical equipment and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
Unless exchanging documents on terms of use etc. in advance, it is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. We do not guarantee quality for disassembled products or the product re-mounted after removing from the mounting board.
When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) When reselling products described in this book to other companies without our permission and receiving any claim of request from the resale destination, please understand that customers will bear the burden.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Panasonic:](#)

[DB2F43100L1](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.