

# Silicon NPN Phototransistor

## Version 1.3

### SFH 310



#### Features:

- **Spectral range of sensitivity:** (typ) 450 ... 1100 nm
- **Package:** 3mm Radial (T 1), Epoxy
- **Special:** high photosensitivity

#### Applications

- Photointerrupters
- Industrial electronics
- For control and drive circuits

#### Ordering Information

Type:	Photocurrent $I_{PCE}$ [ $\mu A$ ] $\lambda = 950 \text{ nm}$ , $E_e = 0.5 \text{ mW/cm}^2$ , $V_{CE} = 5 \text{ V}$	Ordering Code
SFH 310	630 ... 3200	Q62702P0874
SFH 310-2/3	630 ... 2000	Q62702P3595

Note: Only one bin within one packing unit (variation less than 2:1)

**Maximum Ratings ( $T_A = 25^\circ\text{C}$ )**

Parameter	Symbol	Values	Unit
Operating and storage temperature range	$T_{\text{op}}; T_{\text{stg}}$	-40 ... 100	°C
Collector-emitter voltage	$V_{\text{CE}}$	35	V
Collector current	$I_C$	50	mA
Collector surge current	$I_{\text{CS}}$	100	mA
Total Power dissipation	$P_{\text{tot}}$	165	mW
Thermal resistance	$R_{\text{thJA}}$	450	K / W
ESD withstand voltage (acc. to ANSI/ ESDA/ JEDEC JS-001 - HBM)	$V_{\text{ESD}}$	2000	V

**Characteristics ( $T_A = 25^\circ\text{C}$ )**

Parameter	Symbol	Values	Unit
Wavelength of max. sensitivity (typ)	$\lambda_{\text{S max}}$	880	nm
Spectral range of sensitivity (typ)	$\lambda_{10\%}$	(typ) 450 ... 1100	nm
Radiant sensitive area (typ)	A	0.11	mm <sup>2</sup>
Dimensions of chip area (typ)	L x W	(typ) 0.5 x 0.5	mm x mm
Half angle (typ)	$\Phi$	± 25	°
Capacitance ( $V_{\text{CE}} = 0 \text{ V}, f = 1 \text{ MHz}, E = 0$ ) (typ)	$C_{\text{CE}}$	7.5	pF
Dark current ( $V_{\text{CE}} = 20 \text{ V}, E = 0$ ) (typ (max))	$I_{\text{CE0}}$	1 ( $\leq 50$ )	nA

**Grouping** ( $T_A = 25^\circ\text{C}$ ,  $\lambda = 950 \text{ nm}$ )


Group	Min Photocurrent $E_e = 0.5 \text{ mW/cm}^2$ , $V_{CE} = 5 \text{ V}$ $I_{PCE, min} [\mu\text{A}]$	Max Photocurrent $E_e = 0.5 \text{ mW/cm}^2$ , $V_{CE} = 5 \text{ V}$ $I_{PCE, max} [\mu\text{A}]$	Typ Photocurrent $E_V = 1000 \text{ lx}$ , Std. Light A, $V_{CE} = 5 \text{ V}$ $I_{PCE} [\mu\text{A}]$	Rise and fall time $I_C = 1 \text{ mA}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 1 \text{ k}\Omega$ $t_r, t_f [\mu\text{s}]$
-2	630	1250	3000	5
-3	1000	2000	4800	8
-4	1600	3200	7700	12

Group	Collector-emitter saturation voltage $I_C = I_{PCEmin} \times 0.3$ , $E_e = 0.5 \text{ mW/cm}^2$ $V_{CEsat} [\text{mV}]$
-2	150
-3	150
-4	150

Note.:  $I_{PCEmin}$  is the min. photocurrent of the specified group.


### Relative Spectral Sensitivity <sup>1) page 9</sup>





$$S_{\text{rel}} = f(\lambda)$$



### Photocurrent <sup>1) page 9</sup>


$$I_{PCE} = f(E_e), V_{CE} = 5 \text{ V}$$




**Photocurrent** <sup>1) page 9</sup> $I_{PCE} = f(V_{CE})$ , E<sub>e</sub> = Parameter**Photocurrent** <sup>1) page 9</sup> $I_{PCE} / I_{PCE}(25^\circ\text{C}) = f(T_A)$ ,  $V_{CE} = 5 \text{ V}$ **Dark Current** <sup>1) page 9</sup> $I_{CEO} = f(V_{CE})$ , E = 0**Dark Current** <sup>1) page 9</sup> $I_{CEO} = f(T_A)$ , E = 0

**Collector-Emitter Capacitance** <sup>1) page 9</sup>


$$C_{CE} = f(V_{CE}), f = 1 \text{ MHz}, E = 0$$


**Power Consumption**

$$P_{tot} = f(T_A)$$

**Directional Characteristics** <sup>1) page 9</sup>

$$S_{rel} = f(\phi)$$



**Package Outline**

GEXY6710

*Dimensions in mm (inch).***Package**


3mm Radial (T 1), Epoxy

**Approximate Weight:**

0.2 g

**Note**

Packing information is available on the internet (online product catalog).

**Recommended Solder Pad**

Dimensions in mm.

E062.3010.188-01


**Note:**

pad 1: emitter

**TTW Soldering**

IEC-61760-1 TTW

OHA04645



**Disclaimer**

Language english will prevail in case of any discrepancies or deviations between the two language wordings.

**Attention please!**

The information describes the type of component and shall not be considered as assured characteristics.  
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version in the Internet.

**Packing**

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office.  
By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

**Components used in life-support devices or systems must be expressly authorized for such purpose!**

Critical components\* may only be used in life-support devices\*\* or systems with the express written approval of OSRAM OS.

\*) A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or the effectiveness of that device or system.

\*\*) Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health and the life of the user may be endangered.

## Glossary

- <sup>1)</sup> **Typical Values:** Due to the special conditions of the manufacturing processes of LED, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

Published by OSRAM Opto Semiconductors GmbH  
Leibnizstraße 4, D-93055 Regensburg  
www.osram-os.com © All Rights Reserved.

EU RoHS and China RoHS compliant product



此产品符合欧盟 RoHS 指令的要求；

按照中国的相关法规和标准，不含有毒有害物质或元素。



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.