



LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
	N2	REVISED PER ECO-11-004587	11MAR11	RK	HMR		



CONTACT IDENTIFICATION LETTER "B" (LOCATED IN THIS AREA)

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #22-#26 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103644
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 8 MAXIMUM ALLOWABLE BOW OF ASSEMBLY NOT TO EXCEED .055.
- 9 .000015 GOLD IN THE CONTACT AREA. .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA. ALL OVER .000050 NICKEL.
- 10 .000015 GOLD IN THE CONTACT AREA. .000050-.000100 BRIGHT TIN ON THE TERMINATION AREA. ALL OVER .000050 NICKEL.
- 11 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- 12 .000015 GOLD IN THE CONTACT AREA. .000050-.000100 MATTE TIN ON THE TERMINATION AREA. ALL OVER .000050 NICKEL.
- 13 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



EXAMPLE: STRIP ASSEMBLY
SCALE 2:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	L A MAYER	11-4-86	STE TE Connectivity		
DIMENSIONS: INCHES		CHK	P de Jong	11-12-86			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	P de Jong	11-12-86	NAME		
0 PLC ± -		PRODUCT SPEC		RCPT ASSY, AMPMODU MTE, SINGLE			
1 PLC ± -		APPLICATION SPEC		ROW, .100 C/L, LATCHED & POLARIZED			
2 PLC ± .02		WEIGHT		FOR #22-#25 AWG WIRE SIZE, STRIP FORM			
3 PLC ± .005		SIZE		RESTRICTED TO			
4 PLC ± -		CAGE CODE		A2 00779			
ANGLES ± -		DRAWING NO		C=103957			
FINISH		SCALE		SHEET			
HOUSING: SEE TABLE		CUSTOMER DRAWING		4:1 1 of 2			
		REV		N2			

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-

OBSOLETE	△12	2	2.40	1.198	1-104257-1	12	6-103957-1	
	△12	2	2.20	1.098	1-104257-0	11	6-103957-0	
	△12	2	2.00	.998	104257-9	10	5-103957-9	
	△12	2	1.80	.898	104257-8	9	5-103957-8	
	△12	2	1.60	.798	104257-7	8	5-103957-7	
	△12	2	1.40	.698	104257-6	7	5-103957-6	
	△12	4	2.39	.598	104257-5	6	5-103957-5	
	△12	4	1.99	.498	104257-4	5	5-103957-4	
	△12	5	1.99	.398	104257-3	4	5-103957-3	
	△12	8	2.40	.298	104257-2	3	5-103957-2	
	△12	10	2.00	.198	104257-1	2	5-103957-1	
	△10	2	1.40	.698	104257-6	7	2-103957-0	
	△11	△10	2	2.40	1.198	1-104257-1	12	1-103957-9
	△11	△10	2	2.00	.998	104257-9	10	1-103957-8
		△10	2	1.60	.798	104257-7	8	1-103957-7
		△10	4	2.39	.598	104257-5	6	1-103957-6
		△10	4	1.99	.498	104257-4	5	1-103957-5
		△10	5	1.99	.398	104257-3	4	1-103957-4
		△10	8	2.40	.298	104257-2	3	1-103957-3
		△10	10	2.00	.198	104257-1	2	1-103957-2
	△9	2	2.40	1.198	1-104257-1	12	1-103957-1	
	△9	2	2.20	1.098	1-104257-0	11	1-103957-0	
	△9	2	2.00	.998	104257-9	10	103957-9	
	△9	2	1.80	.898	104257-8	9	103957-8	
	△9	2	1.60	.798	104257-7	8	103957-7	
	△9	2	1.40	.698	104257-6	7	103957-6	
	△9	4	2.39	.598	104257-5	6	103957-5	
	△9	4	1.99	.498	104257-4	5	103957-4	
	△9	5	1.99	.398	104257-3	4	103957-3	
	△9	8	2.40	.298	104257-2	3	103957-2	
	△9	10	2.00	.198	104257-1	2	103957-1	
PLATING	△6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	L A MAYER	11-4-86	STE TE Connectivity			
CHK	P de Jong	11-12-86				
APVD	P de Jong	11-12-86				
NAME	RCPT ASSY, AMPMODU MTE, SINGLE ROW, .100 C/L, LATCHED & POLARIZED FOR #22-#25 AWG WIRE SIZE, STRIP FORM					
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
	0 PLC ± - 1 PLC ± - 2 PLC ± .02 3 PLC ± .005 4 PLC ± - ANGLES ± -	108-25034	A2	00779	C=103957	-
MATERIAL	FINISH	APPLICATION SPEC	WEIGHT	SCALE	SHEET	REV
-	SEE TABLE	114-25026	-	1:1	2 OF 2	N2
CUSTOMER DRAWING						

103957

A



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.