

For more Information
please call

1-800-Belden1



General Description:

22 AWG solid .025" bare copper-covered steel conductor, semi-solid polyethylene insulation, bare copper braid shield (95% coverage), PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	22	Solid	BCCS - Bare Copper Covered Steel	.025

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)	Dia. (in.)
Semi-Solid PE - Semi-Solid Polyethylene	0.026	0.146

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.032

Overall Cable

Overall Nominal Diameter: 0.239 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

UL Temperature Rating: 60°C (UL AWM Style 1478)

Bulk Cable Weight: 36 lbs/1000 ft.

Max. Recommended Pulling Tension: 84 lbs.

Min. Bend Radius/Minor Axis: 2.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2, CM

CEC/C(UL) Specification: CM

AWM Specification: UL Style 1478 (30 V 60°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

PMSHA Specification: SC-182/3

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

9269 Coax - 93 Ohms

Customer Part Number Reference Specification: IBM P/N 323921

RG Type: 62A/U

Flame Test

UL Flame Test: UL1685 UL Loading

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 89269, 87269, 82269

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
93

Nom. Inductance:

Inductance (µH/ft)
0.116

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
13.5

Nominal Velocity of Propagation:

VP (%)
84

Nominal Delay:

Delay (ns/ft)
1.21

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
41.2

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.9

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.3
10	0.9
50	1.9
100	2.7
200	3.8
400	5.3
700	7.3
900	8.2
1000	8.7

Max. Operating Voltage - UL:

Voltage	Description
300 V RMS	CM
150 V RMS	CL2
30 V RMS	AWM Style 1478

Max. Operating Voltage - Non-UL:

Voltage
750 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9269 A8RU1000	1,000 FT	36.000 LB	BEIGE, SNOW		RG-62A/U TYPE COAX
9269 003U1000	1,000 FT	36.000 LB	ORANGE		RG-62A/U TYPE COAX
9269 010U1000	1,000 FT	36.000 LB	BLACK		RG-62A/U TYPE COAX
9269 010U500	500 FT	18.500 LB	BLACK		RG-62A/U TYPE COAX 306 2.09
9269 0101000	1,000 FT	38.000 LB	BLACK		RG-62A/U TYPE COAX
9269 0101640	1,640 FT	60.680 LB	BLACK	C	RG-62A/U TYPE COAX
9269 0102000	2,000 FT	76.000 LB	BLACK	C	RG-62A/U TYPE COAX
9269 0103280	3,280 FT	121.360 LB	BLACK	C	RG-62A/U TYPE COAX
9269 010500	500 FT	19.000 LB	BLACK	C	RG-62A/U TYPE COAX
9269 0105000	5,000 FT	185.000 LB	BLACK	C	RG-62A/U TYPE COAX

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

9269 Coax - 93 Ohms

9269 060U1000	1,000 FT	36.000 LB	CHROME		RG-62A/U TYPE COAX
---------------	----------	-----------	--------	--	--------------------

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 08-16-2012

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.