

## 5220FL Multi-Conductor - Commercial Applications - 2 Conductors Cabled

For more Information  
please call

1-800-Belden1



### Description:

16 AWG bare copper conductors, PP insulation, conductors cabled together, Beldfoil® shield and drain wire, PVC jacket with ripcord, sequential footage marking every two feet.

### Usage (Overall)

**Suitable Applications:** Fire Protection, Alarm, Signal, Monitor/Detection, Audio Circuits, Control Circuits, Initiating Circuits, Notification Circuits

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material
2	16	Solid	BC - Bare Copper

**Total Number of Conductors:** 2

#### Insulation

##### Insulation Material:

Insulation Material	Wall Thickness (in.)
PP - Polypropylene	0.007

#### Outer Shield

##### Outer Shield Material:

Outer Shield Trade Name	Outer Shield Material	Coverage (%)
Beldfoil®	Aluminum Foil-Polyester Tape	100

##### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	Solid	TC - Tinned Copper

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.017

**Outer Jacket Ripcord:** Yes

### Overall Cable

#### Overall Cabling Lay Length & Direction:

Length (in.)	Twists (twist/ft)
2,500	4,800

#### Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red

**Overall Nominal Diameter:** 0.170 in.

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -20°C To +75°C

**UL Temperature Rating:** 75°C

## 5220FL Multi-Conductor - Commercial Applications - 2 Conductors Cabled

<b>Bulk Cable Weight:</b>	31.100 lbs/1000 ft.
<b>Max. Recommended Pulling Tension:</b>	75 lbs.
<b>Min. Bend Radius/Minor Axis:</b>	1.750 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>NEC/(UL) Specification:</b>	FPLR
<b>NEC Articles:</b>	760
<b>EU CE Mark:</b>	Yes
<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	04/01/2005
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes
<b>EU Directive 2003/11/EC (BFR):</b>	Yes
<b>CA Prop 65 (CJ for Wire &amp; Cable):</b>	Yes
<b>MII Order #39 (China RoHS):</b>	Yes
<b>Other Specification:</b>	California State Fire Marshall

#### Flame Test

<b>UL Flame Test:</b>	UL1666 Vertical Shaft
<b>CSA Flame Test:</b>	FT4

#### Plenum/Non-Plenum

<b>Plenum (Y/N):</b>	No
<b>Plenum Number:</b>	6220FL

### Electrical Characteristics (Overall)

#### Nom. Inductance:

Inductance (µH/ft)

0.140

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

65.500

#### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

118.000

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.9

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

16.900

#### Max. Operating Voltage - UL:

Voltage

300 V RMS

#### Max. Recommended Current:

Current

6.3 Amps per conductor @ 25°C

### Put Ups and Colors:

## 5220FL Multi-Conductor - Commercial Applications - 2 Conductors Cabled

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5220FL D151000	1,000 FT	24.000 LB	BLUE		2 #16 PP FS FRPVC
5220FL 0021000	1,000 FT	24.000 LB	RED	C	2 #16 PP FS FRPVC
5220FL 0091000	1,000 FT	24.000 LB	WHITE		2 #16 PP FS FRPVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 07-24-2009

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.