

## TRANSIENT VOLTAGE SUPPRESSOR

# VRD

VRD is a transient voltage suppressor used for protecting electric circuits from surge voltage and thus preventing breakdown.

VRD has superior surge suppression characteristics, such as extremely fast response time, very low clamping voltage, and high surge capacity. Unlike metal oxide varistors, VRD does not have characteristics to change with surge variations within the rated capacity. This feature comprises another superior characteristics of the VRD as a transient voltage suppressors.



### Part number

|                       |   |
|-----------------------|---|
| <b>Z2 033 U - 52Z</b> | 52Z : Axial tapping winding type                    |
|                       | 52R : Axial tapping relay type                      |
|                       | FT : Radial form tapping type                       |
|                       | Nil : individually packed in a bag                  |
|                       | U : Uni-Polar                                       |
|                       | Nil : Bi-Polar                                      |
|                       | Break down voltage                                  |
|                       | Type  |
|                       | Z2 : Rated electricity 1.0W                         |
|                       | Z6 : Rated electricity 2.0W                         |
|                       | ZD : Rated electricity 0.5W (reverse blocking type) |

### Electrical characteristics

Figure 1 shows the electrical characteristics. Bipolar type has almost symmetrical breakdown Voltage ( $V_B$ ) The reverse breakdown voltage of the ZD type is 200 Volts or more at  $10\mu\text{A}$  DC.



Fig 1

### Taping

One of standard taping is as shown in Figure.



Fig 2

### Taping qty

| Part series | Taping method  | Qty(pcs)     |       |
|-------------|----------------|--------------|-------|
| Z2,Z2U      | Axial tapping  | reel type    | 5,000 |
|             |                | winding type | 2,000 |
|             | Radial tapping | winding type | 2,000 |
|             |                |              |       |
| Z6,Z6U      | Axial tapping  | reel type    | 2,500 |
|             |                | winding type | 1,000 |

### Surge capability

Allowable surge capability ( $P_{PPMM}$ ) is determined by the following equation:

$$P_{PPMM} = I_{PPMM} \times V_C$$

$I_{PPMM}$ : Rated peak impulse current

$V_C$ : clamping voltage

The allowable surge capability (Rated peak impulse power dissipation  $P_{PPMM}$ ) of VRD is shown in following Figure 3 and the surge capability derating characteristics are shown in Figure 6.



Fig 3

### Surge waveform

There are many types of surge waveform depending on the source of the surge. For the VRD surge suppression characteristics test, the EXP waveform shown below is used. The EXP waveform is shown as  $t_a/t_b$  depending on the time width, however 10/1000 waveform is used as the standard test waveform.



Fig 4

### Surge suppression characteristics

When EXP waveform is applied, the surge suppression waveform shown in the figure 5 can be observed.



### Power derating



### Z2 type VRD has bipolar or unipolar electrical characteristics.

Maximum ratings

Rated peak impulse power dissipation  
:500 W (10/1000 $\mu$ s)  
6.00 kW (8/20 $\mu$ s)

Rated average power dissipation:1W  
Operating and storage temperature  
: -40°C to 125°C

Symbol mark



| Part No.      |                | Stand-off voltage<br>$V_s$<br>V | Stand-by current<br>$I_b$<br>$\mu$ A | Breakdown voltage<br>$V_{(BR)}$<br>V | Pulsed d.c. test current<br>$I_T$<br>mA | Clamping Voltage & Rated peak impulse current |                |              |                | Temperature coefficient (TYP) | Capacitance (TYP) pF |
|---------------|----------------|---------------------------------|--------------------------------------|--------------------------------------|---|---|----------------|--------------|----------------|-------------------------------|----------------------|
| Bi-polar type | Uni-polar type |                                 |                                      |                                      |   | 10/1000 $\mu$ s                               |                | 8/20 $\mu$ s |                |                               |                      |
|               |                |                                 |                                      |                                      |   | $V_C$<br>V                                    | $I_{PPM}$<br>A | $V_C$<br>V   | $I_{PPM}$<br>A |                               |                      |
| -             | Z2008U         | 6.63                            | 500                                  | 7.38-9.02                            | 10                                      | 12.5  | 40.0           | 16.3         | 372            | 0.063                         | 2400                 |
| -             | Z2010U         | 8.10                            | 20                                   | 9.00-11.0                            |   | 15.0  | 33.4           | 19.5         | 311            | 0.071                         | 1900                 |
| Z2012         | -              | 9.72                            |                                      | 10.8-13.2                            |   | 17.3  | 28.9           | 22.7         | 267            | 0.066                         | 790                  |
| -             | Z2012U         |                                 |                                      | 10.8-13.2                            |   |   |                |              |                | 0.074                         | 1580                 |
| Z2015         | -              | 12.1                            |                                      | 13.5-16.5                            |   | 22.0  | 22.7           | 28.4         | 213            | 0.075                         | 640                  |
| -             | Z2015U         |                                 |                                      | 13.5-16.5                            |   |   |                |              |                | 0.079                         | 1280                 |
| Z2018         | -              | 14.5                            |                                      | 16.2-19.8                            |   | 26.5  | 18.8           | 34.0         | 178            | 0.079                         | 520                  |
| -             | Z2018U         |                                 |                                      | 16.2-19.8                            |   |   |                |              |                | 0.083                         | 1040                 |
| Z2022         | -              | 17.8                            |                                      | 19.8-24.2                            |   | 31.9  | 15.7           | 41.2         | 147            | 0.082                         | 420                  |
| -             | Z2022U         |                                 |                                      | 19.8-24.2                            |   |   |                |              |                | 0.086                         | 840                  |
| Z2027         | -              | 21.8                            |                                      | 24.3-29.7                            |   | 39.1  | 12.8           | 50.5         | 120            | 0.085                         | 340                  |
| -             | Z2027U         |                                 |                                      | 24.3-29.7                            |   |   |                |              |                | 0.089                         | 680                  |
| Z2033         | -              | 26.8                            |                                      | 29.7-36.3                            |   | 47.7  | 10.5           | 61.7         | 98.2           | 0.087                         | 280                  |
| -             | Z2033U         |                                 |                                      | 29.7-36.3                            |   |   |                |              |                | 0.092                         | 560                  |
| Z2039         | -              | 31.6                            |                                      | 35.1-42.9                            |   | 56.4  | 8.86           | 73.0         | 83.0           | 0.090                         | 240                  |
| -             | Z2039U         |                                 |                                      | 35.1-42.9                            |   |   |                |              |                | 0.095                         | 480                  |
| Z2047         | -              | 38.1                            | 5                                    | 42.3-51.7                            | 1                                       | 67.8  | 7.37           | 88.0         | 68.9           | 0.092                         | 200                  |
| -             | Z2047U         |                                 |                                      | 42.3-51.7                            |   |   |                |              |                | 0.097                         | 400                  |
| Z2056         | -              | 45.4                            |                                      | 50.4-61.6                            |   | 80.5  | 6.21           | 105.0        | 57.7           | 0.094                         | 160                  |
| -             | Z2056U         |                                 |                                      | 50.4-61.6                            |   |   |                |              |                | 0.099                         | 320                  |
| Z2068         | -              | 55.1                            |                                      | 61.2-74.8                            |   | 98.0  | 5.10           | 127.0        | 47.7           | 0.096                         | 130                  |
| -             | Z2068U         |                                 |                                      | 61.2-74.8                            |   |   |                |              |                | 0.100                         | 260                  |
| Z2082         | -              | 66.4                            |                                      | 73.8-90.2                            |   | 118.0   | 4.24           | 153.0        | 39.6           | 0.099                         | 110                  |
| -             | Z2082U         |                                 |                                      | 73.8-90.2                            |   |   |                |              |                | 0.102                         | 220                  |
| Z2100         | -              | 81.0                            |                                      | 90.0-110                             |   | 144.0   | 3.47           | 187.0        | 32.4           | 0.101                         | 90                   |
| -             | Z2100U         |                                 |                                      | 90.0-110                             |   |   |                |              |                | 0.104                         | 180                  |
| Z2120         | -              | 97.2                            |                                      | 108-132                              |   | 173.0   | 2.89           | 222.0        | 27.3           | 0.103                         | 75                   |
| -             | Z2120U         |                                 |                                      | 108-132                              |   |   |                |              |                | 0.106                         | 150                  |
| Z2150         | -              | 121.0                           |                                      | 135-165                              |   | 215.0   | 2.32           | 277.0        | 21.9           | 0.105                         | 60                   |
| -             | Z2150U         |                                 |                                      | 135-165                              |   |   |                |              |                | 0.107                         | 120                  |
| Z2180         | -              | 146.0                           |                                      | 162-198                              |   | 258.0   | 1.94           | 333.0        | 18.2           | 0.106                         | 49                   |
| -             | Z2180U         |                                 |                                      | 162-198                              |   |   |                |              |                | 0.108                         | 98                   |

NOTE: Nonsuffix:bi-polar, suffix"U" : uni-polar.

| Part No.      |                | Stand-off voltage<br>V <sub>s</sub><br>V | Stand-by current<br>I <sub>b</sub><br>μA | Breakdown voltage<br>V <sub>(BR)</sub><br>V | Pulsed d.c. test current<br>I <sub>T</sub><br>mA | Clamping Voltage & Rated peak impulse current |                       |                     |                       | Max. temp. coef.<br>%/°C | Capacitance (TYP)<br>pF |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
|---------------|----------------|--|--|---|--|---|-----------------------|---------------------|-----------------------|--------------------------|-------------------------|------|-------|-------|-------|------|------|------|-------|-------|------|------|------|-----|-------|------|------|------|-----|-------|------|------|------|-----|-------|------|------|-------|-----|-------|------|------|-------|-----|-------|-------|------|-------|------|-------|------|-------|------|-------|-----|
| Bi-polar type | Uni-polar type |  |  |   |  | 10/1000μs                                     |                       | 8/20μs              |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
|               |                |  |  |   |  | V <sub>C</sub><br>V                           | I <sub>PPM</sub><br>A | V <sub>C</sub><br>V | I <sub>PPM</sub><br>A |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6012         | -              | 9.72                                     | 10                                       | 10.8-13.2                                   | 1  | 17.3  | 86.7                  | 22.7                | 802                   | 0.066                    | 4400                    |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6012U         |  |  | 10.8-13.2                                   |  |   |                       |                     |                       | 0.074                    | 8800                    |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6015         | -              | 12.1                                     | 10                                       | 13.5-16.5                                   |  |   |                       |                     |                       | 22.0                     | 68.2                    | 28.4 | 641   | 0.075 | 3300  |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6015U         |  |  | 13.5-16.5                                   |  |   |                       |                     |                       | 0.079                    | 6600                    |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6018         | -              | 14.5                                     | 10                                       | 16.2-19.8                                   |  |   |                       |                     |                       | 1                        | 26.5                    | 56.6 | 34.0  | 535   | 0.079 | 2700 |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6018U         |  |  | 16.2-19.8                                   |  |   |                       |                     |                       |                          |                         |      |       |       | 0.083 | 5400 |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6022         | -              | 17.8                                     | 10                                       | 19.8-24.2                                   |  |   |                       |                     |                       |                          |                         |      |       |       | 31.9  | 47.0 | 41.2 | 442  | 0.082 | 2400  |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6022U         |  |  | 19.8-24.2                                   |  |   |                       |                     |                       |                          |                         |      |       |       | 0.086 | 4400 |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6027         | -              | 21.8                                     | 10                                       | 24.3-29.7                                   |  |   |                       |                     |                       |                          |                         |      |       |       | 1     | 39.1 | 38.4 | 50.5 | 360   | 0.085 | 1700 |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6027U         |  |  | 24.3-29.7                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       | 0.089 | 3300 |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6033         | -              | 26.8                                     | 10                                       | 29.7-36.3                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       | 1     | 47.7 | 31.4 | 61.7 | 295 | 0.087 | 1400 |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6033U         |  |  | 29.7-36.3                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     | 0.092 | 2800 |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6039         | -              | 31.6                                     | 10                                       | 35.1-42.9                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     | 1     | 56.4 | 26.6 | 73.0 | 249 | 0.090 | 1200 |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6039U         |  |  | 35.1-42.9                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     | 0.095 | 2400 |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6047         | -              | 38.1                                     | 10                                       | 42.3-51.7                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     | 1     | 67.8 | 22.1 | 88.0 | 207 | 0.092 | 1000 |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6047U         |  |  | 42.3-51.7                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     | 0.097 | 2000 |      |       |     |       |      |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6056         | -              | 45.4                                     | 10                                       | 50.4-61.6                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     | 1     | 80.5 | 18.6 | 105.0 | 173 | 0.094 | 850  |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| -             | Z6056U         |  |  | 50.4-61.6                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     | 0.099 | 1700 |      |       |     |       |       |      |       |      |       |      |       |      |       |     |
| Z6068         | -              | 55.1                                     | 10                                       | 61.2-74.8                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     | 1     | 98.0 | 15.3 | 127.0 | 143 | 0.096 | 720   |      |       |      |       |      |       |      |       |     |
| -             | Z6068U         |  |  | 61.2-74.8                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     | 0.100 | 1440  |      |       |      |       |      |       |      |       |     |
| Z6082         | -              | 66.4                                     | 10                                       | 73.8-90.2                                   | 1  | 118.0   | 12.7                  | 153.0               | 119                   |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     | 0.099 | 610   |      |       |      |       |      |       |      |       |     |
| -             | Z6082U         |  |  | 73.8-90.2                                   |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     | 0.102 | 1220  |      |       |      |       |      |       |      |       |     |
| Z6100         | -              | 81.0                                     | 10                                       | 90.0-110                                    |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     | 1     | 144.0 | 10.4 | 187.0 | 97.3 | 0.101 | 520  |       |      |       |     |
| -             | Z6100U         |  |  | 90.0-110                                    |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      | 0.104 | 1040 |       |      |       |     |
| Z6120         | -              | 97.2                                     | 10                                       | 108-132                                     |  |   |                       |                     |                       | 1                        | 173.0                   | 8.67 | 222.0 | 82.0  |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      | 0.103 | 440  |       |      |       |     |
| -             | Z6120U         |  |  | 108-132                                     |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      | 0.106 | 880  |       |      |       |     |
| -             | Z6150U         | 121.0                                    | 10                                       | 135-165                                     |  |   |                       |                     |                       |                          |                         |      |       |       |       |      |      |      |       |       |      |      |      |     |       |      |      |      |     |       |      |      |      |     |       |      |      |       |     |       |      |      |       |     |       |       |      |       |      | 215.0 | 6.98 | 277.0 | 65.7 | 0.107 | 720 |

NOTE : Nonsuffix : Bi-polar, suffix "U" : Uni-polar.

**Z6 type VRD has bipolar or unipolar electrical characteristics.**

Maximum ratings  
 Rated peak impulse power dissipation :1.5kW(10/1000μs)  
 18.0kW(8/20μs)  
 Rated average power dissipation:2W  
 Operating and storage temperature : -40°C to 125°C

Symbol mark



| VRD part No. | Stand-off voltage<br>V <sub>s</sub><br>V | Stand-by current<br>I <sub>b</sub><br>μA | Breakdown voltage<br>V <sub>(BR)</sub><br>V | Pulsed d.c. test current<br>I <sub>T</sub><br>mA | Clamping Voltage & Rated peak impulse current |                       |                     |                       | Max. temp. coef.<br>%/°C | Capacitance (TYP)<br>pF |      |       |       |       |       |      |
|--------------|--|--|---|--|---|-----------------------|---------------------|-----------------------|--------------------------|-------------------------|------|-------|-------|-------|-------|------|
|              |  |  |   |  | 10/1000μs                                     |                       | 8/20μs              |                       |                          |                         |      |       |       |       |       |      |
|              |  |  |   |  | V <sub>C</sub><br>V                           | I <sub>PPM</sub><br>A | V <sub>C</sub><br>V | I <sub>PPM</sub><br>A |                          |                         |      |       |       |       |       |      |
| ZD015        | 11.4                                     | 10                                       | 12.8-17.2                                   | 1  | 24.0  | 10.4                  | 31.0                | 96.7                  | 0.075                    | 31.5                    |      |       |       |       |       |      |
| ZD018        | 13.7                                     |  | 15.3-20.7                                   |  |   |                       |                     |                       |                          |                         | 28.0 | 8.93  | 36.0  | 83.3  | 0.079 | 31.0 |
| ZD022        | 16.8                                     | 5  | 18.7-25.3                                   |  |   |                       |                     |                       |                          |                         | 33.2 | 7.53  | 43.0  | 69.7  | 0.082 | 29.0 |
| ZD027        | 20.6                                     |  | 23.0-31.0                                   |  |   |                       |                     |                       |                          |                         | 40.0 | 6.25  | 52.0  | 57.7  | 0.085 | 28.2 |
| ZD033        | 25.2                                     | 5  | 28.1-37.9                                   |  |   |                       |                     |                       |                          |                         | 48.6 | 5.14  | 63.0  | 47.6  | 0.087 | 27.2 |
| ZD039        | 29.8                                     |  | 33.2-44.8                                   |  |   |                       |                     |                       |                          |                         | 57.4 | 4.35  | 74.0  | 40.5  | 0.090 | 26.3 |
| ZD047        | 35.9                                     | 5  | 40.0-54.0                                   |  |   |                       |                     |                       |                          |                         | 68.5 | 3.65  | 89.0  | 33.7  | 0.092 | 25.0 |
| ZD056        | 42.8                                     |  | 47.6-64.4                                   |  |   |                       |                     |                       |                          |                         | 81.0 | 3.08  | 106.0 | 28.6  | 0.094 | 24.1 |
| ZD068        | 52.0                                     | 57.8-78.2                                | 98.0  |  |   |                       |                     |                       |                          |                         | 2.55 | 127.0 | 23.8  | 0.096 | 22.0  |      |

**Low capacitance type**

Maximum ratings  
 Reverse voltage:200 VDC  
 Rated peak impulse power dissipation :250 W(10/1000μs)  
 3.00 kW(8/20μs)  
 Rated average power dissipation:500 mW  
 Operating and storage temperature : -40°C to 125°C

Symbol mark



# SMD VRD

## Part number



## Dimensions



## Marking



|                                      | Rating                |
|--------------------------------------|-----------------------|
| Rated average power dissipation      | 1.0W                  |
| Rated peak impulse power dissipation | 300W(10/1000 $\mu$ s) |
|                                      | 1200W(1.2/50 $\mu$ s) |
|                                      | 2000W(8/20 $\mu$ s)   |
| Storage temp. range                  | -40°C~150°C           |

## Taping



| A              | B              | W                  | F                  | E              | P <sub>1</sub> |
|----------------|----------------|--------------------|--------------------|----------------|----------------|
| 3.0<br>±0.1    | 5.2<br>±0.1    | 12.0<br>±0.3       | 5.5<br>±0.05       | 1.75<br>±0.1   | 4.0<br>±0.1    |
| P <sub>2</sub> | P <sub>0</sub> | phi D <sub>0</sub> | phi D <sub>1</sub> | T <sub>1</sub> | T <sub>2</sub> |
| 2.0<br>±0.1    | 4.0<br>±0.1    | 1.5<br>+0.1<br>-0  | 1.5<br>+0.2<br>-0  | 0.3<br>±0.05   | (2.6)          |

Unit (mm)

## Specifications

### ZS type

| Part No. | Breakdown voltage | Stand-off voltage | Stand-by current | Maximum clamping voltage & Maximum peak pulse current |      |              |      | Temperature coefficient (TYP) | Capacitance (TYP) |
|----------|-------------------|-------------------|------------------|---|------|--------------|------|-------------------------------|-------------------|
|          |                   |                   |                  | V <sub>Cmax</sub> /I <sub>PPM</sub>                   |      |              |      |                               |                   |
|          |                   |                   |                  | 10/1000 $\mu$ s                                       |      | 8/20 $\mu$ s |      |                               |                   |
|          |                   |                   |                  | V   | A    | V            | A    |                               |                   |
| ZS1012   | 12(10.8~13.2)     | 9.72              | 10               | 17.3  | 17.3 | 22.4         | 89.3 | 0.066                         | 551               |
| ZS1015   | 15(13.5~16.5)     | 12.1              | 5                | 22.0  | 13.6 | 28.5         | 70.2 | 0.075                         | 465               |
| ZS1018   | 18(16.2~19.8)     | 14.5              |                  | 26.5  | 11.3 | 34.4         | 58.1 | 0.079                         | 376               |
| ZS1022   | 22(19.8~24.2)     | 17.8              |                  | 31.9  | 9.40 | 41.4         | 48.3 | 0.082                         | 299               |
| ZS1027   | 27(24.3~29.7)     | 21.8              |                  | 39.1  | 7.67 | 50.7         | 39.4 | 0.085                         | 248               |
| ZS1033   | 33(29.7~36.3)     | 26.8              |                  | 47.7  | 6.29 | 61.8         | 32.4 | 0.087                         | 198               |
| ZS1039   | 39(35.1~42.9)     | 31.6              |                  | 56.4  | 5.32 | 73.1         | 27.4 | 0.090                         | 164               |
| ZS1047   | 47(42.3~51.7)     | 38.1              |                  | 67.8  | 4.42 | 88.0         | 22.7 | 0.092                         | 137               |

### ZS-U type

| Part No. | Breakdown voltage | Stand-off voltage | Stand-by current | Maximum clamping voltage & Maximum peak pulse current |      |              |      | Temperature coefficient (TYP) | Capacitance (TYP) |
|----------|-------------------|-------------------|------------------|---|------|--------------|------|-------------------------------|-------------------|
|          |                   |                   |                  | V <sub>Cmax</sub> /I <sub>PPM</sub>                   |      |              |      |                               |                   |
|          |                   |                   |                  | 10/1000 $\mu$ s                                       |      | 8/20 $\mu$ s |      |                               |                   |
|          |                   |                   |                  | V   | A    | V            | A    |                               |                   |
| ZS1012U  | 12(10.8~13.2)     | 9.72              | 10               | 17.3  | 17.3 | 22.4         | 89.3 | 0.066                         | 1,102             |
| ZS1015U  | 15(13.5~16.5)     | 12.1              | 5                | 22.0  | 13.6 | 28.5         | 70.2 | 0.075                         | 929               |
| ZS1018U  | 18(16.2~19.8)     | 14.5              |                  | 26.5  | 11.3 | 34.4         | 58.1 | 0.079                         | 751               |
| ZS1022U  | 22(19.8~24.2)     | 17.8              |                  | 31.9  | 9.40 | 41.4         | 48.3 | 0.082                         | 598               |
| ZS1027U  | 27(24.3~29.7)     | 21.8              |                  | 39.1  | 7.67 | 50.7         | 39.4 | 0.085                         | 497               |
| ZS1033U  | 33(29.7~36.3)     | 26.8              |                  | 47.7  | 6.29 | 61.8         | 32.4 | 0.087                         | 395               |
| ZS1039U  | 39(35.1~42.9)     | 31.6              |                  | 56.4  | 5.32 | 73.1         | 27.4 | 0.090                         | 328               |
| ZS1047U  | 47(42.3~51.7)     | 38.1              |                  | 67.8  | 4.42 | 88.0         | 22.7 | 0.092                         | 274               |

### ZS-D type

| Part No. | Breakdown voltage | Stand-off voltage | Stand-by current | Maximum clamping voltage & Maximum peak pulse current |      |              |      | Temperature coefficient (TYP) | Capacitance (TYP) |
|----------|-------------------|-------------------|------------------|---|------|--------------|------|-------------------------------|-------------------|
|          |                   |                   |                  | V <sub>Cmax</sub> /I <sub>PPM</sub>                   |      |              |      |                               |                   |
|          |                   |                   |                  | 10/1000 $\mu$ s                                       |      | 8/20 $\mu$ s |      |                               |                   |
|          |                   |                   |                  | V   | A    | V            | A    |                               |                   |
| ZS1012D  | 12(10.8~13.2)     | 9.72              | 10               | 17.3  | 17.3 | 22.4         | 89.3 | 0.066                         | 30.2              |
| ZS1015D  | 15(13.5~16.5)     | 12.1              | 5                | 22.0  | 13.6 | 28.5         | 70.2 | 0.075                         | 29.1              |
| ZS1018D  | 18(16.2~19.8)     | 14.5              |                  | 26.5  | 11.3 | 34.4         | 58.1 | 0.079                         | 28.2              |
| ZS1022D  | 22(19.8~24.2)     | 17.8              |                  | 31.9  | 9.40 | 41.4         | 48.3 | 0.082                         | 27.3              |
| ZS1027D  | 27(24.3~29.7)     | 21.8              |                  | 39.1  | 7.67 | 50.7         | 39.4 | 0.085                         | 26.4              |
| ZS1033D  | 33(29.7~36.3)     | 26.8              |                  | 47.7  | 6.29 | 61.8         | 32.4 | 0.087                         | 25.5              |
| ZS1039D  | 39(35.1~42.9)     | 31.6              |                  | 56.4  | 5.32 | 73.1         | 27.4 | 0.090                         | 24.8              |
| ZS1047D  | 47(42.3~51.7)     | 38.1              |                  | 67.8  | 4.42 | 88.0         | 22.7 | 0.092                         | 24.0              |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.