

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0879751002](#)
Status: **Active**
Description: 1.27mm (.050") Signal Pitch, 0.80mm (.031") SCSI Pitch, 1.27mm (.050") Power Pitch
SAS Receptacle, Right Angle, Surface Mount, with Straight Solder Tab, "Z" Height of
2.85mm (.112"), 29 Circuits, Leadfree

Documents:

[3D Model](#) [Product Specification PS-87975-102 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR19980
UL E29179

General

Product Family I/O Connectors
Series [87975](#)
Application Board-to-Board
Comments No pick and place cap|"Z" Height - 2.85mm (.112")
Component Type Receptacle
Product Name SAS
Type N/A

Physical

Boot Color N/A
Circuits (Loaded) 29
Circuits (maximum) 29
Circuits Detail Signal 7, SCSI 7, Power 15
Color - Resin Black
Durability (mating cycles max) 500
Flammability 94V-0
Gender Female
Keying to Mating Part Yes
Lock to Mating Part None
Material - Plating Mating Gold
Material - Plating Termination Tin
Number of Rows 2
Orientation Right Angle
PC Tail Length (in) 0.000 In
PC Tail Length (mm) 0.00 mm
PCB Locator Yes
PCB Retention Yes
PCB Thickness Recommended (in) 0.063 In
PCB Thickness Recommended (mm) 1.60 mm
Packaging Type Tray
Panel Mount Yes
Pitch - Mating Interface (in) 0.031 In, 0.050 In
Pitch - Mating Interface (mm) 0.80 mm, 1.27 mm
Pitch - Term. Interface (in) 0.031 In, 0.050 In
Pitch - Term. Interface (mm) 0.80 mm, 1.27 mm
Plating min: Mating (µin) 30
Plating min: Mating (µm) 0.76
Plating min: Termination (µin) 102
Plating min: Termination (µm) 2.54
Polarized to Mating Part Yes
Polarized to PCB Yes




image - Reference only

Series

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Halogen-Free

**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

China RoHS



Search Parts in this Series

[87975Series](#)

Mates With

[87679](#) , [87799](#) , [87703](#) , SFF 8482 Hard
Disk Drive and Backplane Plug

Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	0°C to +55°C
Termination Interface: Style	Surface Mount
Waterproof / Dustproof	No
Wire Size AWG	N/A

Electrical

Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	30V

Solder Process Data

Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260


Material Info

Reference - Drawing Numbers

Product Specification	PS-87975-102
Sales Drawing	SD-87975-101

This document was generated on 06/08/2010






PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



PART NUMBERS	HOLD DOWN OPTION
87975-1001	FORK LOCK
87975-1002	BLADE

- NOTES:
- MATERIAL:
HOUSING: NYLON, GLASS FILLED, UL 94V-0, BLACK.
TERMINAL/FORKLOCK/BLADE : COPPER ALLOY.
 - FINISHES:
TERMINAL:
CONTACT: 0.76µm MIN. SELECTIVE GOLD OVER 1.27µm MIN. NICKEL UNDERPLATE.
SOLDERTAIL: 2.54µm MIN. TIN OVER 1.27µm MIN. NICKEL UNDERPLATE.
FORKLOCK/BLADE: 2.54µm MIN. TIN OVER 1.27µm MIN. NICKEL UNDERPLATE.
 - PRODUCT SPECIFICATION: PS-87975-102
 - PACKAGING SPECIFICATION : TRAY.
MOLLEX LOGO AND DATE CODE LOCATED APPROXIMATELY AS SHOWN.
 - NON FUNCTIONAL CORE HOLE MAY VARY.
 - THIS PRODUCT IS COMPLIANT TO RoHS DIRECTIVE WITH THE FOLLOWING BANNED SUBSTANCES - LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, POLYBROMINATED BIPHENYLS AND POLYBROMINATED DIPHENYL ETHERS.
 - MATES WITH : SFF-8482 PLUG
SATA PLUG SERIES 87679, 87703 AND 87799

CHG TO REV A EC NO: S2009-0393 DRWN:GEMARLY CHKD:GKH APPR:BOHOK 2008/12/17 2008/12/17 2008/12/17	QUALITY SYMBOLS ▽=0 ◻=0	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
					DRAWN BY YKOH		DATE 2005/03/16		TITLE SERIAL ATTACH SCSI RECEPTACLE, RIGHT-ANGLE SMT, 2.85MM HEIGHT MOLEX INCORPORATED	
					CHECKED BY DKOH		DATE 2005/03/23			
					APPROVED BY SKTOH		DATE 2005/03/23			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-87975-101		SHEET NO. 1 OF 4				
		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						



SECTION Z-Z

CHG TO REV A EC NO: S2009-0393 DRWN: MENARLY CHKD: CGOH APPR: BOKOK	DESCRIPTION	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION				
			mm	INCH	DRAWN BY YKOH	DATE 2005/03/16	TITLE SERIAL ATTACH SCSI RECEPTACLE, RIGHT-ANGLE SMT, 2.85MM HEIGHT						
			4 PLACES ± ---	± ---	CHECKED BY	DATE 2005/03/23							
			3 PLACES ± ---	± ---	DKOH	DATE 2005/03/23	MOLEX MOLEX INCORPORATED						
			2 PLACES ± 0.20	± ---	APPROVED BY	DATE 2005/03/23							
			1 PLACE ± ---	± ---	SKTOH	DATE 2005/03/23	DOCUMENT NO. SD-87975-101						
			ANGULAR ± 3 °		MATERIAL NO.							SHEET NO. 2 OF 4	
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
							SIZE A3						

10 9 8 7 6 5 4 3 2 1

F


E

D

C


B

A



FORKLOCK OPTION

FORKLOCK OPTION



BLADE OPTION

BLADE OPTION

CHG TO REV A EC NO: S2009-0393 DRWNG:GEMARLY 2008/12/17 CHKD:CGOH 2008/12/17 APPR:BOKOK 2008/12/17			DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
							MM ONLY					
					DRAWN BY YKOH		DATE 2005/03/16		TITLE SERIAL ATTACH SCSI RECEPTACLE, RIGHT-ANGLE SMT, 2.85MM HEIGHT			
					CHECKED BY DKOH		DATE 2005/03/23					
APPROVED BY SKTOH		DATE 2005/03/23		MOLEX INCORPORATED								
MATERIAL NO.		DOCUMENT NO.						SHEET NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SD-87975-101				4 OF 4				
SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										

9 8 7 6 5 4 3 2 1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.