

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – ,– .
© COPYRIGHT – BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
DW	—

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	REVISED (ECR-12-014157)	29AUG12	JL	WK








RECOMMENDED PCB LAYOUT (MOUNTING SIDE)
THICKNESS 1.57mm (TOLERANCE: ±0.05)





NOTE:
1. MATERIAL:
   HOUSING: PA9T WITH 33% GF, UL 94V-0, BLACK COLOR.
   CONTACTS: PHOSPHOR BRONZE.
   SHELL: PHOSPHOR BRONZE.
   MYLAR: POLYAMIDE FILM.
2. FINISH:
   CONTACTS: GOLD FLASH OVER
   0.762µm [30µ"] MIN. PALLADIUM-NICKEL PLATED ON CONTACT AREA,
   (A) 2.54µm [100µ"] MIN. MATTE-TIN ON SOLDER TAIL,
   (B) 2.54µm [100µ"] MIN. MATTE-TIN ON SOLDER TAIL,
   (C) 3.05µm [120µ"] MIN. MATTE-TIN ON SOLDER TAIL,
   WITH ENTIRE CONTACT UNDERPLATED 1.27µm [50µ"] MIN. NICKEL.
   SHELL: (A) & (B) 2.03µm [80µ"] MIN. NICKEL PLATED OVERALL.
   (C) 0.76µm [30µ"] MIN. MATTE-TIN OVER 1.27µm [50µ"] MIN. NICKEL.
3. NO DATECODE ON PRODUCT SURFACE.
4. REFLOW SOLDER CAPABLE TO 260°C PER TE TEST SPEC. 109-201, CONDITION B.

(C)	W/O	W/O	TAPE REEL	W/	3-1734035-2
(B)	W/	W/O	TAPE REEL	W/	2-1734035-4
	W/O	W/	TAPE REEL	W/	2-1734035-3
	W/O	W/O	TAPE REEL	W/	2-1734035-2
	W/O	N/A	TRAY	W/	2-1734035-1
(A)	W/	W/O	TAPE REEL	W/	1734035-4
	W/O	W/	TAPE REEL	W/	1734035-3
	W/O	W/O	TAPE REEL	W/	1734035-2
	W/O	N/A	TRAY	W/	1734035-1
PLATED	MYLAR	LONG CARRIER & COVER TAPE	PACKAGE	POST	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± 0.38
1 PLC ± 0.25
2 PLC ± 0.13
3 PLC ± 0.05
4 PLC ± –
ANGLES ± 3°

MATERIAL: SEE NOTE
FINISH: SEE NOTE

DWN	O. HU 21DEC2007
CHK	S. HOU 21DEC2007
APVD	W. KODAMA 21DEC2007
PRODUCT SPEC	108-57062
QUALIFICATION TEST REPORT	501-57070
WEIGHT	--

TE Connectivity

NAME: MINI USB, R/A, SMT, B TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1734035	—


CUSTOMER DRAWING | SCALE — | SHEET 1 OF 4 | REV E


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – ,– .
© COPYRIGHT – BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
DW	—

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			









RECOMMENDED PCB LAYOUT (MOUNTING SIDE)
THICKNESS 1.57mm (TOLERANCE:±0.05)







NOTE:

1. MATERIAL:
   HOUSING: PA9T WITH 33% GF, UL 94V–0, BLACK COLOR.
   CONTACTS: PHOSPHOR BRONZE.
   SHELL: PHOSPHOR BRONZE.
   MYLAR: POLYAMIDE FILM.

2. FINISH:
   CONTACTS: GOLD FLASH OVER
   0.762μm [30μ″] MIN. PALLADIUM–NICKEL PLATED ON CONTACT AREA,
   2.54μm [100μ″] MIN. MATTE–TIN ON SOLDER TAIL, WITH
   ENTIRE CONTACT UNDERPLATED 1.27μm [50μ″] MIN. NICKEL.
   SHELL: 2.03μm [80μ″] MIN. NICKEL PLATED OVERALL.

3. NO DATECODE ON PRODUCT SURFACE.

4. REFLOW SOLDER CAPABLE TO 260°C PER TE TEST SPEC. 109–201, CONDITION B.

W/	W/O	TAPE REEL	W/O	4–1734035–2
W/O	W/	TAPE REEL	W/O	1–1734035–3
	W/O	TAPE REEL	W/O	1–1734035–2
	N/A	TRAY	W/O	1–1734035–1
MYLAR	LONG CARRIER & COVER TAPE	PACKAGE	POST	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± 0.38
1 PLC	± 0.25
2 PLC	± 0.13
3 PLC	± 0.05
4 PLC	± –
ANGLES	± 3°

MATERIAL: SEE NOTE

FINISH: SEE NOTE

DWN
CHK
APVD
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME: MINI USB, R/A, SMT, B TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C–1734035	—


CUSTOMER DRAWING | SCALE — | SHEET 2 OF 4 | REV E

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – , – .
© COPYRIGHT – BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DW	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			



GROSS WEIGHT	NET WEIGHT	PCS/TRAY	TRAYS /CARTON	QUANTITY	PART NUMBER
9.2 Kg	6.7 Kg	150	56	8400 PCS	2–1734035–1
					1–1734035–1
					1734035–1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –

FINISH –

DWN
CHK
APVD
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME MINI USB, R/A, SMT, B TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C–1734035	—


CUSTOMER DRAWING | SCALE — | SHEET 3 OF 4 | REV E


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – ,– .
© COPYRIGHT – BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
DW	—

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			









DETAIL A




SECTION B–B




FOR 1734035–3, 1–1734035–3 AND 2–1734035–3 (LONG CARRIER & COVER TAPE)



FOR 1734035–2, 1734035–4, 1–1734035–2,
3–1734035–2, 2–1734035–2 AND 2–1734035–4
4–1734035–2



GROSS WEIGHT	NET WEIGHT	PCS/REER	REERS /CARTON	QUANTITY	MYLAR	LONG CARRIER & COVER TAPE	PART NUMBER
6.5 Kg	5.5 Kg	700	5	3500	W/	W/O	4–1734035–2
					W/O	W/O	3–1734035–2
					W/	W/O	2–1734035–4
					W/O	W/	2–1734035–3
					W/O	W/O	2–1734035–2
					W/O	W/	1–1734035–3
					W/O	W/O	1–1734035–2
					W/	W/O	1734035–4
					W/O	W/	1734035–3
					W/O	W/O	1734035–2



OUT BOX PACKAGE DIAGRAM DRAWING

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –

FINISH –

DWN
CHK
APVD
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

CUSTOMER DRAWING

TE Connectivity

NAME
MINI USB, R/A, SMT, B TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C–1734035	—

SCALE	SHEET	REV
—	4 OF 4	E


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.