

## Surface Mount Multilayer Ceramic Chip Capacitors for High Temperature Applications



### FEATURES

- Specialty: High temperature applications
- High operating temperature dielectric, up to + 150 °C
- Maintains capacitance at high temperature for frequency stability
- Wet build process
- Reliable Noble Metal Electrode (NME) system
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)  
Available

### APPLICATIONS

- High temperature modules

### ELECTRICAL SPECIFICATIONS

#### Note

- Electrical characteristics at + 25 °C unless otherwise specified.

**Operating Temperature:** - 55 °C to + 150 °C

**Capacitance Range:** 470 pF to 390 nF

**Voltage Range:** 25 V<sub>DC</sub> to 50 V<sub>DC</sub>

**Temperature Coefficient of Capacitance (TCC):**  
± 15 % from - 55 °C to + 150 °C

#### Dissipation Factor (DF):

25 V ratings: 3.5 % maximum at 1.0 V<sub>RMS</sub> and 1 kHz  
50 V ratings: 2.5 % maximum at 1.0 V<sub>RMS</sub> and 1 kHz

**Aging Rate:** 1 % maximum per decade

#### Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 MΩ minimum or 1000 ΩF, whichever is less

At + 125 °C and rated voltage 10 000 MΩ minimum or 100 ΩF, whichever is less

#### Dielectric Strength Test:

Performed per method 103 of EIA-198-2-E

Applied test voltage:

≤ 50 V<sub>DC</sub>-rated: 250 % of rated voltage



| QUICK REFERENCE DATA |      |                     |             |         |
|----------------------|------|---------------------|-------------|---------|
| DIELECTRIC           | CASE | MAXIMUM VOLTAGE (V) | CAPACITANCE |         |
|                      |      |                     | MINIMUM     | MAXIMUM |
| X8R                  | 0402 | 100                 | 330 pF      | 6.8 nF  |
|                      | 0603 | 100                 | 470 pF      | 33 nF   |
|                      | 0805 | 100                 | 470 pF      | 100 nF  |
|                      | 1206 | 50                  | 1.0 nF      | 220 nF  |
|                      | 1210 | 50                  | 10 nF       | 390 nF  |

**Note**


- Detail ratings see “Selection Chart”

| ORDERING INFORMATION                 |            |   |                                       |   |                                   |   |           |                    |
|--------------------------------------|------------|---|---------------------------------------|---|-----------------------------------|---|-----------|--------------------|
| VJ0805                               | H          | 102   | K                                     | X   | A                                 | A   | C         | ### <sup>(2)</sup> |
| CASE CODE                            | DIELECTRIC | CAPACITANCE NOMINAL CODE  | CAPACITANCE TOLERANCE                 | TERMINATION   | DC VOLTAGE RATING <sup>(1)</sup>  | MARKING <sup>(4)</sup>  | PACKAGING | PROCESS CODE       |
| 0402<br>0603<br>0805<br>1206<br>1210 | H = X8R    | Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier.<br><b>Examples:</b><br>102 = 1000 pF | J = ± 5 %<br>K = ± 10 %<br>M = ± 20 % | X = Ni barrier<br>100 % tin plated<br>F, E = AgPd <sup>(3)(5)</sup> | X = 25 V<br>A = 50 V<br>B = 100 V | A = Unmarked<br>M = Marked<br><b>Note</b><br>Marking is only available for 0805 and 1206 with termination code “X”  |           |                    |
|                                      |            |   |                                       |   |                                   | T = 7" reel/plastic tape<br>C = 7" reel/paper tape<br>R = 11 1/4"/13" reel/plastic tape<br>P = 11 1/4"/13" reel/paper tape<br>O = 7" reel/flamed paper tape<br>I = 11 1/4"/13" reel/flamed paper tape<br><b>Note</b><br>“I” and “O” are used for<br>“F” termination size 0603/0805 and<br>“E” termination size 0402/0603/0805 |           |                    |

**Notes**

- (1) DC voltage rating should not be exceeded in application. Other application factors may affect the MLCC performance. Consult for questions: [mlcc@vishay.com](mailto:mlcc@vishay.com)
- (2) Process code may be added with up to three digits, used to control non-standard products and requirements.
- (3) Termination code “E” for conductive epoxy assembly.
- (4) Marking in reference to EIA198, see [www.vishay.com/doc?45028](http://www.vishay.com/doc?45028)
- (5) Termination code “F” not available for 0402, 0603 - 100 V, 0805 - 100 V.

| ENVIRONMENTAL STATUS |  |                |              |
|----------------------|--|----------------|--------------|
| TERMINATION CODE     | TERMINATION DESCRIPTION                  | RoHS COMPLIANT | VISHAY GREEN |
| X                    | Ni barrier 100 % tin plated matte finish | Yes            | Yes          |
| E                    | AgPd                                     | Yes            | Yes          |
| F                    | AgPd                                     | Yes            | No           |

**DIMENSIONS** in inches (millimeters)


| CASE CODE | STYLE  | LENGTH (L)                                    | WIDTH (W)                                     | MAXIMUM THICKNESS (T) | TERMINATION (P) |                 |
|-----------|--------|---|---|-----------------------|-----------------|-----------------|
|           |        |   |   |                       | MINIMUM         | MAXIMUM         |
| 0402      | VJ0402 | 0.040 + 0.004/- 0.002<br>(1.00 + 0.10/- 0.05) | 0.020 + 0.004/- 0.002<br>(0.50 + 0.10/- 0.05) | 0.024<br>(0.60)       | 0.004<br>(0.10) | 0.016<br>(0.41) |
| 0603      | VJ0603 | 0.063 ± 0.006<br>(1.60 ± 0.15)                | 0.031 ± 0.006<br>(0.80 ± 0.15)                | 0.036<br>(0.92)       | 0.012<br>(0.30) | 0.018<br>(0.46) |
| 0805      | VJ0805 | 0.079 ± 0.008<br>(2.00 ± 0.20)                | 0.049 ± 0.008<br>(1.25 ± 0.20)                | 0.057<br>(1.45)       | 0.010<br>(0.25) | 0.028<br>(0.71) |
| 1206      | VJ1206 | 0.126 ± 0.010<br>(3.20 ± 0.25)                | 0.063 ± 0.010<br>(1.60 ± 0.25)                | 0.067<br>(1.70)       | 0.010<br>(0.25) | 0.028<br>(0.71) |
| 1210      | VJ1210 | 0.126 ± 0.010<br>(3.20 ± 0.25)                | 0.098 ± 0.010<br>(2.50 ± 0.25)                | 0.067<br>(1.70)       | 0.010<br>(0.25) | 0.028<br>(0.71) |



| SELECTION CHART            |        |        |    |     |        |    |     |        |    |     |        |    |                       |    |
|----------------------------|--------|--------|----|-----|--------|----|-----|--------|----|-----|--------|----|-----------------------|----|
| DIELECTRIC                 |        | X8R    |    |     |        |    |     |        |    |     |        |    |                       |    |
| STYLE                      |        | VJ0402 |    |     | VJ0603 |    |     | VJ0805 |    |     | VJ1206 |    | VJ1210 <sup>(1)</sup> |    |
| CASE CODE                  |        | 0402   |    |     | 0603   |    |     | 0805   |    |     | 1206   |    | 1210                  |    |
| VOLTAGE (V <sub>DC</sub> ) |        | 25     | 50 | 100 | 25     | 50 | 100 | 25     | 50 | 100 | 25     | 50 | 25                    | 50 |
| VOLTAGE CODE               |        | X      | A  | B   | X      | A  | B   | X      | A  | B   | X      | A  | X                     | A  |
| CAP. CODE                  | CAP.   |        |    |     |        |    |     |        |    |     |        |    |                       |    |
| 331                        | 330 pF | ••     | •• | ••  |        |    |     |        |    |     |        |    |                       |    |
| 391                        | 390 pF | ••     | •• | ••  |        |    |     |        |    |     |        |    |                       |    |
| 471                        | 470 pF | ••     | •• | ••  |        | •• | ••  | ••     | •• | ••  |        |    |                       |    |
| 561                        | 560 pF | ••     | •• | ••  |        | •• | ••  | ••     | •• | ••  |        |    |                       |    |
| 681                        | 680 pF | ••     | •• | ••  | ••     | •• | ••  | ••     | •• | ••  |        |    |                       |    |
| 821                        | 820 pF | ••     | •• | ••  | ••     | •• | ••  | ••     | •• | ••  |        |    |                       |    |
| 102                        | 1.0 nF | ••     | •• | ••  | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 122                        | 1.2 nF | ••     | •• | ••  | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 152                        | 1.5 nF | ••     | •• |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 182                        | 1.8 nF | ••     | •• |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 222                        | 2.2 nF | ••     | •• |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 272                        | 2.7 nF | ••     |    |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 332                        | 3.3 nF | ••     |    |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 392                        | 3.9 nF | ••     |    |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 472                        | 4.7 nF | ••     |    |     | ••     | •• | ••  | ••     | •• | ••  | •      | •  |                       |    |
| 562                        | 5.6 nF | ••     |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  |                       |    |
| 682                        | 6.8 nF | ••     |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  |                       |    |
| 822                        | 8.2 nF |        |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  |                       |    |
| 103                        | 10 nF  |        |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  | •                     | •  |
| 123                        | 12 nF  |        |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  | •                     | •  |
| 153                        | 15 nF  |        |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  | •                     | •  |
| 183                        | 18 nF  |        |    |     | ••     | •• |     | ••     | •• | ••  | •      | •  | •                     | •  |
| 223                        | 22 nF  |        |    |     | ••     |    |     | ••     | •• | •   | •      | •  | •                     | •  |
| 273                        | 27 nF  |        |    |     | ••     |    |     | ••     | •  | •   | •      | •  | •                     | •  |
| 333                        | 33 nF  |        |    |     | ••     |    |     | ••     | •  |     | •      | •  | •                     | •  |
| 393                        | 39 nF  |        |    |     |        |    |     | ••     | •  |     | •      | •  | •                     | •  |
| 473                        | 47 nF  |        |    |     |        |    |     | •      | •  |     | •      | •  | •                     | •  |
| 563                        | 56 nF  |        |    |     |        |    |     | •      | •  |     | •      | •  | •                     | •  |
| 683                        | 68 nF  |        |    |     |        |    |     | •      |    |     | •      | •  | •                     | •  |
| 823                        | 82 nF  |        |    |     |        |    |     | •      |    |     | •      | •  | •                     | •  |
| 104                        | 100 nF |        |    |     |        |    |     | •      |    |     | •      | •  | •                     | •  |
| 124                        | 120 nF |        |    |     |        |    |     |        |    |     | •      | •  | •                     | •  |
| 154                        | 150 nF |        |    |     |        |    |     |        |    |     | •      |    | •                     | •  |
| 184                        | 180 nF |        |    |     |        |    |     |        |    |     | •      |    | •                     | •  |
| 224                        | 220 nF |        |    |     |        |    |     |        |    |     | •      |    | •                     | •  |
| 274                        | 270 nF |        |    |     |        |    |     |        |    |     |        |    | •                     | •  |
| 334                        | 330 nF |        |    |     |        |    |     |        |    |     |        |    | •                     | •  |
| 394                        | 390 nF |        |    |     |        |    |     |        |    |     |        |    | •                     |    |

**Notes**

- <sup>(1)</sup> See soldering recommendations within this data book, or visit [www.vishay.com/doc245034](http://www.vishay.com/doc245034)
- Plastic tape, •• Paper tape
- RoHS-compliant

| X8R PACKAGING QUANTITIES <sup>(1)</sup> |           |                    |           |                                 |        |
|---|-----------|--------------------|-----------|---------------------------------|--------|
| CASE CODE                               | TAPE SIZE | 7" REEL QUANTITIES |           | 11 1/4" AND 13" REEL QUANTITIES |        |
|   |           | PACKAGING CODE     |           | PACKAGING CODE                  |        |
|   |           | "C"/"O"            | "T"       | "P"/"I"                         | "R"    |
| 0402                                    | 8 mm      | 5000               | n/a       | 10 000                          | n/a    |
| 0603                                    | 8 mm      | 4000               | n/a       | 10 000                          | n/a    |
| 0805 <sup>(2)</sup>                     | 8 mm      | 3000               | 3000      | 10 000                          | 10 000 |
| 1206 <sup>(2)</sup>                     | 8 mm      | n/a                | 3000/2500 | 10 000                          | 10 000 |
| 1210 <sup>(2)</sup>                     | 8 mm      | n/a                | 3000/2000 | 10 000                          | 10 000 |

**Notes**

- <sup>(1)</sup> Reference: EIA standard RS481 - "Taping of Surface Mount Components for Automatic Placement"
- <sup>(2)</sup> Packaging "C"/"P"/"O"/"I" and "T"/"R" or lower quantities can depend from product thickness







**STORAGE AND HANDLING CONDITIONS**

- (1) Store the components at 5 °C to + 40 °C ambient temperature and ≤ 70 % related humidity conditions.
- (2) The product is recommended to be used within a time-frame of 2 years after shipment.  
Check solderability in case extended shelf life beyond the expiry date is needed.

Precautions:

- a. Do not store products in an environment containing corrosive elements, especially where chloride gas, sulfide gas, acid, alkali, salt or the like are present. This may cause corrosion or oxidation of the terminations, which can easily lead to poor soldering.
- b. Store products on the shelf and avoid exposure to moisture or dust.
- c. Do not expose products to excessive shock, vibration, direct sunlight and so on.

**X8R DIELECTRIC - TYPICAL PARAMETERS**





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.