

Laird TECHNOLOGIES®

Innovative **Technology** for a **Connected** World

No Snag Gasket
Fingerstock Gaskets


Part No. 77-079, 83, 84, 85, 86, 91, 92


Part No. 77-012, 14, 33, 78, 81, 82

FINGERSTOCK GASKETS AND METAL GROUNDING PRODUCTS

As the world's leading fabricator of fingerstock, Laird Technologies has developed highly sophisticated, and often proprietary, shielding and grounding technology.

Our innovations are necessary to achieve outstanding combinations of performance parameters. From a vast selection of product configurations, platings and mounting techniques, to a full range of low compression force requirements and high transfer impedance characteristics, there is a Laird Technologies gasket or grounding product just right for the job.

Laird Technologies No Snag Series shielding gaskets offer the designer a low compression, no snag design. Provided with Sticky Fingers® self-adhesive tape, these beryllium copper shielding gaskets provide easy and secure mounting.

FEATURES

- Shielding effectiveness of > 100 db (77-012) and 80 dB (77-014) for a 100 MHz plane wave
- Easy, cost-effective installation since fasteners are not required
- Ideal as an all-purpose contact strip for metal cabinets and electronic enclosures
- Available in a wide variety of plated finishes
- Supplied in standard 24.000 in. (609.600 mm) lengths or other specified lengths

global solutions: local support™

USA: +1.866.928.8181
Europe: +49.0.8031.2460.0
Asia: +86.755.2714.1166


www.lairdtech.com


Laird TECHNOLOGIES®


Innovative **Technology** for a **Connected** World

No Snag Gasket
Fingerstock Gaskets

NO SNAG GASKET DIMENSIONS







SERIES	A	B	C	D	E	H	M RADIUS	LENGTH APPROX
77-012	0.320	0.110	0.002	0.187	0.018	0.210	0.110	24.000
	(8.128)	(2.794)	(0.051)	(4.750)	(0.457)	(5.334)	(2.794)	(609.600)
*77-014	0.600	0.220	0.004	0.375	0.032	0.280	0.180	24.000
	(15.240)	(5.588)	(0.102)	(9.525)	(0.813)	(7.112)	(4.572)	(609.600)
77-033	0.370	0.130	0.002	0.250	0.025	0.210	0.110	16.000
	(9.398)	(3.302)	(0.051)	(6.350)	(0.635)	(5.334)	(2.794)	(406.400)
*77-078	0.800	0.320	0.004	0.375	0.032	0.440	0.190	24.000
	(20.320)	(8.128)	(0.102)	(9.525)	(0.813)	(11.176)	(4.826)	(609.600)
*77-079	0.320	0.100	0.035	0.156	0.018	0.210	0.100	16.000
	(8.128)	(2.540)	(0.889)	(3.962)	(0.457)	(5.334)	(2.540)	(406.400)
77-081	0.280	0.110	0.002	0.187	0.018	0.180	0.100	24.000
	(7.112)	(2.794)	(0.051)	(4.750)	(0.457)	(4.572)	(2.540)	(609.600)
*77-082	1.100	0.400	0.005	0.500	0.040	0.780	0.420	24.000
	(27.940)	(10.160)	(0.127)	(12.700)	(1.016)	(19.812)	(10.668)	(609.600)

SERIES	A	B	C	D	E	H	M RADIUS	LENGTH APPROX
*77-083	0.370	0.130	0.004	0.125	0.025	0.100	0.202	16.000
	(9.398)	(3.302)	(0.102)	(3.175)	(0.635)	(2.540)	(5.131)	(406.400)
*77-084	0.370	0.130	0.004	0.250	0.025	0.100	0.202	16.000
	(9.398)	(3.302)	(0.102)	(6.350)	(0.635)	(2.540)	(5.131)	(406.400)
*77-085	0.600	0.220	0.004	0.375	0.032	0.150	0.295	18.000
	(15.240)	(5.588)	(0.102)	(9.525)	(0.813)	(3.810)	(7.493)	(457.200)
*77-086	0.320	0.090	0.003	0.187	0.018	0.210	0.100	16.000
	(8.128)	(2.286)	(0.762)	(4.750)	(0.457)	(5.334)	(2.540)	(406.400)
*77-091	0.600	0.220	0.004	0.375	0.032	0.780	0.150	18.000
	(15.240)	(5.588)	(0.102)	(9.525)	(0.813)	(19.812)	(3.810)	(457.200)
*77-092	0.600	0.220	0.004	0.187	0.032	0.295	0.150	18.000
	(15.240)	(5.588)	(0.102)	(4.750)	(0.813)	(7.493)	(3.810)	(457.200)

* Available in UltraSoft® low compeession version as -78.

All dimensions shown are in inches (millimeters) unless otherwise specified.

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.