

Features

- Output Voltage:
1.5V/1.8V/2.5V/2.8V/3.0V/3.3V/5V
- High Output Voltage Accuracy: $\pm 2\%$
- Low Voltage Drop: 330mV(Typ.)
($V_{OUT}=2.5V@I_{OUT}=150mA$)
- Maximum Input Voltage: 7.0V
- Guaranteed Output Current: 150mA
- Low Power Consumption: 10 μ A (Typ.)
- High ripple rejection: 70dB (1kHz@ $I_{OUT}=30mA$)
- Power-Saving Shutdown Mode
- Current limiting
- SOT23-5 and SOT89 Package

Applications

- Portable communication equipment
- Portable music player
- Electrical appliances such as cameras, VCRs and camcorders
- Battery-powered equipment

General Description

The HT75Bxx series are CMOS-based voltage regulator devices with high output voltage accuracy, low quiescent current, low on-resistance, and high ripple rejection. Each of the devices includes a voltage reference, error amplifier, resistor-network for voltage setting, current limit circuit, chip enable circuit and so on.

The HT75Bxx's current limiters' fold back circuit also operates as a short circuit protect function for the output current limiter.


These devices offer the benefits of low dropout voltage as well as possessing a chip-enable function. Additional features include an exceptionally low 10 μ A quiescent current in addition to excellent line and load transient response characteristics. With these features the devices will be appropriate for use in a wide range of application among which would include hand-held communication equipment.

The space-saving SOT23-5, SOT89 package will be an attractive additional feature for pocket and hand-held applications.

Selection Table

Part No.	Output Voltage	Tolerance	Package
HT75B15	1.5V	$\pm 2\%$	SOT23-5 SOT89
HT75B18	1.8V		
HT75B25	2.5V		
HT75B28	2.8V		
HT75B30	3.0V		
HT75B33	3.3V		
HT75B50	5.0V		

Block Diagram



Absolute Maximum Ratings (Note1)

Maximum Input Supply Voltage.....	7.5V
Ambient Temperature Range.....	-40°C ~ +85°C


Thermal Information

Symbol	Parameter	Package	Max.	Unit
Q _{JA}	Thermal Resistance (Junction to Ambient) (Assume no ambient airflow, no heat sink)	SOT23-5	500	°C/W
		SOT89	200	°C/W
P _D	Power Dissipation	SOT23-5	0.20	W
		SOT89	0.50	W


Note: P_D is measured at T_a= 25°C

Pin Assignment

SOT23-5



SOT89



SOT23-5 Pin Descriptions		
Pin No.	Symbol	Description
1	VIN	Input Pin
2	GND	Ground Pin
3	CE	Chip Enable Pin - high enable
4	NC	No Connection
5	VOUT	Output Pin

SOT89 Pin Descriptions		
Pin No.	Symbol	Description
1	GND	Ground Pin
2	VIN	Input Pin
3	VOUT	Output Pin

Electrical Characteristics

$T_a=25^{\circ}\text{C}$, $V_{\text{IN}}=V_{\text{OUT}}+1\text{V}$, $I_{\text{OUT}}=30\text{mA}$, unless otherwise specified (Note2)


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_{IN}	Input Voltage	$1.5\text{V} \leq V_{\text{OUT}} \leq 5\text{V}$	2.5	—	7	V
ΔV_{OUT}	Output Voltage Tolerance	$1\text{mA} \leq I_{\text{OUT}} \leq 30\text{mA}$ $1.5\text{V} \leq V_{\text{OUT}} \leq 5.0\text{V}$	-2	—	+2	%
ΔV_{LINE}	Line Regulation	$V_{\text{OUT}}+0.5\text{V} \leq V_{\text{IN}} \leq 7.0\text{V}$, $I_{\text{OUT}}=10\text{mA}$	—	0.02	0.1	%/V
ΔV_{LOAD}	Load Regulation (Note 3)	$1\text{mA} \leq I_{\text{OUT}} \leq 150\text{mA}$				mV
		$1.5\text{V} \leq V_{\text{OUT}} \leq 1.8\text{V}$	—	13	30	
		$2.5\text{V} \leq V_{\text{OUT}} \leq 3.0\text{V}$	—	14	35	
V_{DROP}	Dropout Voltage (Note 4)	$\Delta V_{\text{OUT}}=2\%$ $I_{\text{OUT}}=150\text{mA}$				V
		$V_{\text{OUT}}=1.5\text{V}$	—	0.54	0.86	
		$V_{\text{OUT}}=1.8\text{V}$	—	0.44	0.65	
I_{SHORT}	Short Current Limit	$V_{\text{OUT}}=0\text{V}$	—	50	—	mA
			—	10	20	
I_{SS}	Supply Current	$I_{\text{OUT}}=0\text{mA}$	—	10	20	μA
I_{SD}	Shutdown Current	$\text{CE}=\text{GND}$	—	0.1	1	μA
V_{IH}	CE Input High Threshold	$V_{\text{OUT}}+1\text{V} \leq V_{\text{IN}} \leq 7\text{V}$	1	—	7	V
V_{IL}	CE Input Low Threshold	$V_{\text{OUT}}+1\text{V} \leq V_{\text{IN}} \leq 7\text{V}$	0	—	0.3	V
R_{R}	Ripple Rejection	$I_{\text{OUT}}=30\text{mA}$				dB
		$f=1\text{kHz}$	—	70	—	
V_{NOISE}	Output Noise	Bandwidth=10Hz to 100kHz	—	30	—	μV_{rms}
T_{C}	Temperature Coefficient	$T_{\text{C}} = \frac{\Delta V_{\text{OUT}}}{\Delta T_a \cdot V_{\text{OUT}}}$ $I_{\text{OUT}}=30\text{mA}$, $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$	—	± 100	—	ppm/ $^{\circ}\text{C}$

Note 1. Absolute maximum ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but do not guarantee specific performance limits. The guaranteed specifications apply only for the test conditions listed.






- Specifications are production tested at T_a =room temperature. Specifications over the -40°C to 85°C operating temperature range are assured by design, characterization and correlation with Statistical Quality Controls (SQC).
- Load regulation is measured at constant junction temperature, using pulse testing with a short ON time. The devices are guaranteed up to the maximum power dissipation. Power dissipation is determined by the input/output differential voltage and the output current. Guaranteed maximum power dissipation will not be available over the full input/output range. The maximum allowable power dissipation at any ambient temperature is $P_D=(T_{\text{J(MAX)}}-T_a)/\theta_{\text{JA}}$.
- Dropout voltage is the minimum input to output voltage differential needed to maintain regulation at a specified output current. Under dropout conditions, the output voltage will be equal to: $V_{\text{IN}} - V_{\text{DROP}}$.

Typical Characteristics


Output Voltage vs. Input Voltage








Output Voltage vs. Temperature





Supply Current vs. Temperature




Dropout Voltage vs. Output Current



Supply Current vs. Input Voltage




Ripple Rejection vs. Frequency




HT75B15 $V_{OUT}=1.5V$, $V_{IN}=2.5V$, $I_{OUT}=30, 50, 100mA$


Load Transient Response



HT75B15 $V_{IN}=2.5V$, $C_{IN}=C_{OUT}=1\mu F$, CH1= $V_{OUT(ac)}$;
CH2= I_{OUT}




HT75B15 $V_{IN}=2.5V$, $C_{IN}=C_{OUT}=1\mu F$, CH1= $V_{OUT(ac)}$;
CH2= I_{OUT}




HT75B25 $V_{IN}=3.5V$, $C_{IN}=C_{OUT}=1\mu F$, CH1= $V_{OUT(ac)}$;
CH2= I_{OUT}


Input Transient Response




HT75B25 $V_{IN} = 3.5V$, $C_{IN} = C_{OUT} = 1\mu F$, CH1 = $V_{OUT(ac)}$; CH2 = I_{OUT}




HT75B15 $C_{IN} = 0\mu F$, $C_{OUT} = 1\mu F$, CH1 = $V_{OUT(ac)}$; CH2 = V_{IN}




HT75B50 $V_{IN} = 6.0V$, $C_{IN} = C_{OUT} = 1\mu F$, CH1 = $V_{OUT(ac)}$; CH2 = I_{OUT}



HT75B25 $C_{IN} = 0\mu F$, $C_{OUT} = 1\mu F$, CH1 = $V_{OUT(ac)}$; CH2 = V_{IN}




HT75B50 $V_{IN} = 6.0V$, $C_{IN} = C_{OUT} = 1\mu F$, CH1 = $V_{OUT(ac)}$; CH2 = I_{OUT}




HT75B50 $C_{IN} = 0\mu F$, $C_{OUT} = 1\mu F$, CH1 = $V_{OUT(ac)}$; CH2 = V_{IN}

Turn-on/off Speed With CE Pin





HT75B50 V_{IN}=6.0V, C_{IN}=C_{OUT}=1μF, CH1=V_{CE};
CH2=V_{OUT}



HT75B50 V_{IN}=6.0V, C_{IN}=C_{OUT}=1μF, CH1=V_{CE};
CH2=V_{OUT}


Application Circuit



Package Information


Note that the package information provided here is for consultation purposes only. As this information may be updated at regular intervals users are reminded to consult the Holtek website (<http://www.holtek.com.tw/english/literature/package.pdf>) for the latest version of the package information.

5-pin SOT23-5 Outline Dimensions




Symbol	Dimensions in inch		
	Min.	Nom.	Max.
A	0.039	—	0.051
A1	—	—	0.004
A2	0.028	—	0.035
b	0.014	—	0.020
C	0.004	—	0.010
D	0.106	—	0.122
E	0.055	—	0.071
e	—	0.075	—
H	0.102	—	0.118
L	0.015	—	—
θ	0°	—	9°

Symbol	Dimensions in mm		
	Min.	Nom.	Max.
A	1.00	—	1.30
A1	—	—	0.10
A2	0.70	—	0.90
b	0.35	—	0.50
C	0.10	—	0.25
D	2.70	—	3.10
E	1.40	—	1.80
e	—	1.90	—
H	2.60	—	3.0
L	0.37	—	—
θ	0°	—	9°

3-pin SOT89 Outline Dimensions


Symbol	Dimensions in inch		
	Min.	Nom.	Max.
A	0.173	—	0.181
B	0.059	—	0.072
C	0.090	—	0.102
D	0.035	—	0.047
E	0.155	—	0.167
F	0.014	—	0.019
G	0.017	—	0.022
H	—	0.059	—
I	55	—	63
J	14	—	17

Symbol	Dimensions in mm		
	Min.	Nom.	Max.
A	4.39	—	4.60
B	1.50	—	1.83
C	2.29	—	2.59
D	0.89	—	1.19
E	3.94	—	4.24
F	0.36	—	0.48
G	0.43	—	0.56
H	—	1.50	—
I	1.40	—	1.60
J	0.36	—	0.43


Reel Dimensions

SOT23-5

Symbol	Description	Dimensions in mm
A	Reel Outer Diameter	178.0±1.0
B	Reel Inner Diameter	62.0±1.0
C	Spindle Hole Diameter	13.0±0.2
D	Key Slit Width	2.50±0.25
T1	Space Between Flang	8.4 ^{+1.5/-0.0}
T2	Reel Thickness	11.4 ^{+1.5/-0.0}

SOT89-3

Symbol	Description	Dimensions in mm
A	Reel Outer Diameter	180.0±1.0
B	Reel Inner Diameter	62.0±1.5
C	Spindle Hole Diameter	12.75 ^{+0.15/-0.00}
D	Key Slit Width	1.9±0.15
T1	Space Between Flang	12.4 ^{+0.2/-0.0}
T2	Reel Thickness	17.0 ^{+0.0/-0.4}

Carrier Tape Dimensions



SOT23-5

Symbol	Description	Dimensions in mm
W	Carrier Tape Width	8.0±0.3
P	Cavity Pitch	4.0±0.1
E	Perforation Position	1.75±0.10
F	Cavity to Perforation(Width Direction)	3.50±0.05
D	Perforation Diameter	1.5 ^{+0.1/-0.0}
D1	Cavity Hole Diameter	1.5 ^{+0.1/-0.0}
P0	Perforation Pitch	4.0±0.1
P1	Cavity to Perforation(Length Direction)	2.00±0.05
A0	Cavity Length	3.15±0.10
B0	Cavity Width	3.2±0.1
K0	Cavity Depth	1.4±0.1
t	Carrier Tape Thickness	0.20±0.03
C	Cover Tape Width	5.3±0.1

SOT89-3

Symbol	Description	Dimensions in mm
W	Carrier Tape Width	12.0 ^{+0.3/-0.1}
P	Cavity Pitch	8.0±0.1
E	Perforation Position	1.75±0.10
F	Cavity to Perforation(Width Direction)	5.50±0.05
D	Perforation Diameter	1.5±0.1
D1	Cavity Hole Diameter	1.5±0.1
P0	Perforation Pitch	4.0±0.1
P1	Cavity to Perforation(Length Direction)	2.0±0.1
A0	Cavity Length	4.8±0.1
B0	Cavity Width	4.5±0.1
K0	Cavity Depth	1.8±0.1
t	Carrier Tape Thickness	0.300±0.013
C	Cover Tape Width	9.3±0.1

Holtek Semiconductor Inc. (Headquarters)

No.3, Creation Rd. II, Science Park, Hsinchu, Taiwan

Tel: 886-3-563-1999

Fax: 886-3-563-1189

<http://www.holtek.com.tw>

Holtek Semiconductor Inc. (Taipei Sales Office)

4F-2, No. 3-2, YuanQu St., Nankang Software Park, Taipei 115, Taiwan

Tel: 886-2-2655-7070

Fax: 886-2-2655-7373

Fax: 886-2-2655-7383 (International sales hotline)

Holtek Semiconductor Inc. (Shenzhen Sales Office)

5F, Unit A, Productivity Building, No.5 Gaoxin M 2nd Road, Nanshan District, Shenzhen, China 518057

Tel: 86-755-8616-9908, 86-755-8616-9308

Fax: 86-755-8616-9722

Holtek Semiconductor (USA), Inc. (North America Sales Office)

46729 Fremont Blvd., Fremont, CA 94538, USA

Tel: 1-510-252-9880

Fax: 1-510-252-9885

<http://www.holtek.com>

Copyright© 2011 by HOLTEK SEMICONDUCTOR INC.

The information appearing in this Data Sheet is believed to be accurate at the time of publication. However, Holtek assumes no responsibility arising from the use of the specifications described. The applications mentioned herein are used solely for the purpose of illustration and Holtek makes no warranty or representation that such applications will be suitable without further modification, nor recommends the use of its products for application that may present a risk to human life due to malfunction or otherwise. Holtek's products are not authorized for use as critical components in life support devices or systems. Holtek reserves the right to alter its products without prior notification. For the most up-to-date information, please visit our web site at <http://www.holtek.com.tw>.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.