

## IR25 Dual Gas Series Datasheet

### Infrared Dual Gas Sensor for Mining (Portable and Fixed Systems)

The SGX infrared sensors use the proven Non-Dispersive Infrared (NDIR) principle to detect and monitor the presence of gases. With an infrared source and specific filtering on the pyroelectric detectors mounted inside the optical/gas cavity, individual gases or types of gas can be identified and their concentrations determined.

These sensors are suitable for reliable monitoring of gas levels in mining applications where the sensor size is restricted and require a flameproof enclosure for hazardous environments.

The IR25 Series contain two active detector elements for simultaneous monitoring of Carbon Dioxide and Methane or Hydrocarbon mixtures in the same size housing as some of the single gas sensors from the IR2xxx series sensors, making the sensor more cost effective than two separate sensors.


The IR25xx Series share the same build and performance standard as the IR15xx Series, but are labelled as being intrinsically safe for methane monitoring in mining applications.

### APPLICATIONS

- Mining

### FEATURES

- For detection of the following gases:
  - Carbon Dioxide & Hydrocarbons,
  - Hydrocarbons Mixtures
- Gas concentration ranges:
  - 0 - 5% Carbon Dioxide (also suitable for 0 to 0.5%v/v)
  - 0 - 100% Carbon Dioxide (also suitable for 0 to 10%)
  - 0 - 100%v/v Hydrocarbons (also suitable for 0 to 100%LEL)
- 19mm sensor height
- Embedded thermistor for improved temperature compensation
- Diffused gas sampling via mesh
- Low power
- Reference channel for self-compensation
- Special gold plated optical gas cavity for stable signal levels
- Operational in varying temperature, pressure and humidity
- Fast response
- Rugged stainless steel construction
- No moving parts
- Immunity from 'poisoning'
- Reliable fail-safe operation
- Certified: ATEX & IECEx



### OPERATION

To operate, the sensors must be interfaced to a suitable circuit for power supply, output amplification and signal processing. Sensor outputs require linearisation and compensation for ambient temperature variation using algorithms in the system firmware. This is necessary for sensors to meet their full performance specification. An embedded temperature sensor facilitates this compensation on certain types. Further compensation for pressure changes can also be made in an algorithm, provided there is a suitable input from a pressure sensor.

A set of Application Notes is available from the SGX Sensortech Ltd website, to explain more about NDIR gas sensing and provide advice for the end-user on interfacing the sensors and processing signals.

### TECHNICAL SPECIFICATION

#### Mechanical

Dimensions	See Outlines
Body material	Stainless Steel
Approximate Weight	35g

#### Environmental

Ambient temperature range for operation: storage:	-20°C to +60°C -20°C to +55°C
Operational pressure range	30kPa to 130kPa
Humidity range for operation and storage	0 to 95% RH (Non-condensing)

#### Electrical

DC supply to detectors	3V to 5V
Typical power	180mW @ 5V
IR Source Supply (Recommended)	+5V, 60mA (Square Wave at 4Hz, 50% duty cycle)

Whilst SGX has taken care to ensure the accuracy of the information contained herein it accepts no responsibility for the consequences of any use thereof and also reserves the right to change the specification of goods without notice. SGX accepts no liability beyond the set out in its standard conditions of sale in respect of infringement of third party patents arising from the use of SGX products in accordance with information contained herein. In case of modification of the product, SGX disclaims all liability.

## CONFIGURATIONS

Sensor Type	Target Gas 1			Target Gas 2			Application
	Gas	Concentration Range *		Gas	Concentration Range *		
		Highest	Lowest		Highest	Lowest	
IR25TT	Carbon Dioxide	0 to 5%	0 to 0.5%	Hydrocarbons	0 to 100%	0 to 100%LEL	Mining
IR25TT-M							

\* The Highest Concentration Range is the highest range the sensor is suitable. The Lowest Concentration Range is the lowest range the sensor is suitable. The use of the sensor beyond these ranges will affect the sensor's performance.

### IR25TT

The IR25TT can be used for Mining applications to monitor of both relatively low concentrations of carbon dioxide and simultaneous %LEL and %v/v concentrations of methane. The sensor contains a broadband hydrocarbon detector which is less cross sensitive to other hydrocarbons but does have a slightly higher response to humidity, when compared with the IR15TT-M.

### IR25TT-M

The IR25TT-M is very similar to the IR25TT except that a narrowband hydrocarbon detector is used. The narrowband detector has a slightly lower response to humidity than the IR25TT, but is generally more cross-sensitive to other hydrocarbons.

## HANDLING PRECAUTIONS

1. Do not allow sensors to fall on the floor. This could cause IR Source filament breakage, damage to the pins and the gas entrance aperture.
2. Do not apply mechanical force against the gas entrance aperture.
3. Do not immerse sensors in water or other fluids.
4. Protect the gas entrance aperture against dust ingress and sprayed materials.
5. Anti-static handling precautions must be taken.

## PERFORMANCE

For test purposes, all data taken using the following conditions:

- Performance as tested in the SGX IR-EK2 Evaluation Kit directly after calibration.
- SGX linearisation and temperature compensation algorithms applied; see Infrared Sensor Application Notes.
- IR Source Voltage 5V, square wave, at 4 Hz and 50% duty cycle. Running the IR Source at 3V will decrease performance due to lower output signals.
- Ambient temperature (20°C) and pressure (101 kPa).
- All gases diluted in dry nitrogen.
- Performance for the Hydrocarbons refers to Methane only. Most other hydrocarbons will have an improved performance.
- Performance data is the same for the supported IR Source variants ("\_1" variants).
- Refer to Application Notes for more information.

Sensor type	IR25TT		IR25TT-M	
	CO <sub>2</sub>	Methane <sup>(5)</sup> / Hydrocarbons	CO <sub>2</sub>	Methane <sup>(5)</sup> / Hydrocarbons
Concentration Range	Refer to Configurations Table			
Warm-up Times	<20 sec to operate <60 sec for Zero ±1% of Full Scale,			
Maximum Response Time (T <sub>90</sub> ) <sup>(1)</sup>	20 sec			
Peak-to-Peak Outputs (in N <sub>2</sub> ) <sup>(2)</sup> Active (mV): Reference (mV):	10 to 29	24 to 58	10 to 29	12 to 47
	18 to 43		18 to 43	


Sensor type	IR25TT		IR25TT-M	
Gas	CO <sub>2</sub>	Methane <sup>(5)</sup> / Hydrocarbons	CO <sub>2</sub>	Methane <sup>(5)</sup> / Hydrocarbons
<b>Sensitivity to Standard Test Gas <sup>(2) (3)</sup></b> Minimum Absorbance: Maximum Absorbance:	0.25 0.50	0.07 0.15	0.25 0.50	0.07 0.15
<b>Typical Sensitivity for Gas Range <sup>(3)</sup></b>	Refer to Fractional Absorbance Curves			
<b>Minimum Detection Level <sup>(4)</sup></b>	2ppm CO <sub>2</sub>	30ppm CH <sub>4</sub>	2ppm CO <sub>2</sub>	30ppm CH <sub>4</sub>
<b>Maximum deviation from linearity (±) <sup>(6)</sup></b> 0 to 0.5%v/v Range: 0 to 2%v/v Range: 0 to 2.5%v/v Range: 0 to 5%v/v Range: 0 to 10%v/v Range: 0 to 100%v/v Range:	0.01%v/v 0.05%v/v ----- 0.10%v/v ----- -----	----- ----- ----- 0.15%v/v ----- 5%v/v	0.01%v/v 0.05%v/v ----- 0.10%v/v ----- -----	----- ----- ----- 0.15%v/v ----- 5%v/v
<b>Temperature Variation (± ppm / °C) <sup>(7)</sup></b> Zero and Concentration Range Maximum (-20°C to +55°C) Zero: 0.5%v/v: 2%v/v: 2.5%v/v: 5%v/v: 10%v/v: 100%v/v:	10 25 100 ----- 250 ----- -----	20 ----- ----- 150 ----- 1500	10 25 100 ----- 250 ----- -----	25 ----- ----- 200 ----- 2000
<b>Short Term Stability (±) <sup>(8)</sup>:</b> Zero: 0.5%v/v: 2%v/v: 2.5%v/v: 5%v/v: 10%v/v: 100%v/v:	5 ppm 0.01%v/v 0.05%v/v ----- 0.10%v/v ----- -----	0.01%v/v ----- ----- 0.10%v/v ----- 2%v/v	5 ppm 0.01%v/v 0.05%v/v ----- 0.10%v/v ----- -----	0.01%v/v ----- ----- 0.08%v/v ----- 2%v/v
<b>Humidity Response (+) <sup>(9)</sup></b> Zero: 0.5%v/v: 2%v/v: 2.5%v/v: 5%v/v: 10%v/v: 100%v/v:	Negligible ----- ----- ----- ----- ----- -----	0.15%v/v ----- ----- 0.30%v/v ----- 2%v/v	Negligible ----- ----- ----- ----- ----- -----	0.10%v/v ----- ----- 0.25%v/v ----- 2%v/v
<b>Pressure Effects <sup>(10)</sup></b>	Sensors shall meet specification within a ±5% change in ambient pressure from the ambient pressure during calibration			
<b>MTBF (IR Source only)</b>	>10 years for 5 V operation, >20 years for 3 V operation			
<b>Vibration</b>	Conforms to EN 60079-29-1			
<b>Ingress Protection</b>	Requires extra protection depending on application			

- (1) Based upon an immediate step change in concentration at the aperture of the sensor.
- (2) Production Test Limits, using standard test gases of Dry Nitrogen, 2%v/v Carbon Dioxide and 5%v/v Methane, where appropriate.
- (3) A 0.30 absorbance is equivalent to a 30% decrease in the Active peak-to-peak output.
- (4) The minimum detection level is the smallest detectable change in concentration based upon a 2 sigma variation. The best detectable change occurs at 0% gas concentration due to the non-linear output of the detector (see Fractional Absorbance Curves).
- (5) Performance for most hydrocarbons will be better than for methane for equivalent concentrations, as methane is one of the lower sensitive gases compared to other hydrocarbons.
- (6) After linearisation using the recommended method of linearisation and based upon a calibration gas with a concentration >75% of the full-scale.
- (7) Using average Alpha and Beta coefficients based upon test data from the instrument in which the sensor is being tested. Refer to Application Notes for information on calculating Alpha and Beta coefficients. Accuracy can be improved by measuring each sensor over temperature to define specific Alpha or Alpha & Beta coefficients.
- (8) After sensor stabilisation and over a period of 8 hours.
- (9) Difference in response when changed from 0 %RH to 90 %RH.
- (10) Sensors can be used over a greater ambient pressure using pressure compensation of the concentration. An external pressure sensor will be required for this.

## FRACTIONAL ABSORBANCE CURVES

These show the typical sensitivity versus concentration before linearisation for the range of gases. For further explanation, refer to the Infrared Sensor Application Notes.


### Primary Target Gases



### Relative Absorbance of Narrowband and Broadband Detectors to Alkanes

	Methane 5%v/v	Ethane (0.5%v/v)	Propane (0.35%v/v)
Narrowband IR25TT-M	1.00	0.87	0.82
Broadband IR25TT	1.00	0.62	0.52

## CERTIFICATIONS

	<b>Certificate Numbers:</b>	<b>ATEX:</b> Sira 02ATEX2015U <b>IECEX:</b> IECEX SIR 03.0003U	
	<b>Issued by:</b>	Sira Test & Certification Service Rake Lane Ecclestone Chester, CH4 9JN, UK	
	<b>Have been assessed to the following harmonized standards:</b>	<b>EN 60079-0:2012 &amp; IEC 60079-0:2011 (Ed. 6)</b> Electrical apparatus for explosive gas atmospheres – General requirements <b>EN 60079-11:2012 &amp; IEC 60079-11:2011 (Ed. 6)</b> Explosive atmospheres. Equipment protection by intrinsic safety "i"	
	<b>Product Marking:</b>	<b>ATEX:</b> I M1 Ex ia I Ma <b>IECEX:</b> Ex ia I Ma	Ta -20 °C to +60 °C

## INSTRUCTIONS SPECIFIC TO HAZARDOUS AREA INSTALLATIONS

(Ref: EU ATEX Directive 2014/34/EU)

1. The IR25xx Series Gas Sensing Heads are component-approved only and may not be used as stand-alone items in a hazardous area without further protection.
2. The IR25xx Series Gas Sensing Heads shall be protected in service. The Sensing Head shall be mounted in a protective enclosure such that an impact of 7 J in accordance with IEC 60079-0:2007 clause 26.4.2 from any direction shall not cause the impact head to make contact with the Sensing Head.
3. The thermal resistance the IR25xx Series Gas Sensing Head does not exceed 25 K/W; this shall be taken into account when considering its surface temperature and the temperature classification of the equipment into which it is to be incorporated.
4. The IR25xx Series Gas Sensing Heads have not been assessed as a safety device (EHSR 1.5).
5. There are no user-serviceable parts in the component.
6. The end-user/installer shall be aware that the certification of the IR25xx Series Gas Sensing Heads relies on the following materials used in its construction, which are suitable for most common applications:

Enclosure..... Stainless steel

Mesh..... Stainless steel

Bushing..... Epoxy resin

In accordance with the Note in EN60079-0:2006 clause 6.1, the end-user/installer shall inform the manufacturer of any adverse conditions that the IR25xx Series Gas Sensing Heads may encounter. This is to ensure that the IR25xx Series Gas Sensing Heads are not subjected to conditions that may cause degradation of these materials.


7. The IR25xx Series Gas Sensing Head is only certified for use in ambient temperatures between  $-20^{\circ}\text{C}$  and  $+60^{\circ}\text{C}$  and should not be used outside this range.
8. The IR25xx Series products shall be installed/used in accordance with the following restrictions:

Lamp Circuit	$U_i = 7.2 \text{ V}$
Detector Circuit	$U_i = 10 \text{ V}$
Lamp + Detector Circuit	$P_i = 2.71 \text{ W}$
Detector Circuit	$P_i = 1.2 \text{ W}$

9. The IR25xx Series Gas Sensing Heads are dust-proof (IP5x) but offers no protection against the ingress of water. Where protection in excess of IP50 is required, the apparatus into which the IR25xx Series Head is installed shall provide the necessary ingress protection (for example by fitting an external semi-permeable membrane).

## OUTLINE

(All dimensions in millimetres; dimensions without limits are nominal)



## Connections


Pin	Connection
1	IR Source
2	Reference Detector Output
3	IR Source Return
4	Active 1 Detector Output (CO <sub>2</sub> )
5	+V DC Input
6	Active 2 Detector Output (Hydrocarbon)
7	Thermistor
8	0V (connect Internally to Sensor Body)

## Outline Notes

1. Body dimensional tolerances  $\pm 0.1 \text{ mm}$ . Pin dimensional tolerances as indicated.
2. IR25xx Series sensors are designed to press-fit into PCB sockets. The end-user should choose a socket to accommodate the full sensor pin length. This will ensure a stable mechanical location as well as good electrical contact. SGX Sensortech Ltd recommend the Wearn's Cambion type 450-1813-01-03-00 single-pole solder mount socket with through hole, or a suitable equivalent.

## ACCESSORIES

### Dust Membrane (DPP702964BA)



<b>Material</b>	PTFE
<b>Air Flow</b>	$\geq 6.8 \text{ l/hr/cm}^2$ ( $\Delta p$ 10mbar)
<b>Water Intrusion Pressure</b>	$\geq 210 \text{ mbar}$
<b>Laminated PTFE Thickness</b>	0.28 mm (nominal)
<b>Adhesive Thickness</b>	0.19 mm (nominal)
<b>Typical Pore Size</b>	5 $\mu\text{m}$



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.