

## 8434 Multi-Conductor - Special Audio, Communication and Instrumentation Cable



For more Information  
please call

1-800-Belden1



### Description:

25 AWG stranded (7x33) tinned copper conductors, polyethylene insulation, overall Beldfoil® shield (100% coverage), 25 AWG stranded TC drain wire, PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 2       | 25  | 7x33      | TC - Tinned Copper |

#### Insulation

##### Insulation Material:

| Insulation Material | Wall Thickness (mm) | Dia. (mm) |
|---------------------|---------------------|-----------|
| PE - Polyethylene   | 0.3302              | 1.1938    |

#### Inner Shield

##### Inner Shield Material:

| Inner Shield Trade Name | Type | Inner Shield Material                        | Coverage (%) |
|-------------------------|------|--|--------------|
| Beldfoil®               | Tape | Aluminum Foil-Polyester Tape w/Shorting Fold | 100          |

##### Inner Shield Drain Wire AWG:

| AWG |
|-----|
| 25  |

Inner Shield Drain Wire Stranding: Stranded

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

#### Outer Shield

##### Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material        | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil®               | Tape | Aluminum Foil-Polyester Tape | 100          |

#### Outer Jacket

##### Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 0.508                    |

#### Overall Cabling

Overall Nominal Diameter: 4.191 mm

#### Pair

##### Pair Color Code Chart:

| Number | Color                     |
|--------|---------------------------|
| 1      | Shielded: Red & Black     |
| 2      | Unshielded: Green & White |

##### Pair Lay Length & Direction:

| Lay Length (mm) | Twists/ft. (twist/m) |
|-----------------|----------------------|
| 38.09985        | 26.248               |

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +80°C

## 8434 Multi-Conductor - Special Audio, Communication and Instrumentation Cable

|  |              |
|--|--------------|
| Non-UL Temperature Rating:             | 80°C         |
| Bulk Cable Weight:                     | 20.240 Kg/Km |
| Max. Recommended Pulling Tension:      | 182.376 N    |
| Min. Bend Radius (Install)/Minor Axis: | 43.180 mm    |

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

|                                       |            |
|---------------------------------------|------------|
| EU CE Mark:                           | Yes        |
| EU Directive 2000/53/EC (ELV):        | Yes        |
| EU Directive 2002/95/EC (RoHS):       | Yes        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE):       | Yes        |
| EU Directive 2003/11/EC (BFR):        | Yes        |
| CA Prop 65 (CJ for Wire & Cable):     | Yes        |
| MII Order #39 (China RoHS):           | Yes        |

#### Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

### Electrical Characteristics (Overall)

#### Nom. Inductance:

|                   |
|-------------------|
| Inductance (µH/m) |
| 0.6562            |

#### Nom. Capacitance Conductor to Conductor:

|                    |
|--------------------|
| Capacitance (pF/m) |
| 82.025             |

#### Nom. Capacitance Cond. to Other Conductor & Shield:

|                    |
|--------------------|
| Capacitance (pF/m) |
| 131.24             |

#### Nom. Conductor DC Resistance:

|                     |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 149.286             |

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 62.011 Ohm/km

#### Max. Operating Voltage - Non-UL:

|           |
|-----------|
| Voltage   |
| 400 V RMS |

#### Max. Recommended Current:

|                               |
|-------------------------------|
| Current                       |
| 1.3 Amps per conductor @ 25°C |

### Notes (Overall)

**Notes:** Red and Black pair 100% Beldfoil® shielded with drain wire. 3 copper, 4 copper-covered steel strands in each conductor.

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

| Item #        | Putup  | Ship Weight | Color  | Notes | Item Desc       |
|---------------|--------|-------------|--------|-------|-----------------|
| 8434 060U1000 | 305 MT | 6.350 KG    | CHROME |       | 4 #25 PE SH PVC |
| 8434 060100   | 30 MT  | 0.907 KG    | CHROME |       | 4 #25 PE SH PVC |

## METRIC MEASUREMENT VERSION

### 8434 Multi-Conductor - Special Audio, Communication and Instrumentation Cable

|              |        |          |        |   |                 |
|--------------|--------|----------|--------|---|-----------------|
| 8434 0601000 | 305 MT | 5.443 KG | CHROME | C | 4 #25 PE SH PVC |
| 8434 060500  | 152 MT | 3.175 KG | CHROME |   | 4 #25 PE SH PVC |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 09-18-2008

© 2011 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.