SIGN	DATE	DESCRIPTION	APPROVER
1	2/07'06	Wire range is changed from 22-14 AWG to 22-12 AWG	Tony
2	2/07'06	Part No. is changed	Tony
3	3/13'06	Dimension is changed from 5.7 to 3.9	Tony
4	2006.08.3	Screw torque value is changed from 10.4Lb-in to 12Lb-in	梁仁松
5	2006.08.3	Approval is changed	梁仁松
6	06 /05'07	Material is changed	Lucy
7	3/30'09	Structure changed	JODY
8	3/30'09	Temperature changed from -40~105°C to -40~115°C	JODY
9	11/13'12	Change the screw plating specification	Jacky
10	11/13'12	Change the dimensional tolerance	Jacky
11	11/13'12	Add the dimensional label	Jacky
12	08/25'14	The dimensional tolerance is changed from 17.4 ± 0.30 to $17.4^{+0.80}_{-0.30}$	Airy min
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			









P.C.B LAYOUT(Top View)

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:	300 V, 20 A
WITHSTAND VOLTAGE:	AC 2000 V/Min
INSULATION RESISTANCE:	1000 MΩ OR MORE AT DC 500 V
OPERATING TEMPERATURE RANG:	8 -40 °C ~ +115 °C
4 SCREW TORQUE VALUE:	12Lb-In.
1 WIRE RANGE:	22 - 12 AWG
6 1) MOLDED PARTS:	THERMOPLASTIC, UL 94 V-0 BLACK
2) TERMINAL:	BRASS, 0.8t, Tin PLATED
9 3) TERMINAL SCREWS:	STEEL, M3.5
4) COVER MATERIAL:	PC
5 APPROVAL:	c UL us
2 PART NO.:	
Critical dimension:	C

YK 601 xx 2 x x 00G

- NO. OF POLES
  - 04: 4 POLES
  - 05: 5 POLES
  - 06: 6 POLES
  - :
  - 30: 30 POLES
- MARK
  - 0: "@" MARK
  - 1: "ANY" MARK
- TERMINAL & SCREW PLATED
  - 0: TERMINAL & SCREW: G/F
  - 9 1: TERMINAL: G/F, SCREW: Zinc
  - 2: TERMINAL: Sn, SCREW: G/F
  - 9 3: TERMINAL: Sn, SCREW: Zinc
- G:RoHS compliant(lead<4%) in copper alloy

N=Number of contacts

Dimension A&B

DIM A	N×10+3.5
DIM B	(N-1)×10

10

Poles \ Tol.	Dim A&B
4p	±0.20
5-10p	±0.30
11-24p	±0.40
25-30p	±0.50

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	YK-601 Without Flange&With Cover Series(4-30P)				
PART NO.	YK601xx2xx00G			DWG NO.	8YK0001-601
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Airy min 2014.08.25	Airy min 2014.08.25	UNIT: mm / SCALE: NONE / SHEET: 01/01 / REV.: H	

Tolerance	
X.	±0.50
X.X	±0.30
X.XX	±0.10
X°	±1°

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.