

## 59010 Sub-Miniature Firecracker



### Features

- Magnetically operated proximity sensor
- Compact size requires only 3mm diameter hole
- Choice of contact types
- Customer defined sensitivity
- Choice of cable length

### Benefits

- No standby power requirement
- Hermetically sealed, magnetically operated contacts continue to operate long after optical and other technologies fail due to contamination
- Simple installation and adjustment

### Applications

- Position and limit sensing
- Security system switch
- Level sensing
- Linear actuators

### DIMENSIONS (in) mm



### SPECIFICATIONS

TABLE 1			Normally Open
<b>Contact Type</b>			
Switch Type			1
Contact Rating	Power	Watt - max.	5
	Switching	Vdc - max.	175
Voltage	Breakdown	Vdc - min.	200
	Switching	A - max.	0.35
Current	Carry	A - max.	0.35
	Contact, Initial	Ω - max.	0.16
Resistance	Insulation	Ω - min.	10 <sup>12</sup>
	Contact	pF - typ.	0.2
Capacitance	Operating	°C	-40 to +85
	Storage	°C	-65 to +85
Temperature	Operate	ms - max.	0.35
	Release	us - max.	20
Time	Shock	11ms 1/2 sine	G - max. 150
Shock	Vibration	50-2000 Hz	G - max. 10

### CUSTOMER OPTIONS - Sensitivity, Cable Length and Termination Specification

**TABLE 2**

**Sensitivity Options:-**  
Activate Distances are approximate using Hamlin 57020 actuator as illustrated  
Switch AT before modification

Select Option	S		T	
	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm
I Normally Open	5-10	(.236) 6.0	10-15	(.177) 4.5

**TABLE 3**

**Cable Length Options:-**  
(Cable Type 30 AWG 7/38 PTFE 200°C MIL-W-16878/6)

SELECT OPTION	CABLE LENGTH (in) mm
01	(3.94) 100
02	(11.81) 300
03	(19.69) 500
04	(29.53) 750
05	(39.37) 1000

**TABLE 4**

**Termination Options:-**

SELECT OPTION	DESCRIPTION
A	Tinned leads
F	Untinned leads

### ORDERING INFORMATION



**Hamlin USA** Tel: +1 920 648 3000 • Fax: +1 920 648 3001 • Email: sales.us@hamlin.com  
**Hamlin UK** Tel: +44 (0)1379 649700 • Fax: +44 (0)1379 649702 • Email: sales.uk@hamlin.com  
**Hamlin Germany** Tel: +49 (0) 6142 923920 • Fax: +49 (0) 6142 923921 • Email: sales.de@hamlin.com  
**Hametrol France** Tel: +33(0) 1 6047 3000 • Fax: +33(0) 1 6015 9136 • Email: sales.fr@hamlin.com

INFORMATION PROVIDED ON THIS DATA SHEET IS PROVIDED FOR INFORMATION PURPOSES ONLY AND SHOULD NOT BE RELIED UPON AS BEING ACCURATE FOR ANY PARTICULAR PURPOSE. Product performance may be affected by the application to which the product is put. Upon request, HAMLIN will assist purchasers by providing information specific to any particular application. HAMLIN disclaims any and all liability whatsoever for any purchaser's reliance upon the information contained on this data sheet without further consultation with authorised representatives of HAMLIN.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.