


CGHV59350

350 W, 5200 - 5900 MHz, 50-Ohm Input/Output Matched, GaN HEMT for C-Band Radar Systems

Cree's CGHV59350 is a gallium nitride (GaN) high electron mobility transistor (HEMT) designed specifically with high efficiency, high gain and wide bandwidth capabilities, which makes the CGHV59350 ideal for 5.2 - 5.9 GHz C-Band radar amplifier applications. The transistor is supplied in a ceramic/metal flange package, type 440217 and 440218.



PN: CGHV59350
Package Type: 440217 and 440218

Typical Performance Over 5.2 - 5.9 GHz ($T_c = 25^\circ\text{C}$) of Demonstration Amplifier

Parameter	5.2 GHz	5.55 GHz	5.9 GHz	Units
Output Power	440	445	490	W
Gain	10.5	10.5	11	dB
Drain Efficiency	59	54	55	%

Note:

Measured in the CGHV59350-TB under 100 μs pulse width, 10% duty cycle, $P_{IN} = 46 \text{ dBm}$

Features

- 5.2 - 5.9 GHz Operation
- 450 W Typical Output Power
- 10.5 dB Power Gain
- 55% Typical Drain Efficiency
- 50 Ohm Internally Matched
- <0.3 dB Pulsed Amplitude Droop

Absolute Maximum Ratings (not simultaneous)

Parameter	Symbol	Rating	Units	Conditions
Pulse Width	PW	100	μs	
Duty Cycle	DC	10	%	
Drain-Source Voltage	V _{DSS}	125	Volts	25°C
Gate-to-Source Voltage	V _{GS}	-10, +2	Volts	25°C
Storage Temperature	T _{STG}	-65, +150	°C	
Operating Junction Temperature	T _J	225	°C	
Maximum Forward Gate Current	I _{GMAX}	64	mA	25°C
Maximum Drain Current ¹	I _{DMAX}	24	A	25°C
Soldering Temperature ²	T _S	245	°C	
Screw Torque	τ	40	in-oz	
Pulsed Thermal Resistance, Junction to Case	R _{θJC}	0.31	°C/W	100 μsec, 10%, 85°C, P _{DISS} = 320 W
Case Operating Temperature	T _C	-40, +85	°C	

Notes:

¹ Current limit for long term, reliable operation

² Refer to the Application Note on soldering at <http://www.cree.com/rf/tools-and-support/document-library>

Electrical Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Units	Conditions
DC Characteristics¹ (T_c = 25°C)						
Gate Threshold Voltage	V _{GS(th)}	-3.8	-3.0	-2.3	V _{DC}	V _{DS} = 10 V, I _D = 64 mA
Gate Quiescent Voltage	V _{GS(Q)}	-	-2.7	-	V _{DC}	V _{DS} = 50 V, I _D = 1.0 A
Saturated Drain Current ²	I _{DS}	48	57.8	-	A	V _{DS} = 6.0 V, V _{GS} = 2.0 V
Drain-Source Breakdown Voltage	V _{BR}	150	-	-	V _{DC}	V _{GS} = -8 V, I _D = 64 mA

Notes:

¹ Measured on wafer prior to packaging.

² Scaled from PCM data.

Electrical Characteristics Continued...


Characteristics	Symbol	Min.	Typ.	Max.	Units	Conditions
RF Characteristics³ ($T_c = 25^\circ\text{C}$, $F_0 = 5.2 - 5.9\text{ GHz}$ unless otherwise noted)						
Output Power at 5.2 GHz	P_{OUT1}	–	440	–	W	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Output Power at 5.55 GHz	P_{OUT2}	–	445	–	W	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Output Power at 5.9 GHz	P_{OUT3}	–	490	–	W	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Gain at 5.2 GHz	G_{P1}	–	10.5	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Gain at 5.55 GHz	G_{P2}	–	10.5	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Gain at 5.9 GHz	G_{P3}	–	11	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Drain Efficiency at 5.2 GHz	D_{E1}	–	59	–	%	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Drain Efficiency at 5.55 GHz	D_{E2}	–	54	–	%	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Drain Efficiency at 5.9 GHz	D_{E3}	–	55	–	%	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Small Signal Gain	S_{21}	–	15	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = -10\text{ dBm}$
Input Return Loss	S_{11}	–	-7	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = -10\text{ dBm}$
Output Return Loss	S_{22}	–	-11	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = -10\text{ dBm}$
Amplitude Droop	D	–	-0.3	–	dB	$V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm}$
Output Stress Match	VSWR	–	5:1	–	Ψ	No damage at all phase angles, $V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $P_{IN} = 46\text{ dBm Pulsed}$

Notes:


³ Measured in CGHV59350-TB. Pulse Width = 100 μs , Duty Cycle = 10%.

Typical Performance

**Figure 1. - Small Signal S-Parameters
CGHV59350 in Test Fixture
 $V_{DD} = 50\text{ V}$, $I_{DQ} = 1\text{ A}$, $T_{case} = 25\text{ }^{\circ}\text{C}$**



**Figure 2. - CGHV59350 Pout, D_{Eff} and Gain vs. Frequency at $T_{case} = 25\text{ }^{\circ}\text{C}$
 $V_{DD} = 50\text{ V}$, $I_{DQ} = 1.0\text{ A}$, $P_{IN} = 46\text{ dBm}$, Pulse Width = $100\text{ }\mu\text{s}$, Duty Cycle = 10%**



Typical Performance

Figure 3. - CGHV59350 Output Power vs. Input Power

$V_{DD} = 50V, I_{DQ} = 1.0 A, \text{Pulse Width} = 100\mu S, \text{Duty Cycle} = 10\%, T_{case} = 25^\circ C$






Figure 4. - CGHV59350 Output Power vs. Input Power

$V_{DD} = 50V, I_{DQ} = 1.0 A, \text{Pulse Width} = 100\mu S, \text{Duty Cycle} = 10\%, T_{case} = 25^\circ C$



Typical Performance

Figure 5. - Output Power vs. Time
 $V_{DD} = 50V, P_{IN} = 46 \text{ dBm}, \text{Duty Cycle} = 10\%$




CGHV59350-TB Application Circuit Bill of Materials

Designator	Description	Qty
R1	RES, 5.10HM, +/- 1%, 1/16W,0603	1
R2	RES, 100HM, +/- 1%, 1/16W,0603	1
C1,C2	CAP, 5.6pF, +/- 0.25 pF,250V, 0603	2
C3,C8	CAP, 20pF, +/- 0.25 pF,250V, 0603	2
C4,C9	CAP, 470PF, 5%, 100V, 0603, X	2
C5	CAP, 0.1MF, 1206, 250 V, X7R	1
L1	IND, FERRITE, 220 OHM, 0603	1
C10	CAP, 1.0UF, 100V, 10%, X7R, 1210	1
C7	CAP, 5.6pF, +/- 0.25 pF,250V, 0603	1
C11	CAP, 3300 UF, +/-20%, 100V, ELECTROLYTIC	1
C12	CAP, 33 UF, 20%, G CASE	1
J1,J2	CONN, SMA, PANEL MOUNT JACK, FL	2
J3	HEADER RT>PLZ .1CEN LK 9POS	1
J4	CONNECTOR ; SMB, Straight, JACK,SMD	1
W1	CABLE ,18 AWG, 4.2	1
-	PCB, TEST FIXTURE, TACONIC RF35P 20MIL OVER 0.250 COPPER BACK, 2.5 X 3 X 0.26", CGHV59350-TB	1
-	2-56 SOC HD SCREW 1/4 SS	4
-	#2 SPLIT LOCKWASHER SS	4
Q1	CGHV59350	1


CGHV59350 Power Dissipation De-rating Curve

Figure 4. - Transient Power Dissipation De-Rating Curve




Note 1. Area exceeds Maximum Case Temperature (See Page 2).

CGHV59350-AMP1 Application Circuit Schematic




CGHV59350-AMP1 Application Circuit Outline



Product Dimensions CGHV59350F (Package Type – 440217)

NOTES: (UNLESS OTHERWISE SPECIFIED)


1. INTERPRET DRAWING IN ACCORDANCE WITH ANSI Y14.5M-2009
2. ADHESIVE FROM LID MAY EXTEND A MAXIMUM OF .020 BEYOND EDGE OF LID
3. LID MAY BE MISALIGNED TO THE BODY OF PACKAGE BY A MAXIMUM OF .008 IN ANY DIRECTION
4. ALL PLATED SURFACES ARE GOLD OVER NICKEL




Product Dimensions CGHV59350P (Package Type – 440218)

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. INTERPRET DRAWING IN ACCORDANCE WITH ANSI Y14.5M-2009
2. ADHESIVE FROM LID MAY EXTEND A MAXIMUM OF .020 BEYOND EDGE OF LID
3. LID MAY BE MISALIGNED TO THE BODY OF PACKAGE BY A MAXIMUM OF .008 IN ANY DIRECTION
4. ALL PLATED SURFACES ARE GOLD OVER NICKEL



CGHV59350F/P



Parameter	Value	Units
Upper Frequency ¹	5.9	GHz
Power Output	350	W
Package	Flange/Pill	-





Table 1.

Note¹: Alpha characters used in frequency code indicate a value greater than 9.9 GHz. See Table 2 for value.

Character Code	Code Value
A	0
B	1
C	2
D	3
E	4
F	5
G	6
H	7
J	8
K	9
Examples:	1A = 10.0 GHz 2H = 27.0 GHz

Table 2.

Product Ordering Information

Order Number	Description	Unit of Measure	Image
CGHV59350F	GaN HEMT	Each	
CGHV59350P	GaN HEMT	Each	
CGHV59350-TB	Test board without GaN HEMT	Each	
CGHV59350-AMP1	Test board with GaN HEMT installed	Each	



Disclaimer

Specifications are subject to change without notice. Cree, Inc. believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Cree for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Cree. Cree makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Cree in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Cree products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Cree product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.

For more information, please contact:

Cree, Inc.
4600 Silicon Drive
Durham, North Carolina, USA 27703
www.cree.com/rf

Sarah Miller
Marketing & Export
Cree, RF Components
1.919.407.5302

Ryan Baker
Marketing
Cree, RF Components
1.919.407.7816

Tom Dekker
Sales Director
Cree, RF Components
1.919.407.5639



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.