



Quality Products. Service Excellence.

Type 12 Mild Steel Two Door Freestanding Enclosure 1418 FS Series

Continuous Hinge Door with Handle



Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls with provision for panel mounting or rack mounting of equipment.
- Provides a degree of protection from falling dirt, dust, oil and water.
- Available with front access only or both front and rear access.
- A variety of inner panels, rack mounting angles and swing frames are available to provide flexibility in equipment mounting.

Standards

- UL 508A Type 12
- CSA Type 12
- Complies with
 - NEMA Type 12
 - IEC 60529, IP54

Construction

- Formed 12 gauge steel (10 gauge on back of single access enclosures).
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Stiffeners on the rear of the enclosure provide rigidity. (Single access)
- Lifting eyes provide for easy enclosure handling.
- Doors are supported with heavy gauge continuous hinges.
- Doors are secured with a three point latch and operated with a key locking automotive type handle.
- Latch rods are equipped with rollers for easier door closing.
- Oil resistant gaskets are permanently secured.
- Provision for light kit mounting.
- Mounting channels are welded on the inside of the enclosure for mounting of optional inner panels or rack equipment rails.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided for the inside of the door (Two pockets are provided for dual access units).

Finish

- Cover and enclosure are phosphatized and finished in recoatable smooth ANSI 61 gray powder coating.
- Optional inner panels, rails, frames and supports are available in white powder coating.

Accessories

- Inner Panels
- Panel Rails
- Door Stop Kit
- Climate Control
- Center Panel Supports
- Swing Out Frames
- Top Hat Cable Modules
- Window Kits

- Lighting
- General Accessories

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

Single Access

| Part No. | Enclosure | | | Optional Full Panel ¹ |
|----------|-----------|-------|-------|----------------------------------|
| | H | W | D | |
| 1418AW18 | 60.06 | 48.06 | 18.06 | 60AWFW |
| 1418ZW18 | 72.06 | 48.06 | 18.06 | 72ZWFW |
| 1418ZX18 | 72.06 | 60.06 | 18.06 | 72ZXFW |
| 1418ZY18 | 72.06 | 72.06 | 18.06 | 72ZYFW |
| 1418BW20 | 90.06 | 48.06 | 20.06 | 90BWFW |
| 1418BY20 | 90.06 | 72.06 | 20.06 | 90BYFW |
| 1418BY24 | 90.06 | 72.06 | 24.06 | 90BYFW |
| 1418ZW24 | 72.06 | 48.06 | 24.06 | 72ZWFW |
| 1418ZX24 | 72.06 | 60.06 | 24.06 | 72ZXFW |
| 1418ZY24 | 72.06 | 72.06 | 24.06 | 72ZYFW |
| 1418ZX36 | 72.06 | 60.06 | 36.06 | 72ZXFW |
| 1418BY36 | 90.06 | 72.06 | 36.06 | 90BYFW |

¹ Refers to optional full height/full width panels. **Depth panels/half height width panels are also available**

Dual Access

| Part No. | Enclosure | | | Optional Full Panel ¹ |
|-----------|-----------|-------|-------|----------------------------------|
| | H | W | D | |
| 1418ZWD24 | 72.06 | 48.06 | 24.06 | 72ZWFW |
| 1418ZXD24 | 72.06 | 60.06 | 24.06 | 72ZXFW |
| 1418ZXD24 | 72.06 | 60.06 | 24.06 | 72ZXFW |
| 1418ZYD24 | 72.06 | 72.06 | 24.06 | 72ZYFW |
| 1418BYD24 | 90.06 | 72.06 | 24.06 | 90BYFW |
| 1418ZXD36 | 72.06 | 60.06 | 36.06 | 72ZXFW |

¹ Refers to optional full height/full width panels. **Depth panels/half height width panels are also available**

Data subject to change without notice

© 2020. Hammond Manufacturing Ltd. All rights reserved.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.