

## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### FEATURES

- Single Low EMI IC to replace multiple crystals and oscillators on Notebooks and Motherboards (27MHz, 10MHz, 14.318MHz, 8MHz, 12MHz, 24.576MHz, 25MHz).
- Selectable crystal input: 24.576MHz or 14.318MHz (accuracy requirement +/- 20ppm)
- Less than 10ppm Frequency Synthesis error, meeting AC97, IEEE1394, IEEE802 and USB2.0 frequency precision specification.
- 27MHz clock with 5 levels of Selectable Spread Spectrum modulation form +/- 0.5% to +/- 1.5% center.
- 25MHz clock with double drive strength (Ethernet PHY and MAC).
- 24.576MHz clocks for Audio Codec and IEEE1394.
- 12MHz for USB 2.0.
- Selectable 10MHz and 8MHz for Keyboard controller.
- Dual power source selection for 24.576MHz, 10MHz, and 12MHz.
- Available in 16-Pin SOIC or TSSOP.

**Table 1. SPREAD SPECTRUM SELECTION**


| SST1 | SST0 | SST Modulation only on 27MHz. (pin 15) |
|------|------|----------------------------------------|
| 1    | 1    | +/- 1.5 %                              |
| 1    | 0    | +/- 1.25 %                             |
| 1    | M    | +/- 1 %                                |
| 0    | 1    | +/- 0.75 %                             |
| 0    | 0    | +/- 0.5 %                              |
| 0    | M    | SST OFF (Default)                      |

Notes: M = Do not connect. 1 = Pulled up. 0 = Pulled down.

**Table 2. POWER SELECTION TABLE**

| VDD_SEL | 24.576MHz (pin 7) | 12MHz (pin 12) |
|---------|-------------------|----------------|
| 0       | VDDDB1            | VDDDB2         |
| 1       | VDD25M            | VDD25M         |

### PIN ASSIGNMENT



Note: 25MHzx2: double drive strength  
<sup>v</sup>: Internal pull-down resistor (120kΩ)  
<sup>\*</sup>: Bi-directional pin  
<sup>T</sup>: Tri-level input

### POWER GROUPS

- VDDOSC – VSSOSC: XIN, XOUT, analog core and digital part.
- VDDDB1 – VSSB1: 24.576MHz.
- VDDDB2 – VSSB2: 27MHz, 10\_8MHz, and 12MHz.
- VDD25M – VSS25M: 25MHz, (10\_8MHz, 12MHz, 24.576MHz when power VDDDB1, VDDDB2 not present).

**Table 3. FREQUENCY SELECTION TABLE**


| SEL10_8 | 10_8MHz ( pin 13 ) |                  |
|---------|--------------------|------------------|
|         | Power Source       | Output Frequency |
| M       | VDD25M             | 8MHz             |
| 1       | VDDDB2             | 10MHz            |
| 0       | OFF                | -                |

**Table 4. CRYSTAL SELECTION TABLE**

| Crystal Input | XTAL_SEL |
|---------------|----------|
| 24.576MHz     | 0        |
| 14.318MHz     | 1        |

## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### BLOCK DIAGRAM



**Note 1:** In order to use VDD25M as power source for 10\_8MHz (pin 13), 24.576MHz (pin 7), and 12MHz (pin 12), it is necessary to select this feature through the VDD\_SEL and SEL10\_8M inputs (see Power Selection and 10\_8MHz Frequency Selection Tables on p.1).

**Note 2:** Only 27MHz output is modulated for low EMI via Spread Spectrum.

## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### PIN DESCRIPTIONS

| Name                  | Pin# | Type | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------|------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| VDDOSC                | 1    | P    | 3.3V power supply for oscillator, analog core and digital circuitry.                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| XIN                   | 2    | I    | Crystal input: accepts either 24.576MHz or 14.31818MHz fundamental crystal (CL = 20pF, parallel resonant mode, +/-20ppm). On-chip load capacitors: no external load capacitors required. (See the table #4 )                                                                                                                                                                                                                                                                                                                                      |
| XOUT                  | 3    | O    | Crystal output.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| VSSOSC                | 4    | P    | Ground connection.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| VSSB1                 | 5    | P    | Ground connection.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 24.576MHz/SST0        | 6    | B    | Bi-directional and Tri-Level pin. Upon power-on, the value of SST0 is latched in and used to select the SST control (see Spread Spectrum selection table 1). Tri level input: M = Do not connect, 1 = Pull up, 0 = Pull down. After power-up this pin acts as 24.576MHz output clock.                                                                                                                                                                                                                                                             |
| 24.576MHz/SST1        | 7    | B    | Bi-directional pin. Upon power-on, the value of SST1 is latched in and used to select the SST control (see Spread Spectrum selection table 1). Internal pull down defaults SST1 to 0, use external pull-up to set to 1. After power-up this pin acts as 24.576MHz output clock.                                                                                                                                                                                                                                                                   |
| Vddb1                 | 8    | P    | 3.3V power supply for 24.576MHz clock.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| VDD25M                | 9    | P    | 3.3V power supply for 25MHz, 10_8MHz, 12MHz, 24.576MHz.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 25MHzx2               | 10   | O    | 25MHz Ethernet output clock (double drive strength).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| VSS25M                | 11   | P    | Ground connection.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 12MHz/VDD_SEL         | 12   | B    | Bi-directional pin. Upon power-on, the value of VDD_SEL is latched in and used to select the power (see Power Selection table 2 ). Internal pull down defaults SST1 to 0, use external pull-up to set to 1. After power-up this pin acts as 12MHz output clock.                                                                                                                                                                                                                                                                                   |
| 10_8MHz/SEL10_8       | 13   | B    | Bi-directional and Tri-level pin. Upon power-on, the value of SEL10_8 is latched in and used to select the output frequency (See frequency selection table 3 ). Tri level input: M = Do not connect, 1 = Pull up, 0 = Pull down. After power-up this pin acts as 10MHz clock, 8MHz clock, or "No output", depending on SEL10_8.                                                                                                                                                                                                                   |
| VSSB2                 | 14   | P    | Ground connection.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 27_14.318MHz/XTAL_SEL | 15   | B    | Bi-directional pin. Upon power-on, the value of XTAL_SEL is latched in and used to set the input crystal frequency (24.575MHz or 14.31818MHz). Set XTAL_SEL to 0 (default) for 24.576MHz input crystal, set XTAL_SEL to 1 for 14.31818MHz input crystal (see Crystal Selection Table on page 1). . After power-up this pin acts as 27MHz output (with 24.576MHz crystal) or as 14.31818MHz pass through clock (with 14.31818MHz crystal), depending on the input crystal.<br>The 27MHz output can be modulated for low EMI using Spread Spectrum. |
| Vddb2                 | 16   | P    | 3.3V power supply for 27MHz, 10MHz, 12MHz, and 24.576MHz.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

### FUNCTIONAL DESCRIPTION

#### Tri-level and two-level inputs

In order to reduce pin usage, the PLL702-02 uses tri-level input pins. These pins allow 3 levels for input selection: namely, 0 = Connect to GND, 1 = Connect to VDD, M = Do not connect. Thus, unlike the two-level selection pins, the tri-level input pins are in the "M" (mid) state when not connected. In order to connect a tri-level pin to a logical "zero", the pin must be connected to GND. Likewise, in order to connect to a logical "one", the pin must be connected to VDD.

## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### Connecting a bi-directional pin


The PLL702-02 also uses bi-directional pins. The same pin serves as input upon power-up, and as output as soon as the inputs have been latched. The value of the input is latched-in upon power-up. Depending on the pin (see pin description), the input can be tri-level or a standard two-level. Unlike unidirectional pins, bi-directional pins cannot be connected directly to GND or VDD in order to set the input to "0" or "1", since the pin also needs to serve as output. In the case of two level input pins, an internal pull-up resistor is present. This allows a default value to be set when no external pull down resistor is connected between the pin and GND (by definition, a tri-level input has a the default value of "M" (mid) if it is not connected). In order to connect a bi-directional pin to a non-default value, the input must be connected to GND or VDD through an external pull-down/pull-up resistor.

**Note:** when the output load presents a low impedance in comparison to the internal pull-up resistor, the internal pull-up resistor may not be sufficient to pull the input up to a logical "one", and an external pull-up resistor may be required.

For bi-directional inputs, the external loading resistor between the pin and GND has to be sufficiently small (compared to the internal pull-up resistor) so that the pin voltage be pulled below 0.8V (logical "zero"). In order to avoid loading effects when the pin serves as output, the value of the external pull-down resistor should however be kept as large as possible. In general, it is recommended to use an external resistor of around one sixth to one quarter of the internal pull-up resistor (see Application Diagram).

**Note:** when the output is used to drive a load presenting an small resistance between the output pin and VDD, this resistance is in essence connected in parallel to the internal pull-up resistor. In such a case, the external pull-down resistor may have to be dimensioned smaller to guarantee that the pin voltage will be low enough achieve the desired logical "zero". This is particularly true when driving 74FXX TTL components.

### APPLICATION DIAGRAM: BI-DIRECTIONAL PINS WITH INTERNAL PULL-UP



## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### Electrical Specifications

#### 1. Absolute Maximum Ratings

| PARAMETERS                        | SYMBOL   | MIN. | MAX.         | UNITS |
|-----------------------------------|----------|------|--------------|-------|
| Supply Voltage                    | $V_{DD}$ |      | 4.6          | V     |
| Input Voltage, dc                 | $V_I$    | -0.5 | $V_{DD}+0.5$ | V     |
| Output Voltage, dc                | $V_O$    | -0.5 | $V_{DD}+0.5$ | V     |
| Storage Temperature               | $T_S$    | -65  | 150          | °C    |
| Ambient Operating Temperature*    | $T_A$    | -40  | 85           | °C    |
| Junction Temperature              | $T_J$    |      | 125          | °C    |
| Lead Temperature (soldering, 10s) |          |      | 260          | °C    |
| ESD Protection, Human Body Model  |          |      | 2            | kV    |

Exposure of the device under conditions beyond the limits specified by Maximum Ratings for extended periods may cause permanent damage to the device and affect product reliability. These conditions represent a stress rating only, and functional operations of the device at these or any other conditions above the operational limits noted in this specification is not implied.

\* **Note:** Operating Temperature is guaranteed by design for all parts (COMMERCIAL and INDUSTRIAL), but tested for COMMERCIAL grade only.

#### 2. AC Specifications

| PARAMETERS                               | CONDITIONS                | MIN. | TYP.     | MAX. | UNITS |
|------------------------------------------|---------------------------|------|----------|------|-------|
| Input Frequency (to be set via XTAL_SEL) | +/- 20ppm accuracy        |      | 14.31818 |      | MHz   |
|                                          |                           |      | 24.576   |      | MHz   |
| Output Rise Time                         | 0.8V to 2.0V with no load |      |          | 1.5  | ns    |
| Output Fall Time                         | 2.0V to 0.8V with no load |      |          | 1.5  | ns    |
| Duty Cycle                               | At $V_{DD}/2$             | 45   | 50       | 55   | %     |
| Duty Cycle 8MHz clock                    | At $V_{DD}/2$             | 43   | 50       | 57   | %     |
| Max. Absolute Period Jitter              | Long term, No SST         |      |          | 150  | ps    |
| Max. Jitter, cycle to cycle              | Long term + Short term    |      |          | 120  | ps    |

## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### 3. DC Specifications


| PARAMETERS                        | SYMBOL    | CONDITIONS                             | MIN.         | TYP.       | MAX.           | UNITS |
|-----------------------------------|-----------|----------------------------------------|--------------|------------|----------------|-------|
| Operating Voltage                 | $V_{DD}$  | Nominal voltage 3.3V                   | 2.97         |            | 3.63           | V     |
| Input High Voltage                | $V_{IH}$  |                                        |              | $V_{DD}/2$ |                | V     |
| Input Low Voltage                 | $V_{IL}$  |                                        |              | $V_{DD}/2$ | $V_{DD}/2 - 1$ | V     |
| Input High Voltage                | $V_{IH}$  | For all Tri-level input                | $V_{DD}-0.5$ |            |                | V     |
| Input Low Voltage                 | $V_{IL}$  | For all Tri-level input                |              |            | 0.5            | V     |
| Input High Voltage                | $V_{IH}$  | For all normal input                   | 2            |            |                | V     |
| Input Low Voltage                 | $V_{IL}$  | For all normal input                   |              |            | 0.8            | V     |
| Output High Voltage               | $V_{OH}$  | $I_{OH} = -30\text{mA}$ (normal drive) | 2.4          |            |                | V     |
|                                   |           | $I_{OH} = -60\text{mA}$ (double drive) |              |            |                |       |
| Output Low Voltage                | $V_{OL}$  | $I_{OL} = 30\text{mA}$ (normal drive)  |              |            | 0.4            | V     |
|                                   |           | $I_{OL} = -60\text{mA}$ (double drive) |              |            |                |       |
| Output High Voltage At CMOS Level | $V_{OH}$  | $I_{OH} = -8\text{mA}$                 | $V_{DD}-0.4$ |            |                | V     |
| Nominal Output Current            | $I_{OUT}$ | Normal drive strength                  | 30           |            |                | mA    |
|                                   |           | Double drive strength                  | 60           |            |                |       |
| Operating Supply Current          | $I_{DD}$  | No Load                                |              | 17         |                | mA    |
| Short-circuit Current             | $I_S$     |                                        |              | $\pm 100$  |                | mA    |

## Low EMI Peripheral Clock Generator for Notebook & Motherboards

### PACKAGE INFORMATION

16 PIN Narrow SOIC, TSSOP ( mm )

|        | SOIC     |       | TSSOP    |      |
|--------|----------|-------|----------|------|
| Symbol | Min.     | Max.  | Min.     | Max. |
| A      | 1.35     | 1.75  | -        | 1.20 |
| A1     | 0.10     | 0.25  | 0.05     | 0.15 |
| B      | 0.33     | 0.51  | 0.19     | 0.30 |
| C      | 0.19     | 0.25  | 0.09     | 0.20 |
| D      | 9.80     | 10.00 | 4.90     | 5.10 |
| E      | 3.80     | 4.00  | 4.30     | 4.50 |
| H      | 5.80     | 6.20  | 6.40 BSC |      |
| L      | 0.40     | 1.27  | 0.45     | 0.75 |
| e      | 1.27 BSC |       | 0.65 BSC |      |



### ORDERING INFORMATION

**For part ordering, please contact our Sales Department:**

47745 Fremont Blvd., Fremont, CA 94538, USA

Tel: (510) 492-0990 Fax: (510) 492-0991

#### PART NUMBER

The order number for this device is a combination of the following:

Device number, Package type and Operating temperature range

|                     |  |                  |          |          |          |          |                     |
|---------------------|--|------------------|----------|----------|----------|----------|---------------------|
| <b>PART NUMBER</b>  |  | <b>PLL702-02</b> | <b>X</b> | <b>C</b> | <b>X</b> | <b>X</b> |                     |
|                     |  |                  |          |          |          |          | NONE= TUBE          |
|                     |  |                  |          |          |          |          | R=TAPE AND REEL     |
|                     |  |                  |          |          |          |          | NONE=NORMAL PACKAGE |
|                     |  |                  |          |          |          |          | L=GREEN PACKAGE     |
| <b>PACKAGE TYPE</b> |  |                  |          |          |          |          | <b>TEMPERATURE</b>  |
|                     |  |                  |          |          |          |          | C=COMMERCIAL,       |
|                     |  |                  |          |          |          |          | I=INDUSTRIAL        |
|                     |  |                  |          |          |          |          |                     |

O=TSSOP  
S = SOIC

| Part / Order Number | Marking    | Package Option                   | Temperature  |
|---------------------|------------|----------------------------------|--------------|
| PLL702-02XCR        | P702-02XC  | SSOP/SOIC -Tape and Reel         | 0 to +70 ° C |
| PLL702-02XC         | P702-02XC  | SSOP/SOIC -Tubes                 | 0 to +70 ° C |
| PLL702-02XCLR       | P702-02XCL | SSOP/SOIC -Tape and Reel (GRREN) | 0 to +70 ° C |
| PLL702-02XCL        | P702-02XCL | SSOP/SOIC -Tubes (GREEN)         | 0 to +70 ° C |

PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.

**LIFE SUPPORT POLICY:** PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.