



For more Information
please call

1-800-Belden1



Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring for electronic and electrical equipment.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 1 | 22 | 7x30 | TC - Tinned Copper |

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|--------------------------|---------------------|
| PVC - Polyvinyl Chloride | 0.762 |

Overall Insulation

Overall Cabling

Overall Nominal Diameter: 2.362 mm

Mechanical Characteristics (Overall)

Bulk Cable Weight: 8.632 Kg/Km

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|----------------------|
| UL Rating: | 600 V, 105°C |
| UL Type: | MTW or AWM 1015/1230 |
| CSA Rating: | 600 V, 105°C |
| CSA Type: | AWM I A/B or TEW |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flame Test

| | |
|-----------------|------|
| UL Flame Test: | VW-1 |
| CSA Flame Test: | FT1 |

Plenum/Non-Plenum

Plenum (Y/N): No

Related Documents:

No related documents are available for this product

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------------|----------|-------------|-------------|-------|------------------|
| 8920 0011000 | 305 MT | 3.175 KG | BROWN | P | 22 STR PVC BRN |
| 8920 002100 | 30 MT | 0.318 KG | RED | | 22 STR PVC RED |
| 8920 0021000 | 305 MT | 3.175 KG | RED | P | 22 STR PVC RED |
| 8920 0025000 | 1,524 MT | 15.876 KG | RED | | 22 STR PVC RED |
| 8920 0031000 | 305 MT | 3.175 KG | ORANGE | P | 22 STR PVC ORG |
| 8920 004100 | 30 MT | 0.318 KG | YELLOW | | 22 STR PVC YEL |
| 8920 0041000 | 305 MT | 3.175 KG | YELLOW | P | 22 STR PVC YEL |
| 8920 0051000 | 305 MT | 3.175 KG | GREEN, DARK | P | 22 STR PVC GRN |
| 8920 0071000 | 305 MT | 3.175 KG | VIOLET | P | #22 STR PVC VIO |
| 8920 0081000 | 305 MT | 3.175 KG | GRAY | P | #22 STR PVC GRY |
| 8920 009100 | 30 MT | 0.318 KG | WHITE | | 22 STR PVC WHITE |
| 8920 0091000 | 305 MT | 3.175 KG | WHITE | P | 22 STR PVC WHITE |
| 8920 010100 | 30 MT | 0.318 KG | BLACK | | 22 STR PVC BLK |
| 8920 0101000 | 305 MT | 3.175 KG | BLACK | P | 22 STR PVC BLK |
| 8920 0105000 | 1,524 MT | 15.876 KG | BLACK | C | #22 STR PVC BLK |
| 8920 013100 | 30 MT | 0.318 KG | BLUE, DARK | | 22 STR PVC D BLU |
| 8920 0131000 | 305 MT | 3.175 KG | BLUE, DARK | P | 22 STR PVC D BLU |

Notes:

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 08-26-2008

© 2011 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.