

HIGH DENSITY LED FLEX RIBBON


Features

VOLTAGE: 12V DC
 CURRENT: 4.4 Amps
 LED VIEWING ANGLE (2 θ 1/2): 120°

STANDARD PACKAGING:
 5 METER REEL (600 LED'S)

OPTIONAL PACKAGING:
 INDIVIDUAL 500mm Sections (60 LED's)
 Order as ZFS-85000HD-XX/SEC

NOTE: Individual sections ARE NOT supplied with insulated wire connection.



Accessories

ZPS-1235 12V, 35 Watt Power Supply
 ZPS-1260 12V, 60 Watt Power Supply
 ZDM-01 PWM LED Dimmer

Note: ZPS-1235 and ZPS-1260 require use of wire nuts for connections.

Parameter	Symbol	Rating	Units
Forward Current	IF	4.4	A
Power Dissipation	PD	52.8	W
Electrostatic Discharge	ESD	800	V
Operating Temperature	Topr	-25~+60	°C
Storage Temperature	Tstg	-40~+80	°C



E365522

Electro-Optical Characteristics (Ta = 25°C)

JKL Part Number	Color	Number of LED's	Input Voltage (V DC)	Power (W)	Current (A)	Radiance Angle	CCT (K)	Lumen Flux (lm)
ZFS-85000HD-WW	Warm White	600	12	52.8	4.4	120°	3500°K	1650
ZFS-85000HD-CW	Cool White	600	12	52.8	4.4	120°	6250°K	1800
ZFS-85000HD-NW	Neutral White	600	12	52.8	4.4	120°	4250°K	1800
ZFS-85000HD-R	Red	600	12	48.0	4.0	120°	626 nm	1820
ZFS-85000HD-B	Blue	600	12	48.0	4.0	120°	460 nm	1820

Note

Please refer to JKL Application Sheet JKL-AS-ZFS-LED FLEX for Installation and Power Recommendations.




ATTENTION
 OBSERVE PRECAUTION FOR HANDLING ELECTROSTATIC DISCHARGE SENSITIVE DEVICES


F	DELETE MATING COMPONENTS	1/6/14	<p>METRIC DIMENSIONS ARE IN mm (INCHES) TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/-</p>	JKL COMPONENTS CORPORATION TITLE HIGH DENSITY LED FLEX RIBBON, 12V						
E	ADD PART NO. ZFS-85000HD-NW	9/23/13								
D	ADD PART NO. ZFS-85000HD-WW	1/14/13								
C	CHANGE CURRENT TO READ (A)	12/19/12								
B	ADD COMPONENTS, NOTES & PAGE 2	8/23/11								
A	ADD WIRE SIZE & CHNG ACCESS. PART #'S	6/27/11	DRAWN BY L. WENGSTROM	APP'VD BY L.R.	DATE 1/6/14	SIZE A	FSCM NO. 55335	DRAWING NO. ZFS-85000HD MULTI		
	RELEASE & CANCEL PL-0901-08, PL-0905-05	5/23/11	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 5/23/11	REVISION DATE 1/6/14	REV. NO. F	SHEET 1 OF 2
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE								

HIGH DENSITY LED FLEX RIBBON

Dimensions



Circuit Diagram





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.