





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMPHENOL INTERCONNECT PRODUCTS CORP. ANY REPRODUCTION OR DISCLOSURE, TO THIRD PARTIES, IN PART OR WHOLE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMPHENOL INTERCONNECT PRODUCTS CORP. IS PROHIBITED.


AIPC P/N	LENGTH "A"	WIRE AWG (REF)	NOTES	EPROM REV	ACD P/N
624410001	1000 MM ±20 MM	30G	16	A	SF-QSFPEXPAS-001
624410003	3000 MM ±60 MM	30G	16	A	SF-QSFPEXPAS-003
624410005	5000 MM ±100 MM	26G	16	A	SF-QSFPEXPAS-005
624410007	7000 MM ±140 MM	26G EXD	14	A	SF-QSFPEXPAS-007

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE PER EO 3044XX	7/13	DEC



- THIS DRAWING IS RESERVED FOR AMPHENOL CABLES ON DEMAND.
- TEST COMPLETED ASSEMBLIES PER AMPHENOL CS-1199. TEST ASSEMBLIES AT 10 Gbps.
- A PRE-PRINTED LABEL WITH THE INFORMATION SHOWN IN THE CABLE LABEL DETAIL IS POSITIONED WITHIN THE INDICATED AREA ON THE CABLE ASSEMBLY.
- UL LABEL MUST BE ON SHIPPING CARTON PER SUBJECT 764 OF THE UL COMPONENT WIRING HARNESS (ZPFW2) FILE #E86140. CSA LABEL MUST BE ON SHIPPING CARTON.
- PACKAGE COMPLETED ASSY IN AN APPROPRIATELY SIZED ANTI-STATIC BAG. LABEL PER BAG LABEL DETAIL.
- INSTALL DUST COVER (ITEM 10) OVER CONNECTORS PER MFG PROCESS PRIOR TO SHIPMENT TO CUSTOMER.
- MARK LABEL WITH SERIAL NUMBER. ENDICOTT LOCATION PREFIX IS 'APL'; CHINA LOCATION PREFIX IS 'APF'.
- EPROM PROGRAM PER AMPHENOL SPEC CS-1154. EPROM SERIAL No. MUST MATCH CABLE LABEL SERIAL No.
- CAUTION: ANTI-STATIC CONTROL MEASURES MUST BE OBSERVED DURING THE MANUFACTURE OF THIS ASSEMBLY.
- POT MOLD BOTH CABLE ENDS PER MFG PROCESS. USE LOCTITE 3106 TO COVER CABLE TERMINATION AREAS.
- SOLDER PER AMPHENOL CS-1186 (LEAD FREE SOLDER).
- ALL MATERIALS USED IN THE MANUFACTURE OF THIS ASSEMBLY SHALL COMPLY WITH AMPHENOL REGULATED MATERIALS SPECIFICATION CS-1152.
- SIMILAR TO AMPHENOL DRAWING 60302XXXX.
- REMOVE CBL JACKET AND WRAP ONE TURN OF COPPER TAPE (ITEM 14) OVER CBL BRAID IN AREA OF STRAIN RLF. ADD SHK TBG (ITEM 13) OVER CBL BRAID OVERLAPPING COPPER TAPE. WHEN CLOSING ADD SHK TBG (ITEM 12) OVER CBL JACKET/BRAID AND UP TO BACKSHELL.
- PERMANENTLY MARK LABEL WITH 'WEEE' LOGO AND 'CE' LOGO, REF AHSI SPEC CS-1210. A ROHS2 CERTIFICATE OF COMPLIANCE MUST BE INCLUDED IN EACH SHIPPING CARTON.
- WRAP ONE TURN OF COPPER TAPE (ITEM 16) AROUND CBL JACKET BEFORE PULLING BACK BRAID.

NOTE: DC BLOCKING CAP VALUE IS 0.1 µF
EPROM CONNECTED TO VCCTX



SPECIFICATION CONTROL DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: DECIMALS .X ±.X .XX ±.01 .XXX ±.005 ANGLES ±.5°	EAR NO. AMPH7006-004A	Amphenol Interconnect Products Corp. 20 Valley St. Endicott, NY, 13760	
	APPROVALS DRAWN D.CASHIMERE CHECKED	DATE 7/13	CABLE ASSEMBLY, QSFP/QSFP, PASSIVE, 100Ω, RoHS, 40 GbE-CR4
THIRD ANGLE PROJECTION 	RESP ENG	MFG ENG	SIZE DWG. NO. 62441XXXX
CAD FILE: S:\SolidWorks\PE 5 DIGIT NO\62441		SCALE 1:1	SHEET 1 OF 1

NOTES: UNLESS OTHERWISE SPECIFIED



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.