

Features

- ◆ 10 Watt in 1" x 1" package
- ◆ Shielded metal case with isolated baseplate
- ◆ Ultrawide 4:1 input voltage ranges
- ◆ Remote On/Off control
- ◆ Operating temp. range -40°C to $+75^{\circ}\text{C}$ and up to $+85^{\circ}\text{C}$ with heat-sink
- ◆ I/O isolation voltage 1500 VDC
- ◆ Input filter meets EN 55022 class A without external components
- ◆ Cost optimized design
- ◆ Industry standard pinout
- ◆ 3-year product warranty



The THL 10WI is a series of general purpose 10 Watt dc/dc-converters packed in the compact 1" x 1" case and is a pin to pin replacement for the popular 1" x 2" size products. The industrial standard pinout, the ultra wide 4:1 input voltage range and the input filter that meets EN 55022 Class A without external components make these converters easy to design in and suitable for to cost optimize many existing and new applications.

The models have a remote On/Off control, short circuit and overvoltage protection and are applicable in temperature ranges of up to $+75^{\circ}\text{C}$ or $+85^{\circ}\text{C}$ with optional mounted heat sink. Typical applications are instrumentation, distributed power architectures in communication and industrial electronics.

Models

| Order code | Input voltage range | Output voltage | Output current max. | Efficiency typ. |
|---------------|---------------------------------|----------------|---------------------|-----------------|
| THL 10-2410WI | 9 – 36 VDC (24 VDC nominal) | 3.3 VDC | 2200 mA | 86 % |
| THL 10-2411WI | | 5.1 VDC | 2000 mA | 84 % |
| THL 10-2412WI | | 12 VDC | 830 mA | 86 % |
| THL 10-2413WI | | 15 VDC | 660 mA | 87 % |
| THL 10-2415WI | | 24 VDC | 410 mA | 86 % |
| THL 10-2421WI | | ± 5.0 VDC | ± 1000 mA | 84 % |
| THL 10-2422WI | | ± 12 VDC | ± 410 mA | 86 % |
| THL 10-2423WI | | ± 15 VDC | ± 330 mA | 87 % |
| THL 10-4810WI | 18 – 75 VDC (48 VDC nominal) | 3.3 VDC | 2200 mA | 85 % |
| THL 10-4811WI | | 5.1 VDC | 2000 mA | 84 % |
| THL 10-4812WI | | 12 VDC | 830 mA | 86 % |
| THL 10-4813WI | | 15 VDC | 660 mA | 87 % |
| THL 10-4815WI | | 24 VDC | 410 mA | 86 % |
| THL 10-4821WI | | ± 5.0 VDC | ± 1000 mA | 84 % |
| THL 10-4822WI | | ± 12 VDC | ± 410 mA | 86 % |
| THL 10-4823WI | | ± 15 VDC | ± 330 mA | 87 % |

Input Specifications

| | |
|---|--|
| Input current at no load (at nominal input voltage) | 24 V models: 30 mA typ. 48 V models: 20 mA typ. |
| Input current at full load (at nominal input voltage) | 24 V; 3.3 VDC models: 400 mA typ. 24 V; other models: 500 mA typ.. 48 V; 3.3 VDC models: 200 mA typ. 48 V; other models: 250 mA typ. |
| Start-up voltage / under voltage lockout (hysteresis for assertive on) | 24 V models: 9 VDC / 8.5 VDC (or lower) 48 V models: 18 VDC / 17 VDC (or lower) (long term operation at undervoltage will damage the converter!) |
| Surge voltage (1 sec. max.) | 24 Vin models: 50 V max. 48 Vin models: 100 V max. |
| Conducted noise (input) | EN 55022 class A, FCC part 15, level A without external components |
| Recommended input fuse (slow blow) | 24 V models: 2000 mA 48 V models: 1000 mA |

Output Specifications

| | |
|-------------------------------------|---|
| Voltage set accuracy | ±2 % |
| Regulation | – Input variation (Vmin – Vmax) 1.0 % max. – Load variation single output models: 1.2 % max. (15 – 100 % load) dual output models: 2.0 % max. (15 – 100 % balanced load) |
| Minimum load | 15 % |
| Ripple and noise (20 MHz bandwidth) | 60 mVp-p typ. |
| Temperature coefficient | ±0.02 %/K |
| Output current limitation | >110 % of Iout max. |
| Short circuit protection | indefinite, automatic recovery |
| Transient response setting time | 300 µs typ. (25 % load step change) |
| Maximum capacitive load | 3.3 VDC models: 560 µF 5 VDC models: 560 µF 12 VDC models: 150 µF 15 VDC models: 150 µF 24 VDC models: 68 µF ±5.0 VDC models: 220 µF (each output) ±12 VDC models: 100 µF (each output) ±15 VDC models: 100 µF (each output) |

General Specifications

| | | |
|---|--|---|
| Temperature ranges | <ul style="list-style-type: none"> - Operating without heat sink - Operating with heat sink - Case temperature - Storage | <ul style="list-style-type: none"> -40°C to +75°C (with derating) -40°C to +85°C (with derating) +100°C max. -40°C to +125°C |
| Power derating | <ul style="list-style-type: none"> - Operating without heat sink - Operating with heat sink | <ul style="list-style-type: none"> 2.5 %/K above +60°C 3.5 %/K above +70°C |
| Thermal impedance | <ul style="list-style-type: none"> - Natural convection - Natural convection with heat sink | <ul style="list-style-type: none"> 18.2°C/W 15.8°C/W |
| Humidity (non condensing) | | 95 % rel H max. |
| Reliability, calculated MTBF (MIL-HDBK-217F, at +25°C, ground benign) | | >350'000 h |
| Isolation voltage (60 sec.) | - Input/Output | 1'500 VDC |
| Isolation capacitance | - Input/Output | 1200 pF max. |
| Isolation resistance | - Input/Output (500 VDC) | >1'000 MOhm |
| Remote On/Off | <ul style="list-style-type: none"> - On: - Off: - Off idle current: | <ul style="list-style-type: none"> 2.5 ... 50 VDC or open circuit 0 ... +1.0 VDC or short circuit pin 6 and pin 2 10 mA max. |
| Switching frequency (fixed) | | 400 kHz typ. (pulse width modulation PWM) |
| Altitude during operation | | 5'000 m max. (16'400 ft) approved |
| Safety standards | | UL/cUL 60950-1, IEC/EN 60950-1 |
| Safety approvals | <ul style="list-style-type: none"> - UL/cUL - CB test certificate according IEC 60950-1 - CSA certificate for UL/cUL 60950-1 | <ul style="list-style-type: none"> www.ul.com -> File no. e188913 (entry pending) www.tracopower.com/products/thl10wi-cb.pdf www.tracopower.com/products/thl10wi-csa.pdf |
| Environmental compliance | <ul style="list-style-type: none"> - Reach - RoHS | <ul style="list-style-type: none"> www.tracopower.com/products/thl10wi-reach.pdf RoHS directive 2011/65/EU |

Physical Specifications

| | |
|-----------------------|------------------------|
| Casing material | metal |
| Baseplate | non conductive FR4 |
| Potting material | epoxy (UL 94V-0 rated) |
| Weight | 15 g (0.53oz) |
| Soldering temperature | max. +260°C / 10sec. |

Application note : www.tracopower.com/products/thl10wi-application.pdf

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Outline Dimensions



| Pin-Out | | |
|---------|---------------|------------|
| Pin | Single | Dual |
| 1 | +Vin (Vcc) | +Vin (Vcc) |
| 2 | -Vin (GND) | -Vin (GND) |
| 3 | + Vout | + Vout |
| 4 | No pin | Common |
| 5 | -Vout | -Vout |
| 6 | Remote On/Off | |



Dimensions in [mm], () = Inch
 Pin diameter \varnothing 1.0 (0.04)
 Pin pitch tolerances: ± 0.25 (± 0.01)
 Tolerances: ± 0.5 (± 0.02)

Heat-Sink (Option)

Order code: THL-HS1
 (cont.: heat-sink, thermal pad, 2 clamps)
Material: Aluminum
Finish: Anodic treatment (black)
Weight: 4.0 g (0.14oz) without converter
 Thermal impedance after assembling: 15.8 K/W



Note:
 The product label on converter has to be removed before mounting the heat-sink.
 For volume orders converters will be supplied with heat-sink already mounted. Please contact factory for quotation.
 Separate heat-sinks are only available for prototypes and small quantity orders.



Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.