


## Insulated Ultrafast Rectifier Module, 80 A



SOT-227

### FEATURES

- Two fully independent diodes
- Fully insulated package
- Ultrafast, soft reverse recovery, with high operation junction temperature ( $T_J$  max. = 175 °C)
- Low forward voltage drop
- Optimized for power conversion: welding and industrial SMPS applications
- Easy to use and parallel
- Industry standard outline
- UL approved file E78996 
- Designed and qualified for industrial level
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS  
COMPLIANT**

| PRODUCT SUMMARY                          |                          |
|--|--------------------------|
| $V_R$                                    | 600 V                    |
| $I_{F(AV)}$ per module at $T_C = 115$ °C | 80 A                     |
| $t_{rr}$                                 | 41 ns                    |
| Type                                     | Modules - Diode FRED Pt® |
| Package                                  | SOT-227                  |

### DESCRIPTION

The VS-UFL80FA60 insulated modules integrate two state of the art ultrafast recovery rectifiers in the compact, industry standard SOT-227 package. The diodes structure, and its life time control, provide an ultrasoft recovery current shape, together with the best overall performance, ruggedness and reliability characteristics.

These devices are thus intended for high frequency applications in which the switching energy is designed not to be predominant portion of the total energy, such as in the output rectification stage of welding machines, SMPS, DC/DC converters. Their extremely optimized stored charge and low recovery current reduce both over dissipation in the switching elements (and snubbers) and EMI/RFI.

| ABSOLUTE MAXIMUM RATINGS                    |                |                                      |             |       |
|---|----------------|--------------------------------------|-------------|-------|
| PARAMETER                                   | SYMBOL         | TEST CONDITIONS                      | MAX.        | UNITS |
| Cathode to anode voltage                    | $V_R$          |                                      | 600         | V     |
| Continuous forward current per diode        | $I_F$          | $T_C = 85$ °C                        | 65          | A     |
| Single pulse forward current per diode      | $I_{FSM}$      | $T_C = 25$ °C                        | 300         |       |
| Maximum power dissipation per module        | $P_D$          | $T_C = 85$ °C                        | 176         | W     |
| RMS isolation voltage                       | $V_{ISOL}$     | Any terminal to case, $t = 1$ minute | 2500        | V     |
| Operating junction and storage temperatures | $T_J, T_{Stg}$ |                                      | - 55 to 175 | °C    |



| ELECTRICAL SPECIFICATIONS PER DIODE ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified) |          |  |                                   |      |      |               |      |
|--|----------|--|-----------------------------------|------|------|---------------|------|
| PARAMETER  | SYMBOL   | TEST CONDITIONS  | MIN.                              | TYP. | MAX. | UNITS         |      |
| Cathode to anode breakdown voltage   | $V_{BR}$ | $I_R = 100\text{ }\mu\text{A}$                               | 600                               | -    | -    | V             |      |
| Forward voltage  | $V_{FM}$ | $I_F = 30\text{ A}$  | -                                 | 1.1  | 1.43 |               |      |
|  |          | $I_F = 60\text{ A}$  | -                                 | 1.27 | 1.49 |               |      |
|  |          | $I_F = 30\text{ A}$  | $T_J = 125\text{ }^\circ\text{C}$ | -    | 1.0  |               | 1.23 |
|  |          | $I_F = 60\text{ A}$  |                                   | -    | 1.17 |               | 1.35 |
| Reverse leakage current  | $I_{RM}$ | $V_R = V_R\text{ rated}$                                     | -                                 | 0.1  | 50   | $\mu\text{A}$ |      |
|  |          | $T_J = 175\text{ }^\circ\text{C}$ , $V_R = V_R\text{ rated}$ | -                                 | 0.2  | 1.0  | mA            |      |
| Junction capacitance   | $C_T$    | $V_R = 600\text{ V}$   | -                                 | 30   | -    | pF            |      |

| DYNAMIC RECOVERY CHARACTERISTICS ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified) |           |                                   |      |      |      |       |
|---|-----------|-----------------------------------|------|------|------|-------|
| PARAMETER   | SYMBOL    | TEST CONDITIONS                   | MIN. | TYP. | MAX. | UNITS |
| Reverse recovery time   | $t_{rr}$  | $T_J = 25\text{ }^\circ\text{C}$  | -    | 41   | -    | ns    |
|   |           | $T_J = 25\text{ }^\circ\text{C}$  |      |      |      |       |
|   |           | $T_J = 125\text{ }^\circ\text{C}$ |      |      |      |       |
| Peak recovery current   | $I_{RRM}$ | $T_J = 25\text{ }^\circ\text{C}$  | -    | 11   | -    | A     |
|   |           | $T_J = 125\text{ }^\circ\text{C}$ |      |      |      |       |
| Reverse recovery charge   | $Q_{rr}$  | $T_J = 25\text{ }^\circ\text{C}$  | -    | 600  | -    | nC    |
|   |           | $T_J = 125\text{ }^\circ\text{C}$ |      |      |      |       |

| THERMAL - MECHANICAL SPECIFICATIONS     |            |                       |         |      |      |                    |
|---|------------|-----------------------|---------|------|------|--------------------|
| PARAMETER                               | SYMBOL     | TEST CONDITIONS       | MIN.    | TYP. | MAX. | UNITS              |
| Junction to case, single leg conducting | $R_{thJC}$ |                       | -       | -    | 1.02 | $^\circ\text{C/W}$ |
| Junction to case, both leg conducting   |            |                       | -       | -    | 0.51 |                    |
| Case to heatsink                        | $R_{thCS}$ | Flat, greased surface | -       | 0.10 | -    |                    |
| Weight                                  |            |                       | -       | 30   | -    | g                  |
| Mounting torque                         |            |                       | -       | -    | 1.3  | Nm                 |
| Case style                              |            |                       | SOT-227 |      |      |                    |




Fig. 1 - Typical Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current (Per Leg)




Fig. 7 - Typical Reverse Recovery Time vs.  $di_F/dt$




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 8 - Typical Stored Charge vs.  $di_F/dt$




Fig. 9 - Typical Stored Current vs.  $di_F/dt$

**Note**

- (1) Formula used:  $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$ ;  
 $Pd$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $Pd_{REV}$  = Inverse power loss =  $V_{R1} \times I_{rr} (1 - D)$ ;  $I_{rr}$  at  $V_{R1} = 80\%$  rated  $V_R$




Fig. 10 - Reverse Recovery Parameter Test Circuit






Fig. 11 - Reverse Recovery Waveform and Definitions

**ORDERING INFORMATION TABLE**

|             |            |           |          |           |          |          |           |
|-------------|------------|-----------|----------|-----------|----------|----------|-----------|
| Device code | <b>VS-</b> | <b>UF</b> | <b>L</b> | <b>80</b> | <b>F</b> | <b>A</b> | <b>60</b> |
|             | ①          | ②         | ③        | ④         | ⑤        | ⑥        | ⑦         |

- 1** - Vishay Semiconductors product
- 2** - Ultrafast rectifier
- 3** - Ultrafast Pt diffused, Low  $V_F$
- 4** - Current rating (80 = 80 A)
- 5** - Circuit configuration (2 separate diodes, parallel pin-out)
- 6** - Package indicator (SOT-227 standard insulated base)
- 7** - Voltage rating (60 = 600 V)

| CIRCUIT CONFIGURATION               |                            |   |
|-------------------------------------|----------------------------|---|
| CIRCUIT                             | CIRCUIT CONFIGURATION CODE | CIRCUIT DRAWING   |
| 2 separate diodes, parallel pin-out | F                          | <br> |

| LINKS TO RELATED DOCUMENTS |  |
|----------------------------|--|
| Dimensions                 | <a href="http://www.vishay.com/doc?95423">www.vishay.com/doc?95423</a> |
| Packaging information      | <a href="http://www.vishay.com/doc?95425">www.vishay.com/doc?95425</a> |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.