Switches in momentary action SMS, PMS, PMK

Models	Construction	Dimensions	Solder pads

SMS
Gullwing-leads

1 2







Solder pads

Gullwing



SMS
J-leads



1 2







Solder pads

J-leads



Buttons in variable heights



Overall height **h** variable



PMS
Through hole mounting



1 2







Drilling diagram

through hole



PMS
height variable



Overall height **h** variable



Circuit diagram



PMK



Shape 1 Shape 2









Technical Data SMS, PMS, PMK

1. Mechanical data	SMS	PMS	PMK
Actuating force IP 40 IP 67	1,8 N ±0,4 N 2,2 N ±0,4 N	1,8 N ±0,4 N 2,2 N ±0,4 N	2,2 N ±0,4 N
Contact travel	0,35 mm ±0,1 mm	0,35 mm ±0,1 mm	0,30 mm ±0,1 mm
(DIN 41640 Teil 19) / End stop strength	> 100 N		
(IEC 512-5 Test 9a, actuating force 5 N) / Lifetime	> 10^6 Operations		

2. Electrical data	
Switching voltage max.	30 V AC / 42 V DC
Switching current max.	50 mA
Lifetime (at rated breaking capacity 0,12 W)	> 10^6 Cycles
(IEC 512-2, mV-Method) Initial contact resistance, new	< 50 mΩ
Initial contact resistance after 10^6 cycles	< 150 mΩ
(IEC 512-2) Insulation resistance	> 10^8 Ω
Contact bounce time	typ. 0,15 ms

3. Other data	SMS	PMS	PMK
Solderability (CECC 00802 und IEC 68-2-20)	IR-Reflow		
(IEC 68-2-20 Test Tb, Method 1A) Soldering heat resistance (IEC 68-2-20 Test Tb, Method 2) (CECC 00802 Classification B) (CECC 00802 Classification C)	 350 °C / 10 s 215 °C / 40 s 260 °C / 10 s	260 °C / 10 s 350 °C / 10 s	 260 °C / 10 s 350 °C / 10 s
Ambient temperature	-40 °C…+85 °C		
Storage temperature	-40 °C…+85 °C		
(IEC 68-2-45) Testmedium Cleaning agent proof	Zestron		
(DIN 41640 Teil 84) Flux-proof	—	given	given
Degree of protection	IP 40 / IP 67	IP 40 / IP 67	IP 67

4. Materials	SMS	PMS	PMK
Contact material gold	CuZn – 1,5 µm Ni + 0,5 µm Au		
Terminals	CuZn – 8 µm SnPb		
Socket	Thermoplast PA 4.6		
Actuator	Thermoplast PPS		
Cover plate	X12CrNi17 7		
Sealing membrane	—	VMQ	VMQ

5. Packaging	SMS	PMS	PMK
	taped and reeled		
	loose in boxes	loose in boxes	loose in boxes

Switches in momentary action SMS, PMS

Models	Variations			Part Number
SMS				
Gullwing-leads 	Degree of protection	IP 40		1241.1600. XX
		IP 67		1241.1606. XX
J-leads 		IP 40		1241.1601. XX
		IP 67		1241.1607. XX
Gullwing-leads 		IP 40		1241.1612. XX
		IP 67		1241.1618. XX
J-leads 		IP 40		1241.1613. XX
		IP 67		1241.1619. XX
	Packaging	loose in boxes		11
		taped and reeled		23
Button in variable heights for long actuators (must be ordered seperately) 	Overall height h 	8,50 mm	(yellow)	0862.8101
		9,25 mm	(orange)	0862.8102
		10,00 mm	(red)	0862.8103
		10,75 mm	(blue)	0862.8104
		11,50 mm	(green)	0862.8105
		12,25 mm	(grey)	0862.8106
		13,00 mm	(black)	0862.8107
		13,75 mm	(white)	0862.8108
	[1] additional key cap			0862.8226

[1] Starting with 14,50 mm, additional (second) key caps for midsizes (h +6 mm) are necessary. Order seperately.

PMS				
Short actuator 	Degree of protection	IP 40		1241.1602
		IP 67		1241.1608
Long actuator 		IP 40		1241.1614
		IP 67		1241.1620
Height variable 	Degree of protection	IP 40		1241.1624. XX
		IP 67		1241.1625. XX
	Overall height h 	(yellow)	8,35 mm = 1	[2]14,35 mm = 11
		(orange)	9,10 mm = 2	15,10 mm = 21
		(red)	9,85 mm = 3	15,85 mm = 31
		(blue)	10,60 mm = 4	16,60 mm = 41
		(green)	11,35 mm = 5	17,35 mm = 51
		(grey)	12,10 mm = 6	18,10 mm = 61
		(black)	12,85 mm = 7	18,85 mm = 71
		(white)	13,60 mm = 8	19,60 mm = 81

[2] Starting with 14,35 mm the heights were realized with an additional (second) keycap.

PMK and key caps for SMS, Illumination key caps

Models	Variations		Part Number
PMK			
Shape 1 	Degree of protection	with legend	1241.1629. X . XXX
		without legend	1241.1629. X . XXX
Shape 2 		with legend	1241.1633. X . XXX
		without legend	1241.1633. X . XXX
Shape 1 	for IP 67 with short actuator	with legend	0865.9541. X . XXX
		without legend	0865.9541. X . XXX
Shape 2 		with legend	0865.9542. X . XXX
		without legend	0862.800 X
SMS Tastkappe Key cap			
Shape 1 	Color of key cap	red	3
		green	5
		grey	6
		black	7
		white	8
	Legend of key cap/insert plate (Type height/ type face see page 39)	A = 001, B = 002, C = 003, D = 004, E = 005, F = 006, G = 007, H = 008, I = 009, J = 010, K = 011, L = 012, M = 013, N = 014, O = 015	P = 016, Q = 017, R = 018, S = 019, T = 020, U = 021, V = 022, W = 023, X = 024, Y = 025, Z = 026, 0 = 027, 1 = 028, 2 = 029, 3 = 030
		4 = 031, 5 = 032, 6 = 033, 7 = 034, 8 = 035, 9 = 036, + = 037, - = 038, · = 039, x = 040, ÷ = 041, ✳ = 042, = = 043, # = 044, ↔ = 045	↕ = 046, → = 047, ← = 048, ↓ = 049, ↑ = 050, % = 051, √ = 052, CTRL = 053, RETURN = 054, SHIFT = 055, LOCK = 056, STOP = 057, ENTER = 058, BACK = 059, LINE = 060
			EIN = 061, AUS = 062, AUF = 063, AB = 064, ON = 065, OFF = 066, UP = 067, DOWN = 068, HIGH = 069, LOW = 070, ON/OFF = 071, START = 072
PMK			
Shape 2 	Color of insert plate without legend shape 1	yellow = 091, orange = 092, red = 093, blue = 094, green = 095	grey = 096, black = 097, white = 098, anthracite = 099
Illumination key cap 	In Preparation		
	Color of key cap	transparent	0859.9335

Aufragsbezogene Fertigung / Order specific production

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.