

Flexible RF cable S_01162_D-01

Description

S: Low loss RF cables with foam PE dielectrics
 50 Ohm, 2 GHz, 85°C, ø2.7 mm, LSFH jacket



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Strand-07	0.54 mm
Dielectric	SPE (Foamed Polyethylene)		1.37 mm
Outer conductor	Copper	Braid, 91%	1.7 mm
Outer conductor	Copper	Braid, 90 %	2.2 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	2.7 mm +/- 0.1

Print: No print on jacket

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	2 GHz
Capacitance	82 pF/m
Velocity of signal propagation	82 %
Signal delay	4.15 ns/m
Screening effectiveness	≥ 50 dB (up to 2 GHz)
Operating voltage	≤ 0.2 kV _{rms} (at sea level)
Test voltage	0.4 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		1.3 kg/100 m
Min. bending radius	static	12 mm
	repeated	26 mm
	dynamic	40 mm

Environmental Data

Temperature range	-40 °C ... +85 °C
Installation temperature	-20 °C... +60 °C
Halogen test	IEC 60754
Halogen free	Yes
2011/65/EU (RoHS)	compliant
2006/1907/EC (REACH)	compliant
2000/53/EC (ELV)	compliant
2012/19/EU (WEEE)	no special marking needed

Additional Information

Ordering Information

Order as S_01162_D-01

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group X3 2 mm / 50 Ohm

Flexible RF cable S_01162_D-01

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.7625

b = 0.0428

$f_{max} = 2$

P at 1GHz = 42

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,1	0,25	0,075	133
0,2	0,35	0,107	94
0,3	0,43	0,131	77
0,4	0,5	0,152	66
0,5	0,56	0,171	59
0,6	0,62	0,188	54
0,7	0,67	0,204	50
0,8	0,72	0,218	47
0,9	0,76	0,232	44
1,0	0,81	0,245	42
1,1	0,85	0,258	40
1,2	0,89	0,270	38
1,3	0,93	0,282	37
1,4	0,96	0,293	35
1,5	1,0	0,304	34
1,6	1,03	0,315	33
1,7	1,07	0,325	32
1,8	1,1	0,335	31
1,9	1,13	0,345	30
2,0	1,16	0,355	30

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[S_01162_D-01](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.