



RS-WC-201: ADVANCED WI-FI FOR M2M APPLICATIONS

The RS-WC-201 WiSeConnect™ module is a fully integrated 802.11 b/g/n module with advanced features for M2M, industrial, medical, enterprise and IOT (Internet of Things) applications. Powered with Wi-Fi Direct™, it can directly communicate with smartphones and tablet PCs without any Access Point based infrastructure. Integrated with Enterprise Security as well as TCP/IP and WLAN stacks, it can be designed quickly into any Host platform for secure and standards based Wi-Fi connectivity. The module also supports Access Point mode and can host data from a variety of sources such as sensors etc. in the module's in-built web server. Requiring no external BOM, the module integrates a MAC, Baseband Processor, RF Transceiver with power amplifier, a frequency reference and an antenna. The module comes with a comprehensive API set to make software integration quick and seamless. Based on Redpine Signals' 802.11n SoC RS9110, it is designed to provide wireless connectivity to devices that have a UART, SPI or USB interface.



Features

- 802.11b/g and single stream 802.11n
- Wi-Fi Direct™, Access Point and Client mode
- Enterprise Security - EAP-TLS, EAP-TTLS, EAP-FAST, PEAP-MSCHAP-V2
- Integrated TCP/IP stack, HTTP Server/Client, DHCP, DNS
- Over the air Firmware Upgrade
- Integrated antenna and option for external antenna
- Ultra low power operation with power save modes
- Single supply 3.1 to 3.6 V operation

Applications

- Consumer - Wi-Fi Connectivity for home appliances
- Enterprise - Wireless printers, Security cameras, Point of Sale terminals
- Industrial - M2M communication, industrial monitoring and control, data logging and streaming
- Medical - Patient monitoring, medical instrumentation with secure wireless connectivity


Specifications

Network Standard Support	IEEE 802.11b/g/n
Frequency band	2.400 - 2.500 GHz
Data Rates	802.11n: 6.5, 13, 19.5, 26, 39, 52, 58.5 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps
Modulation Techniques	OFDM with BPSK, QPSK, 16-QAM, and 64-QAM 802.11b with CCK and DSSS
Connectivity	Wi-Fi Direct mode, Access Point mode and Client mode
Wireless Security	WPA/WPA2-Enterprise, WPA/WPA2-PSK, WPS Provisioning
Networking protocols	TCP, UDP, DHCP, ARP, IGMP, DNS client
HTTP Server	Integrated Web Server for browser based connectivity
Host Interfaces	SPI, USB, UART(AT Commands supported)
Data throughput	Up to 5.5 Mbps in SPI and USB modes, 90 kbps in UART mode at a benchmark baud rate of 115200 bps
Operating Temperature	-40°C to +85°C
Supply Voltage	3.1 - 3.6 V
Dimensions	35mm x 22mm

Evaluation Package

Redpine Signals provides a comprehensive evaluation package that includes an evaluation board, software, driver source code for the Host interface and documentation.

RS-WC-201 SYSTEM ARCHITECTURE



For additional information, please contact Sales at Redpine Signals, Inc.:

Redpine Signals, Inc. • 2107 North First Street • Suite 680 • San Jose, CA 95131

Phone: +1 408 748 3385 • Email: sales@redpinesignals.com

www.redpinesignals.com

Redpine Signals, Inc. reserves the right to make changes to the product(s) or information contained herein without notice. No Liability is assumed as a result of their use or application. Redpine, Redpine Signals, the Redpine logo, Driving Wireless Convergence, WiSeConnect and Lite-Fi are trademarks of Redpine Signals, Inc. All other company names, products and logos are registered trademarks of their respective companies.

© Copyright 2012 Redpine Signals, Inc. All Rights Reserved.

WiSeConnect™



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.