


## Power Schottky rectifier

Datasheet - production data



### Description

This dual Schottky rectifier is designed for switch mode power supplies and other power converters.

This device is intended for use in low and medium voltage operation, and in particular high frequency circuits where low switching losses are required (free wheeling and polarity protection).

**Table 1: Device summary**

| Symbol      | Value   |
|-------------|---------|
| $I_{F(AV)}$ | 2 x 3 A |
| $V_{RRM}$   | 40 V    |
| $T_j$ (max) | 150 °C  |
| $V_F$ (typ) | 0.50 V  |

### Features

- Very small conduction losses
- Extremely fast switching
- Low thermal resistance
- Negligible switching losses
- Low forward voltage drop
- Low capacitance
- Avalanche specification
- ECOPACK®2 compliant component for DPAK on demand

# 1 Characteristics

**Table 2: Absolute ratings (limiting values at 25 °C, per diode, unless otherwise specified)**

| Symbol              | Parameter                                             |                                            | Value       | Unit |
|---------------------|-------------------------------------------------------|--------------------------------------------|-------------|------|
| V <sub>RRM</sub>    | Repetitive peak reverse voltage                       |                                            | 40          | V    |
| I <sub>F(RMS)</sub> | Forward rms current                                   |                                            | 6           | A    |
| I <sub>F(AV)</sub>  | Average forward current $\delta = 0.5$ , square wave  | T <sub>C</sub> = 135 °C                    | 3           | A    |
| I <sub>FSM</sub>    | Surge non repetitive forward current                  | tp = 10 ms sinusoidal                      | 75          | A    |
| P <sub>ARM</sub>    | Repetitive peak avalanche power                       | tp = 10 $\mu$ s<br>T <sub>J</sub> = 125 °C | 90          | W    |
| T <sub>stg</sub>    | Storage temperature range                             |                                            | -65 to +150 | °C   |
| T <sub>J</sub>      | Maximum operating junction temperature <sup>(1)</sup> |                                            | 150         | °C   |

**Notes:**

<sup>(1)</sup>(dP<sub>tot</sub>/dT<sub>J</sub>) < (1/R<sub>th(j-a)</sub>) condition to avoid thermal runaway for a diode on its own heatsink.

**Table 3: Thermal parameters**

| Symbol               | Parameter        |            | Max. value | Unit |
|----------------------|------------------|------------|------------|------|
| R <sub>th(j-c)</sub> | Junction to case | Per diode  | 5.5        | °C/W |
|                      |                  | Per device | 3          |      |
| R <sub>th(c)</sub>   | Coupling         |            | 0.5        |      |

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_j (\text{diode1}) = P_{(\text{diode1})} \times R_{th(j-c)} (\text{per diode}) + P_{(\text{diode2})} \times R_{th(c)}$$

**Table 4: Static electrical characteristics (per diode)**

| Symbol                        | Parameter               | Test conditions         |                                   | Min. | Typ. | Max. | Unit    |
|-------------------------------|-------------------------|-------------------------|-----------------------------------|------|------|------|---------|
| I <sub>R</sub> <sup>(1)</sup> | Reverse leakage current | T <sub>J</sub> = 25 °C  | V <sub>R</sub> = V <sub>RRM</sub> | -    |      | 100  | $\mu$ A |
|                               |                         | T <sub>J</sub> = 125 °C |                                   | -    | 2    | 10   | mA      |
| V <sub>F</sub> <sup>(2)</sup> | Forward voltage drop    | T <sub>J</sub> = 25 °C  | I <sub>F</sub> = 3 A              | -    |      | 0.63 | V       |
|                               |                         | T <sub>J</sub> = 125 °C |                                   | -    | 0.50 | 0.57 |         |
|                               |                         | T <sub>J</sub> = 25 °C  | I <sub>F</sub> = 6 A              | -    |      | 0.84 |         |
|                               |                         | T <sub>J</sub> = 125 °C |                                   | -    | 0.67 | 0.72 |         |

**Notes:**

<sup>(1)</sup>Pulse test: t<sub>p</sub> = 5 ms,  $\delta < 2\%$


<sup>(2)</sup>Pulse test: t<sub>p</sub> = 380  $\mu$ s,  $\delta < 2\%$

To evaluate the conduction losses, use the following equation:


$$P = 0.42 \times I_{F(AV)} + 0.050 \times I_{F(RMS)}^2$$

## 1.1 Characteristics (curves)


**Figure 1: Average forward power dissipation versus average forward current(per diode)**




**Figure 2: Average forward current versus ambient temperature (per diode,  $\delta = 0.5$ )**




**Figure 3: Normalized avalanche power derating versus pulse duration ( $T_j = 125^\circ\text{C}$ )**




**Figure 4: Relative variation of thermal impedance junction to case versus pulse duration**





**Figure 5: Reverse leakage current versus reverse voltage applied (typical values, per diode)**



**Figure 6: Junction capacitance versus reverse voltage applied (typical values, per diode)**



**Figure 7: Forward voltage drop versus forward current (maximum values, per diode)****Figure 8: Thermal resistance junction to ambient versus copper surface under tab**


## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

- Cooling method: by conduction (C)
- Epoxy meets UL 94,V0

### 2.1 DPAK package information

Figure 9: DPAK package outline




This package drawing may slightly differ from the physical package. However, all the specified dimensions are guaranteed.

Table 5: DPAK package mechanical data

| Ref. | Dimensions  |       |            |       |
|------|-------------|-------|------------|-------|
|      | Millimeters |       | Inches     |       |
|      | Min.        | Max.  | Min.       | Max.  |
| A    | 2.18        | 2.40  | 0.085      | 0.094 |
| A1   | 0.90        | 1.10  | 0.035      | 0.043 |
| A2   | 0.03        | 0.23  | 0.001      | 0.009 |
| b    | 0.64        | 0.90  | 0.025      | 0.035 |
| b4   | 4.95        | 5.46  | 0.194      | 0.215 |
| c    | 0.46        | 0.61  | 0.018      | 0.024 |
| c2   | 0.46        | 0.60  | 0.018      | 0.023 |
| D    | 5.97        | 6.22  | 0.235      | 0.244 |
| D1   | 4.95        | 5.60  | 0.194      | 0.220 |
| E    | 6.35        | 6.73  | 0.250      | 0.265 |
| E1   | 4.32        | 5.50  | 0.170      | 0.216 |
| e    | 2.286 typ.  |       | 0.090 typ. |       |
| e1   | 4.40        | 4.70  | 0.173      | 0.185 |
| H    | 9.35        | 10.40 | 0.368      | 0.409 |
| L    | 1.0         | 1.78  | 0.039      | 0.070 |
| L2   |             | 1.27  |            | 0.050 |
| L4   | 0.60        | 1.02  | 0.023      | 0.040 |
| V2   | -8°         | +8°   | -8°        | +8°   |

Figure 10: DPAK recommended footprint (dimensions in mm)



### 3 Ordering information

Table 6: Ordering information

| Order code   | Marking | Package | Weight | Base qty | Delivery mode |
|--------------|---------|---------|--------|----------|---------------|
| STPS640CB    | S6 40C  | DPAK    | 0.32 g | 75       | Tube          |
| STPS640CB-TR | S6 40C  |         |        | 2500     | Tape and reel |

### 4 Revision history

Table 7: Document revision history

| Date        | Revision | Changes                                                                                               |
|-------------|----------|-------------------------------------------------------------------------------------------------------|
| Aug-2003    | 6B       | Last issue                                                                                            |
| 22-Mar-2007 | 7        | Updated <i>Figure 8</i> Updated ECOPACK statement.                                                    |
| 20-Nov-2014 | 8        | <i>Figure 3</i> . Removed PARM (T <sub>j</sub> = 25 °C), TO-220AB and TO-220FPAB package information. |
| 16-May-2017 | 9        | Updated DPAK package information and reformatted to current standard.                                 |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.