# DSC1101/21

## Low-Jitter Precision CMOS Oscillator

### Features

- Low RMS Phase Jitter: <1 ps (typ.)
- High Stability: ±10 ppm, ±20 ppm, ±25 ppm, ±50 ppm
- Wide Temperature Range:
  - Automotive: –55°C to +125°C
  - Ext. Industrial: –40°C to +105°C
  - Industrial: –40°C to +85°C
  - Commercial: –20°C to +70°C
- High Supply Noise Rejection: –50 dBc
- Wide Freq. Range: 2.3 MHz to 170 MHz
- Small Industry Standard Footprints
  - 2.5 mm x 2.0 mm, 3.2 mm x 2.5 mm, 5.0 mm x 3.2 mm, and 7.0 mm x 5.0 mm
- Excellent Shock and Vibration Immunity
  - Qualified to MIL-STD-883
- High Reliability
  - 20x Better MTF than Quartz Oscillators
- Low Current Consumption
- Supply Range of 2.25 to 3.6V
- Standby and Output Enable Function
- Lead-Free and RoHS Compliant

### Applications

- Storage Area Networks
  - SATA, SAS, Fibre Channel
- Passive Optical Networks
  - EPON, 10G-EPON,V GPON, 10G-PON
- Ethernet
  - 1G, 10GBASE-T/KR/LR/SR, and FCoE
- HD/SD/SDI Video and Surveillance
- PCI Express
- Display Port

### General Description

The DSC1101 and DSC1121 series of high performance oscillators utilize a proven silicon MEMS technology to provide excellent jitter and stability over a wide range of supply voltages and temperatures. By eliminating the need for quartz or SAW technology, MEMS oscillators significantly enhance reliability and accelerate product development, while meeting stringent clock performance criteria for a variety of communications, storage, and networking applications.

DSC1101 has a standby feature that allows it to completely power-down when EN pin is pulled low; whereas for DSC1121, only the outputs are disabled when EN is low. Both oscillators are available in industry standard packages, including the small 2.5 mm x 2.0 mm, and are “drop-in” replacements for standard 4-pin CMOS quartz crystal oscillators.

### Functional Block Diagram




© 2017 Microchip Technology Inc.

## 1.0 ELECTRICAL CHARACTERISTICS

### Absolute Maximum Ratings †

Input Voltage, $V_{IN}$ .....–0.3V to $V_{DD}$ + 0.3V
Supply Voltage .....–0.3V to +4.0V
ESD Protection On All Pins .....4000V HBM, 1500V CDM (max.)

† **Notice:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

| **Note:** | 1000+ years of data retention on internal memory. |
|---|---|

**TABLE 1-1: DC CHARACTERISTICS**

| **Electrical Characteristics** | | | | | | |
|---|---|---|---|---|---|---|
| **Parameters** | **Sym.** | **Min.** | **Typ.** | **Max.** | **Units** | **Conditions** |
| Supply Voltage (Note 1) | $V_{DD}$ | 2.25 | — | 3.6 | V | — |
| Supply Current | $I_{DD}$ | — | — | 0.095 | mA | DSC1101, EN pin low, output is disabled |
| | | — | 20 | 22 | | DSC1121, EN pin low, output is disabled |
| | | — | 31 | 35 | | Output enabled, $C_L$ = 15 pF, $F_0$ = 100 MHz |
| Frequency Stability (Including frequency variations due to initial tolerance, temp. and power supply voltage.) | Δf | — | — | ±10 | ppm | Ext Comm. & Ind. only |
| | | | | ±20 | | All temp ranges |
| | | — | — | ±25 | | All temp ranges |
| | | — | — | ±50 | | All temp ranges |
| Aging | Δf | — | — | ±5 | ppm | 1 year @ 25°C |
| Startup Time (Note 2) | $t_{SU}$ | — | — | 5 | ms | T = 25°C |
| Input Logic Levels<br>Input Logic High<br>Input Logic Low | $V_{IH}$ | 0.75×$V_{DD}$ | — | — | V | — |
| | $V_{IL}$ | — | — | 0.1×$V_{DD}$ | | |
| Output Disable Time (Note 3) | $t_{DS}$ | — | — | 5 | ns | — |
| Output Enable Time | $t_{EN}$ | — | — | 5 | ms | DSC1101 |
| | | — | — | 20 | ns | DSC1121 |
| Enable Pull-up Resistor (Note 4) | — | — | — | 40 | — | kΩ | Pull-up Resistor Exist |
| **CMOS Output** | | | | | | |
| Output Logic Levels<br>Output Logic High<br>Output Logic Low | $V_{OH}$ | 0.9×$V_{DD}$ | — | — | V | I = ±6 mA |
| | $V_{OL}$ | — | — | 0.1×$V_{DD}$ | | |

**Note 1:** Pin 6 $V_{DD}$ should be filtered with 0.1 µF capacitor.
**2:** $t_{SU}$ is time to 100 ppm of output frequency after $V_{DD}$ is applied and outputs are enabled.
**3:** Output Waveform and Test Circuit figures define the parameters.
**4:** Output is enabled if pad is floated or not connected.


© 2017 Microchip Technology Inc.

**TABLE 1-1: DC CHARACTERISTICS (CONTINUED)**

| Electrical Characteristics | | | | | | |
|---|---|---|---|---|---|---|
| **Parameters** | **Sym.** | **Min.** | **Typ.** | **Max.** | **Units** | **Conditions** |
| Output Transition Time<br>Rise Time<br>Fall Time | $t_R$ | — | 1.1 | 2 | ns | 20% to 80%<br>$C_L$ = 15 pF |
| | $t_F$ | — | 1.3 | 2 | | |
| Frequency | $f_0$ | 2.3 | — | 170 | MHz | $C_L$ = 15 pF, –20°C to +70°C and –40°C to +85°C |
| | | 3.3 | — | 170 | | $C_L$ = 15 pF, –40°C to +105°C and –55°C to +125°C |
| Output Duty Cycle | SYM | 45 | — | 55 | % | — |
| Period Jitter | $J_{PER}$ | — | 3 | — | $ps_{RMS}$ | $F_{OUT}$ = 125 MHz |
| Integrated Phase Noise | $J_{PH}$ | — | 0.3 | — | $ps_{RMS}$ | 200 kHz to 20 MHz @ 125 MHz |
| | | — | 0.38 | — | | 100 kHz to 20 MHz @ 125 MHz |
| | | — | 1.7 | 2 | | 12 kHz to 20 MHz @ 125 MHz |

**Note 1:** Pin 6 $V_{DD}$ should be filtered with 0.1 µF capacitor.

**2:** $t_{SU}$ is time to 100 ppm of output frequency after $V_{DD}$ is applied and outputs are enabled.

**3:** Output Waveform and Test Circuit figures define the parameters.

**4:** Output is enabled if pad is floated or not connected.

## TEMPERATURE SPECIFICATIONS (Note 1)

| Parameters | Sym. | Min. | Typ. | Max. | Units | Conditions |
|---|---|---|---|---|---|---|
| **Temperature Ranges** | | | | | | |
| Operating Temperature Range (T) | $T_A$ | –20 | — | +70 | °C | Ordering Option E |
| | $T_A$ | –40 | — | +85 | °C | Ordering Option I |
| | $T_A$ | –40 | — | +105 | °C | Ordering Option L |
| | $T_A$ | –55 | — | +125 | °C | Ordering Option M |
| Junction Operating Temperature | $T_J$ | — | — | +150 | °C | — |
| Storage Temperature Range | $T_A$ | –40 | — | +150 | °C | — |
| Soldering Temperature Range | $T_S$ | — | — | +260 | °C | 40 sec. max |

**Note 1:** The maximum allowable power dissipation is a function of ambient temperature, the maximum allowable junction temperature and the thermal resistance from junction to air (i.e., $T_A$, $T_J$, $\theta_{JA}$). Exceeding the maximum allowable power dissipation will cause the device operating junction temperature to exceed the maximum +125°C rating. Sustained junction temperatures above +125°C can impact the device reliability.


© 2017 Microchip Technology Inc.

## 2.0 NOMINAL PERFORMANCE CURVES

**Note:** The graphs and tables provided following this note are a statistical summary based on a limited number of samples and are provided for informational purposes only. The performance characteristics listed herein are not tested or guaranteed. In some graphs or tables, the data presented may be outside the specified operating range (e.g., outside specified power supply range) and therefore outside the warranted range.




***FIGURE 2-1:*** *Phase Jitter (Integrated Phase Noise).*




***FIGURE 2-2:*** *Power Supply Rejection Ratio.*

## 3.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in Table 3-1. Pin order and descriptions apply across all package types.

**TABLE 3-1: PIN FUNCTION TABLE**

| Pin Number 7x5 w/ Pad | Pin Number 7x5 w/o Pad | Pin Number 5x3.2 | Pin Number 3.2x2.5 | Pin Number 2x2.5 | Pin Name | Description |
|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 1 | 1 | EN | Enable. |
| 2 | 2 | 2 | 2 | 2 | NC | Do not connect. |
| 3 | 3 | 3 | 3 | 3 | GND | Ground. |
| 4 | 4 | 4 | 4 | 4 | OUT | Output. |
| 5 | 5 | 5 | 5 | 5 | NC | Do not connect. |
| 6 | 6 | 6 | 6 | 6 | $V_{DD}$ | Supply voltage. |
| PAD | — | — | — | — | PAD | Tie to ground. |

**TABLE 3-2: OUTPUT ENABLE MODES**

| EN Pin | DSC1101 | DSC1121 |
|---|---|---|
| High | Output Active | Output Active |
| NC | Output Active | Output Active |
| Low | Standby | Output Disabled |


© 2017 Microchip Technology Inc.

## 4.0 OUTPUT WAVEFORM




***FIGURE 4-1:*** *DSC1101/21 Output Waveform.*

## 5.0 TYPICAL TERMINATION SCHEME




***FIGURE 5-1:*** *Typical Termination Scheme for DSC1101/21.*


© 2017 Microchip Technology Inc.

## 6.0 BOARD LAYOUT (RECOMMENDED)




***FIGURE 6-1:*** *DSC1101/21 Recommended Board Layout.*

## 7.0 SOLDER REFLOW PROFILE




| MSL 1 @ 260°C refer to JSTD-020C | |
|---|---|
| Ramp-Up Rate (200°C to Peak Temp) | 3°C/Sec. Max. |
| Preheat Time 150°C to 200°C | 60-180 Sec. |
| Time Maintained Above 217°C | 60-150 Sec. |
| Peak Temperature | 255-260°C |
| Time within 5°C of Actual Peak | 20-40 Sec. |
| Ramp-Down Rate | 6°C/Sec. Max. |
| Time 25°C to Peak Temperature | 8 minute Max. |


© 2017 Microchip Technology Inc.

## 8.0 PACKAGING INFORMATION

### 8.1 Package Marking Information

6-Pin CDFN/VDFN*




Example




| | | |
|---|---|---|
| **Legend:** | XX...X | Product code, customer-specific information, or frequency in MHz without printed decimal point |
| | Y | Year code (last digit of calendar year) |
| | YY | Year code (last 2 digits of calendar year) |
| | WW | Week code (week of January 1 is week ‘01’) |
| | SSS | Alphanumeric traceability code |
| | (e3) | Pb-free JEDEC® designator for Matte Tin (Sn) |
| | * | This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package. |
| | ●, ▲, ▼ | Pin one index is identified by a dot, delta up, or delta down (triangle |
| **Note**: | In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo. | |
| | Underbar (_) and/or Overbar (¯) symbol may not be to scale. | |

## 6-Lead VDFN 2.5 mm x 2.0 mm Package Outline and Recommended Land Pattern

### 6-Lead Very Thin Dual Flatpack No-Leads (J7A) - 2.5x2.0 mm Body [VDFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1005A Sheet 1 of 2


© 2017 Microchip Technology Inc.

### 6-Lead Very Thin Dual Flatpack No-Leads (J7A) - 2.5x2.0 mm Body [VDFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



| Units | | MILLIMETERS | | |
|---|---|---|---|---|
| Dimension Limits | | MIN | NOM | MAX |
| Number of Terminals | N | | 6 | |
| Pitch | e | | 0.825 BSC | |
| Overall Height | A | 0.80 | 0.85 | 0.90 |
| Standoff | A1 | 0.00 | 0.02 | 0.05 |
| Overall Length | D | | 2.50 BSC | |
| Overall Width | E | | 2.00 BSC | |
| Terminal Width | b1 | 0.60 | 0.65 | 0.70 |
| Terminal Width | b2 | 0.20 | 0.25 | 0.30 |
| Terminal Length | L1 | 0.60 | 0.70 | 0.80 |
| Terminal Length | L2 | 0.665 | 0.765 | 0.865 |

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1005A Sheet 2 of 2

### 6-Lead Very Thin Dual Flatpack No-Leads (J7A) - 2.5x2.0 mm Body [VDFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




RECOMMENDED LAND PATTERN

| Units | | MILLIMETERS | | |
|---|---|---|---|---|
| Dimension Limits | | MIN | NOM | MAX |
| Contact Pitch | E | | 0.825 BSC | |
| Contact Pad Width (X4) | X1 | | | 0.65 |
| Contact Pad Width (X2) | X2 | | | 0.25 |
| Contact Pad Length (X6) | Y | | | 0.85 |
| Contact Pad Spacing | C | | 1.45 | |
| Space Between Contacts (X4) | G1 | 0.38 | | |
| Space Between Contacts (X3) | G2 | 0.60 | | |

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3005A


© 2017 Microchip Technology Inc.

## 6-Lead VDFN 3.2 mm x 2.5 mm Package Outline and Recommended Land Pattern

### 6-Lead Very Thin Plastic Dual Flatpack No-Lead (H5A) - 3.2x2.5 mm Body [VDFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1007A Sheet 1 of 2

### 6-Lead Very Thin Plastic Dual Flatpack No-Lead (H5A) - 3.2x2.5 mm Body [VDFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



| Units | | MILLIMETERS | | |
|---|---|---|---|---|
| Dimension Limits | | MIN | NOM | MAX |
| Number of Terminals | N | | 6 | |
| Pitch | e | | 1.05 BSC | |
| Overall Height | A | 0.80 | 0.85 | 0.90 |
| Standoff | A1 | 0.00 | 0.02 | 0.05 |
| Overall Length | D | | 3.20 BSC | |
| Overall Width | E | | 2.50 BSC | |
| Terminal Width | b1 | 0.85 | 0.90 | 0.95 |
| Terminal Width | b2 | 0.45 | 0.50 | 0.55 |
| Terminal Length | L | 0.65 | 0.70 | 0.75 |
| Terminal Pullback | L1 | | 0.10 REF | |

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1007A Sheet 2 of 2


© 2017 Microchip Technology Inc.

**6-Lead Very Thin Plastic Dual Flatpack No-Lead (H5A) - 3.2x2.5 mm Body [VDFN]**

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




RECOMMENDED LAND PATTERN

| Units | | MILLIMETERS | | |
|---|---|---|---|---|
| Dimension Limits | | MIN | NOM | MAX |
| Contact Pitch | E | | 1.05 BSC | |
| Contact Pad Spacing | C | | 1.60 | |
| Contact Pad Width (X4) | X1 | | | 1.00 |
| Contact Pad Width (X2) | X2 | | | 0.60 |
| Contact Pad Length (X6) | Y | | | 0.85 |
| Space Between Contacts (X4) | G1 | 0.25 | | |

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-3007A

## 6-Lead CDFN 5.0 mm x 3.2 mm Package Outline and Recommended Land Pattern

**TITLE**
6 LEAD CDFN 5.0x3.2mm COL PACKAGE OUTLINE & RECOMMENDED LAND PATTERN

| DRAWING # | CDFN5032-6LD-PL-1 | UNIT | MM |
|---|---|---|---|




Top View




Bottom View




Side View




Recommended Land Pattern

NOTE:

1. * Power Supply Decoupling Capacitor is required in Recommended Land Pattern.
2. Green shaded rectangles in Recommended Land Pattern are solder stencil opening.
3. Red circles in Recommended Land Pattern are thermal VIA.

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging.


© 2017 Microchip Technology Inc.

## 6-Lead VDFN 7.0 mm x 5.0 mm Package Outline and Recommended Land Pattern

### 6-Lead Very Thin Plastic Quad Flat, No Lead Package (H8A) - 7x5 mm Body [VDFN] With 2.8x1.8 mm Exposed Pad

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




RECOMMENDED LAND PATTERN

| Units | | MILLIMETERS | | |
|---|---|---|---|---|
| Dimension Limits | | MIN | NOM | MAX |
| Contact Pitch | E | 2.54 BSC | | |
| Optional Center Pad Width | X2 | | | 2.90 |
| Optional Center Pad Length | Y2 | | | 1.90 |
| Contact Pad Spacing | C | | 3.70 | |
| Contact Pad Width (X6) | X1 | | | 1.50 |
| Contact Pad Length (X6) | Y1 | | | 1.35 |
| Contact Pad to Center Pad (X2) | G | 0.20 | | |
| Thermal Via Diameter (X6) | V | | 0.33 | |
| Thermal Via Pitch | EV | | 1.20 | |

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3010A

**6-Lead Very Thin Plastic Quad Flat, No Lead Package (H8A) - 7x5 mm Body [VDFN] With 2.8x1.8 mm Exposed Pad**

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




TOP VIEW




SIDE VIEW




BOTTOM VIEW

Microchip Technology Drawing C04-1010A Sheet 1 of 2


© 2017 Microchip Technology Inc.

**6-Lead Very Thin Plastic Quad Flat, No Lead Package (H8A) - 7x5 mm Body [VDFN] With 2.8x1.8 mm Exposed Pad**

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



| Units | | MILLIMETERS | | |
|---|---|---|---|---|
| Dimension Limits | | MIN | NOM | MAX |
| Number of Terminals | N | | 6 | |
| Pitch | e | | 2.54 | |
| Overall Height | A | 0.80 | 0.85 | 0.90 |
| Standoff | A1 | 0.00 | 0.02 | 0.05 |
| Overall Length | D | | 7.00 BSC | |
| Exposed Pad Length | D2 | 2.70 | 2.80 | 2.90 |
| Overall Width | E | | 5.00 BSC | |
| Exposed Pad Width | E2 | 1.70 | 1.80 | 1.90 |
| Terminal Width | b | 1.35 | 1.40 | 1.45 |
| Terminal Length | L | 1.00 | 1.10 | 1.20 |
| Terminal-to-Exposed-Pad | K | | 0.20 REF | |

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

   REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1010A Sheet 2 of 2

## 6-Lead CDFN 7.0 mm x 5.0 mm Package Outline and Recommended Land Pattern

**TITLE**

6 LEAD CDFN 7.0x5.0mm COL PACKAGE OUTLINE & RECOMMENDED LAND PATTERN

| DRAWING # | CDFN75-6LD-PL-1 | UNIT | MM |
|---|---|---|---|




Top View




Bottom View

Side View




Recommended Land Pattern

NOTE:

1. * Power Supply Decoupling Capacitor is required in Recommended Land Pattern.
2. Green shaded rectangles in Recommended Land Pattern are solder stencil opening.
3. Red circles in Recommended Land Pattern are thermal VIA.

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging.


© 2017 Microchip Technology Inc.

**NOTES:**

© 2017 Microchip Technology Inc.

# APPENDIX A: REVISION HISTORY

## Revision A (August 2017)

- Initial creation of document DSC1101/21 to Microchip data sheet template DS20005613A.
- Minor text changes throughout.

## Revision B (December 2017)

- Military temperature range changed to Automotive in Features and Product Identification System.
- Supply Current values updated in Table 1-1.
- Test Circuit section removed.
- Updated Figure 6-1, Recommended Board Layout.

**NOTES:**


© 2017 Microchip Technology Inc.

## PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

| PART NO. | X | X | X | -XXX.XXXX | X |
|---|---|---|---|---|---|
| Device | Package | Temperature Range | Stability | Frequency | Packaging Option |

| | | | |
|---|---|---|---|
| **Device:** | DSC1101: | | Low-Power Precision CMOS Oscillator with Standby |
| | DSC1121: | | Low-Power Precision CMOS Oscillator |
| **Package:** | A | = | 6-Lead 7.0 mm x 5.0 mm VDFN |
| | B | = | 6-Lead 5.0 mm x 3.2 mm CDFN |
| | C | = | 6-Lead 3.2 mm x 2.5 mm VDFN |
| | D | = | 6-Lead 2.5 mm x 2.0 mm VDFN |
| | N | = | 6-Lead 7.0 mm x 5.0 mm CDFN (no center pad) |
| **Temperature Range:** | E | = | –20°C to +70°C (Extended Commercial) |
| | I | = | –40°C to +85°C (Industrial) |
| | L | = | –40°C to +105°C (Extended Industrial) |
| | M | = | –55°C to +125°C (Automotive) |
| **Stability:** | 1 | = | ±50 ppm |
| | 2 | = | ±25 ppm |
| | 3 | = | ±20 ppm |
| | 5 | = | ±10 ppm |
| **Frequency:** | xxx.xxxx | = | 2.3 MHz to 170 MHz (user-defined) |
| **Packing Option:** | <blank>= | | 110/Tube |
| | T | = | 1,000/Reel |

**Examples:**

a) DSC1101AM1-010.0000T: Low-Power Precision CMOS Oscillator with Standby, 6-LD 7.0X5.0 VDFN, Automotive Temperature Range, ±50 ppm, 10 MHz Output Frequency, 1,000/Reel

b) DSC1101BL2-030.0000: Low-Power Precision CMOS Oscillator with Standby, 6-LD 5.0X3.2 CDFN, Extended Industrial Temperature Range, ±25 ppm, 30 MHz Output Frequency, 110/Tube

c) DSC1101DE5-150.0000: Low-Power Precision CMOS Oscillator with Standby, 6-LD 2.5X2.0 VDFN, Extended Commercial Temperature Range, ±10 ppm, 150 MHz Output Frequency, 110/Tube

d) DSC1101AI2-075.0000T: Low-Power Precision CMOS Oscillator with Standby, 6-LD 7.0X5.0 VDFN, Industrial Temperature Range, ±25 ppm, 75 MHz Output Frequency, 1,000/Reel

**Note 1:** Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

**NOTES:**


© 2017 Microchip Technology Inc.

**Note the following details of the code protection feature on Microchip devices:**

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE**.** Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

*Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.*

**QUALITY MANAGEMENT SYSTEM**
**CERTIFIED BY DNV**
**═ ISO/TS 16949 ═**

**Trademarks**

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BeaconThings, BitCloud, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KEELOQ, KEELOQ logo, Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, RightTouch, SAM-BA, SpyNIC, SST, SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BodyCom, chipKIT, chipKIT logo, CodeGuard, CryptoAuthentication, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PureSilicon, QMatrix, RightTouch logo, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2017, Microchip Technology Incorporated, All Rights Reserved.

ISBN: 978-1-5224-2480-2

# Worldwide Sales and Service


## AMERICAS

**Corporate Office**
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
http://www.microchip.com/support
Web Address:
www.microchip.com

**Atlanta**
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

**Austin, TX**
Tel: 512-257-3370

**Boston**
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

**Chicago**
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

**Dallas**
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

**Detroit**
Novi, MI
Tel: 248-848-4000

**Houston, TX**
Tel: 281-894-5983

**Indianapolis**
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

**Los Angeles**
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

**Raleigh, NC**
Tel: 919-844-7510

**New York, NY**
Tel: 631-435-6000

**San Jose, CA**
Tel: 408-735-9110
Tel: 408-436-4270

**Canada - Toronto**
Tel: 905-695-1980
Fax: 905-695-2078

## ASIA/PACIFIC

**Australia - Sydney**
Tel: 61-2-9868-6733

**China - Beijing**
Tel: 86-10-8569-7000

**China - Chengdu**
Tel: 86-28-8665-5511

**China - Chongqing**
Tel: 86-23-8980-9588

**China - Dongguan**
Tel: 86-769-8702-9880

**China - Guangzhou**
Tel: 86-20-8755-8029

**China - Hangzhou**
Tel: 86-571-8792-8115

**China - Hong Kong SAR**
Tel: 852-2943-5100

**China - Nanjing**
Tel: 86-25-8473-2460

**China - Qingdao**
Tel: 86-532-8502-7355

**China - Shanghai**
Tel: 86-21-3326-8000

**China - Shenyang**
Tel: 86-24-2334-2829

**China - Shenzhen**
Tel: 86-755-8864-2200

**China - Suzhou**
Tel: 86-186-6233-1526

**China - Wuhan**
Tel: 86-27-5980-5300

**China - Xian**
Tel: 86-29-8833-7252

**China - Xiamen**
Tel: 86-592-2388138

**China - Zhuhai**
Tel: 86-756-3210040

## ASIA/PACIFIC

**India - Bangalore**
Tel: 91-80-3090-4444

**India - New Delhi**
Tel: 91-11-4160-8631

**India - Pune**
Tel: 91-20-4121-0141

**Japan - Osaka**
Tel: 81-6-6152-7160

**Japan - Tokyo**
Tel: 81-3-6880- 3770

**Korea - Daegu**
Tel: 82-53-744-4301

**Korea - Seoul**
Tel: 82-2-554-7200

**Malaysia - Kuala Lumpur**
Tel: 60-3-7651-7906

**Malaysia - Penang**
Tel: 60-4-227-8870

**Philippines - Manila**
Tel: 63-2-634-9065

**Singapore**
Tel: 65-6334-8870

**Taiwan - Hsin Chu**
Tel: 886-3-577-8366

**Taiwan - Kaohsiung**
Tel: 886-7-213-7830

**Taiwan - Taipei**
Tel: 886-2-2508-8600

**Thailand - Bangkok**
Tel: 66-2-694-1351

**Vietnam - Ho Chi Minh**
Tel: 84-28-5448-2100

## EUROPE

**Austria - Wels**
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

**Denmark - Copenhagen**
Tel: 45-4450-2828
Fax: 45-4485-2829

**Finland - Espoo**
Tel: 358-9-4520-820

**France - Paris**
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

**Germany - Garching**
Tel: 49-8931-9700

**Germany - Haan**
Tel: 49-2129-3766400

**Germany - Heilbronn**
Tel: 49-7131-67-3636

**Germany - Karlsruhe**
Tel: 49-721-625370

**Germany - Munich**
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

**Germany - Rosenheim**
Tel: 49-8031-354-560

**Israel - Ra'anana**
Tel: 972-9-744-7705

**Italy - Milan**
Tel: 39-0331-742611
Fax: 39-0331-466781

**Italy - Padova**
Tel: 39-049-7625286

**Netherlands - Drunen**
Tel: 31-416-690399
Fax: 31-416-690340

**Norway - Trondheim**
Tel: 47-7289-7561

**Poland - Warsaw**
Tel: 48-22-3325737

**Romania - Bucharest**
Tel: 40-21-407-87-50

**Spain - Madrid**
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

**Sweden - Gothenberg**
Tel: 46-31-704-60-40

**Sweden - Stockholm**
Tel: 46-8-5090-4654

**UK - Wokingham**
Tel: 44-118-921-5800
Fax: 44-118-921-5820



© 2017 Microchip Technology Inc.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Microchip:

DSC1121CM1-010.7000T DSC1121CI2-020.0000T DSC1121CI2-125.0000T DSC1101CI5-048.0000 DSC1121CI2-060.0000T DSC1121CI2-074.2500T DSC1121CI5-040.0000 DSC1121CI5-050.0000T DSC1121DL2-032.0000 DSC1121CI2-024.0000T DSC1121CI2-040.0000 DSC1101BE2-025.0000 DSC1121CI2-062.5000 DSC1121CI2-150.0000 DSC1121CI2-150.0000T DSC1121CM1-025.0000T DSC1101DI5-026.0000T DSC1121AI2-029.4912T DSC1121BI1-026.0000 DSC1121CE1-016.0000 DSC1121CE2-066.6600T DSC1121AE1-040.0000T DSC1121AI5-125.0032 DSC1121AI5-125.0032T DSC1121AM1-025.0000T DSC1121CI2-025.0000 DSC1121CI2-025.0012T DSC1121CM2-027.0000 DSC1121AE2-156.2500 DSC1121AM1-033.0000 DSC1121AM1-050.0000T DSC1121BI2-156.2539T DSC1121AE1-024.5760T DSC1121DI2-010.0000T DSC1121DI2-065.5360T DSC1121CI2-024.5760T DSC1121BL1-125.0000 DSC1121CE2-066.6600 DSC1121CI1-125.0000T DSC1121BI2-120.0000T DSC1121CE2-025.0000T DSC1121CI2-012.2880 DSC1121CI2-013.0000T DSC1121CI2-066.0000 DSC1121CL2-027.0000 DSC1121AE2-125.0000T DSC1121AI1-155.5200T DSC1121AI2-050.0000T DSC1121AI5-050.0000 DSC1121BI2-010.0000T DSC1121BI2-025.0000T DSC1121AE1-125.0000T DSC1121AE1-016.0000T DSC1121BI2-100.0000 DSC1121BI5-150.0000 DSC1121BM2-120.0000 DSC1121AE2-025.0000T DSC1101AE1-050.0000 DSC1101CL2-010.0000 DSC1101CM2-062.2080 DSC1101DM2-125.0000 DSC1121AE1-025.0000T DSC1121AE1-075.0000 DSC1121AE1-075.0000T DSC1121AE2-075.0000T DSC1121AI1-025.0000 DSC1121CL2-027.0000T DSC1121DL1-016.0000T DSC1121DL2-127.0000T DSC1121AI2-003.6864T DSC1121AI2-025.0000T DSC1121AI2-125.0000T DSC1121AI2-131.0750T DSC1101CI5-020.0000T DSC1101DI5-066.0000T DSC1121CI5-014.7456T DSC1121CL2-040.0000 DSC1121DI2-125.0000T DSC1101CI2-066.0000 DSC1101CI5-024.7500 DSC1101DI5-060.0000T DSC1121CE1-075.0000T DSC1121CE2-026.0000T DSC1121CI2-012.2880T DSC1121CI2-050.0000 DSC1121CI2-050.0000T DSC1121CI2-133.0000 DSC1121CI2-025.0000T DSC1121CL2-040.0000T DSC1121CM1-048.0000T DSC1121CM1-125.0000T DSC1121DL2-024.7500 DSC1121BI2-150.0000T DSC1121BI2-125.0037T DSC1121BI2-200.0000T DSC1121BI5-012.6500 DSC1121BM1-060.0000T DSC1121CE1-025.0012T DSC1121CE2-025.0000 DSC1121CM1-016.0000T

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.