

NTC Thermistors, Mini Lug Sensors



| QUICK REFERENCE DATA | | |
|--|----------------|----------|
| PARAMETER | VALUE | UNIT |
| Resistance value at 25 °C | 10K to 47K | Ω |
| Tolerance on R_{25} -value | ± 2 to ± 3 | % |
| $B_{25/85}$ -value | 3740 to 3984 | K |
| Tolerance on $B_{25/85}$ -value | ± 0.5 to ± 1.5 | % |
| Operating temperature range: At zero dissipation | - 40 to + 125 | °C |
| Response time | 3.5 | s |
| Thermal time constant τ | ≈ 5 | s |
| Dissipation factor δ | 10 | mW/K |
| Maximum power dissipation at 25 °C | 100 | mW |
| Min. dielectric withstanding voltage between terminals and lug | 1000 | V_{AC} |
| Climatic category (LCT/UCT/days) | 40/125/56 | - |
| Weight | | |
| without connector | 0.5 | g |
| with connector | 0.6 | g |

Note

- Other R_{25} values and tolerances available upon request

FEATURES

- Fast time response for surface applications compared to industry standard NTC lug sensors
- Reduced thermal gradient, due to the use of small dimensions and nickel conductor, allowing for an accurate surface temperature measurement
- The sensor is not suitable for being permanently in contact with water or liquids
- Small size connector and small lug ring tongue terminal, allowing for temperature sensing at locations where only limited space is available
- Connector ZHR-2 (optional)
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

APPLICATIONS

Thermistors used for surface temperature sensing and control in:

- Computer equipment
- MOSFETS, IC's, Power Electronics, heatsink temperature control, LED emitter heat-sink control
- Consumer appliances
- Industrial equipment
- Automotive equipment

DESCRIPTION

Miniature insulated chip thermistor with a negative temperature coefficient in accordance with IEC 60539. The device has no marking.

MOUNTING


- The sensor can be mounted by means of a screw. For stud size, metric 2 mm M2/American stud #1 or #2
- The end wire can be soldered, welded or crimped to a connector
- Optional connector for Wire-to-Wire or Wire-to-Board connections

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | |
|--|--------------------|------------------------|-------------------------|---------------------|--|-----------|
| R_{25} -VALUE (kΩ) | R_{25} -TOL. (%) | $B_{25/85}$ -VALUE (K) | $B_{25/85}$ -TOL. (± %) | SAP MATERIAL NUMBER | DESCRIPTION | R/T TABLE |
| 10 | ± 3 | 3984 | 0.5 | NTCALUG03A103H | NTC Mini Lug 10K 3 % 3984 K 0.5 % | Table 1 |
| 10 | ± 3 | 3984 | 0.5 | NTCALUG03A103HC | NTC Mini Lug 10K 3 % 3984 K 0.5 % with connector | Table 1 |
| 10 | ± 2 | 3984 | 0.5 | NTCALUG03A103G | NTC Mini Lug 10K 2 % 3984 K 0.5 % | Table 2 |
| 10 | ± 2 | 3984 | 0.5 | NTCALUG03A103GC | NTC Mini Lug 10K 2 % 3984 K 0.5 % with connector | Table 2 |
| 12 | ± 3 | 3740 | 1.5 | NTCALUG03A123H | NTC Mini Lug 12K 3 % | Table 3 |
| 12 | ± 3 | 3740 | 1.5 | NTCALUG03A123HC | NTC Mini Lug 12K 3 % with connector | Table 3 |
| 47 | ± 3 | 3740 | 1.5 | NTCALUG03A473H | NTC Mini Lug 47K 3 % | Table 4 |
| 47 | ± 3 | 3740 | 1.5 | NTCALUG03A473HC | NTC Mini Lug 47 kΩ 3 % with connector | Table 4 |

Note

- Ordering information can be found on: www.vishay.com/doc?33036

DIMENSIONS in millimeters



| L ₁ | L ₂ | L ₃ | L ₄ | L ₁ + L ₃ (item without connector) | Ø D ₁ | Ø D ₂ | Ø D ₃ | Ø D ₄ | T | Pitch P |
|----------------|----------------|----------------|----------------|---|------------------|------------------|------------------|------------------|-----------|-----------|
| 70 ± 5 | 4 ± 1 | 11.5 ± 0.3 | 8.8 ± 0.3 | 81.5 ± 5 | 2.2 ± 0.3 | 5.5 ± 0.3 | 3.4 ± 0.3 | 0.35 ± 0.1 | 0.8 ± 0.1 | 1.5 ± 0.3 |

Notes

- (1) Vishay Thermistor chip NTC, with epoxy coating and middle buffer layer
- (2) Metal ring lug, tin plated
- (3) Insulated leads: AWG#32, monostranded, diam 0.20 mm, silver plated Nickel, insulated, diameter 0.35 mm
- (4) End wire stripped or 2-poles connector crimped (optional)

MOUNTING

- With screw size metric M2, or American stud 1-2
- For the type without connector, the electrical connection can be made by soldering, crimping or welding.
- For the type with connector, the connector can mate with following counter-connectors ⁽⁵⁾:
 - A. One of the PCB connector - Through Hole:
 - JST B 2B-ZR (top entry)
 - JST S 2B-ZR (side entry)
 - JST B 2B-ZR-3.4 (top entry, for 1.6 mm board)
 - JST S 2B-ZR-3.4 (side entry, for 1.6 mm board)
 - B. One of the PCB Board connector - SMT Surface Mount:
 - JST S 2B-ZR-SM2-TF (SM2 side entry)
 - JST B 2B-ZR-SM3-TF (SM3 top entry)
 - JST S 2B-ZR-SM3A-TF (SM3 side entry)
 - JST B 2B-ZR-SM4-TF (SM4 top entry)
 - JST S 2B-ZR-SM4A-TF (SM4 side entry)
 - C. The Wire-to-wire connector:
 - JST ZMR-02 housing (x 1) + JST SMM-033T-P0.5 terminals (x 2)

Note

- (5) Additional details and dimensions can be found in JST ZH and JST ZM datasheets.

PACKAGING

Available in plastic bags of 250 pieces. SPQ = 2000 pieces

DESIGN-IN SUPPORT

- Other resistance curves and tolerances are available on request
- Consult Vishay for other lead length, other connector crimping or other features
- Other applicable screw size are available, for example stud size metric 3 mm/American 3 to 4
- 3D solid models: www.vishay.com/doc?29106
- NTC curve computation: www.vishay.com/resistors-non-linear/curve-computation-list/



For complete Curve Computation, visit: www.vishay.com/resistors-non-linear/curve-computation-list/

TABLE 1

| | |
|-----------------|--|
| NTCALUG03A103H | NTC Mini Lug 10K 3 % 3984 K 0.5 % |
| NTCALUG03A103HC | NTC Mini Lug 10K 3 % 3984 K 0.5 % with connector |

| RESISTANCE TEMPERATURE CHARACTERISTICS | | | | | | | |
|---|------------------|----------------|------------------|----------------|----------------|----------------|----------------|
| TEMP. (°C) | $R_{(T)}/R_{25}$ | RESISTANCE (Ω) | $\Delta R/R$ (%) | α (%/K) | ΔT (K) | $R_{MIN.}$ (Ω) | $R_{MAX.}$ (Ω) |
| - 40 | 33.427 | 334 274 | 4.92 | - 6.63 | 0.74 | 317 833 | 350 716 |
| - 35 | 24.132 | 241 323 | 4.73 | - 6.41 | 0.74 | 229 899 | 252 747 |
| - 30 | 17.613 | 176 133 | 4.56 | - 6.19 | 0.74 | 168 107 | 184 158 |
| - 25 | 12.990 | 129 900 | 4.39 | - 5.99 | 0.73 | 124 202 | 135 598 |
| - 20 | 9.676 | 96 761 | 4.22 | - 5.79 | 0.73 | 92 675 | 100 848 |
| - 15 | 7.276 | 72 765 | 4.07 | - 5.61 | 0.73 | 69 806 | 75 723 |
| - 10 | 5.522 | 55 218 | 3.92 | - 5.43 | 0.72 | 53 056 | 57 380 |
| - 5 | 4.227 | 42 268 | 3.77 | - 5.26 | 0.72 | 40 674 | 43 861 |
| 0 | 3.262 | 32 624 | 3.63 | - 5.10 | 0.71 | 31 440 | 33 808 |
| 5 | 2.538 | 25 381 | 3.49 | - 4.94 | 0.71 | 24 494 | 26 268 |
| 10 | 1.990 | 19 897 | 3.36 | - 4.80 | 0.70 | 19 227 | 20 566 |
| 15 | 1.571 | 15 711 | 3.24 | - 4.65 | 0.70 | 15 202 | 16 220 |
| 20 | 1.249 | 12 493 | 3.12 | - 4.52 | 0.69 | 12 103 | 12 882 |
| 25 | 1.000 | 10 000 | 3.00 | - 4.39 | 0.68 | 9700.0 | 10 300 |
| 30 | 0.806 | 8056.0 | 3.11 | - 4.26 | 0.73 | 7805.1 | 8306.8 |
| 35 | 0.653 | 6529.7 | 3.22 | - 4.14 | 0.78 | 6319.3 | 6740.2 |
| 40 | 0.532 | 5323.9 | 3.33 | - 4.03 | 0.83 | 5146.6 | 5501.1 |
| 45 | 0.437 | 4365.3 | 3.43 | - 3.92 | 0.88 | 4215.4 | 4515.1 |
| 50 | 0.360 | 3598.7 | 3.53 | - 3.81 | 0.93 | 3471.6 | 3725.8 |
| 55 | 0.298 | 2982.3 | 3.63 | - 3.71 | 0.98 | 2874.0 | 3090.5 |
| 60 | 0.248 | 2483.8 | 3.72 | - 3.61 | 1.03 | 2391.3 | 2576.3 |
| 65 | 0.208 | 2078.7 | 3.81 | - 3.51 | 1.09 | 1999.4 | 2157.9 |
| 70 | 0.175 | 1747.7 | 3.90 | - 3.42 | 1.14 | 1679.5 | 1815.9 |
| 75 | 0.148 | 1475.9 | 3.99 | - 3.34 | 1.20 | 1417.1 | 1534.8 |
| 80 | 0.125 | 1251.8 | 4.07 | - 3.25 | 1.25 | 1200.8 | 1302.8 |
| 85 | 0.107 | 1066.1 | 4.15 | - 3.17 | 1.31 | 1021.8 | 1110.4 |
| 90 | 0.091 | 911.59 | 4.23 | - 3.09 | 1.37 | 873.01 | 950.16 |
| 95 | 0.078 | 782.46 | 4.31 | - 3.02 | 1.43 | 748.75 | 816.17 |
| 100 | 0.067 | 674.11 | 4.38 | - 2.94 | 1.49 | 644.56 | 703.66 |
| 105 | 0.058 | 582.84 | 4.46 | - 2.87 | 1.55 | 556.87 | 608.82 |
| 110 | 0.051 | 505.68 | 4.53 | - 2.81 | 1.61 | 482.79 | 528.57 |
| 115 | 0.044 | 440.19 | 4.60 | - 2.74 | 1.68 | 419.96 | 460.42 |
| 120 | 0.038 | 384.41 | 4.66 | - 2.68 | 1.74 | 366.49 | 402.34 |
| 125 | 0.034 | 336.75 | 4.73 | - 2.62 | 1.81 | 320.83 | 352.67 |



For complete Curve Computation, visit: www.vishay.com/resistors-non-linear/curve-computation-list/

TABLE 2

| | |
|-----------------|--|
| NTCALUG03A103G | NTC Mini Lug 10K 2 % 3984 K 0.5 % |
| NTCALUG03A103GC | NTC Mini Lug 10K 2 % 3984 K 0.5 % with connector |

| RESISTANCE TEMPERATURE CHARACTERISTICS | | | | | | | |
|---|---------------|----------------|------------------|----------------|----------------|----------------|----------------|
| TEMP. (°C) | $R(T)/R_{25}$ | RESISTANCE (Ω) | $\Delta R/R$ (%) | α (%/K) | ΔT (K) | $R_{MIN.}$ (Ω) | $R_{MAX.}$ (Ω) |
| - 40 | 33.427 | 334 274 | 3.90 | - 6.63 | 0.59 | 321 238 | 347 311 |
| - 35 | 24.132 | 241 323 | 3.72 | - 6.41 | 0.58 | 232 353 | 250 293 |
| - 30 | 17.613 | 176 133 | 3.54 | - 6.19 | 0.57 | 169 895 | 182 370 |
| - 25 | 12.990 | 129 900 | 3.37 | - 5.99 | 0.56 | 125 518 | 134 282 |
| - 20 | 9.676 | 96 761 | 3.21 | - 5.79 | 0.55 | 93 654 | 99 869 |
| - 15 | 7.276 | 72 765 | 3.06 | - 5.61 | 0.54 | 70 541 | 74 988 |
| - 10 | 5.522 | 55 218 | 2.91 | - 5.43 | 0.54 | 53 613 | 56 823 |
| - 5 | 4.227 | 42 268 | 2.76 | - 5.26 | 0.53 | 41 100 | 43 435 |
| 0 | 3.262 | 32 624 | 2.62 | - 5.10 | 0.51 | 31 768 | 33 480 |
| 5 | 2.538 | 25 381 | 2.49 | - 4.94 | 0.50 | 24 749 | 26 013 |
| 10 | 1.990 | 19 897 | 2.36 | - 4.80 | 0.49 | 19 427 | 20 367 |
| 15 | 1.571 | 15 711 | 2.24 | - 4.65 | 0.48 | 15 360 | 16 063 |
| 20 | 1.249 | 12 493 | 2.12 | - 4.52 | 0.47 | 12 228 | 12 757 |
| 25 | 1.000 | 10 000 | 2.00 | - 4.39 | 0.46 | 9800.0 | 10 200 |
| 30 | 0.806 | 8056.0 | 2.11 | - 4.26 | 0.50 | 7885.8 | 8226.1 |
| 35 | 0.653 | 6529.7 | 2.22 | - 4.14 | 0.54 | 6384.7 | 6674.8 |
| 40 | 0.532 | 5323.9 | 2.33 | - 4.03 | 0.58 | 5200.0 | 5447.7 |
| 45 | 0.437 | 4365.3 | 2.43 | - 3.92 | 0.62 | 4259.3 | 4471.3 |
| 50 | 0.360 | 3598.7 | 2.53 | - 3.81 | 0.66 | 3507.8 | 3689.7 |
| 55 | 0.298 | 2982.3 | 2.62 | - 3.71 | 0.71 | 2904.0 | 3060.5 |
| 60 | 0.248 | 2483.8 | 2.72 | - 3.61 | 0.75 | 2416.4 | 2551.3 |
| 65 | 0.208 | 2078.7 | 2.81 | - 3.51 | 0.80 | 2020.3 | 2137.0 |
| 70 | 0.175 | 1747.7 | 2.89 | - 3.42 | 0.85 | 1697.1 | 1798.2 |
| 75 | 0.148 | 1475.9 | 2.98 | - 3.34 | 0.89 | 1432.0 | 1519.9 |
| 80 | 0.125 | 1251.8 | 3.06 | - 3.25 | 0.94 | 1213.5 | 1290.1 |
| 85 | 0.107 | 1066.1 | 3.14 | - 3.17 | 0.99 | 1032.6 | 1099.6 |
| 90 | 0.091 | 911.59 | 3.22 | - 3.09 | 1.04 | 882.23 | 940.94 |
| 95 | 0.078 | 782.46 | 3.30 | - 3.02 | 1.09 | 756.67 | 808.25 |
| 100 | 0.067 | 674.11 | 3.37 | - 2.94 | 1.14 | 651.40 | 696.83 |
| 105 | 0.058 | 582.84 | 3.44 | - 2.87 | 1.20 | 562.79 | 602.90 |
| 110 | 0.051 | 505.68 | 3.51 | - 2.81 | 1.25 | 487.92 | 523.43 |
| 115 | 0.044 | 440.19 | 3.58 | - 2.74 | 1.31 | 424.43 | 455.95 |
| 120 | 0.038 | 384.41 | 3.65 | - 2.68 | 1.36 | 370.39 | 398.43 |
| 125 | 0.034 | 336.75 | 3.71 | - 2.62 | 1.42 | 324.25 | 349.25 |



For complete Curve Computation, visit: www.vishay.com/resistors-non-linear/curve-computation-list/

TABLE 3

| | |
|-----------------|-------------------------------------|
| NTCALUG03A123H | NTC Mini Lug 12K 3 % |
| NTCALUG03A123HC | NTC Mini Lug 12K 3 % with connector |

| RESISTANCE TEMPERATURE CHARACTERISTICS | | | | | | | |
|--|------------------|----------------|------------------|----------------|----------------|----------------|----------------|
| TEMP. (°C) | $R_{(T)}/R_{25}$ | RESISTANCE (Ω) | $\Delta R/R$ (%) | α (%/K) | ΔT (K) | $R_{MIN.}$ (Ω) | $R_{MAX.}$ (Ω) |
| - 40 | 25.783 | 309 396 | 8.40 | - 6.07 | 1.38 | 283 397 | 335 395 |
| - 35 | 19.125 | 229 504 | 7.88 | - 5.88 | 1.34 | 211 413 | 247 595 |
| - 30 | 14.320 | 171 840 | 7.38 | - 5.70 | 1.30 | 159 152 | 184 528 |
| - 25 | 10.819 | 129 825 | 6.90 | - 5.52 | 1.25 | 120 861 | 138 789 |
| - 20 | 8.244 | 98 933 | 6.45 | - 5.35 | 1.20 | 92 556 | 105 309 |
| - 15 | 6.335 | 76 019 | 6.00 | - 5.19 | 1.16 | 71 455 | 80 582 |
| - 10 | 4.907 | 58 879 | 5.58 | - 5.03 | 1.11 | 55 595 | 62 163 |
| - 5 | 3.829 | 45 953 | 5.17 | - 4.88 | 1.06 | 43 578 | 48 328 |
| 0 | 3.011 | 36 129 | 4.77 | - 4.74 | 1.01 | 34 405 | 37 854 |
| 5 | 2.384 | 28 607 | 4.39 | - 4.60 | 0.95 | 27 350 | 29 864 |
| 10 | 1.900 | 22 804 | 4.03 | - 4.47 | 0.90 | 21 886 | 23 723 |
| 15 | 1.525 | 18 298 | 3.67 | - 4.34 | 0.85 | 17 626 | 18 970 |
| 20 | 1.231 | 14 773 | 3.33 | - 4.22 | 0.79 | 14 281 | 15 265 |
| 25 | 1.000 | 12 000 | 3.00 | - 4.10 | 0.73 | 11 640 | 12 360 |
| 30 | 0.817 | 9803.7 | 3.32 | - 3.99 | 0.83 | 9478.2 | 10 129 |
| 35 | 0.671 | 8053.9 | 3.63 | - 3.88 | 0.94 | 7761.7 | 8346.2 |
| 40 | 0.554 | 6651.9 | 3.93 | - 3.77 | 1.04 | 6390.6 | 6913.2 |
| 45 | 0.460 | 5522.3 | 4.22 | - 3.67 | 1.15 | 5289.3 | 5755.2 |
| 50 | 0.384 | 4607.2 | 4.50 | - 3.58 | 1.26 | 4399.9 | 4814.5 |
| 55 | 0.322 | 3862.1 | 4.77 | - 3.48 | 1.37 | 3677.8 | 4046.4 |
| 60 | 0.271 | 3252.4 | 5.04 | - 3.39 | 1.48 | 3088.6 | 3416.2 |
| 65 | 0.229 | 2751.1 | 5.29 | - 3.30 | 1.60 | 2605.5 | 2896.7 |
| 70 | 0.195 | 2336.9 | 5.54 | - 3.22 | 1.72 | 2207.4 | 2466.4 |
| 75 | 0.166 | 1993.3 | 5.78 | - 3.14 | 1.84 | 1878.0 | 2108.6 |
| 80 | 0.142 | 1707.0 | 6.02 | - 3.06 | 1.96 | 1604.2 | 1809.7 |
| 85 | 0.122 | 1467.3 | 6.25 | - 2.99 | 2.09 | 1375.7 | 1559.0 |
| 90 | 0.105 | 1266.0 | 6.47 | - 2.92 | 2.22 | 1184.1 | 1347.9 |
| 95 | 0.091 | 1096.2 | 6.69 | - 2.85 | 2.35 | 1022.9 | 1169.4 |
| 100 | 0.079 | 952.38 | 6.90 | - 2.78 | 2.48 | 886.71 | 1018.0 |
| 105 | 0.069 | 830.20 | 7.10 | - 2.71 | 2.62 | 771.26 | 889.15 |
| 110 | 0.061 | 726.02 | 7.30 | - 2.65 | 2.75 | 673.03 | 779.02 |
| 115 | 0.053 | 636.88 | 7.49 | - 2.59 | 2.89 | 589.16 | 684.61 |
| 120 | 0.047 | 560.36 | 7.68 | - 2.53 | 3.04 | 517.31 | 603.41 |
| 125 | 0.041 | 494.46 | 7.87 | - 2.47 | 3.18 | 455.56 | 533.37 |



For complete Curve Computation, visit: www.vishay.com/resistors-non-linear/curve-computation-list/

TABLE 4

| | |
|-----------------|-------------------------------------|
| NTCALUG03A473H | NTC Mini Lug 47K 3 % |
| NTCALUG03A473HC | NTC Mini Lug 47K 3 % with connector |

| RESISTANCE TEMPERATURE CHARACTERISTICS | | | | | | | |
|--|------------------|----------------|------------------|----------------|----------------|----------------|----------------|
| TEMP. (°C) | $R_{(T)}/R_{25}$ | RESISTANCE (Ω) | $\Delta R/R$ (%) | α (%/K) | ΔT (K) | $R_{MIN.}$ (Ω) | $R_{MAX.}$ (Ω) |
| - 40 | 25.783 | 1 211 802 | 8.40 | - 6.07 | 1.38 | 1 109 973 | 1 313 631 |
| - 35 | 19.125 | 898 891 | 7.88 | - 5.88 | 1.34 | 828 034 | 969 749 |
| - 30 | 14.320 | 673 040 | 7.38 | - 5.70 | 1.30 | 623 344 | 722 736 |
| - 25 | 10.819 | 508 481 | 6.90 | - 5.52 | 1.25 | 473 370 | 543 592 |
| - 20 | 8.244 | 387 486 | 6.45 | - 5.35 | 1.20 | 362 512 | 412 460 |
| - 15 | 6.335 | 297 740 | 6.00 | - 5.19 | 1.16 | 279 866 | 315 613 |
| - 10 | 4.907 | 230 608 | 5.58 | - 5.03 | 1.11 | 217 745 | 243 471 |
| - 5 | 3.829 | 179 983 | 5.17 | - 4.88 | 1.06 | 170 681 | 189 285 |
| 0 | 3.011 | 141 507 | 4.77 | - 4.74 | 1.01 | 134 752 | 148 262 |
| 5 | 2.384 | 112 043 | 4.39 | - 4.60 | 0.95 | 107 121 | 116 966 |
| 10 | 1.900 | 89 317 | 4.03 | - 4.47 | 0.90 | 85 721 | 92 914 |
| 15 | 1.525 | 71 665 | 3.67 | - 4.34 | 0.85 | 69 033 | 74 297 |
| 20 | 1.231 | 57 863 | 3.33 | - 4.22 | 0.79 | 55 936 | 59 790 |
| 25 | 1.000 | 47 000 | 3.00 | - 4.10 | 0.73 | 45 590 | 48 410 |
| 30 | 0.817 | 38 398 | 3.32 | - 3.99 | 0.83 | 37 123 | 39 672 |
| 35 | 0.671 | 31 545 | 3.63 | - 3.88 | 0.94 | 30 400 | 32 689 |
| 40 | 0.554 | 26 053 | 3.93 | - 3.77 | 1.04 | 25 030 | 27 077 |
| 45 | 0.460 | 21 629 | 4.22 | - 3.67 | 1.15 | 20 717 | 22 541 |
| 50 | 0.384 | 18 045 | 4.50 | - 3.58 | 1.26 | 17 233 | 18 857 |
| 55 | 0.322 | 15 127 | 4.77 | - 3.48 | 1.37 | 14 405 | 15 848 |
| 60 | 0.271 | 12 739 | 5.04 | - 3.39 | 1.48 | 12 097 | 13 380 |
| 65 | 0.229 | 10 775 | 5.29 | - 3.30 | 1.60 | 10 205 | 11 345 |
| 70 | 0.195 | 9153.0 | 5.54 | - 3.22 | 1.72 | 8645.8 | 9660.2 |
| 75 | 0.166 | 7807.1 | 5.78 | - 3.14 | 1.84 | 7355.6 | 8258.7 |
| 80 | 0.142 | 6685.6 | 6.02 | - 3.06 | 1.96 | 6283.2 | 7087.9 |
| 85 | 0.122 | 5747.0 | 6.25 | - 2.99 | 2.09 | 5388.0 | 6106.0 |
| 90 | 0.105 | 4958.4 | 6.47 | - 2.92 | 2.22 | 4637.7 | 5279.2 |
| 95 | 0.091 | 4293.3 | 6.69 | - 2.85 | 2.35 | 4006.3 | 4580.3 |
| 100 | 0.079 | 3730.1 | 6.90 | - 2.78 | 2.48 | 3472.9 | 3987.3 |
| 105 | 0.069 | 3251.6 | 7.10 | - 2.71 | 2.62 | 3020.8 | 3482.5 |
| 110 | 0.061 | 2843.6 | 7.30 | - 2.65 | 2.75 | 2636.0 | 3051.2 |
| 115 | 0.053 | 2494.5 | 7.49 | - 2.59 | 2.89 | 2307.5 | 2681.4 |
| 120 | 0.047 | 2194.7 | 7.68 | - 2.53 | 3.04 | 2026.1 | 2363.4 |
| 125 | 0.041 | 1936.6 | 7.87 | - 2.47 | 3.18 | 1784.3 | 2089.0 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.