

1	2	3	4	5	6	7	8																																																																																																																																													
har-flexicon female connector, vertical, screwing RoHS compliant				Cable connection <table><tr><td>Type</td><td>har-flexicon 3.50/3.81 FSV</td><td>har-flexicon 5.08 FSV</td></tr><tr><td>Part numbers</td><td>1431xx14401xxx & 1431xx15401xxx</td><td>1431xx17401xxx</td></tr><tr><td>Conductor size AWG max</td><td>14 AWG</td><td>12 AWG</td></tr><tr><td>Conductor size AWG min</td><td>30 AWG</td><td>30 AWG</td></tr><tr><td>Conductor size solid max</td><td>1.5 mm²</td><td>2.5 mm²</td></tr><tr><td>Conductor size solid min</td><td>0.05 mm²</td><td>0.05 mm²</td></tr><tr><td>Conductor size stranded max</td><td>1.5 mm²</td><td>1.5 mm²</td></tr><tr><td>Conductor size stranded min</td><td>0.05 mm²</td><td>0.05 mm²</td></tr><tr><td>Conductor size stranded for end sleeve</td><td></td><td></td></tr><tr><td>Stripping length max</td><td>6 mm</td><td>7.5 mm</td></tr><tr><td>Stripping length min</td><td>5 mm</td><td>6 mm</td></tr><tr><td>Screw thread</td><td>M2</td><td>M2</td></tr><tr><td>Tightening Torque max</td><td>0.25 Nm</td><td>0.6 Nm</td></tr><tr><td>Tightening Torque min</td><td>0.2 Nm</td><td>0.5 Nm</td></tr></table>				Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV	Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx	Conductor size AWG max	14 AWG	12 AWG	Conductor size AWG min	30 AWG	30 AWG	Conductor size solid max	1.5 mm ²	2.5 mm ²	Conductor size solid min	0.05 mm ²	0.05 mm ²	Conductor size stranded max	1.5 mm ²	1.5 mm ²	Conductor size stranded min	0.05 mm ²	0.05 mm ²	Conductor size stranded for end sleeve			Stripping length max	6 mm	7.5 mm	Stripping length min	5 mm	6 mm	Screw thread	M2	M2	Tightening Torque max	0.25 Nm	0.6 Nm	Tightening Torque min	0.2 Nm	0.5 Nm																																																																																																			
Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV																																																																																																																																																		
Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx																																																																																																																																																		
Conductor size AWG max	14 AWG	12 AWG																																																																																																																																																		
Conductor size AWG min	30 AWG	30 AWG																																																																																																																																																		
Conductor size solid max	1.5 mm ²	2.5 mm ²																																																																																																																																																		
Conductor size solid min	0.05 mm ²	0.05 mm ²																																																																																																																																																		
Conductor size stranded max	1.5 mm ²	1.5 mm ²																																																																																																																																																		
Conductor size stranded min	0.05 mm ²	0.05 mm ²																																																																																																																																																		
Conductor size stranded for end sleeve																																																																																																																																																				
Stripping length max	6 mm	7.5 mm																																																																																																																																																		
Stripping length min	5 mm	6 mm																																																																																																																																																		
Screw thread	M2	M2																																																																																																																																																		
Tightening Torque max	0.25 Nm	0.6 Nm																																																																																																																																																		
Tightening Torque min	0.2 Nm	0.5 Nm																																																																																																																																																		
General information <table><tr><td colspan="3">female connector</td></tr><tr><td>Type</td><td>har-flexicon 3.50/3.81 FSV</td><td>har-flexicon 5.08 FSV</td></tr><tr><td>Part numbers</td><td>1431xx14401xxx & 1431xx15401xxx</td><td>1431xx17401xxx</td></tr><tr><td>Contact pitch</td><td>3.5 mm & 3.81 mm</td><td>5.08 mm</td></tr><tr><td>No. of contacts</td><td>2-25 poles</td><td>2-25 poles</td></tr><tr><td>Rated surge voltage (II/2)</td><td>2,5 kV</td><td>4 kV</td><td>(overvoltage cat. II / pollution degree 2)</td></tr><tr><td>Rated surge voltage (III/2)</td><td>2,5 kV</td><td>4 kV</td><td>(overvoltage cat. III / pollution degree 2)</td></tr><tr><td>Rated surge voltage (III/3)</td><td>2,5 kV</td><td>4 kV</td><td>(overvoltage cat. III / pollution degree 3)</td></tr><tr><td>Rated Voltage</td><td>300 V</td><td>300 V</td><td></td></tr><tr><td>Rated voltage (II/2)</td><td>300 V</td><td>600 V</td><td>(overvoltage cat. II / pollution degree 2)</td></tr><tr><td>Rated voltage (III/2)</td><td>150 V</td><td>300 V</td><td>(overvoltage cat. III / pollution degree 2)</td></tr><tr><td>Rated voltage (III/3):</td><td>150 V</td><td>250 V</td><td>(overvoltage cat. III / pollution degree 3)</td></tr><tr><td>Working current</td><td>10 A</td><td>15 A</td><td></td></tr><tr><td>Usegroup B, rated voltage / current</td><td>300 V / 10 A</td><td>300 V / 15 A</td><td></td></tr><tr><td>Usegroup C, rated voltage / current</td><td>- / -</td><td>- / -</td><td></td></tr><tr><td>Usegroup D, rated voltage / current</td><td>300 V / 10 A</td><td>300 V / 15 A</td><td></td></tr><tr><td>Contact resistance</td><td colspan="3">max. 15 mOhm</td></tr><tr><td>Insulation resistance</td><td colspan="3">min. 10⁹ Ohm (500 V DC)</td></tr><tr><td>Temperature range</td><td colspan="3">-40°C ... +110°C</td></tr><tr><td>Termination technology</td><td colspan="3">screw</td></tr><tr><td>Insertion force</td><td colspan="3">max. 3 N</td></tr><tr><td>Withdrawal force</td><td colspan="3">min. 1,5 N</td></tr><tr><td>Hot plugging</td><td colspan="3">No</td></tr><tr><td>Vibration</td><td colspan="3">10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs</td></tr><tr><td>RoHS - compliant</td><td colspan="3">Yes</td></tr><tr><td>UL file</td><td colspan="3">E314677</td></tr></table>				female connector			Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV	Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx	Contact pitch	3.5 mm & 3.81 mm	5.08 mm	No. of contacts	2-25 poles	2-25 poles	Rated surge voltage (II/2)	2,5 kV	4 kV	(overvoltage cat. II / pollution degree 2)	Rated surge voltage (III/2)	2,5 kV	4 kV	(overvoltage cat. III / pollution degree 2)	Rated surge voltage (III/3)	2,5 kV	4 kV	(overvoltage cat. III / pollution degree 3)	Rated Voltage	300 V	300 V		Rated voltage (II/2)	300 V	600 V	(overvoltage cat. II / pollution degree 2)	Rated voltage (III/2)	150 V	300 V	(overvoltage cat. III / pollution degree 2)	Rated voltage (III/3):	150 V	250 V	(overvoltage cat. III / pollution degree 3)	Working current	10 A	15 A		Usegroup B, rated voltage / current	300 V / 10 A	300 V / 15 A		Usegroup C, rated voltage / current	- / -	- / -		Usegroup D, rated voltage / current	300 V / 10 A	300 V / 15 A		Contact resistance	max. 15 mOhm			Insulation resistance	min. 10 ⁹ Ohm (500 V DC)			Temperature range	-40°C ... +110°C			Termination technology	screw			Insertion force	max. 3 N			Withdrawal force	min. 1,5 N			Hot plugging	No			Vibration	10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs			RoHS - compliant	Yes			UL file	E314677			Packging unit <table><tr><th>Type of packaging</th><th>No. of poles (xx)</th><th>Quantity</th><th>MOQ</th><th>Index (xxx)</th><th>Remark</th></tr><tr><td>box</td><td>2</td><td>300</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>3</td><td>200</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>4 - 5</td><td>150</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>6 - 12</td><td>100</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>13 - 20</td><td>50</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>21 - 25</td><td>25</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr></table> 1431xx14401xxx				Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark	box	2	300	1	000 = green, 163 = black		box	3	200	1	000 = green, 163 = black		box	4 - 5	150	1	000 = green, 163 = black		box	6 - 12	100	1	000 = green, 163 = black		box	13 - 20	50	1	000 = green, 163 = black		box	21 - 25	25	1	000 = green, 163 = black	
female connector																																																																																																																																																				
Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV																																																																																																																																																		
Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx																																																																																																																																																		
Contact pitch	3.5 mm & 3.81 mm	5.08 mm																																																																																																																																																		
No. of contacts	2-25 poles	2-25 poles																																																																																																																																																		
Rated surge voltage (II/2)	2,5 kV	4 kV	(overvoltage cat. II / pollution degree 2)																																																																																																																																																	
Rated surge voltage (III/2)	2,5 kV	4 kV	(overvoltage cat. III / pollution degree 2)																																																																																																																																																	
Rated surge voltage (III/3)	2,5 kV	4 kV	(overvoltage cat. III / pollution degree 3)																																																																																																																																																	
Rated Voltage	300 V	300 V																																																																																																																																																		
Rated voltage (II/2)	300 V	600 V	(overvoltage cat. II / pollution degree 2)																																																																																																																																																	
Rated voltage (III/2)	150 V	300 V	(overvoltage cat. III / pollution degree 2)																																																																																																																																																	
Rated voltage (III/3):	150 V	250 V	(overvoltage cat. III / pollution degree 3)																																																																																																																																																	
Working current	10 A	15 A																																																																																																																																																		
Usegroup B, rated voltage / current	300 V / 10 A	300 V / 15 A																																																																																																																																																		
Usegroup C, rated voltage / current	- / -	- / -																																																																																																																																																		
Usegroup D, rated voltage / current	300 V / 10 A	300 V / 15 A																																																																																																																																																		
Contact resistance	max. 15 mOhm																																																																																																																																																			
Insulation resistance	min. 10 ⁹ Ohm (500 V DC)																																																																																																																																																			
Temperature range	-40°C ... +110°C																																																																																																																																																			
Termination technology	screw																																																																																																																																																			
Insertion force	max. 3 N																																																																																																																																																			
Withdrawal force	min. 1,5 N																																																																																																																																																			
Hot plugging	No																																																																																																																																																			
Vibration	10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs																																																																																																																																																			
RoHS - compliant	Yes																																																																																																																																																			
UL file	E314677																																																																																																																																																			
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark																																																																																																																																															
box	2	300	1	000 = green, 163 = black																																																																																																																																																
box	3	200	1	000 = green, 163 = black																																																																																																																																																
box	4 - 5	150	1	000 = green, 163 = black																																																																																																																																																
box	6 - 12	100	1	000 = green, 163 = black																																																																																																																																																
box	13 - 20	50	1	000 = green, 163 = black																																																																																																																																																
box	21 - 25	25	1	000 = green, 163 = black																																																																																																																																																
Isulator material <table><tr><td>Material</td><td>PA/PPA</td></tr><tr><td>Color</td><td>green</td></tr><tr><td>UL classification</td><td>UL 94-V0</td></tr><tr><td>Material group acc. to. IEC 60664-1</td><td>I (CTI > 600)</td></tr></table>				Material	PA/PPA	Color	green	UL classification	UL 94-V0	Material group acc. to. IEC 60664-1	I (CTI > 600)	Contact material <table><tr><td>Contact material</td><td>Copper alloy</td></tr><tr><td>Plating termination zone</td><td>Ni</td></tr><tr><td>Plating contact zone</td><td>Sn</td></tr></table>				Contact material	Copper alloy	Plating termination zone	Ni	Plating contact zone	Sn																																																																																																																															
Material	PA/PPA																																																																																																																																																			
Color	green																																																																																																																																																			
UL classification	UL 94-V0																																																																																																																																																			
Material group acc. to. IEC 60664-1	I (CTI > 600)																																																																																																																																																			
Contact material	Copper alloy																																																																																																																																																			
Plating termination zone	Ni																																																																																																																																																			
Plating contact zone	Sn																																																																																																																																																			
Derating The current carrying capacity is limited by maximum temperature of materialsfor inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given,without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5				All Dimensions in mm Original Size DIN A3 Scale 1:1 Free size tol. Ref. Sub. All rights reserved Department EC PD - DE Created by TADJE Inspected by ZWAHR Standardisation HOFFMANN Date 2016-09-07 State Final Release har-flexicon female connector, vertical, screwing Type DS Number 14312401201 Doc-Key / ECM-Nr. 100579803/UGD/000/D 500000108598 Rev. D Page 1/1 HARTING Electronics GmbH D-32339 Espelkamp																																																																																																																																																
1	2	3	4	5	6	7	8																																																																																																																																													

		All Dimensions in mm		Scale	Free size tol.		Ref.	
		Original Size DIN A3		1:1			Sub.	
		All rights reserved		Created by	Inspected by	Standardisation	Date	State
		Department EC PD - DE		TADJE	ZWAHR	HOFFMANN	2016-09-07	Final Release
HARTING Electronics GmbH D-32339 Espelkamp		Title har-flexicon female connector, vertical, screwing						Doc-Key / ECM-Nr. 100579803/UGD/000/D 500000108598
		Type DS	Number 14312401201					Rev. D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[14311214401000](#) [14310414401000](#) [14310214401000](#) [14310614401000](#) [14310814401000](#) [14310314401000](#)
[14311014401000](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.