


1	2	3	4	5	6	7	8																																																																																																																												
A	har-flexicon female connector, vertical, screwing RoHS compliant			Cable connection <table><tr><td>Type</td><td>har-flexicon 3.50/3.81 FSV</td><td>har-flexicon 5.08 FSV</td></tr><tr><td>Part numbers</td><td>1431xx14401xxx & 1431xx15401xxx</td><td>1431xx17401xxx</td></tr><tr><td>Conductor size AWG max</td><td>14 AWG</td><td>12 AWG</td></tr><tr><td>Conductor size AWG min</td><td>30 AWG</td><td>30 AWG</td></tr><tr><td>Conductor size solid max</td><td>1.5 mm²</td><td>2.5 mm²</td></tr><tr><td>Conductor size solid min</td><td>0.05 mm²</td><td>0.05 mm²</td></tr><tr><td>Conductor size stranded max</td><td>1.5 mm²</td><td>1.5 mm²</td></tr><tr><td>Conductor size stranded min</td><td>0.05 mm²</td><td>0.05 mm²</td></tr><tr><td>Conductor size stranded for end sleeve</td><td></td><td></td></tr><tr><td>Stripping length max</td><td>6 mm</td><td>7.5 mm</td></tr><tr><td>Stripping length min</td><td>5 mm</td><td>6 mm</td></tr><tr><td>Screw thread</td><td>M2</td><td>M2</td></tr><tr><td>Tightening Torque max</td><td>0.25 Nm</td><td>0.6 Nm</td></tr><tr><td>Tightening Torque min</td><td>0.2 Nm</td><td>0.5 Nm</td></tr></table>				Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV	Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx	Conductor size AWG max	14 AWG	12 AWG	Conductor size AWG min	30 AWG	30 AWG	Conductor size solid max	1.5 mm ²	2.5 mm ²	Conductor size solid min	0.05 mm ²	0.05 mm ²	Conductor size stranded max	1.5 mm ²	1.5 mm ²	Conductor size stranded min	0.05 mm ²	0.05 mm ²	Conductor size stranded for end sleeve			Stripping length max	6 mm	7.5 mm	Stripping length min	5 mm	6 mm	Screw thread	M2	M2	Tightening Torque max	0.25 Nm	0.6 Nm	Tightening Torque min	0.2 Nm	0.5 Nm	A																																																																																	
Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV																																																																																																																																	
Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx																																																																																																																																	
Conductor size AWG max	14 AWG	12 AWG																																																																																																																																	
Conductor size AWG min	30 AWG	30 AWG																																																																																																																																	
Conductor size solid max	1.5 mm ²	2.5 mm ²																																																																																																																																	
Conductor size solid min	0.05 mm ²	0.05 mm ²																																																																																																																																	
Conductor size stranded max	1.5 mm ²	1.5 mm ²																																																																																																																																	
Conductor size stranded min	0.05 mm ²	0.05 mm ²																																																																																																																																	
Conductor size stranded for end sleeve																																																																																																																																			
Stripping length max	6 mm	7.5 mm																																																																																																																																	
Stripping length min	5 mm	6 mm																																																																																																																																	
Screw thread	M2	M2																																																																																																																																	
Tightening Torque max	0.25 Nm	0.6 Nm																																																																																																																																	
Tightening Torque min	0.2 Nm	0.5 Nm																																																																																																																																	
B	General information <table><tr><td colspan="3">female connector</td></tr><tr><td>Design</td><td colspan="2"></td></tr><tr><td>Type</td><td>har-flexicon 3.50/3.81 FSV</td><td>har-flexicon 5.08 FSV</td></tr><tr><td>Part numbers</td><td>1431xx14401xxx & 1431xx15401xxx</td><td>1431xx17401xxx</td></tr><tr><td>Contact pitch</td><td>3.5 mm & 3.81 mm</td><td>5.08 mm</td></tr><tr><td>No. of contacts</td><td>2-25 poles</td><td>2-25 poles</td></tr><tr><td>Rated surge voltage (II/2)</td><td>2,5 kV</td><td>4 kV</td></tr><tr><td>Rated surge voltage (III/2)</td><td>2,5 kV</td><td>4 kV</td></tr><tr><td>Rated surge voltage (III/3)</td><td>2,5 kV</td><td>4 kV</td></tr><tr><td>Rated Voltage</td><td>300 V</td><td>300 V</td></tr><tr><td>Rated voltage (II/2)</td><td>300 V</td><td>600 V</td></tr><tr><td>Rated voltage (III/2)</td><td>150 V</td><td>300 V</td></tr><tr><td>Rated voltage (III/3):</td><td>150 V</td><td>250 V</td></tr><tr><td>Working current</td><td>10 A</td><td>15 A</td></tr><tr><td>Usegroup B, rated voltage / current</td><td>300 V / 10 A</td><td>300 V / 15 A</td></tr><tr><td>Usegroup C, rated voltage / current</td><td>- / -</td><td>- / -</td></tr><tr><td>Usegroup D, rated voltage / current</td><td>300 V / 10 A</td><td>300 V / 15 A</td></tr><tr><td>Contact resistance</td><td colspan="2">max. 15 mOhm</td></tr><tr><td>Insulation resistance</td><td colspan="2">min. 10⁹ Ohm (500 V DC)</td></tr><tr><td>Temperature range</td><td colspan="2">-40°C ... +110°C</td></tr><tr><td>Termination technology</td><td colspan="2">screw</td></tr><tr><td>Insertion force</td><td colspan="2">max. 3 N</td></tr><tr><td>Withdrawal force</td><td colspan="2">min. 1,5 N</td></tr><tr><td>Hot plugging</td><td colspan="2">No</td></tr><tr><td>Vibration</td><td colspan="2">10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs</td></tr><tr><td>RoHS - compliant</td><td colspan="2">Yes</td></tr><tr><td>UL file</td><td colspan="2">E314677</td></tr></table>			female connector			Design			Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV	Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx	Contact pitch	3.5 mm & 3.81 mm	5.08 mm	No. of contacts	2-25 poles	2-25 poles	Rated surge voltage (II/2)	2,5 kV	4 kV	Rated surge voltage (III/2)	2,5 kV	4 kV	Rated surge voltage (III/3)	2,5 kV	4 kV	Rated Voltage	300 V	300 V	Rated voltage (II/2)	300 V	600 V	Rated voltage (III/2)	150 V	300 V	Rated voltage (III/3):	150 V	250 V	Working current	10 A	15 A	Usegroup B, rated voltage / current	300 V / 10 A	300 V / 15 A	Usegroup C, rated voltage / current	- / -	- / -	Usegroup D, rated voltage / current	300 V / 10 A	300 V / 15 A	Contact resistance	max. 15 mOhm		Insulation resistance	min. 10 ⁹ Ohm (500 V DC)		Temperature range	-40°C ... +110°C		Termination technology	screw		Insertion force	max. 3 N		Withdrawal force	min. 1,5 N		Hot plugging	No		Vibration	10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs		RoHS - compliant	Yes		UL file	E314677		Packging unit <table><tr><th>Type of packaging</th><th>No. of poles (xx)</th><th>Quantity</th><th>MOQ</th><th>Index (xxx)</th><th>Remark</th></tr><tr><td>box</td><td>2</td><td>300</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>3</td><td>200</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>4 - 5</td><td>150</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>6 - 12</td><td>100</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>13 - 20</td><td>50</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr><tr><td>box</td><td>21 - 25</td><td>25</td><td>1</td><td>000 = green, 163 = black</td><td></td></tr></table>				Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark	box	2	300	1	000 = green, 163 = black		box	3	200	1	000 = green, 163 = black		box	4 - 5	150	1	000 = green, 163 = black		box	6 - 12	100	1	000 = green, 163 = black		box	13 - 20	50	1	000 = green, 163 = black		box	21 - 25	25	1	000 = green, 163 = black		B
female connector																																																																																																																																			
Design																																																																																																																																			
Type	har-flexicon 3.50/3.81 FSV	har-flexicon 5.08 FSV																																																																																																																																	
Part numbers	1431xx14401xxx & 1431xx15401xxx	1431xx17401xxx																																																																																																																																	
Contact pitch	3.5 mm & 3.81 mm	5.08 mm																																																																																																																																	
No. of contacts	2-25 poles	2-25 poles																																																																																																																																	
Rated surge voltage (II/2)	2,5 kV	4 kV																																																																																																																																	
Rated surge voltage (III/2)	2,5 kV	4 kV																																																																																																																																	
Rated surge voltage (III/3)	2,5 kV	4 kV																																																																																																																																	
Rated Voltage	300 V	300 V																																																																																																																																	
Rated voltage (II/2)	300 V	600 V																																																																																																																																	
Rated voltage (III/2)	150 V	300 V																																																																																																																																	
Rated voltage (III/3):	150 V	250 V																																																																																																																																	
Working current	10 A	15 A																																																																																																																																	
Usegroup B, rated voltage / current	300 V / 10 A	300 V / 15 A																																																																																																																																	
Usegroup C, rated voltage / current	- / -	- / -																																																																																																																																	
Usegroup D, rated voltage / current	300 V / 10 A	300 V / 15 A																																																																																																																																	
Contact resistance	max. 15 mOhm																																																																																																																																		
Insulation resistance	min. 10 ⁹ Ohm (500 V DC)																																																																																																																																		
Temperature range	-40°C ... +110°C																																																																																																																																		
Termination technology	screw																																																																																																																																		
Insertion force	max. 3 N																																																																																																																																		
Withdrawal force	min. 1,5 N																																																																																																																																		
Hot plugging	No																																																																																																																																		
Vibration	10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs																																																																																																																																		
RoHS - compliant	Yes																																																																																																																																		
UL file	E314677																																																																																																																																		
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark																																																																																																																														
box	2	300	1	000 = green, 163 = black																																																																																																																															
box	3	200	1	000 = green, 163 = black																																																																																																																															
box	4 - 5	150	1	000 = green, 163 = black																																																																																																																															
box	6 - 12	100	1	000 = green, 163 = black																																																																																																																															
box	13 - 20	50	1	000 = green, 163 = black																																																																																																																															
box	21 - 25	25	1	000 = green, 163 = black																																																																																																																															
C	Isulator material <table><tr><td>Material</td><td colspan="2">PA/PPA</td></tr><tr><td>Color</td><td colspan="2">green</td></tr><tr><td>UL classification</td><td colspan="2">UL 94-V0</td></tr><tr><td>Material group acc. to IEC 60664-1</td><td colspan="2">I (CTI > 600)</td></tr></table>			Material	PA/PPA		Color	green		UL classification	UL 94-V0		Material group acc. to IEC 60664-1	I (CTI > 600)		1431xx14401xxx				C																																																																																																															
Material	PA/PPA																																																																																																																																		
Color	green																																																																																																																																		
UL classification	UL 94-V0																																																																																																																																		
Material group acc. to IEC 60664-1	I (CTI > 600)																																																																																																																																		
D	Contact material <table><tr><td>Contact material</td><td colspan="2">Copper alloy</td></tr><tr><td>Plating termination zone</td><td colspan="2">Ni</td></tr><tr><td>Plating contact zone</td><td colspan="2">Sn</td></tr></table>			Contact material	Copper alloy		Plating termination zone	Ni		Plating contact zone	Sn						D																																																																																																																		
Contact material	Copper alloy																																																																																																																																		
Plating termination zone	Ni																																																																																																																																		
Plating contact zone	Sn																																																																																																																																		
E	Derating The current carrying capacity is limited by maximum temperature of materialsfor inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given,without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5							E																																																																																																																											
F				har-flexicon female connector, vertical, screwing HARTING Department EC PD - DE DS 14312401201 Doc-Key / ECM-Nr. 100579803/UGD/000/D 500000108598 Rev. D Page 1/1				F																																																																																																																											
1	2	3	4	5	6	7	8																																																																																																																												

		All Dimensions in mm		Scale		Free size tol.		Ref.							
		Original Size DIN A3		1:1				Sub.							
		All rights reserved		Created by		Inspected by		Standardisation		Date		State			
		Department EC PD - DE		TADJE		ZWahr		HOFFMANN		2016-09-07		Final Release			
HARTING Electronics GmbH D-32339 Espelkamp		Title									Doc-Key / ECM-Nr.				
		har-flexicon female connector, vertical, screwing									100579803/UGD/000/D 500000108598				
		Type		DS		Number		14312401201		Rev.		D		Page	
														1/1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[14311214401000](#) [14310414401000](#) [14310214401000](#) [14310614401000](#) [14310814401000](#) [14310314401000](#)
[14311014401000](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.