


## Parascan™ tunable integrated capacitor



WLCSP 3 solder bars



### Features

- High power capability
- 5:1 tuning range
- High linearity (48x)
- High quality factor (Q)
- Low leakage current
- Compatible with high voltage control IC (STHV DAC series)
- RF tunable passive implementation in mobile phones to optimize antenna radiated performance
- Available in wafer level chip scale package:
  - WLCSP package 0.75 x 0.72 x 0.32 mm
- ECOPACK®2 compliant component

### Applications

- Cellular antenna open loop tunable matching network in multi-band GSM/WCDMA/LTE mobile phone
- Open loop tunable RF filters

### Description

The ST integrated tunable capacitor offers excellent RF performance, low power consumption and high linearity required in adaptive RF tuning applications. The fundamental building block of PTIC is a tunable material called Parascan™, which is a version of barium strontium titanate (BST) developed by Paratek microwave.

BST capacitors are tunable capacitors intended for use in mobile phone application and dedicated to RF tunable applications. These tunable capacitors are controlled through an extended bias voltage ranging from 1 to 24 V. The implementation of BST tunable capacitor in mobile phones enables significant improvement in terms of radiated performance making the performance almost insensitive to the external environment.

Parascan is a trademark of Paratek Microwave Inc.

Product status link

[STPTIC-15C4](#)

## 1 STPTIC-15C4 characteristics

**Table 1. Absolute maximum ratings (limiting values)**

Symbol	Parameter	Rating	Unit
$P_{IN}$	Input power $RF_{IN}$ (CW model) / all RF ports	+40	dBm
$V_{ESD(HBM)}$	Human body model, JESD22-A114-B, all I/O	Class 1B	V
$V_{ESD(MM)}$	Machine model, JESD22-A115-A, all I/O	+100	V
$T_{device}$	Device temperature	+125	°C
$T_{stg}$	Storage temperature	-55 to +150	
$V_x$	Bias voltage	25	V

1. Class 1B defined as passing 500 V, but fails after exposure to 1000V ESD pulse.

**Table 2. Recommended operating conditions**

Symbol	Parameter	Rating			Unit
		Min.	Typ.	Max.	
$P_{IN}$	RF input power		+33	+39	dBm
$F_{OP}$	Operating frequency	700		2700	MHz
$T_{device}$	Device temperature			+100	°C
$T_{OP}$	Operating temperature	-30		+85	
$V_{BIAS}$	Bias voltage	1		24	V

**Table 3. Representative performance ( $T_{amb} = 25$  °C otherwise specified)**

Symbol	Parameter	Conditions	Value			Unit
			Min.	Typ.	Max.	
$C_{1V}$	Capacitor at 1 V bias		1.58	1.8	2.02	pF
$C_{2V}$	Capacitor at 2 V bias		1.35	1.5	1.65	pF
$C_{20V}$	Capacitor at 20 V bias		0.39	0.42	0.46	pF
$C_{24V}$	Capacitor at 24 V bias		0.35	0.38	0.42	pF
$C$	Capacitance accuracy	$V_{BIAS}$ range = 2 V/ 20 V			10	%
$\Delta C$	Tuning range	Ratio between $C_{1V}/C_{24V}$ <sup>(1)</sup>		5/1		
$I_L$	Leakage current	Measured with $V_{BIAS} = 24$ V			100	nA
$Q_{LB}$	Quality factor	Measured at 700 MHz at 2 V	50	55		
$Q_{HB}$	Quality factor	Measured at 2700 MHz at 2 V	35	40		
IP3	Third order intercept point	$V_{BIAS} = 2$ V <sup>(2)</sup> <sup>(3)</sup>	60			dBm
		$V_{BIAS} = 20$ V <sup>(2)(3)</sup>	80			dBm
H2	Second harmonic	$V_{BIAS} = 2$ V <sup>(4)(3)</sup>		-70	-55	dBm
		$V_{BIAS} = 20$ V <sup>(4)</sup> <sup>(3)</sup>		-80	-70	dBm



Symbol	Parameter	Conditions	Value			Unit
			Min.	Typ.	Max.	
H3	Third harmonic	$V_{BIAS} = 2\text{ V}$ <sup>(4)(3)</sup>		-55	-45	dBm
		$V_{BIAS} = 20\text{ V}$ <sup>(4)(3)</sup>		-85	-70	dBm
$t_T$	Transition time	Transition between 20 V to 2 V <sup>(5)</sup>			120	$\mu\text{s}$
		Transition between 2 V to 20 V <sup>(5)</sup>			70	$\mu\text{s}$
		Transition between 20 V to 4 V <sup>(5)</sup>			70	$\mu\text{s}$
		Transition between 4 V to 20 V <sup>(5)</sup>			50	$\mu\text{s}$

1. Measured at low frequency
2.  $F_1 = 894\text{ MHz}$ ,  $F_2 = 849\text{ MHz}$ ,  $P_1 = +25\text{ dBm}$ ,  $P_2 = +25\text{ dBm}$ ,  $2f_1 - f_2 = 939\text{ MHz}$
3. IP3 and harmonics are measured in the shunt configuration in a 50  $\Omega$  environment
4. 850 MHz,  $P_{IN} = +34\text{ dBm}$
5. One or both of  $RF_{IN}$  and  $RF_{OUT}$  must be connected to DC ground, using the HVDAC turbo mode. Transition time for tuner between  $C_{min.}$  to 90% of  $C_{max.}$  or  $C_{max.}$  to 90% of  $C_{min.}$  include MIPI order work time (trig with last MIPI CLK).

### 1.1 RF measurements

Figure 1. Capacitor variation versus bias voltage




Figure 2. Quality factor versus frequency




Figure 3. Harmonic power versus bias voltage (shunt)




Figure 4. Harmonic power versus bias voltage (series)




Figure 5. Third order intercept point (IP3)




Figure 6. Settling time from 2 V to  $V_{FINAL}$





Figure 7. Settling time from  $V_{START}$  to 2 V



## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 2.1 WLCSP 3 solder bars package information

Figure 8. WLCSP 3 solder bars package outline




Table 4. WLCSP 3 solder bars package dimensions

Dimensions	A1	A2	B1	B2	B3	C1	C2	C3	D1	D2	D3	E1	E2
STPTIC-15L2C4	720	750	100	420	200	100	550	375	225	90	315	125	300
Tolerance	±30	±30	±15	±10	±15	±15	±10	±15	±20	±25	±40	±25	±25

Figure 9. Recommended PCB land pattern for WLCSP 3 solder bars package




Table 5. Dimensions

Ball	L1	W1	X1	Y1	Y2
Typical values (in microns)	300	200	270	130	200

## 2.2 Packing information

Figure 10. Tape and reel outline




Table 6. Pocket dimensions

Pocket dimensions	L	W	H
STPTIC-15L2C4	820	790	385

Figure 11. Marking





Table 7. Pinout description

Pad / ball number	pin name	Description
A1	DC bias	DC bias voltage
B1	RF1	RF input / output
B2	RF2 <sup>(1)</sup>	RF input / output

1. When connected in shunt, please connect RF2 (B2 ball) to GND

## 2.3 Reflow profile

Figure 12. ST ECOPACK® recommended soldering reflow profile for PCB mounting



Note: Minimize air convection currents in the reflow oven to avoid component movement.

Table 8. Recommended values for soldering reflow

Profile	Value	
	Typical	Max.
Temperature gradient in preheat (T = 70-180 °C)	0.9 °C/s	3 °C/s
Temperature gradient (T = 200-225 °C)	2 °C/s	3 °C/s
Peak temperature in reflow	240-245 °C	260 °C
Time above 220 °C	60 s	90 s
Temperature gradient in cooling	-2 to -3 °C/s	-6 °C/s
Time from 50 to 220 °C	160 to 220 s	



### 3 Evaluation board

Figure 13. Series and shunt connection




Figure 14. Layer 1 and layer 4





Figure 15. Layer 2 and layer 3



## 4 Ordering information

Figure 16. Ordering information scheme

ST	PTIC	-	15	L	2	C4
<u>Manufacturer</u>	<u>Product family</u>	-	<u>Capacitor value</u>	<u>Linearity</u>	<u>Tuning</u>	<u>Package</u>
ST Microelectronics	PTIC Parascan™ tunable Integrated capacitor		15 = 1.5 pF 27 = 2.7 pF 33 = 3.3 pF 39 = 3.9 pF 47 = 4.7 pF 56 = 5.6 pF 68 = 6.8 pF 82 = 8.2 pF	F: Standard (x24) G: Standard (x24) L: High (x48)	1 = 4/1 tuning 2 = 5/1 tuning	M6 : QFN C5 : WLCSP 400 μm coating C4 : WLCSP 3 solder bars

Table 9. Ordering information

Order code	Marking	Base qty.	Package	Delivery mode
STPTIC-15L2C4	15R	15 000	WLCSP 3 solder bars	Tape and reel

## Revision history

**Table 10. Document revision history**

Date	Version	Changes
03-Jul-2018	1	Initial release.

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.