



## High Voltage, Input Rectifier Diode, 80 A



### FEATURES

- Very low forward voltage drop
- 150 °C max. operating junction temperature
- Glass passivated pellet chip junction
- Designed and qualified according to JEDEC®-JESD 47
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
Available

| PRODUCT SUMMARY |                 |
|-----------------|-----------------|
| Package         | TO-247AC        |
| $I_{F(AV)}$     | 80 A            |
| $V_R$           | 800 V to 1200 V |
| $V_F$ at $I_F$  | 1.17 V          |
| $I_{FSM}$       | 1500 A          |
| $T_J$ max.      | 150 °C          |
| Diode variation | Single die      |

### APPLICATIONS

- Input rectification
- Vishay Semiconductors switches and output rectifiers which are available in identical package outlines

### DESCRIPTION

High voltage rectifiers optimized for very low forward voltage drop with moderate leakage.

These devices are intended for use in main rectification (single or three phase bridge).

| MAJOR RATINGS AND CHARACTERISTICS |                            |             |       |
|-----------------------------------|----------------------------|-------------|-------|
| SYMBOL                            | CHARACTERISTICS            | VALUES      | UNITS |
| $I_{F(AV)}$                       | Sinusoidal waveform        | 80          | A     |
| $V_{RRM}$                         | Range                      | 800/1200    | V     |
| $I_{FSM}$                         |                            | 1500        | A     |
| $V_F$                             | 80 A, $T_J = 25\text{ °C}$ | 1.17        | V     |
| $T_J$                             |                            | -40 to +150 | °C    |

| VOLTAGE RATINGS              |   |  |                           |
|------------------------------|---|--|---------------------------|
| PART NUMBER                  | $V_{RRM}$ , MAXIMUM PEAK REVERSE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE<br>V | $I_{RRM}$ AT 150 °C<br>mA |
| VS-80APS08PbF, VS-80APS08-M3 | 800   | 900  | 1.5                       |
| VS-80APS12PbF, VS-80APS12-M3 | 1200  | 1300   |                           |

| ABSOLUTE MAXIMUM RATINGS                            |               |  |         |                   |
|---|---------------|--|---------|-------------------|
| PARAMETER   | SYMBOL        | TEST CONDITIONS  | VALUES  | UNITS             |
| Maximum average forward current                     | $I_{F(AV)}$   | $T_C = 100\text{ °C}$ , 180° conduction half sine wave     | 80      | A                 |
| Maximum peak one cycle non-repetitive surge current | $I_{FSM}$     | 10 ms sine pulse, rated $V_{RRM}$ applied                  | 1450    |                   |
|   |               | 10 ms sine pulse, no voltage reapplied                     | 1500    |                   |
| Maximum $I^2t$ for fusing                           | $I^2t$        | 10 ms sine pulse, rated $V_{RRM}$ applied                  | 10 500  | A <sup>2</sup> s  |
|   |               | 10 ms sine pulse, no voltage reapplied                     | 14 000  |                   |
| Maximum $I^2\sqrt{t}$ for fusing                    | $I^2\sqrt{t}$ | $t = 0.1\text{ ms to }10\text{ ms}$ , no voltage reapplied | 140 000 | A <sup>2</sup> √s |



| ELECTRICAL SPECIFICATIONS       |             |  |                               |        |            |
|---------------------------------|-------------|--|-------------------------------|--------|------------|
| PARAMETER                       | SYMBOL      | TEST CONDITIONS                        |                               | VALUES | UNITS      |
| Maximum forward voltage drop    | $V_{FM}$    | 80 A, $T_J = 25\text{ }^\circ\text{C}$ |                               | 1.17   | V          |
| Forward slope resistance        | $r_t$       | $T_J = 150\text{ }^\circ\text{C}$      |                               | 3.17   | m $\Omega$ |
| Threshold voltage               | $V_{F(TO)}$ |  |                               | 0.73   | V          |
| Maximum reverse leakage current | $I_{RM}$    | $T_J = 25\text{ }^\circ\text{C}$       | $V_R = \text{Rated } V_{RRM}$ | 0.1    | mA         |
|                                 |             | $T_J = 150\text{ }^\circ\text{C}$      |                               | 1.5    |            |

| THERMAL - MECHANICAL SPECIFICATIONS             |                             |  |         |            |                        |
|---|-----------------------------|--|---------|------------|------------------------|
| PARAMETER                                       | SYMBOL                      | TEST CONDITIONS                            |         | VALUES     | UNITS                  |
| Maximum junction and storage temperature range  | $T_J, T_{Stg}$              |  |         | -40 to 150 | $^\circ\text{C}$       |
| Maximum thermal resistance, junction to case    | $R_{thJC}$                  | DC operation                               |         | 0.35       | $^\circ\text{C/W}$     |
| Maximum thermal resistance, junction to ambient | $R_{thJA}$                  |  |         | 40         |                        |
| Typical thermal resistance, case to heatsink    | $R_{thCS}$                  | Mounting surface, flat, smooth and greased |         | 0.2        |                        |
| Approximate weight                              |                             |  |         | 6          | g                      |
|   |                             |  |         | 0.21       | oz.                    |
| Mounting torque                                 | minimum                     |  |         | 6 (5)      | kgf · cm<br>(lbf · in) |
|   | maximum                     |  |         | 12 (10)    |                        |
| Marking device                                  | Case style TO-247AC (JEDEC) |  | 80APS08 |            |                        |
|   |                             |  | 80APS12 |            |                        |




Fig. 1 - Current Rating Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 4 - Forward Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristics

**ORDERING INFORMATION TABLE**

|             |            |           |          |          |          |           |            |
|-------------|------------|-----------|----------|----------|----------|-----------|------------|
| Device code | <b>VS-</b> | <b>80</b> | <b>A</b> | <b>P</b> | <b>S</b> | <b>12</b> | <b>PbF</b> |
|             | ①          | ②         | ③        | ④        | ⑤        | ⑥         |            |

- 1** - Vishay Semiconductors product
- 2** - Current rating (80 = 80 A)
- 3** - Circuit configuration:  
A = single diode, 3 pins
- 4** - Package:  
P = TO-247AC
- 5** - Type of silicon:  
S = standard recovery rectifier
- 6** - Voltage ratings ————— 08 = 800 V  
12 = 1200 V
- 7** - Environmental digit:  
PbF = lead (Pb)-free and RoHS-compliant  
-M3 = halogen-free, RoHS-compliant, and terminations lead (Pb)-free


| <b>ORDERING INFORMATION (Example)</b> |                  |                        |                          |
|---------------------------------------|------------------|------------------------|--------------------------|
| PREFERRED P/N                         | QUANTITY PER T/R | MINIMUM ORDER QUANTITY | PACKAGING DESCRIPTION    |
| VS-80APS08PbF                         | 25               | 500                    | Antistatic plastic tubes |
| VS-80APS08-M3                         | 25               | 500                    | Antistatic plastic tubes |
| VS-80APS12PbF                         | 25               | 500                    | Antistatic plastic tubes |
| VS-80APS12-M3                         | 25               | 500                    | Antistatic plastic tubes |

| <b>LINKS TO RELATED DOCUMENTS</b> |  |
|-----------------------------------|--|
| Dimensions                        | <a href="http://www.vishay.com/doc?95542">www.vishay.com/doc?95542</a>                       |
| Part marking information          | TO-247AC modified PbF <a href="http://www.vishay.com/doc?95226">www.vishay.com/doc?95226</a> |
|                                   | TO-247AC modified -M3 <a href="http://www.vishay.com/doc?95007">www.vishay.com/doc?95007</a> |
| SPIICE model                      | <a href="http://www.vishay.com/doc?95550">www.vishay.com/doc?95550</a>                       |



TO-247AC - 50 mils L/F

DIMENSIONS in millimeters and inches



| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES | SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|--------|-------|-------|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| A      | 4.65        | 5.31  | 0.183  | 0.209 |       | D2     | 0.51        | 1.35  | 0.020     | 0.053 |       |
| A1     | 2.21        | 2.59  | 0.087  | 0.102 |       | E      | 15.29       | 15.87 | 0.602     | 0.625 | 3     |
| A2     | 1.17        | 1.37  | 0.046  | 0.054 |       | E1     | 13.46       | -     | 0.53      | -     |       |
| b      | 0.99        | 1.40  | 0.039  | 0.055 |       | e      | 5.46 BSC    |       | 0.215 BSC |       |       |
| b1     | 0.99        | 1.35  | 0.039  | 0.053 |       | Ø K    | 0.254       |       | 0.010     |       |       |
| b2     | 1.65        | 2.39  | 0.065  | 0.094 |       | L      | 14.20       | 16.10 | 0.559     | 0.634 |       |
| b3     | 1.65        | 2.34  | 0.065  | 0.092 |       | L1     | 3.71        | 4.29  | 0.146     | 0.169 |       |
| b4     | 2.59        | 3.43  | 0.102  | 0.135 |       | Ø P    | 3.56        | 3.66  | 0.14      | 0.144 |       |
| b5     | 2.59        | 3.38  | 0.102  | 0.133 |       | Ø P1   | -           | 7.39  | -         | 0.291 |       |
| c      | 0.38        | 0.89  | 0.015  | 0.035 |       | Q      | 5.31        | 5.69  | 0.209     | 0.224 |       |
| c1     | 0.38        | 0.84  | 0.015  | 0.033 |       | R      | 4.52        | 5.49  | 0.178     | 0.216 |       |
| D      | 19.71       | 20.70 | 0.776  | 0.815 | 3     | S      | 5.51 BSC    |       | 0.217 BSC |       |       |
| D1     | 13.08       | -     | 0.515  | -     | 4     |        |             |       |           |       |       |

Notes

- (1) Dimensioning and tolerancing per ASME Y14.5M-1994
- (2) Contour of slot optional
- (3) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outermost extremes of the plastic body
- (4) Thermal pad contour optional with dimensions D1 and E1
- (5) Lead finish uncontrolled in L1
- (6) Ø P to have a maximum draft angle of 1.5 to the top of the part with a maximum hole diameter of 3.91 mm (0.154")
- (7) Outline conforms to JEDEC® outline TO-247 with exception of dimension c and Q



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.