




# EJECT-A-DIP® Lock/Eject DIP Collet Sockets with Solder Tail Pins

## FEATURES:

- Aries EJECT-A-DIP® is a rugged, solderable socket with a unique ejector/latch for fast in-field board maintenance.
- The latch locks in the connector or device, making it ideal for high vibration environments.
- The latch, when used as an ejector, removes DIP packages without pin damage.

## SPECIFICATIONS:

- Latch and body are black UL-94V-0 Glass-filled 4/6 Nylon.
- Pin body is Brass Alloy 360 1/2 hard per UNS C36000 ASTM-B16-00.
- Pin body plating is either 10  $\mu$  [.25 $\mu$ m] min. Gold per MIL-G-45204 or 200 $\mu$  [5.08 $\mu$ m] min. 93/7 Tin/Lead per ASTM B545 or 200 $\mu$  [5.08 $\mu$ m] min. Tin per ASTM B545 Type 1 over 100 $\mu$  [2.54 $\mu$ m] min. Nickel per SAE-AMS-QQ-N-290.
- 6-fingered collet contact is Beryllium Copper Alloy per UNS C17200 ASTM-B194-01.
- Contact plating is either 200 $\mu$  [5.08 $\mu$ m] min. 93/7 Tin/Lead per ASTM B545 or 200 $\mu$  [5.08 $\mu$ m] min. Tin per ASTM B545 Type 1 or 10 $\mu$  [.25 $\mu$ m] min. Gold per MIL-G-45204 over 50  $\mu$  [1.27 $\mu$ m] min. Nickel per SAE-AMS-QQ-N-290. Heavy 30 $\mu$  [.76 $\mu$ m] Gold plating on contact also available.
- Contact current rating=3 Amps.
- Insulation resistance=10,000 MOhms @ 500 VDC.
- Withstanding voltage=1000 V RMS.
- Operating temp.= -67°F to 221°F [-55°C to 105°C] Tin plating, -67°F to 257°F [-55°C to 125°C] Gold.
- Insertion Force= 67g/pin; Withdrawal Force=30g/pin; Normal Force=45g/pin; based on .018 [.46] dia. test lead.



Note: Aries specializes in custom design and production. In addition to the standard products shown on this page, special materials, platings, sizes, and configurations can be furnished, depending on quantities. Aries reserves the right to change product specifications without notice.

## ORDERING INFORMATION



XX-CXXX-1XXXXX

No. of pins ———  
Dim. "H" (see table) ———  
Solder tail pin ———

Optional plating suffix:  
H=Heavy Gold collet  
T=Tin collet/Tin Body  
TL=Tin/Lead collet & Body

### Plating:

0=Gold collet/Tin Body  
0TL=Gold collet/Tin/Lead Body  
1=Gold collet/Gold Body



### SOLDER TAIL PIN

Consult Data Sheet No. 12025 for EJECT-A-DIP® collet sockets with wire wrap pins.

All tolerances ± .005 [.13] unless otherwise specified

ALL DIMENSIONS: INCHES [MILLIMETERS]

Suggested PCB hole size=.030 ± .002 [.76 ± .05] dia.

| No. of Pins | Catalog No. | Dim. A        | Dim. B        | Centers "C"  | Dim "D"      | Dim. "E"      | Dim. "F"      | Dim. "G"     | Dim. "H"    |
|-------------|-------------|---------------|---------------|--------------|--------------|---------------|---------------|--------------|-------------|
| 14          | 14-C280-XX  | .950 [24.10]  | .600 [15.24]  | .300 [7.62]  | .400 [10.16] | .770 [19.56]  | 1.300 [33.02] | .490 [12.45] | .280 [7.11] |
| 14          | 14-C195-XX  | .950 [24.10]  | .600 [15.24]  | .300 [7.62]  | .400 [10.16] | .770 [19.56]  | 1.300 [33.02] | .450 [11.43] | .194 [4.95] |
| 16          | 16-C280-XX  | 1.050 [26.70] | .700 [17.78]  | .300 [7.62]  | .400 [10.16] | .870 [22.10]  | 1.540 [39.12] | .490 [12.45] | .280 [7.11] |
| 16          | 16-C195-XX  | 1.050 [26.70] | .700 [17.78]  | .300 [7.62]  | .400 [10.16] | .870 [22.10]  | 1.390 [35.31] | .450 [11.43] | .195 [4.95] |
| 24          | 24-C300-XX  | 1.490 [37.85] | 1.100 [27.94] | .600 [15.24] | .700 [17.78] | 1.300 [33.02] | 1.970 [50.04] | .570 [14.48] | .300 [7.62] |
| 24          | 24-C212-XX  | 1.490 [37.85] | 1.100 [27.94] | .600 [15.24] | .700 [17.78] | 1.300 [33.02] | 1.850 [47.00] | .490 [12.45] | .212 [5.39] |
| 24          | 24-C182-XX  | 1.490 [37.85] | 1.100 [27.94] | .600 [15.24] | .700 [17.78] | 1.300 [33.02] | 1.800 [45.72] | .460 [11.68] | .182 [4.62] |
| 28          | 28-C300-XX  | 1.690 [42.90] | 1.300 [33.02] | .600 [15.24] | .700 [17.78] | 1.500 [38.10] | 2.170 [55.12] | .570 [14.48] | .300 [7.62] |
| 28          | 28-C212-XX  | 1.690 [42.90] | 1.300 [33.02] | .600 [15.24] | .700 [17.78] | 1.500 [38.10] | 2.050 [52.07] | .490 [12.45] | .212 [5.39] |
| 28          | 28-C182-XX  | 1.690 [42.90] | 1.300 [33.02] | .600 [15.24] | .700 [17.78] | 1.500 [38.10] | 2.000 [50.80] | .460 [11.68] | .182 [4.62] |
| 32          | 32-C300-XX  | 1.890 [48.00] | 1.500 [38.10] | .600 [15.24] | .700 [17.78] | 1.700 [43.18] | 2.540 [64.52] | .570 [14.48] | .300 [7.62] |
| 32          | 32-C212-XX  | 1.890 [48.00] | 1.500 [38.10] | .600 [15.24] | .700 [17.78] | 1.700 [43.18] | 2.070 [52.58] | .490 [12.45] | .212 [5.39] |
| 32          | 32-C182-XX  | 1.890 [48.00] | 1.500 [38.10] | .600 [15.24] | .700 [17.78] | 1.700 [43.18] | 2.200 [55.88] | .460 [11.68] | .182 [4.62] |
| 40          | 40-C300-XX  | 2.290 [58.20] | 1.900 [48.26] | .600 [15.24] | .700 [17.78] | 2.100 [53.34] | 2.780 [70.61] | .570 [14.48] | .300 [7.62] |
| 40          | 40-C212-XX  | 2.290 [58.20] | 1.900 [48.26] | .600 [15.24] | .700 [17.78] | 2.100 [53.34] | 2.650 [67.31] | .490 [12.45] | .212 [5.39] |
| 40          | 40-C182-XX  | 2.290 [58.20] | 1.900 [48.26] | .600 [15.24] | .700 [17.78] | 2.100 [53.34] | 2.600 [66.04] | .460 [11.68] | .182 [4.62] |



**ARIES**  
ELECTRONICS, INC.

Bristol, PA 19007-6810 USA  
TEL(215)781-9956•FAX(215)781-9845  
WWW.ARIESELEC.COM • INFO@ARIESELEC.COM



12024  
REV. G



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.