


45 V field-effect rectifier diode

Datasheet - production data



Features

- ST advanced rectifier process
- Stable leakage current over reverse voltage
- Low forward voltage drop
- High frequency operation
- ECOPACK®2 compliant component for DPAK on demand

Description

This single rectifier is based on a proprietary technology that achieves the best in class V_F/I_R trade-off for a given silicon surface.

Therefore it can advantageously replace 45 V low voltage Schottky diodes.

Packaged in DPAK, this device is intended to be used in rectification and freewheeling operations in power supplies.

Table 1: Device summary

Symbol	Value
$I_{F(AV)}$	20 A
V_{RRM}	45 V
$V_F(\text{typ.})$	0.29 V
$T_j(\text{max.})$	150 °C

1 Characteristics

Table 2: Absolute ratings (limiting values at 25 °C, unless otherwise specified, anode terminals short-circuited)

Symbol	Parameter	Value	Unit	
V_{RRM}	Repetitive peak reverse voltage	45	V	
$I_{F(RMS)}$	Forward rms current	40	A	
$I_{F(AV)}$	Average forward current $\delta = 0.5$, square wave	20	A	
I_{FSM}	Surge non repetitive forward current	$t_p = 10 \text{ ms sinusoidal}$	180	A
T_{stg}	Storage temperature range	-65 to +175	°C	
T_j	Maximum operating junction temperature range ⁽¹⁾	-40 to +150	°C	

Notes:

⁽¹⁾ $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$ condition to avoid thermal runaway for a diode on its own heatsink.

Table 3: Thermal resistance parameters

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	Junction to case	1.4	°C/W

Table 4: Static electrical characteristics (anode terminals short circuited)

Symbol	Parameter	Test conditions		Min.	Typ.	Max.	Unit
$I_R^{(1)}$	Reverse leakage current	$T_j = 25 \text{ °C}$	$V_R = 35 \text{ V}$	-	100	300	µA
		$T_j = 125 \text{ °C}$		-	12	24	mA
		$T_j = 25 \text{ °C}$	$V_R = V_{RRM}$	-	200	600	µA
		$T_j = 125 \text{ °C}$		-	18	40	mA
$V_F^{(2)}$	Forward voltage drop	$T_j = 25 \text{ °C}$	$I_F = 5 \text{ A}$	-	0.35		V
		$T_j = 125 \text{ °C}$		-	0.29		
		$T_j = 25 \text{ °C}$	$I_F = 10 \text{ A}$	-	0.41	0.45	
		$T_j = 125 \text{ °C}$		-	0.38	0.42	
		$T_j = 25 \text{ °C}$	$I_F = 20 \text{ A}$	-	0.51	0.55	
		$T_j = 125 \text{ °C}$		-	0.52	0.57	

Notes:

⁽¹⁾Pulse test: $t_p = 5 \text{ ms}$, $\delta < 2\%$

⁽²⁾Pulse test: $t_p = 380 \mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation:

$$P = 0.27 \times I_{F(AV)} + 0.015 \times I_{F^2(RMS)}$$

1.1 Characteristics (curves)

Figure 1: Average forward current versus ambient temperature ($\delta = 0.5$)




Figure 2: Relative variation of thermal impedance junction to case versus pulse duration




Figure 3: Reverse leakage current versus reverse voltage applied (typical values)




Figure 4: Junction capacitance versus reverse voltage applied (typical values)




Figure 5: Forward voltage drop versus forward current (typical values)




Figure 6: Forward voltage drop versus forward current (typical values)





Figure 7: Thermal resistance junction to ambient versus copper surface under tab for DPAK


2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

- Cooling method: by conduction (C)
- Epoxy meets UL 94,V0

2.1 DPAK package information

Figure 8: DPAK package outline




This package drawing may slightly differ from the physical package. However, all the specified dimensions are guaranteed.

Table 5: DPAK package mechanical data

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.18	2.40	0.085	0.094
A1	0.90	1.10	0.035	0.043
A2	0.03	0.23	0.001	0.009
b	0.64	0.90	0.025	0.035
b4	4.95	5.46	0.194	0.215
c	0.46	0.61	0.018	0.024
c2	0.46	0.60	0.018	0.023
D	5.97	6.22	0.235	0.244
D1	4.95	5.60	0.194	0.220
E	6.35	6.73	0.250	0.265
E1	4.32	5.50	0.170	0.216
e	2.286 typ.		0.090 typ.	
e1	4.40	4.70	0.173	0.185
H	9.35	10.40	0.368	0.409
L	1.0	1.78	0.039	0.070
L2		1.27		0.050
L4	0.60	1.02	0.023	0.040
V2	-8°	+8°	-8°	+8°

Figure 9: DPAK recommended footprint (dimensions in mm)



3 Ordering information

Table 6: Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
FERD2045SB-TR	FERD 2045	DPAK	0.32 g	2500	Tape and reel

4 Revision history

Table 7: Document revision history

Date	Revision	Changes
15-Jan-2018	1	Initial release.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.