
Restricted to: General Release


USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT PER EC#



Left Side

Connector(s): MT-RJ (No Pins)
Mode: MM
Housing Color: Black
Geom. Spec: 115-1215



VIEW C-C
NOT TO SCALE

Fiber Path


Fiber A - ——— - Fiber B
Fiber B - ——— - Fiber A

Notes:

1. Product and Processing must meet requirements of Tyco Electronics Standard 230-702
2. Label 2 will not be present on any cable assembly less than 5 meters long.
3. Includes dust caps (not shown on print).

Right Side

Connector(s): MT-RJ SECURE (No Pins)
Mode: MM
Housing Color: Green
Geom. Spec: 115-1215



VIEW D-D
NOT TO SCALE

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND MAY NOT BE REPRODUCED, USED OR DISCLOSED EXCEPT AS AUTHORIZED BY TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

LOC CE
DIST 16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A	Rev Per EC# RELEASE	8/7/2006	-	MK

DIMENSIONS: meters
TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC # -
1 PLC # -
2 PLC # -
3 PLC # -
4 PLC # -

Customer Print

DWN: Cable Assy Configurator
CHK: Michael Kepko
APVD: Michael Kepko
NAME: FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, MT-RJ (No Pins) to MT-RJ SECURE (No Pins)

MATERIAL: -
HEAT TREAT: -

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 1754408	1 of 3	A

8 7 6 5 4 3 2 1

D C B A

Restricted to: General Release

USED ON

Part #	L (meters)	L (feet)	MT-RJ (No Pins), Black IL (dB)	MT-RJ (No Pins), Black RL (dB)	MT-RJ SECURE (No Pins), Green IL (dB)	MT-RJ SECURE (No Pins), Green RL (dB)
0-1754408-1	0.950 - 1.050	3.11 - 3.44	0.5	20	0.5	20
0-1754408-2	1.950 - 2.050	6.39 - 6.72	0.5	20	0.5	20
0-1754408-3	2.950 - 3.050	9.67 - 10.00	0.5	20	0.5	20
0-1754408-4	3.920 - 4.080	12.86 - 13.38	0.51	20	0.51	20
0-1754408-5	4.920 - 5.080	16.14 - 16.66	0.51	20	0.51	20
0-1754408-6	5.920 - 6.080	19.42 - 19.94	0.51	20	0.51	20
0-1754408-7	6.920 - 7.080	22.70 - 23.22	0.51	20	0.51	20
0-1754408-8	7.920 - 8.080	25.98 - 26.50	0.51	20	0.51	20
0-1754408-9	8.850 - 9.150	29.03 - 30.01	0.51	20	0.51	20
1-1754408-0	9.850 - 10.150	32.31 - 33.30	0.52	20	0.52	20
1-1754408-1	10.850 - 11.150	35.59 - 36.58	0.52	20	0.52	20
1-1754408-2	11.850 - 12.150	38.87 - 39.86	0.52	20	0.52	20
1-1754408-3	12.850 - 13.150	42.15 - 43.14	0.52	20	0.52	20
1-1754408-4	13.850 - 14.150	45.43 - 46.42	0.52	20	0.52	20
1-1754408-5	14.850 - 15.150	48.72 - 49.70	0.52	20	0.52	20
1-1754408-6	15.840 - 16.160	51.96 - 53.01	0.52	20	0.52	20
1-1754408-7	16.830 - 17.170	55.21 - 56.33	0.53	20	0.53	20
1-1754408-8	17.820 - 18.180	58.46 - 59.64	0.53	20	0.53	20
1-1754408-9	18.810 - 19.190	61.71 - 62.95	0.53	20	0.53	20
2-1754408-0	19.800 - 20.200	64.96 - 66.27	0.53	20	0.53	20
2-1754408-1	20.790 - 21.210	68.20 - 69.58	0.53	20	0.53	20
2-1754408-2	21.780 - 22.220	71.45 - 72.90	0.53	20	0.53	20
2-1754408-3	22.770 - 23.230	74.70 - 76.21	0.53	20	0.53	20
2-1754408-4	23.760 - 24.240	77.95 - 79.52	0.54	20	0.54	20
2-1754408-5	24.750 - 25.250	81.20 - 82.84	0.54	20	0.54	20
2-1754408-6	25.740 - 26.260	84.44 - 86.15	0.54	20	0.54	20
2-1754408-7	26.730 - 27.270	87.69 - 89.46	0.54	20	0.54	20
2-1754408-8	27.720 - 28.280	90.94 - 92.78	0.54	20	0.54	20
2-1754408-9	28.710 - 29.290	94.19 - 96.09	0.54	20	0.54	20
3-1754408-0	29.700 - 30.300	97.44 - 99.40	0.55	20	0.55	20
3-1754408-1	30.690 - 31.310	100.68 - 102.72	0.55	20	0.55	20
3-1754408-2	31.680 - 32.320	103.93 - 106.03	0.55	20	0.55	20
3-1754408-3	32.670 - 33.330	107.18 - 109.35	0.55	20	0.55	20
3-1754408-4	33.660 - 34.340	110.43 - 112.66	0.55	20	0.55	20
3-1754408-5	34.650 - 35.350	113.68 - 115.97	0.55	20	0.55	20
3-1754408-6	35.640 - 36.360	116.92 - 119.29	0.55	20	0.55	20
3-1754408-7	36.630 - 37.370	120.17 - 122.60	0.56	20	0.56	20
3-1754408-8	37.620 - 38.380	123.42 - 125.91	0.56	20	0.56	20
3-1754408-9	38.610 - 39.390	126.67 - 129.23	0.56	20	0.56	20
4-1754408-0	39.600 - 40.400	129.92 - 132.54	0.56	20	0.56	20
5-1754408-0	49.500 - 50.500	162.40 - 165.68	0.58	20	0.58	20

Qty	U of M	Description	Item No.
1	piece	HOUSING, CONN, MT-RJ,BLACK	1
2	piece	DUST COVER, MT-RJ	2
2	piece	SPRING, MT-RJ, 3.8 DESIGN	3
2	piece	PIN KEEPER, 3.8MM	4
2	piece	MT-RJ, SPRING PUSH, UNIVERSAL	5
2	piece	CRIMP EYELET, MT-RJ	6
1	piece	MT-RJ Keyed Connector Housing - Green	7
2	piece	MT-RJ FERRULE, THERMOPLAST,MM	8
AR	meter	2 fiber, XG-50/125, 1.8mm, Twinzip, Aqua, OFNR (Riser)	9
2	piece	MT-RJ TwinZip Bend Limiting Boot, Beige	10
2	piece	Trace Label	11

DWG NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND MAY NOT BE REPRODUCED, USED OR DISCLOSED EXCEPT AS AUTHORIZED BY TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

LOC CE

DIST 16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A	Rev Per EC# RELEASE	8/7/2006	-	MK

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ±

Customer Print

DWN: Cable Assy Configurator
CHK: Michael Kepko
APVD: Michael Kepko
MATERIAL: -
HEAT TREAT: -

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

NAME: FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, MT-RJ (No Pins) to MT-RJ SECURE (No Pins)

SCALE: NTS | SIZE: A2 | DRAWING NO: C- 1754408 | SHEET: 2 of 3 | REV: A

8 7 6 5 4 3 2 1

D C B A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWG NO

Restricted to: General Release

USED ON

Label 1 Per specification 107-1645-1



This label is used on all lengths on this drawing.

Label 2 Per specification 107-1645-1



This label is used on all lengths on this drawing.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND IS NOT TO BE DISCLOSED TO ANY OTHER PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE REPRODUCED, IN WHOLE OR IN PART, OR USED FOR MANUFACTURING ANYWHERE IN THE WORLD, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

LOC CE

DIST 16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
A		Rev Per EC# RELEASE	8/7/2006	-	MK

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Customer Print

DWN Cable Assy Configurator

CHK Michael Kepko

APVD Michael Kepko

MATERIAL -

HEAT TREAT -

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

NAME FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, MT-RJ (No Pins) to MT-RJ SECURE (No Pins)

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 1754408	3 of 3	A

8 7 6 5 4 3 2 1

D C B A


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.