


PRODUCT NR:	ROW#	CONFIGURATION 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	DIM A	PCB THICKNESS
85869-X01	D	X	X	X	–	–	–	X	X	X	X	–	–	X	X	X	X	X	X	–	–	X	X	X	X	2.90	1.6
85869-X01LF	C	X	X	X	–	–	X	X	X	X	X	X	–	X	X	X	X	X	X	X	–	X	X	X	X		
	B	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	A	X	X	X	–	–	X	X	X	X	X	X	–	X	X	X	X	X	X	X	–	X	X	X	X		
85869-X02	D	X	X	–	X	X	–	X	X	–	–	X	X	–	X	X	–	X	X	X	X	X	X	X	X	2.90	1.6
85869-X02LF	C	X	X	–	X	X	–	X	X	–	–	X	X	–	X	X	–	X	X	X	X	X	X	X	X		
	B	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	X	X	X	X	X	X	X	X		
	A	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	–	X	X	X	X	X	X	X	X		
85869-X03	D	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X03LF	C	X	–	–	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X		
	A	X	–	X	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
85869-X04	D	–	X	–	X	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X04LF	C	X	–	–	X	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X		
	A	X	–	X	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
85869-X05	D	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X05LF	C	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	A	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		

"–" POSITION NOT LOADED
"X" POSITION LOADED


PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
–1YY/1YYLF	TELCORDIA CO
–2YY/2YYLF	CUSTOMER SPECIAL
–3YY/3YYLF	CUSTOMER SPECIAL








PRODUCT AFTER PC BOARD APPLICATION.



NOTES:
1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 um SnPb 90-97, OR 2-8 um PURE Sn FOR PART NUMBER WITH LF SUFFIX.
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PART NUMBER & BATCH ID.
6 DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.
7 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
8 THE HOUSING WILL WITHSTAND EXPOSURE TO 260 DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.



RECOMMENDED HOLE PATTERN, COMPONENT SIDE.

mat'l. code SEE NOTES				tolerances unless otherwise specified				CUSTOMER COPY	FCI www.fciconnect.com
ltr	ecn no	dr	date						
R	DG09-0068	Cenh	06/06/09	linear				projection	title: RA RECEPTACLE SIG48mm PRESS PEG
K	DG06-0478	Cenh	11/23/06	angles					
L	DG07-0230	Cenh	05/30/07	dr	R VISSCHERS	951017		mm	product family METRAL(tm) / code
M	DG07-0232	Cenh	05/31/07	engr	P SCHALK	951017			size dwg no / 213
N	DG07-0169	Cenh	6/08/07	chn	P SCHALK	951017		scale 5:1	A2 85869 / sheet 1 of 3
P	DG08-0171	TER	8/26/08	appd	P SCHALK	951017			
sheet	revision	R	R	R					
index	sheet	1	2	3					

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. @ F C I b.v.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. @ F C I b.v.


form A2


PDM: Rev:R STATUS: Released Printed: May 19, 2011


PRODUCT NR:	ROW#	CONFIGURATION 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	DIM A	PCB THICKNESS
85869-X20	D	X	X	X	–	–	–	X	X	X	X	–	–	X	X	X	X	X	X	–	–	X	X	X	X	2.90	1.6
85869-X20LF	C	X	X	X	–	–	X	X	X	X	X	X	–	X	X	X	X	X	X	X	–	X	X	X	X		
	B	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	A	X	X	X	–	–	X	X	X	X	X	X	–	X	X	X	X	X	X	X	–	X	X	X	X		
85869-X21	D	X	X	–	X	X	–	X	X	–	–	X	X	–	X	X	–	X	X	X	X	X	X	X	X	2.90	1.6
85869-X21LF	C	X	X	–	X	X	–	X	X	–	–	X	X	–	X	X	–	X	X	X	X	X	X	X	X		
	B	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	X	X	X	X	X	X	X	X		
	A	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	–	X	X	X	X	X	X	X	X		
85869-X22	D	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X22LF	C	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X	–		
	B	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X		
	A	X	–	X	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
85869-X23	D	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X23LF	C	X	–	–	X	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X		
	A	X	–	X	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
85869-X24	D	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X24LF	C	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	A	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
85869-X25	D	X	X	–	–	X	X	–	–	X	X	–	–	–	–	X	X	X	X	X	X	X	X	X	X	2.90	1.6
85869-X25LF	C	X	X	–	–	X	X	–	–	X	X	–	–	–	–	X	X	X	X	X	X	X	X	X	X		
	B	X	X	–	–	X	X	–	–	X	X	–	–	–	–	X	X	X	X	X	X	X	X	X	X		
	A	X	X	–	–	X	X	–	–	X	X	–	–	–	–	X	X	X	X	X	X	X	X	X	X		


PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
–1YY/1YYLF	TELCORDIA CO
–2YY/2YYLF	CUSTOMER SPECIAL
–3YY/3YYLF	CUSTOMER SPECIAL

"–" POSITION NOT LOADED
"X" POSITION LOADED











PRODUCT AFTER PC BOARD APPLICATION.



NOTES:
1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 um SnPb 90-97. OR 2-8 um PURE Sn FOR PART NUMBER WITH LF SUFFIX.
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PART NUMBER & BATCH ID.
6 SET BACK FOR PRESS BLOCK
7 DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.
8 TOP SURFACE OF PRESS BLOCK MAY EXTEND UP TO 0.4MM HIGHER THAN HOUSING. THIS MAY AFFECT THE TAIL LENGTH BEFORE APPLICATION TO A BOARD.
9 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
10 THE HOUSING WILL WITHSTAND EXPOSURE TO 245 DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.



RECOMMENDED HOLE PATTERN, COMPONENT SIDE.

mat'l. code SEE NOTES				tolerances unless otherwise specified				CUSTOMER COPY	www.fciconnect.com
ltr	ecn no	dr	date	linear				projection	title: RA RECEPTACLE SIG48mm PRESS PEG
R				angles					
				dr	H. Mengede	990525		mm	product family METRAL(tm) code
				engr	M. Loman	990525			size dwg no 213
				chr	M. Loman	990525		scale 5:1	A2 85869 sheet 2 of-
				appd	M. Loman	990525			
sheet index	revision sheet								

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. @ F C I b.v.
All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. @ F C I b.v.


form A2


PDM: Rev:R STATUS: Released Printed: May 19, 2011

PRODUCT NR:	ROW#	CONFIGURATION 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	DIM A	PCB THICKNESS
85869-X30	D	X	X	X	–	–	–	X	X	X	X	–	–	X	X	X	X	X	X	X	–	X	X	X	X	2.90	1.6
85869-X30LF	C	X	X	X	–	–	X	X	X	X	X	X	–	X	X	X	X	X	X	X	–	X	X	X	X		
	B	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	A	X	X	X	–	–	X	X	X	X	X	X	–	X	X	X	X	X	X	X	–	X	X	X	X		
85869-X31	D	X	X	–	X	X	–	X	X	–	–	X	X	–	X	X	–	X	X	X	X	X	X	X	X	2.90	1.6
85869-X31LF	C	X	X	–	X	X	–	X	X	–	–	X	X	–	X	X	–	X	X	X	X	X	X	X	X		
	B	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	X	X	X	X	X	X	X	X		
	A	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	–	X	X	X	X	X	X	X	X		
85869-X32	D	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X32LF	C	X	–	–	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X		
	A	X	–	X	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
85869-X33	D	–	X	–	X	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X33LF	C	X	–	–	X	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	–	X	–	–	–	X	–	X	–	–	–	X	–	X	X	X	–	X	–	X	–	X	–	X		
	A	X	–	X	–	X	–	–	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
85869-X34	D	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	2.90	1.6
85869-X34LF	C	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–	X	–		
	B	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	A	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		


"–" POSITION NOT LOADED
"X" POSITION LOADED


PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
–1YY/1YYLF	TELCORDIA CO
–2YY/2YYLF	CUSTOMER SPECIAL
–3YY/3YYLF	CUSTOMER SPECIAL






PRODUCT AFTER PC BOARD APPLICATION.







RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.

NOTES:
1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 um SnPb 90-97. OR 2-8 um PURE Sn FOR PART NUMBER WITH LF SUFFIX.
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PART NUMBER & BATCH ID.
6 DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.
7 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
8 THE HOUSING WILL WITHSTAND EXPOSURE TO 260 DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.

mat'l. code SEE NOTES	tolerances unless otherwise specified	CUSTOMER COPY	www.fciconnect.com
ltr ecn no dr date: R	linear	projection	title: RA RECEPTACLE SIG48mm PRESS PEG
	angles		
	dr Heaven Cen 11/23/06	mm	product family METRAL(tm) code
	engr Collins Lu 11/23/06		size dwg no 213
	chr Beer Fu 11/23/06	scale 5:1	A2 85869 sheet 3 of-
	appd Joseph Hsia 11/23/06		
sheet revision / index sheet			

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. ©F C I b.v.
All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. ©F C I b.v.

PDM: Rev:R STATUS: Released Printed: May 19, 2011


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.