



P.C.B LAYOUT (Top View)

SIGN	DATE	DESCRIPTION	APPROVER
△	10 / 31'08	Temperature changed from -40°C ~ +105°C to -40°C ~ +115°C	Kind
△	10 / 31'08	Screw Torque Value changed from 6.0kgf.cm to 8.6kgf.cm	Kind
△	10 / 31'08	Screw sort changed from M3.0 to #5-40.	Kind
△	04 / 30'09	Screw Torque Value changed from 8.6kgf.cm to 5.2lb-in	Eris
△	04 / 30'09	approved cULus	Eris
△	05 / 04'09	Structure changed	Eris
△	05 / 04'09	Dimension allowance	Eris
△	11 / 21'12	Change the screw plating specification	Jacky
△	11 / 21'12	Change the dimensional tolerance	Jacky
△	04 / 20'13	Update the drawing	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:	300V, 15 A
WITHSTAND VOLTAGE:	AC 2000 V/Min
INSULATION RESISTANCE:	1000 MΩ OR MORE AT DC 500 V
△ OPERATING TEMPERATURE RANG:	-40 °C ~ +115 °C
△ △ SCREW TORQUE VALUE:	5.2 Lb-In
WIRE RANGE:	22 - 14 AWG
1) MOLDED PARTS:	THERMOPLASTIC, UL 94 V-0 BLACK
2) TERMINAL:	BRASS, 0.8t, Tin PLATED
△ △ 3) TERMINAL SCREWS:	STEEL, #5-40
△ Safety Approval:	cULus

PART NO.:
Critical dimension: ▽

YK 321 xx 0 x x 00G

NO. OF POLES
02: 2 POLES
03: 3 POLES
04: 4 POLES
...
30: 30 POLES

G:RoHS compliant(lead<4%)
in copper alloy

MARK
0: "@" MARK
1: "ANY" MARK

TERMINAL & SCREW PLATED

0: TERMINAL & SCREW: G/F
△ 1: TERMINAL: G/F, SCREW: Zinc
2: TERMINAL: Sn, SCREW: G/F
△ 3: TERMINAL: Sn, SCREW: Zinc
4: TERMINAL: Sn, SCREW: Blue Zn

N= Number of poles △

DIM		TOL		
		2P-4P	5P-21P	22P-30P
△ Dim A	(N-1)×7.62+8.48	±0.20	±0.30	±0.50
Dim B	(N-1)×7.62	±0.20	±0.30	±0.50

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK-321 W/O Flange Series				DWG NO.		8YK0001-321	
PART NO.		YK321xx0xx00G				DWG NO.		8YK0001-321	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
			Jacky 2013.04.20	Jacky 2013.04.20			UNIT: mm	X.	±0.50
							SCALE: NONE	X.X	±0.30
					SHEET: 01/01		REV: G	X.XX	±0.10
								X°	±1°



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.