

For more Information  
please call

1-800-Belden1



### Description:

22 AWG stranded (7x30) tinned copper conductors, Datalene® insulation, twisted pairs, overall Beldfoil® shield (100% coverage) plus a tinned copper braid (65% coverage), drain wire, UV resistant PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	1	22	7x30	TC - Tinned Copper	.030

Total Number of Conductors: 3

#### Insulation

##### Insulation Material:

Insulation Trade Name	Insulation Material
Datalene®	FHDPE - Foam High Density Polyethylene

#### Outer Shield

##### Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000
2		Braid	TC - Tinned Copper	65.000

##### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Outer Shield Drain Wire Diameter: .030

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

##### Overall Cabling Color Code Chart:

Number	Color
1	White/Orange Stripe
2	Orange/White Stripe
3	Blue/White Stripe

Overall Nominal Diameter: 0.300 in.

#### Pair

##### Pair Lay Length & Direction:

Lay Length (in.)
3.000

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Non-UL Temperature Rating: 60°C

Bulk Cable Weight: 48 lbs/1000 ft.

Max. Recommended Pulling Tension:	65 lbs.
Min. Bend Radius/Minor Axis:	3 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

CEC/C(UL) Specification:	CM
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	UL1685 UL Loading
CSA Flame Test:	FT1

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Surface Printing (Overall)

## Electrical Characteristics (Overall)

### Nom. Inductance:

Inductance (µH/ft)
.203

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
11.0

### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
20.9

### Nominal Velocity of Propagation:

VP (%)
78

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
14.7

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.8

### Nom. Attenuation:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100 ft.)
	1			.5

### Max. Operating Voltage - UL:

Voltage
300 V RMS

### Max. Recommended Current:

Current
2.7 Amps per conductor @ 25°C

## 3106A Multi-Conductor - EIA Industrial RS-485 PLTC/CM

### Input/Unfitted Impedance:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Impedance (Ohm)
	1			120

### Notes (Overall)

**Notes:** Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order YR46721.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3106A 0101000	1,000 FT	47.000 LB	BLACK	C	#22 FS PR,1#22PVCBRDPVC
3106A 010500	500 FT	25.000 LB	BLACK	C	#22 FS PR,1#22PVCBRDPVC
3106A 0105000	5,000 FT	230.000 LB	BLACK	C N	#22 FS PR,1#22PVCBRDPVC

**Notes:**

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 1    Revision Date: 12-05-2008

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.