



## 44000RC SERIES

### Precision Epoxy NTC Thermistors

Interchangeable Thermistors – TE Connectivity (TE) provides highly accurate and stable temperature sensing for measurement, control, indication and compensation. The tight interchangeability of our precision components allows precise measurement without calibration of circuitry to match individual components.

TE offers two interchangeability tolerances  $\pm 0.2^{\circ}\text{C}$  and  $\pm 0.1^{\circ}\text{C}$ . Choose epoxy-encapsulated components for applications where cost, flexibility and a wide range of resistance values are important.

#### Specifications

##### Time Constant

1 sec max when suspended by their leads in a well-stirred oil bath. In still air, 10 sec max.

##### Dissipation Constant

8mW/ $^{\circ}\text{C}$  min when suspended by their leads in a well-stirred oil bath, or 1mW/ $^{\circ}\text{C}$  in still air.

##### Stability

TE thermistors are chemically stable and not significantly affected by aging or exposure to strong nuclear radiation.

##### Resistance/Temperature Data

A  $^{\circ}\text{C}$  resistance vs temperature table in  $1^{\circ}\text{C}$  increments is available on [www.te.com](http://www.te.com).

##### Interchangeability Tolerance Data

Tables on [www.te.com](http://www.te.com) show nominal resistance values, ohms per degree and tolerance at select temperatures over the operating range.

##### Maximum Power

30mW at  $25^{\circ}\text{C}$  de-rated to zero power at  $125^{\circ}\text{C}$

#### Features

- ♦ High sensitivity to detect small temperature changes
- ♦ High density ceramic sensor provides:
  - Stability
  - $\pm 0.2^{\circ}$ ,  $\pm 0.1^{\circ}$  interchangeability

#### Applications

- ♦ Temperature control for DNA replication/analysis and cytology equipment
- ♦ Temperature control in photocopier machines and in photo reproduction and enlargement machines
- ♦ Temperature monitoring for telecommunications battery backup systems
- ♦ Temperature monitoring and control in clean rooms/controlled environments
- ♦ Temperature monitoring on the ocean floor
- ♦ Heater monitor/control for outdoor pool/spa
- ♦ Temperature monitoring for fruit growers

**Mechanical Details**



**Performance Specifications**

|                | Tolerance on Beta Value | Time Response in Air | Dissipation Constant in Air | Insulation Resistance (Min. of 100Mohms for 1 Sec.) |       |
|----------------|-------------------------|----------------------|-----------------------------|---|-------|
|                | %                       | Seconds              | mW/°C                       | Volts   |       |
| <b>44001RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44002RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44003RC</b> | 1.0                     | < 10                 | 1                           | 500   |       |
| <b>44004RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44005RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44007RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44016RC</b> | 0.8                     | < 10                 | 1                           | 1   | 500 1 |
| <b>44006RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44008RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44011RC</b> | 0.8                     | < 10                 | 1                           | 500   |       |
| <b>44033RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |
| <b>44030RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |
| <b>44034RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |
| <b>44036RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |
| <b>44037RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |
| <b>44031RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |
| <b>44032RC</b> | 0.4                     | < 10                 | 1                           | 500   |       |

**Ordering Information**

| Parameters                                       | Ordering Part Number | Model Number | Zero Power Resistance | Beta 0-50(K) | Ratio 25/125° | Max Working Temp. | Best Storage & Working Temp. | Mix |
|--|----------------------|--------------|-----------------------|--------------|---------------|-------------------|------------------------------|-----|
| ±0.2°C Interchangeability<br>Tolerance 0 to 70°C | 701001-M             | 44001RC      | 100                   | 2854         | 11.49         | 100°C             | -80°C to 50°C                | L   |
|  | 701002               | 44002RC      | 300                   | 3118         | 15.15         | 100°C             | -80°C to 50°C                | L   |
|  | 701003-M             | 44003RC      | 1,000                 | 3217         | 17.33         | 100°C             | -80°C to 50°C                | L   |
|  | 701004               | 44004RC      | 2,252                 | 3891         | 29.26         | 150°C             | -80°C to 120°C               | B   |
|  | 701005-M             | 44005RC      | 3,000                 | 3891         | 29.26         | 150°C             | -80°C to 120°C               | B   |
|  | 701007-M             | 44007RC      | 5,000                 | 3891         | 29.26         | 150°C             | -80°C to 120°C               | B   |
|  | 701016-M             | 44016RC      | 10,000                | 3891         | 29.26         | 150°C             | -80°C to 120°C               | B   |
|  | 701006               | 44006RC      | 10,000                | 3574         | 23.51         | 150°C             | -80°C to 120°C               | B   |
|  | 701008-M             | 44008RC      | 30,000                | 3810         | 29.15         | 150°C             | -80°C to 120°C               | B   |
|  | 701011-M             | 44011RC      | 100,000               | 3988         | 34.82         | 150°C             | -80°C to 120°C               | B   |
| ±0.1°C Interchangeability<br>Tolerance 0 to 70°C | 701033               | 44033RC      | 2,252                 | 3891         | 29.26         | 75°C              | -80°C to 75°C                | B   |
|  | 701030-M             | 44030RC      | 3,000                 | 3891         | 29.26         | 75°C              | -80°C to 75°C                | B   |
|  | 701034-M             | 44034RC      | 5,000                 | 3891         | 29.26         | 75°C              | -80°C to 75°C                | B   |
|  | 701036-M             | 44036RC      | 10,000                | 3891         | 29.26         | 75°C              | -80°C to 75°C                | B   |
|  | 701037-M             | 44037RC      | 6,000                 | 3891         | 29.26         | 75°C              | -80°C to 75°C                | B   |
|  | 701031-M             | 44031RC      | 10,000                | 3574         | 23.51         | 75°C              | -80°C to 75°C                | H   |
|  | 701032               | 44032RC      | 30,000                | 3810         | 29.15         | 75°C              | -80°C to 75°C                | H   |

**NORTH AMERICA**

Measurement Specialties, Inc.,  
a TE Connectivity Company  
Tel: 800-522-6752  
[customercare.ando@te.com](mailto:customercare.ando@te.com)

**te.com/sensorsolutions**

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.