



# ETA-USA

## HIGH QUALITY SWITCHING POWER SUPPLIES

AC/DC MEDICAL GRADE  
SWITCHING DESKTOP ADAPTER  
POWER SUPPLY WITH PFC  
SINGLE OUTPUT / UNIVERSAL RANGE INPUT  
250 WATTS

### MTE250-SX-W-C2 Series



Dimension: L188.5×W104.5×H60mm



#### General Description

#### Features

#### Input

<b>Input Voltage Range:</b>	90-264VAC
<b>Frequency:</b>	47-63Hz
<b>Input Current (rms):</b>	3.5A @ 90Vac; 1.7A @ 264Vac max.
<b>Inrush current:</b>	<65A peak @115VAC, <130A peak at 230VAC cold start at 25°C
<b>Power Factor:</b>	>0.95 (115VAC100%Load) >0.9 (230VAC full load)
<b>Efficiency :</b>	>87% @ full load, 115VAC/230VAC

1. Built-in DC fan with speed control (40x40x10mm)
2. Earth leakage current <228uA @264VAC
3. 3-pole IEC320-14 AC inlet
4. Fully meets CEC, ERP, EISA efficiency level V requirements
5. 2 year warranty
6. Green functions+ No load power consumption <.3 W





# ETA-USA

## HIGH QUALITY SWITCHING POWER SUPPLIES

Environmental Specification	
Operating Temperature	0 to +60°C (derate linearly 2.5% / °C from 41 to 60°C)
Storage Temperature	-20 to +85°C
MTBF demonstrated	>140,000 hours at full load and 25 °C ambient temperature
Humidity	10%~95%
Environmental Agencies	
Safety Standards	UL 60601 -1 3 <sup>rd</sup> ed CSA 22.2-No.60601-1 3 <sup>rd</sup> ed TUV EN60601-1 3 <sup>rd</sup> ed IEC 60601-1 3 <sup>rd</sup> ed
EMC Standards	FCC PART 18 Class B, EN60601-1-2, CE, EN55011 CLASS B
Protection	
Short circuit protection	Auto Recover
Over Load Protection	Auto Recover
Over Voltage Protection	LATCH, AC Recycle
Mechanical	
Dimension [mm]: L188.5×W104.5×H60mm	
Weight: 1005 grams	
AC Input : IEC 320-C14	


Output Characteristic	Unit	Models						
		MTE250-12SX-F-W-C2	MTE250-16SX-F-W-C2	MTE250-19SX-F-W-C2	MTE250-20SX-F-W-C2	MTE250-24SX-F-W-C2	MTE250-36SX-F-W-C2	MTE250-48SX-F-W-C2
Output Voltage	Vdc	12	16	19	20	24	36	48
Output Current	A	20.83	15.63	13.16	12.5	10.42	6.94	5.21
Power	W	250						
O/P Regulation		±5%						
Ripple & Noise(max)*3	mVpp	240	300	300	300	300	300	300
Rise up time	mS	>16ms typical at full load @ 115VAC						
* Peak-to-peak with 20MHz bandwidth with a tantalum 10uF in parallel with a 0.1uF ceramic capacitor.								





# ETA-USA


HIGH QUALITY SWITCHING POWER SUPPLIES





# ETA-USA

## HIGH QUALITY SWITCHING POWER SUPPLIES



ETA USA  
16170 Vineyard Blvd. Suite 180, Morgan Hill, CA 95037  
Phone: 1-800-ETA-POWR, (408) 778-2793 Fax: (408) 779-2753

Visit us at: [www.eta-usa.com](http://www.eta-usa.com)  
email at: [sales@eta-usa.com](mailto:sales@eta-usa.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.