



## 3-Channel EMI-Filter with ESD-Protection




19423



20517

1

### MARKING (example only)



21001

Dot = pin 1 marking

YY = type code (see table below)

XX = date code

### FEATURES

- Ultra compact LLP75-7L package
- 3-channel EMI-filter and ESD-protection
- Low leakage current
- Line resistance  $R_S = 30 \Omega$
- Typical cut off frequency  $f_{3dB} = 100 \text{ MHz}$
- ESD-protection acc. IEC 61000-4-2  
 $\pm 30 \text{ kV}$  contact discharge  
 $\pm 30 \text{ kV}$  air discharge
- e4 - precious metal (e.g. Ag, Au, NiPd, NiPdAu) (no Sn)
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



### ORDERING INFORMATION

| DEVICE NAME  | ORDERING CODE     | TAPED UNITS PER REEL<br>(8 mm TAPE ON 7" REEL) | MINIMUM ORDER QUANTITY |
|--------------|-------------------|--|------------------------|
| VEMI353A-HAF | VEMI353A-HAF-G-08 | 3000   | 15 000                 |

### PACKAGE DATA

| DEVICE NAME  | PACKAGE NAME | TYPE CODE | WEIGHT | MOLDING COMPOUND<br>FLAMMABILITY RATING | MOISTURE SENSITIVITY LEVEL           | SOLDERING CONDITIONS     |
|--------------|--------------|-----------|--------|---|--------------------------------------|--------------------------|
| VEMI353A-HAF | LLP75-7L     | 9D        | 4.2 mg | UL 94 V-0                               | MSL level 1<br>(according J-STD-020) | 260 °C/10 s at terminals |


### ABSOLUTE MAXIMUM RATINGS

| PARAMETER             | TEST CONDITIONS   | SYMBOL    | VALUE         | UNIT |
|-----------------------|---|-----------|---------------|------|
| Peak pulse current    | All I/O pin to pin 7; acc. IEC 61000-4-5;<br>$t_p = 8/20 \mu\text{s}$ ; single shot | $I_{PPM}$ | 4             | A    |
| ESD immunity          | Contact discharge acc. IEC61000-4-2; 10 pulses                                      | $V_{ESD}$ | $\pm 30$      | kV   |
|                       | Air discharge acc. IEC61000-4-2; 10 pulses  |           | $\pm 30$      |      |
| Operating temperature | Junction temperature  | $T_J$     | - 40 to + 125 | °C   |
| Storage temperature   |   | $T_{STG}$ | - 55 to + 150 | °C   |


\*\* Please see document "Vishay Material Category Policy": [www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)

## APPLICATION NOTE


With the VEMI353A-HAF 3 different signal or data lines can be filtered and clamped to ground. Due to the different clamping levels in forward and reverse direction the clamping behavior is Bidirectional and Asymmetric (BiAs).



19424



19420




19421

The 3 independent EMI-filter are placed between

- pin 1 and pin 6
- pin 2 and pin 5, and
- pin 3 and pin 4.

They all are connected to a common ground pin 7 on the backside of the package. Each filter is symmetrical so that all ports (pin 1 to 6) can be used as input or output.

The circuit diagram of one EMI-filter-channel shows two identical Z-diodes at the input to ground and the output to ground. These Z-diodes are characterized by the breakthrough voltage level ( $V_{BR}$ ) and the diode capacitance ( $C_D$ ). Below the breakthrough voltage level the Z-diodes can be considered as capacitors. Together with these capacitors and the line resistance  $R_S$  between input and output the device works as a low pass filter. Low frequency signals ( $f < f_{3dB}$ ) pass the filter while high frequency signals ( $f > f_{3dB}$ ) will be shorted to ground through the diode capacitances  $C_D$ .



21060

Each filter is symmetrical so that both ports can be used as input or output.

| <b>ELECTRICAL CHARACTERISTICS VEMI353A-HAF</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |               |       |      |      |               |
|---|--|---------------|-------|------|------|---------------|
| PARAMETER   | TEST CONDITIONS/REMARKS  | SYMBOL        | MIN.  | TYP. | MAX. | UNIT          |
| Protection paths  | Number of channels which can be protected  | $N_{channel}$ | -     | -    | 3    | channel       |
| Reverse stand off voltage   | at $I_R = 1\text{ }\mu\text{A}$ each input to pin 2  | $V_{RWM}$     | 5     | -    | -    | V             |
| Reverse current   | at $V_R = 5\text{ V}$ each input to pin 2  | $I_R$         | -     | -    | 1    | $\mu\text{A}$ |
| Reverse break down voltage  | Each input to pin 2 at $I_R = 1\text{ mA}$   | $V_{BR}$      | 6     | -    | -    | V             |
| Pos. clamping voltage   | at $I_{PP} = 1\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5            | $V_{C-out}$   | -     | -    | 7.8  | V             |
|   | at $I_{PP} = I_{PPM} = 4\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5  | $V_{C-out}$   | -     | -    | 8    | V             |
| Neg. clamping voltage   | at $I_{PP} = -1\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5           | $V_{C-out}$   | - 1   | -    | -    | V             |
|   | at $I_{PP} = I_{PPM} = -4\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5 | $V_{C-out}$   | - 1.2 | -    | -    | V             |
| Input capacitance   | at $V_R = 0\text{ V}$ ; $f = 1\text{ MHz}$   | $C_{IN}$      | -     | 60   | -    | pF            |
|   | at $V_R = 2.5\text{ V}$ ; $f = 1\text{ MHz}$   | $C_{IN}$      | -     | 37   | -    | pF            |
| ESD-clamping voltage  | at $\pm 30\text{ kV}$ ESD-pulse acc. IEC 61000-4-2   | $V_{CESD}$    | -     | 7.5  | -    | V             |
| Line resistance   | Measured between input and output;<br>$I_S = 10\text{ mA}$   | $R_S$         | 27    | 30   | 35   | $\Omega$      |
| Cut-off frequency   | $V_{IN} = 0\text{ V}$ ; measured in a $50\text{ }\Omega$ system                                      | $f_{3dB}$     | -     | 100  | -    | MHz           |

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - ESD Discharge Current Wave Form  
acc. IEC 61000-4-2 (330  $\Omega$ /150 pF)




Fig. 2 - 8/20  $\mu\text{s}$  Peak Pulse Current Wave Form  
acc. IEC 61000-4-5




Fig. 3 - Typical Forward Current  $I_F$  vs. Forward Voltage  $V_F$




Fig. 6 - Typical Capacitance  $C_D$  vs. Reverse Voltage  $V_R$




Fig. 4 - Typical Input Voltage  $V_{IN}$  vs. Input Current  $I_{IN}$




Fig. 7 - Typical Small Signal Transmission ( $S_{21}$ ) at  $Z_O = 50 \Omega$





Fig. 5 - Typical Peak Clamping Voltage  $V_C$  vs. Peak Pulse Current  $I_{PP}$

**PACKAGE DIMENSIONS** in millimeters (inches): **LLP75-7L**


Document no.:S8-V-3906.02-014 (4)  
 Created - Date: 04. April 2006  
 20500



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.