



## Dell Embedded Box PC 3000 and 5000 Series



### Dell Embedded Box PC 3000 and 5000 Series

Speed your solutions to market with quality, reliable embedded box PCs delivered in weeks, not months

#### An underserved embedded industry

Do you need reliable embedded PCs, delivered quickly? Some embedded vendors substitute cheaper, unreliable components that can cause expensive downtime and impact your business reputation. Or they provide highly complex systems, difficult to aggregate. Some offer no scalability from small to large quantities, only high volume discounts. Lead times are typically measured in months or quarters, with only basic hardware warranties and no certifications of the device.

#### Addressing the industrial PC market

Dell now brings to embedded computers (also called industrial PCs) new ruggedized devices, Internet of Things (IoT)-ready, with broad connectivity and backed by Dell's brand and proven heritage of business benefits:

- Delivery in weeks at effective price points, with a configure-to-order approach — for orders of one, small batches or large volumes
- Commercial quality standards for Dell products and suppliers to reduce risk and improve reliability
- Enterprise-grade security and manageability options, to improve protection and flexibility
- Global service and support, with five-year support program options, so you have peace of mind
- Flexible payment options designed to help you acquire the total solution.<sup>1</sup>

#### Ruggedized and ready to commission

Dell Embedded Box PC 3000 and 5000 are designed to MIL-STD-810G standards, building on the expertise of our ruggedized device engineers. They are meant to be used 24x7x365 for a long planned life, headless or with keyboard, mouse and monitor. Dell Embedded Box PCs are ruggedized, fanless, highly reliable devices for a variety of use cases, including process and discrete manufacturing, fleet management, kiosks, digital signage, surveillance and automated retail solutions. Flexible, with many input/output (I/O) options, they run on powerful multi-core Intel® processors. PCI/PCIe card slots provide flexible

expansion for new I/O and graphics capabilities. Form factors are optimized for VESA, DIN-rail and wall mounting and they come with regulatory, mobile, broadband and Wi-Fi certifications complete for many countries.

#### Right quantities

At Dell, we offer good price points on minimum order quantities of one, small batches and essentially no volume too big for our global organization. Our fully configured systems in stock deliver in weeks, not months. No need to order and store large quantities, so you lower costs of carried inventory and have less risk of technology obsolescence.

#### Quality and reliability

Lost availability can cause expensive downtime. Dell delivers reliability with stringent process and leading validation practices on our embedded PCs. Our advanced product reliability engineering occurs at all levels of the product prior to release and with rigorous requirements for our suppliers as well. With Dell as your OEM, you can be confident your own solutions support your brand.

#### End-to-End Support

With the Dell Embedded Box PC, you also get an end-to-end service solution, including Dell Deployment Services and Dell Basic Hardware Warranty that can be extended up to 5 years. Dell ProSupport with options up to 5 years are available. The Dell services solution helps your business streamline deployment and support so you can focus on innovation.

#### Flexible branding options and OEM

An OEM-Ready version of the Embedded PCs is available. From bezel to BIOS to packaging, your Embedded PCs can look and feel as if they were designed and built by you. Contact your account team for details on options, like additional memory, storage and embedded or other operating systems. Also visit [Dell.com/OEM](http://Dell.com/OEM).

# Technical Specifications

Model Number <sup>1</sup>	Dell Embedded Box PC 3000		Dell Embedded Box PC 5000	
<b>Dimensions</b>	237 mm wide x 160 mm high x 60 mm deep (9.5 x 6.5 x 2.5 inches)		246 mm wide x 270 mm high x 107 mm deep (9.5 x 10.5 x 4.2 inches)	
<b>Form Factor</b>	Fanless design, optimized for wall, DIN-rail and VESA mounting			
<b>Weight</b>	Minimum 2.1 Kg; Maximum 2.25 Kg		Minimum 5.5 Kg; Maximum 5.8 Kg	
<b>Processor</b>	Intel® Atom™ E3825 1.33GHz   2 cores	Intel® Atom™ E3827 1.75GHz   2 cores	Intel® Celeron® G3900E 2.4GHz   2 cores	Intel® Core i3-6100E 2.7GHz   2 cores
	Intel® Atom™ E3845 1.91GHz   4 cores		Intel® Core i5-6440EQ <sup>2</sup> up to 3.4GHz   4 cores	Intel® Core i7-6820EQ <sup>2</sup> up to 3.4GHz   4 cores
<b>Operating systems</b>	Factory options for Ubuntu Desktop 16.04. Win7 Pro (via Win 10 Pro downgrade license), Win7 Pro for Embedded Systems (FES7), Win10 Pro, Win10 IoT Enterprise 2015 LTSB, Win Standard Embedded 7 (WES7P & WES7E). Dell OEM may offer additional OSes.			
<b>Memory</b>	DDR3L type @ 1600MHz: 4GB (1x4GB) or 8GB (1x8GB)		DDR4 type @2133MHz: 4GB (1x4GB), 8GB (2x4GB or 1x8GB), 16GB (2x8GB) or 32GB (2x16GB)	
<b>Drive/Storage</b>	Options: 1x SSD or 1x HDD. SSD is 32 GB, 64 GB, 128 GB or 256 GB. Client SATA HDD is 500 GB or 1 TB. (Drive affects temperature.)		Options: 2x SSD or 2x HDD or 1x SSD + 1x HDD. SSD is 32 GB, 64 GB, 128 GB or 256GB. Client SATA HDD is 500 GB or 1 TB. (Drive affects temperature.)	
<b>I/O</b>	Dual Gigabit Ethernet: 2 x RJ-45. USB: 4 x USB2, 1 x USB3. Serial interfaces: 2 x RS-232/485; 1 x RS-232/422 via multifunction port; set by BIOS. GPIO: 12 bit (via multi-function port). Wireless: Wi-Fi IEEE 802.11n +Bluetooth LE; Mobile Broadband/WWAN (3G or LTE). Options: ZigBee module, CAN bus card, Bluetooth option via WLAN. (Limited to 2 out of 3: WWAN, WLAN or CAN bus)		Dual Gigabit Ethernet: 2 x RJ-45. USB: 4 x USB2, 4 x USB3. Serial Interfaces: 4 x RS-232/422/485 (set by BIOS). GPIO: 16-bit. Wireless: Wi-Fi IEEE 802.11n +Bluetooth LE; Mobile Broadband/WWAN (3G or LTE). Options: ZigBee module, CAN bus card, Bluetooth option via WLAN, Parallel via PCIe card. (Limited to 2 out of 3: WWAN, WLAN or CAN bus)	
<b>Expansion</b>	None		2 PCI/PCIe slots: riser card options: 2 x PCI, 1 x PCI + 1 x PCIe x 16 or 2 PCIe x8.	
<b>Video</b>	2 simultaneous displays: 1 x DP++ 1.1, VGA. Resolution: Max DP++ 4096x2304; max VGA 2560x1080@60Hz.		3 simultaneous displays: 2 x DP++ 1.2, HDMI 1.4, VGA. Resolution: Max DP++ 4096x2304; max HDMI 4096x2160@24Hz; max VGA 1920x1200@60Hz.	
<b>Audio</b>	Via multi-function port: Mic-in, Line-in, Line-out.		Native: Mic-in, Line-in, Line-out.	
<b>Power input</b>	Nominal input 24V DC (12-26V). Also accepts Dell AC adapter, 130W with locking plug.		Nominal input 24V DC (12-26V). Also accepts Dell AC adapter, 180W with locking plug.	
<b>Accessories/ Ecosystem</b>	Wall mounting kit. DIN Rail Mounting kit. Antenna options for 2-Port Wifi, 2-Port LTE or 4-in-1 LTE/Wifi. 7-in-1 cable for multi-function port cable (for I/O connections to 1 x RS-232/422 serial, 12-bit GPIO, Mic-in, line-in, line-out, PS/2 mouse, PS/2 keyboard).		Wall mounting kit. Antenna options for 2-Port Wifi, 2-Port LTE or 4-in-1 LTE/Wifi.	
<b>Environmental/ Design</b>	Temp without airflow	Operating: 0°C to 50°C with SSD, 0°C to 40°C with HDD Non-Operating: -40°C to 65°C (-40°F to 149°F)		
	Temp with 0.7 m/s airflow	Operating: 0°C to 60°C with SSD		
	Relative Humidity	Operating: 10% to 90% (non-condensing) @ 40°C Non-operating: 5% to 95% (non-condensing) @ 40°C		
	Vibration During Operation	ASTM-D4169-04, Random Operational Vibration, 0.52grms MIL-STD-810G, Method 514.7, Procedure 2 MIL-STD-810G, Method 514.6, Procedure 1, Cat 4		
	Thermal Shock	-40°C to 65°C 150 cycles 20°C per minute ramp		

	Shock	Non-Operating: MIL-STD-810G, Method 514.7, Procedure 5 (Shock) - 75G Operating: MIL-STD-810G, Method 514.7, Procedure 1 (Shock) - 40G
	EMC	CE,FCC, VCCI and BSMI
	Safety	AS/NZS 60950.1:2011_A1:2013, CSA C22.2 No.61010-1 +CSA C22.2 No. 61010-2-201, EN60950-1:2006+A1+A2+A11+A12, EN62311:2008, EN61010-1:2010 ed3+ EN61010-2-201:2013, SASO GSO IEC6090-1:2012, CNS14336-1, UL61010-1+UL61010-2-201
	Altitude	Operating: –15.20 m to 5000 m (–50 ft. to 16,404 ft.) Non-Operating: –15.20 m to 10,668 m (sea level to 35,000 ft.)
	Ingress Protection	IP30, IEC 60529
<b>Security</b>	Trusted Platform Module (TPM) v2.0 capable for Windows 10 OS; TPM v1.2 for Win7 and Ubuntu OS. Secure Boot, BIOS password and I/O port disablement.	
<b>Manageability</b>	Available Microsoft® SCCM integration (on Windows platforms) and remote cloud management option via Dell Edge Device Manager. All options are purchased as separate submissions.	
<b>Software</b>	Support for third-party software solutions, including offerings from our curated IoT technical partners (software, sensors, platforms, etc.) – more information at Dell IoT Solutions Partner Program web site <a href="http://www.delliotpartners.com">http://www.delliotpartners.com</a>	
<b>Data integration and analytics</b>	Embedded Box PC 3000 and 5000 Series can support a wide variety of third-party solutions, including offerings from our qualified ISV partners ( <a href="http://www.delliotpartners.com">www.delliotpartners.com</a> ).	
<b>Warranty</b>	Commercial services vary. Limited hardware warranty <sup>3</sup> with mail in service; Optional ProSupport with <b>on-site service</b> <sup>4</sup> after remote diagnosis, contracts up to 5 years. <b>Custom warranties available.</b> Restrictions apply.	
<b>Configuration Services</b>	Image load, BIOS customization, Laser Etching, Asset tagging and reporting. <b>Custom configuration services available.</b> Restrictions apply. <sup>5</sup>	
<b>OEM/Co-branding</b>	OEM-Ready version available: from bezel to BIOS to packaging, your system can look and feel as if they were designed and built by you. For more information, visit <a href="http://Dell.com/OEM">Dell.com/OEM</a> .	

Visit online for more information: [dell.com/embedded](http://dell.com/embedded)

1. Terms subject to product availability, credit approval, execution of documentation provided by and acceptable to DFS.

2. Some configurations may enable power protection management in your operating environments above 35°C.

3. For copy of Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 7882 or see [www.dell.com/warranty](http://www.dell.com/warranty)

4. Onsite Service after Remote Diagnosis: Remote Diagnosis is determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by Limited Hardware Warranty ([www.dell.com/warranty](http://www.dell.com/warranty)) and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.

5. Dell Services: availability and terms of Dell Services vary by region. For more information visit [dell.com/servicesdescriptions](http://dell.com/servicesdescriptions).





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.