


# Wirewound Resistors, Precision Power, Surface Mount



## FEATURES

- All welded construction
- Molded encapsulation
- Wraparound terminations
- Excellent stability at different environmental conditions
- High power ratings (up to 3 W)
- Superior surge capability
- Available in non-inductive styles with Ayrton-Perry winding (WSN in lieu of WSC, maximum resistance is one-half WSC range)
- AEC-Q200 qualified available <sup>(1)</sup>
- Compliant to RoHS Directive 2002/95/EC

### Note

<sup>(1)</sup> Flame retardance test may not be applicable to some resistor technologies.

**AUTOMOTIVE  
GRADE**  
Available



Available



**RoHS\***  
COMPLIANT

**GREEN**  
[5-2008]\*\*  
Available

## STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL MODEL | HISTORICAL MODEL | SIZE | POWER RATING $P_{70^{\circ}\text{C}}$<br>W | RESISTANCE RANGE<br>$\Omega$ | TOLERANCE<br>$\pm \%$               | WEIGHT (typical)<br>g/1000 pieces | ENCAPSULATION                |
|--------------|------------------|------|--------------------------------------------|------------------------------|-------------------------------------|-----------------------------------|------------------------------|
| WSC01/2      | WSC-1/2          | 2012 | 0.5                                        | 0.1 to 4.99                  | 0.5, 1, 5                           | 90                                | Epoxy                        |
| WSC0001      | WSC-1            | 2515 | 1                                          | 0.1 to 2.77K                 | 0.5, 1, 5                           | 165                               | Thermoplastic <sup>(3)</sup> |
| WSC2515      | WSC2515          | 2515 | 1                                          | 0.1 to 2.5K                  | 0.1, 0.25, 0.5, 1, 5 <sup>(2)</sup> | 165                               | Thermoplastic                |
| WSC0002      | WSC-2            | 4527 | 2                                          | 0.1 to 4.92K                 | 0.5, 1, 5                           | 760                               | Thermoplastic <sup>(3)</sup> |
| WSC4527      | WSC4527          | 4527 | 2                                          | 0.1 to 4.92K                 | 0.5, 1, 5                           | 760                               | Thermoplastic                |
| WSC6927      | WSC6927          | 6927 | 3                                          | 0.1 to 8K                    | 0.5, 1, 5                           | 1675                              | Thermoplastic                |

### Notes

• Part marking: 1/2 W - DALE, value; 1 W - model, value, tolerance, date code; 2 W and 3 W - DALE, model, value, tolerance, date code.

<sup>(2)</sup> 0.1 % and 0.25 % is available on the WSC2515 for 0.499  $\Omega$  to 2.5 k $\Omega$  range.

<sup>(3)</sup> As of 1/1/2010, the WSC0001 and WSC0002 are molded with thermoplastic in lieu of epoxy. Reference PCN-DR-002-2009 and PCN-DR-003-2009

## TECHNICAL SPECIFICATIONS

| PARAMETER                       | UNIT            | WSC01/2                                           | WSC0001                                                                        | WSC2515                                                                                                    | WSC0002                                                                      | WSC4527/WSC6927                                                                                        |
|---------------------------------|-----------------|---------------------------------------------------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Temperature Coefficient         | ppm/°C          | ± 50 = 1.0 Ω to 4.99 Ω;<br>± 90 = 0.1 Ω to 0.99 Ω | ± 20 = 26.51 Ω and above;<br>± 50 = 1.0 Ω to 26.5 Ω;<br>± 90 = 0.1 Ω to 0.99 Ω | ± 20 = 26.51 Ω and above;<br>± 50 = 1.0 Ω to 26.5 Ω;<br>± 90 = 0.31 Ω to 0.99 Ω;<br>± 150 = 0.1 Ω to 0.3 Ω | ± 20 = 10.0 Ω and above;<br>± 50 = 1.0 Ω to 9.9 Ω;<br>± 90 = 0.1 Ω to 0.99 Ω | ± 20 = 10 Ω and above;<br>± 50 = 1.0 Ω to 9.9 Ω;<br>± 90 = 0.31 Ω to 0.99 Ω;<br>± 150 = 0.1 Ω to 0.3 Ω |
| Dielectric Withstanding Voltage | V <sub>AC</sub> | > 500                                             |                                                                                |                                                                                                            |                                                                              |                                                                                                        |
| Insulation Resistance           | Ω               | > 10 <sup>9</sup>                                 |                                                                                |                                                                                                            |                                                                              |                                                                                                        |
| Operating Temperature Range     | °C              | - 65 to + 175                                     | - 65 to + 275                                                                  |                                                                                                            |                                                                              |                                                                                                        |
| Maximum Working Voltage         | V               | (P x R) <sup>1/2</sup>                            |                                                                                |                                                                                                            |                                                                              |                                                                                                        |

## GLOBAL PART NUMBER INFORMATION

Global Part Numbering example: WSC2515R7000FEA

|              |   |                                              |   |                                                                 |   |                                                                                                                                                    |   |                                                                                                                            |   |   |   |                                                                    |   |   |  |  |
|--------------|---|----------------------------------------------|---|-----------------------------------------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------|---|----------------------------------------------------------------------------------------------------------------------------|---|---|---|--------------------------------------------------------------------|---|---|--|--|
| W            | S | C                                            | 2 | 5                                                               | 1 | 5                                                                                                                                                  | R | 7                                                                                                                          | 0 | 0 | 0 | F                                                                  | E | A |  |  |
| GLOBAL MODEL |   | SIZE                                         |   | VALUE                                                           |   | TOLERANCE                                                                                                                                          |   | PACKAGING                                                                                                                  |   |   |   | SPECIAL                                                            |   |   |  |  |
| WSC<br>WSN   |   | 01/2<br>0001<br>2515<br>0002<br>4527<br>6927 |   | R = Decimal<br>K = Thousand<br>R7000 = 0.70 Ω<br>1K500 = 1.5 kΩ |   | B = ± 0.1 % <sup>(4)</sup><br>C = ± 0.25 % <sup>(4)</sup><br>D = ± 0.5 %<br>F = ± 1.0 %<br>G = ± 2.0 %<br>H = ± 3.0 %<br>J = ± 5.0 %<br>K = ± 10 % |   | EA = Lead (Pb)-free, tape/reel<br>EK = Lead (Pb)-free, bulk<br>TA = Tin/lead, tape/reel (R86)<br>BA = Tin/lead, bulk (B43) |   |   |   | (Dash number)<br>(Up to 2 digits)<br>From 1 to 99<br>as applicable |   |   |  |  |

Historical Part Numbering example: WSC-1 0.7  $\Omega$  1 % R86


|                  |                  |           |           |
|------------------|------------------|-----------|-----------|
| WSC-1            | 0.7 $\Omega$     | 1 %       | R86       |
| HISTORICAL MODEL | RESISTANCE VALUE | TOLERANCE | PACKAGING |

### Note



<sup>(4)</sup> WSC2515 only

\* Pb containing terminations are not RoHS compliant, exemptions may apply

\*\* Please see document "Vishay Material Category Policy": [www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)

**DIMENSIONS** in inches (millimeters)

| GLOBAL MODEL | DIMENSIONS                       |                                 |                                 |                                 |                                 | SOLDER PAD DIMENSIONS |              |               |
|--------------|----------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|-----------------------|--------------|---------------|
|              | L                                | H                               | T                               | W                               | W <sub>1</sub>                  | A                     | B            | L             |
| WSC01/2      | 0.200 ± 0.020<br>(5.08 ± 0.508)  | 0.096 ± 0.015<br>(2.44 ± 0.381) | 0.040 ± 0.010<br>(1.02 ± 0.254) | 0.125 ± 0.005<br>(3.18 ± 0.127) | 0.050 ± 0.010<br>(1.27 ± 0.254) | 0.085 (2.16)          | 0.070 (1.78) | 0.080 (2.03)  |
| WSC0001      | 0.250 ± 0.020<br>(6.35 ± 0.508)  | 0.110 ± 0.015<br>(2.79 ± 0.381) | 0.045 ± 0.010<br>(1.14 ± 0.254) | 0.150 ± 0.005<br>(3.81 ± 0.127) | 0.098 ± 0.005<br>(2.49 ± 0.127) | 0.090 (2.29)          | 0.115 (2.92) | 0.115 (2.92)  |
| WSC2515      | 0.250 ± 0.020<br>(6.35 ± 0.508)  | 0.110 ± 0.015<br>(2.79 ± 0.381) | 0.045 ± 0.010<br>(1.14 ± 0.254) | 0.150 ± 0.005<br>(3.81 ± 0.127) | 0.098 ± 0.005<br>(2.49 ± 0.127) | 0.090 (2.29)          | 0.115 (2.92) | 0.120 (3.05)  |
| WSC0002      | 0.455 ± 0.020<br>(11.56 ± 0.508) | 0.167 ± 0.010<br>(4.24 ± 0.254) | 0.100 ± 0.010<br>(2.54 ± 0.254) | 0.275 ± 0.005<br>(6.98 ± 0.127) | 0.215 ± 0.005<br>(5.46 ± 0.127) | 0.155 (3.94)          | 0.230 (5.84) | 0.205 (5.21)  |
| WSC4527      | 0.455 ± 0.020<br>(11.56 ± 0.508) | 0.167 ± 0.010<br>(4.24 ± 0.254) | 0.100 ± 0.010<br>(2.54 ± 0.254) | 0.275 ± 0.005<br>(6.98 ± 0.127) | 0.215 ± 0.005<br>(5.46 ± 0.127) | 0.155 (3.94)          | 0.230 (5.84) | 0.205 (5.21)  |
| WSC6927      | 0.690 ± 0.032<br>(17.53 ± 0.813) | 0.280 ± 0.015<br>(7.11 ± 0.381) | 0.100 ± 0.010<br>(2.54 ± 0.254) | 0.275 ± 0.005<br>(6.98 ± 0.127) | 0.215 ± 0.015<br>(5.46 ± 0.381) | 0.155 (3.94)          | 0.235 (5.97) | 0.470 (11.94) |

**TEMPERATURE RISE****DERATING****Note**

(1) As of 1/1/2010, WSC0001 and WSC0002 will be molded with thermoplastic and have the higher 275 °C temperature derating.

**PERFORMANCE**

| TEST                      | CONDITIONS OF TEST                                           | TEST LIMITS           |
|---------------------------|--------------------------------------------------------------|-----------------------|
| Thermal Shock             | - 55 °C to + 150 °C, 1000 cycles, 15 min at each extreme     | ± (0.5 % + 0.05 Ω) ΔR |
| Short Time Overload       | 5 x rated power for 5 s                                      | ± (0.2 % + 0.05 Ω) ΔR |
| Low Temperature Storage   | - 65 °C for 24 h                                             | ± (0.2 % + 0.05 Ω) ΔR |
| High Temperature Exposure | 1000 h at + 275 °C (+ 175 °C for WSC01/2)                    | ± (0.5 % + 0.05 Ω) ΔR |
| Bias Humidity             | + 85 °C, 85 % RH, 10 % bias, 1000 h                          | ± (0.2 % + 0.05 Ω) ΔR |
| Mechanical Shock          | 100 g's for 11 ms, 5 pulses                                  | ± (0.1 % + 0.05 Ω) ΔR |
| Vibration                 | Frequency varied 10 Hz to 500 Hz in 1 min, 3 directions, 9 h | ± (0.1 % + 0.05 Ω) ΔR |
| Load Life                 | 1000 h at rated power, + 70 °C, 1.5 h "ON", 0.5 h "OFF"      | ± (1.0 % + 0.05 Ω) ΔR |
| Resistance to Solder Heat | + 260 °C solder, 10 s to 12 s dwell, 25 mm/s emergence       | ± (0.5 % + 0.05 Ω) ΔR |

**PACKAGING**

| MODEL           | REEL                   |            |             |       |
|-----------------|------------------------|------------|-------------|-------|
|                 | TAPE WIDTH             | DIAMETER   | PIECES/REEL | CODE  |
| WSC01/2         | 12 mm/embossed plastic | 330 mm/13" | 2000        | EA/TA |
| WSC0001/WSC2515 | 16 mm/embossed plastic | 330 mm/13" | 2000        | EA/TA |
| WSC0002/WSC4527 | 24 mm/embossed plastic | 330 mm/13" | 1200        | EA/TA |
| WSC6927         | 32 mm/embossed plastic | 330 mm/13" | 725         | EA/TA |

**Note**

- Embossed Carrier Tape per EIA-481.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.