


SMT POWER INDUCTORS

Shielded Drum Core - P1167 Series



-  **Height:** 4.8mm Max
-  **Footprint:** 7.5mm x 7.5mm Max
-  **Current Rating:** up to 3.5A
-  **Inductance Range:** 1.8μH to 750μH

Electrical Specifications @ 25°C — Operating Temperature -40°C to +130°C


Part Number	Inductance @ 0Aoc (μH ±20%)	Inductance @ Irated (μH) MIN	Irated ⁵ (Aoc)	DCR (mΩ)		Saturation Current ⁶ -25% (A)	Heating Current ⁷ +40°C (A)	Core Loss Factor ⁸ (K2)	SRF (MHz)
				TYP	MAX				
P1167.272	2.7*	1.8	3.5	13	16	3.5	3.6	590	>40
P1167.362	3.6*	2.3	3.1	15	20	3.1	3.4	690	>40
P1167.452	4.5*	2.9	2.6	25	30	2.9	2.6	770	>40
P1167.542	5.4*	3.5	2.5	27	33	2.7	2.5	840	>40
P1167.632	6.3*	4.1	2.4	30	35	2.5	2.4	900	36
P1167.103	10	7.5	2.0	42	50	2.1	2.0	1100	26
P1167.123	12	9.0	1.9	46	57	1.9	1.9	1200	24
P1167.153	15	11.3	1.7	53	66	1.7	1.8	1300	20
P1167.183	18	13.5	1.5	59	73	1.5	1.7	1400	18
P1167.223	22	16.5	1.4	87	105	1.4	1.4	1700	17
P1167.273	27	20.3	1.2	100	130	1.2	1.3	1800	15
P1167.333	33	24.8	1.1	139	170	1.1	1.1	2000	13
P1167.393	39	29.3	1.0	156	200	1.0	1.0	2200	12
P1167.473	47	35.3	0.94	173	220	0.94	1.0	2400	10
P1167.563	56	42	0.86	225	270	0.86	0.86	2600	9.2
P1167.683	68	51	0.78	251	310	0.78	0.81	2900	8.8
P1167.823	82	61.5	0.7	282	350	0.7	0.77	3200	8.0
P1167.104	100	75	0.63	317	390	0.63	0.72	3500	6.2
P1167.124	120	90	0.57	418	530	0.57	0.63	3900	6.1
P1167.154	150	113	0.52	497	610	0.52	0.58	4300	5.6
P1167.184	180	135	0.47	635	820	0.47	0.51	4800	4.5
P1167.224	220	165	0.43	745	930	0.43	0.47	5200	4.3
P1167.274	270	203	0.39	840	1040	0.39	0.44	5700	3.8
P1167.334	330	248	0.35	1162	1470	0.35	0.38	6400	3.0
P1167.394	390	293	0.32	1237	1570	0.32	0.37	6900	2.8
P1167.474	470	353	0.29	1688	2180	0.29	0.31	7600	2.6
P1167.564	560	420	0.26	2240	2960	0.26	0.27	8300	2.4
P1167.684	680	510	0.23	2402	3180	0.23	0.26	9300	2.1
P1167.824	820	615	0.21	2702	3500	0.21	0.25	10000	2.0
P1167.105	1000	750	0.19	3703	4930	0.19	0.21	11000	1.8

*Inductance at 0Aoc tolerance on indicated part numbers is ±30%; tolerance is ±20% on all other parts.

NOTES FROM TABLE: (See page 43)

Mechanical

Schematic



Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0.25}$

SMT POWER INDUCTORS

Shielded Drum Core Series



Notes from Tables (pages 27 - 42)

1. Unless otherwise specified, all testing is made at 100kHz, 0.1VAC.
2. Optional Tape & Reel packaging can be ordered by adding a "T" suffix to the part number (i.e. P1166.102 becomes P1166.102T). Pulse complies with industry standard Tape and Tape & Reel specification EIA481.
3. To order RoHS compliant part, add the suffix "NL" to the part number (i.e. P1166.102 becomes P1166.102NL and P1166.102T becomes P1166.102NLT).
4. Temperature of the component (ambient plus temperature rise) must be within specified operating temperature range.
5. The rated current (I_{rated}) as listed is either the saturation current or the heating current depending on which value is lower.
6. The saturation current, I_{sat} , is the current at which the component inductance drops by the indicated percentage (typical) at an ambient temperature of 25°C. This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effects) to the component.
7. The heating current, I_{dc} , is the DC current required to raise the component temperature by the indicated delta (approximately). The heating current is determined by mounting the component on a typical PCB and applying current for 30 minutes. The temperature is measured by placing the thermocouple on top of the unit under test.

8. In high volt*time (Et) or ripple current applications, additional heating in the component can occur due to core losses in the inductor which may necessitate derating the current in order to limit the temperature rise of the component. In order to determine the approximate total loss (or temperature rise) for a given application, both copper losses and core losses should be taken into account.

Estimated Temperature Rise:

$$T_{rise} = [Total\ loss\ (mW) / K0]^{.833}\ (^{\circ}C)$$

$$Total\ loss = Copper\ loss + Core\ loss\ (mW)$$

$$Copper\ loss = I_{RMS}^2 \times DCR\ (Typical)\ (mW)$$

$$I_{rms} = [I_{DC}^2 + \Delta I^2/12]^{1/2}\ (A)$$

$$Core\ loss = K1 \times f\ (kHz)^{1.23} \times B_{ac}(Ga)^{2.38}\ (mW)$$


$$B_{ac}\ (peak\ to\ peak\ flux\ density) = K2 \times \Delta I\ (Ga)$$

$$[= K2/L(\mu H) \times Et(V\text{-}\mu Sec)\ (Ga)]$$

where f varies between 25kHz and 1MHz, and B_{ac} is less than 2500 Gauss.

$K2$ is a core size and winding dependant value and is given for each p/n in the proceeding datasheets. $K0$ & $K1$ are platform and material dependant constants and are given in the table below for each platform.

Part No.	Trise Factor (K0)	Core Loss Factor (K1)
PG0085/86	2.3	5.29E-10
PG0087	5.8	15.2E-10
PG0040/41	0.8	2.80E-10
P1174	0.8	6.47E-10
PF0601	4.6	14.0E-10
PF0464	3.6	24.7E-10
PF0465	3.6	33.4E-10
P1166	1.9	29.6E-10
P1167	2.1	42.2E-10
PF0560NL	5.5	136E-10
P1168/69	4.8	184E-10
P1170/71	4.3	201E-10
P1172/73	5.6	411E-10
PF0552NL	8.3	201E-10
PF0553NL	7.1	411E-10



Take note that the component's temperature rise varies depending on the system condition. It is suggested that the component be tested at the system level, to verify the temperature rise of the component during system operation.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.