

STRADA

The most versatile modular product family especially designed for street lighting, but also suitable for wide range of other applications

STRADA is LEDiL's most comprehensive product family with a wide variety of different beams suitable for both outdoor and indoor lighting. The standardized modules are available in 2X2 and 2X6 layouts as well as in two different single formats. 2X2MX features a standardized 90 x 90 mm footprint. The latest addition to the product family includes silicone versions for increased durability and thermal resistance. Being especially designed for street lighting they provide highly efficient and uniform lighting.


STRADA-IP-2X6

173 x 71.4 mm ingress protected 2X6 arrays with a silicone gasket for up to 5050 size LED packages



PRODUCTS:


CS16401_STRADA-IP-2X6-PX



Dimensions: 173.0 mm x 71.4 mm
Height: 9.60 mm

Double asymmetric beam designed to highlight pedestrian crossings for right side traffic


CS15020_STRADA-IP-2X6-VSM



Dimensions: 173.0 mm x 71.4 mm
Height: 8.00 mm

IESNA Type V (square) beam for wide area lighting such as car parks

CS15887_STRADA-IP-2X6-T3-B-90




Dimensions: 71.4 mm x 173.0 mm
Height: 12.75 mm

IESNA Type III (medium) beam with minimized backlight. Variant with beam direction rotated 90°.

PRODUCTS:


CS14144_STRADA-IP-2X6-ME



Dimensions: 71.4 mm x 173.0 mm
Height: 8.42 mm

Beam with excellent longitudinal luminance uniformity fulfilling EN13201 M-class requirements where road width is equal to or less than the pole height


CS15871_STRADA-IP-2X6-T3-L



Dimensions: 173.0 mm x 71.4 mm
Height: 13.00 mm

IESNA Type III Medium beam for long pole distances and up to 8x mounting height. Suitable for European P-class and pathway lighting


CS14055_STRADA-IP-2X6-T2



Dimensions: 71.4 mm x 173.0 mm
Height: 9.17 mm

IESNA Type II (medium) beam applicable for European P-class standard pedestrian lighting and M-class roads


CS15689_STRADA-IP-2X6-FW



Dimensions: 173.0 mm x 71.4 mm
Height: 12.40 mm

Beam with wide light distribution and good illuminance uniformity for residential street lighting and staggered pole setups


CS12862_STRADA-IP-2X6-DWC



Dimensions: 173.0 mm x 71.4 mm
Height: 9.00 mm

Universal road lighting (IESNA Type II medium) beam with excellent mixed illuminance and luminance uniformity.

CS15418_STRADA-IP-2X6-SCL




Dimensions: 173.0 mm x 71.4 mm
Height: 9.60 mm

Type II/III (long) beam for very wide pole to pole distances. Ideal for pedestrian walkways and residential road lighting. (EN13201 P-classes)

PRODUCTS:


CS15362_STRADA-IP-2X6-T3-B



Dimensions: 71.4 mm x 173.0 mm
Height: 12.75 mm

IESNA Type III (medium) beam with minimized backlighting


CS15158_STRADA-IP-2X6-T4-B



Dimensions: 71.4 mm x 173.0 mm
Height: 10.57 mm

Wide IESNA Type IV beam with forward-throw beam for wide area lighting like car parks


CS17259_STRADA-IP-2X6-T4-B-PC



Dimensions: 71.4 mm x 173.0 mm
Height: 10.57 mm

Wide IESNA Type IV beam with forward-throw beam for wide area lighting like car parks. Variant made from PC.


CS15068_STRADA-IP-2X6-T3-PC



Dimensions: 71.4 mm x 173.0 mm
Height: 8.50 mm

IESNA Type III (medium) beam for roads that are equal to or wider than mounting height. Variant made from PC.


CS17082_STRADA-IP-2X6-VSM-PC



Dimensions: 173.0 mm x 71.4 mm
Height: 8.00 mm

IESNA Type V (square) beam for wide area lighting such as car parks. Variant made from PC.

CS15055_STRADA-IP-2X6-DWC-90-PC




Dimensions: 173.0 mm x 71.4 mm
Height: 9.00 mm

Universal road lighting (typically IESNA Type III medium) beam with excellent mixed illuminance and luminance uniformity. Variant with beam direction rotated 90°. Variant made from PC.

PRODUCTS:


CS16397_STRADA-IP-2X6-T2-C-90-PC



Dimensions: 173.0 mm x 71.4 mm
Height: 9.00 mm

IESNA Type II (medium) beam with added house side backlight. Designed for tilted and long armatures. Variant with beam direction rotated 90°. Variant made from PC.


CS14145_STRADA-IP-2X6-DWC-90



Dimensions: 71.4 mm x 173.0 mm
Height: 8.98 mm

Universal road lighting (typically IESNA Type III medium) beam with excellent mixed illuminance and luminance uniformity. Variant with beam direction rotated 90°.


CS15886_STRADA-IP-2X6-T2-B-90



Dimensions: 71.4 mm x 173.0 mm
Height: 12.10 mm

IESNA Type II (medium) beam with minimized house side backlight. Variant with beam direction rotated 90°.


CS14143_STRADA-IP-2X6-T3



Dimensions: 71.4 mm x 173.0 mm
Height: 8.50 mm

IESNA Type III (medium) beam for roads that are equal to or wider than mounting height


CS15870_STRADA-IP-2X6-T2-L



Dimensions: 173.0 mm x 71.4 mm
Height: 13.00 mm

IESNA Type II Medium beam for long pole distances and up to 8x mounting height. Suitable for European P-class and pathway lighting.

CS13756_STRADA-IP-2X6-DWC-PC




Dimensions: 173.0 mm x 71.4 mm
Height: 7.92 mm

Universal road lighting (IESNA Type II medium) beam with excellent mixed illuminance and luminance uniformity. Variant made from PC.

PRODUCTS:


CS15671_STRADA-IP-2X6-DWC-B



Dimensions: 173.0 mm x 71.4 mm
Height: 8.90 mm

Universal road lighting (IESNA Type II Medium) beam with excellent mixed illuminance, luminance uniformity and minimized backlight.


CS15363_STRADA-IP-2X6-T2-B



Dimensions: 71.4 mm x 173.0 mm
Height: 12.03 mm

IESNA Type II (medium) beam with minimized house side backlight.


CS15223_STRADA-IP-2X6-T2-C-90



Dimensions: 173.0 mm x 71.4 mm
Height: 9.25 mm

IESNA Type II (medium) beam with added house side backlight. Designed for tilted and long armatures. Variant with beam direction rotated 90°.


CS17307_STRADA-IP-2X6-T2-B-PC



Dimensions: 71.4 mm x 173.0 mm
Height: 12.03 mm

IESNA Type II (medium) beam with minimized house side backlight. Variant made from PC.

CS15071_STRADA-IP-2X6-ME-PC



Dimensions: 71.4 mm x 173.0 mm
Height: 8.42 mm

Beam with excellent longitudinal luminance uniformity fulfilling EN13201 M-class requirements where road width is equal to or less than the pole height. Variant made from PC.

CS17255_STRADA-IP-2X6-T3-L-PC




Dimensions: 173.0 mm x 71.4 mm
Height: 13.00 mm

IESNA Type III Medium beam for long pole distances and up to 8x mounting height. Suitable for European P-class and pathway lighting. Variant made from PC.

PRODUCTS:

CS15066_STRADA-IP-2X6-T2-PC



Dimensions: 71.4 mm x 173.0 mm

Height: 9.17 mm

IESNA Type II (medium) beam applicable
for European P-class standard
pedestrian lighting and M-class roads.

Variant made from PC.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.