VAOL-3MWY4
3mm (T-1) Thru-hole LED Superbright LED Lamp

VAOL3 Series consists of T-1 (3mm) thru-hole LEDs with high intensity light output

Application

- Commercial Outdoor Sign Board
- LED Bulb
- Front Panel Indicator
- Electrical Panels
- Dot-Matrix Module
- Appliances

Key Features

- Low Power Consumption
- High Intensity LEDs are Based on InGaN/Sapphire Material Technology
- Emitted color: White
- Water Transparent Lens
- Available with clear and diffused lens, flanged and flangeless, multiple viewing angles
- Conflict Mineral Free
- Compliant with RoHS and REACH requirements

Package Dimension

All dimensions in inches/mm



*Tolerance: $\frac{0.01}{0.25}$

Product Specifications

Absolute Maximum Ratings at Ta= 25°C

Symbol	Parameter	Max	Unit
PD	Power Dissipation	120	mW
VR	Reverse Voltage	5	V
IAF	Average Forward Current	30	mA
IPF	Peak Forward Current (Duty=0.1 , 1kHz)	100	mA
-	Derating Linear Form 25°C	0.4	mA/°C
Topr	Operating Temperature Range	-40 to +80	°C
Tstg	Storage Temperature Range	-40 to +100	°C
Lead Soldering Temperature [1.6mm (0.063inch) From Body] 260°C For 5 Seconds.			

Electrical / Optical Characteristics and Curves at Ta= 25°C

Symbol	Parameter	Test Condition	Min	Typ.	Max	Unit
VF	Forward Voltage	IF=20mA		3.5	4.0	V
IR	Reverse Current	VR=5V			50	μA
Δθ	Half Intensity Angle	IF= 20mA		60		Deg
IV	Luminous Intensity	IF= 20mA		2500		mcd.
X	Chromaticity	IF= 20mA		0.31		
Y	Coordination	IF= 20mA		0.31		

Product Specifications

Electrical Characteristics at Ta= 25°C

Symbol	Iv		V_F		λD	
Parameter	Luminous Intensity		Forward Voltage		Dominant Wavelength	
Condition	IF=20mA		IF= 20mA		IF= 20mA	
Unit	mcd		V		nm	
Binning	Grade	Range	Grade	Range	Grade	Range
	BIN18	1800~2500	P1	3.0~3.2	WA	Bluish White
	BIN19	2500~3500	P2	3.2~3.4	WB	Pure White
	BIN20	3500~4900	P3	3.4~3.6	WC	White
	BIN21	4900~6900	P4	3.6~3.8	WD	Yellowish White
	BIN22	6900~9700	P5	3.8~4.0		

Intensity: Tolerance of minimum and maximum = ± 15%
Vf: Tolerance of minimum and maximum = ± 0.05v

Note:
1. Static electricity and surge damages the LED. It is recommend to use a anti-static wrist band or anti-electrostatic glove when handing the LEDs. All devices, equipment and machinery must be properly grounded.
2. Specific binning requirements- please contact our home office

Radiation Diagram

IF=20 mA 50% Power Angle Angle =60



Product Specifications

White - Typical Electro-optical Characteristic Curves
(25°C Free Air Temperature Unless Otherwise Specified)













Compliances and Approvals

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.