

FLIR Exx-Series™

Advanced Thermal Imaging Cameras for Electrical and Mechanical Applications



reddot award 2017
best of the best



Find problems quickly and eliminate costly plant shutdowns



Streamlined data collection and sharing speeds analysis and repairs



One-handed operation with convenient buttons helps maintain workplace safety

FLIR E75, E85, and E95 cameras offer the superior resolution and range performance needed to quickly identify hot spots and discover potential points of failure in electrical distribution and mechanical systems. With up to 161,472 pixel resolution and a larger, more vibrant LCD screen than any other pistol-grip thermal camera, the Exx-Series makes it easier than ever to diagnose problems – even at a distance. Avoid costly shutdowns and lost production time through regular predictive maintenance routines with these rugged, intuitive cameras.

Improve Plant Reliability

Equipment failures are costly and can impact on-time delivery, so it's important to have the right tools to find potential problems before they happen.

- High-resolution infrared detectors, up to 464 x 348, for crisp, detailed images
- Wide temperature ranges: -40°C to 120°C, 0°C to 650°C, 300°C up to 1500°C (E95)
- Superior spot-size performance for accurate temperature measurements on smaller, more distant targets
- Laser-assisted autofocus for precise identification of hot spots, even in cluttered scenes

Increase Plant Safety

The Exx-Series improves plant safety by helping you diagnose and report electrical problems before they result in fire or damage.

- Detect temperature differences down to 30 mK for immediate identification of failing components
- Interchangeable lenses, from wide angle to telephoto, offer complete coverage of near and far targets
- Lenses auto-calibrate with camera for the most precise temperature readings
- MSX® image enhancement adds the depth and detail to image

Designed to Make Your Work Easier

FLIR designed the E75, E85, and E95 to make your work faster, safer, and more efficient.

- Rapid-response touch screen with intuitive new user interface
- Convenient menu buttons allow for one-handed operation
- New folder and naming structure that makes finding images easier
- Connect over Wi-Fi to mobile devices or via METERLiNK® to FLIR clamps and multimeters

Key Features:

- 320 x 240 – 464 x 348 true native resolution
- Laser-assisted autofocus
- Wide temperature ranges, up to 1500°C
- Vibrant, 4" optically-bonded PCAP touchscreen with 160° viewing angle
- Wi-Fi, METERLiNK® connectivity
- Streamlined reporting features
- FLIR's industry-leading 2-5-10 warranty

Specifications

Features By Camera	E75	E85	E95
IR Resolution	320 x 240	384 x 288	464 x 348
Object Temperature Range	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) Optional 300°C to 1000°C (572°F to 1830°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) 300°C to 1200°C (572°F to 2192°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) 300°C to 1500°C (572°F to 2732°F)
Time-lapse (Infrared)	No	No	10 sec to 24 hours
Measurement Features by Camera			
Area Measurement Information	No	Yes	Yes
Spotmeter	1 in live mode	3 in live mode	3 in live mode
Area	No	3 in live mode	3 in live mode
Common Features	Exx-Series		
Detector Type and Pitch	Uncooled microbolometer, 17 µm		
Thermal Sensitivity/NETD	< 0.03°C @ 30°C (86°F)		
Spectral Range	7.5 - 14.0 µm		
Image Frequency	30 Hz		
Field of View (FOV)	24° x 18° (17 mm lens), 42° x 32° (10 mm lens), 14° x 10° (29 mm lens)		
F-Number	f/1.3, f/1.1		
Lens Identification	Automatic		
Focus	Continuous, one-shot laser distance meter (LDM), one-shot contrast, manual		
Digital Zoom	1-4x continuous		
Image Presentation and Modes			
Display	4", 640 x 480 optically-bonded PCAP touchscreen, with 400 cd/m² surface brightness		
Digital Camera	5 MP, 53° x 41° FOV		
Color Palettes	Iron, Gray, Rainbow, Arctic, Lava, Rainbow HC		
Image Modes	Infrared, visual, MSX®, Picture-in-Picture		
Picture-in-Picture	Resizable and movable		
MSX®	Embosses visual details on full resolution thermal image		
UltraMax™	Super-resolution process quadruples pixel count, activated in FLIR Tools+		
Measurement and Analysis			
Accuracy	±2°C (±3.6°F) or ±2% of reading for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)		
Alarms	Moisture alarm, insulation alarm, measurement alarms		
Color Alarm (Isotherm)	Above/below/interval/condensation/insulation		
Laser Distance Measurement	Yes, on-screen		
Measurement Presets	No measurement, center spot, hot spot, cold spot, User Preset 1, User Preset 2		
Compass, GPS	Yes; automatic GPS image tagging		
METERLiNK®	Yes; several readings		
Image Storage			
Storage Media	Removable SD card (8 GB)		
Image File Format	Standard radiometric JPEG, measurement data included		
Video Recording and Streaming			
Radiometric IR Video Recording	Real-time radiometric recording (.csq)		
Non-Radiometric IR or Visual Video	H.264 to memory card		
Radiometric IR Video Streaming	Yes, over UVC or Wi-Fi		
Non-Radiometric IR Video Streaming	H.264 or MPEG-4 over Wi-Fi MJPEG over UVC or Wi-Fi		
Communication Interfaces	USB 2.0, Bluetooth, Wi-Fi		
Video Out	DisplayPort over USB Type-C		
Additional Data			
Battery Type	Li-ion battery, charged in camera or on separate charger		
Battery Operating Time	Approx. 2.5 hours at 25°C (77°F) ambient temperature and typical use		
Operating Temperature Range	-15°C to 50°C (5°F to 122°F)		
Storage Temperature Range	-40°C to 70°C (-40°F to 158°F)		
Shock/Vibration/Encapsulation; Safety	25 g / IEC 60068-2-27, 2 g / IEC 60068-2-6, IP 54 / IEC 60529; EN/UL/CSA/PSE 60950-1		
Weight/Dimensions w/o Lens	1 kg (2.2 lbs), 27.8 x 11.6 x 11.3 cm (11.0 x 4.6 x 4.4 in)		
Box Contents			
Packaging	Infrared camera with lens, battery (2 ea), battery charger with power supply, front lens and light protection, straps (hand and wrist), lanyards, lens caps (front and rear), lens cleaning cloth, 15 W3 A power supply, printed documentation, 8 GB SD card, Torx screwdriver, cables (USB 2.0 A to USB Type-C, USB Type-C to HDMI, USB Type-C to USB Type-C)		

Specifications are subject to change without notice.

For the most up-to-date specs, go to www.support.flir.com

PORTLAND
Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 866.477.3687

NASHUA
FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
PH: +1 866.477.3687

CANADA
FLIR Systems, Ltd.
920 Sheldon Court
Burlington, ON L7L 5K6
Canada
PH: +1 800.613.0507

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella,
320 Srocaba,
SP 18085-852
Brasil
PH: +55 15 3238 7080

CHINA
FLIR Systems Co., Ltd
Rm 1613-16, Tower II
Grand Central Plaza 1
38 Shatin Rural
Committee Rd.
Shatin, New Territories
Hong Kong
PH: +852 2792 8955

BELGIUM
FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

UNITED KINGDOM
FLIR Systems UK
2 Kings Hill Ave., Kings Hill
West Malling, Kent
ME19 4AQ
United Kingdom
PH +44 (0)1732 220 011
www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. [01/17] 16-1455



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.