


# Shielded Power Inductors – LPS4414



- Very low DCR; excellent current handling
- 4.4 × 4.4 mm footprint; only 1.4 mm tall

**Designer's Kit C340** contains 3 of each values

**Core material** Ferrite

**Core and winding loss** See [www.coilcraft.com/coreloss](http://www.coilcraft.com/coreloss)

**Environmental** RoHS compliant, halogen free

**Terminations** RoHS compliant matte tin over nickel over silver.  
Other terminations available at additional cost.

**Weight** 82.3 – 89.8 mg

**Ambient temperature** –40°C to +85°C with Irms current, +85°C to +125°C with derated current

**Storage temperature** Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**Packaging** 1000/7" reel; 3500/13" reel Plastic tape: 12 mm wide, 0.3 mm thick, 8 mm pocket spacing, 1.52 mm pocket depth

**Recommended pick and place nozzle:** OD: 4.5 mm; ID: ≤2 mm

**PCB washing** Tested with pure water or alcohol only. For other solvents, see [Doc787\\_PCB\\_Washing.pdf](#).

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>±20% (μH) | DCR<br>max <sup>3</sup><br>(Ohms) | SRF<br>typ <sup>4</sup><br>(MHz) | Isat (A) <sup>5</sup> |             |             | Irms (A) <sup>6</sup> |              |
|--------------------------|--------------------------------------|-----------------------------------|----------------------------------|-----------------------|-------------|-------------|-----------------------|--------------|
|                          |                                      |                                   |                                  | 10%<br>drop           | 20%<br>drop | 30%<br>drop | 20°C<br>rise          | 40°C<br>rise |
| LPS4414-301MR_           | 0.30                                 | 0.040                             | 470                              | 5.6                   | 5.7         | 5.8         | 2.35                  | 3.25         |
| LPS4414-501MR_           | 0.50                                 | 0.050                             | 330                              | 4.3                   | 4.4         | 4.5         | 2.10                  | 2.80         |
| LPS4414-701MR_           | 0.70                                 | 0.055                             | 225                              | 3.7                   | 3.75        | 3.8         | 1.85                  | 2.50         |
| LPS4414-102MR_           | 1.0                                  | 0.060                             | 190                              | 3.0                   | 3.1         | 3.2         | 1.75                  | 2.30         |
| LPS4414-152MR_           | 1.5                                  | 0.078                             | 150                              | 2.9                   | 3.1         | 3.2         | 1.55                  | 2.00         |
| LPS4414-182MR_           | 1.8                                  | 0.087                             | 130                              | 2.7                   | 2.8         | 2.9         | 1.50                  | 1.90         |
| LPS4414-222MR_           | 2.2                                  | 0.110                             | 115                              | 2.2                   | 2.3         | 2.35        | 1.25                  | 1.60         |
| LPS4414-332MR_           | 3.3                                  | 0.165                             | 85.0                             | 1.8                   | 1.9         | 1.95        | 1.15                  | 1.50         |
| LPS4414-472MR_           | 4.7                                  | 0.215                             | 68.0                             | 1.4                   | 1.5         | 1.55        | 0.90                  | 1.20         |
| LPS4414-562MR_           | 5.6                                  | 0.260                             | 58.0                             | 1.4                   | 1.4         | 1.5         | 0.75                  | 1.10         |
| LPS4414-682MR_           | 6.8                                  | 0.270                             | 54.0                             | 1.2                   | 1.3         | 1.4         | 0.70                  | 1.00         |
| LPS4414-822MR_           | 8.2                                  | 0.350                             | 50.0                             | 1.1                   | 1.3         | 1.3         | 0.70                  | 0.98         |
| LPS4414-103MR_           | 10                                   | 0.380                             | 43.0                             | 1.1                   | 1.2         | 1.3         | 0.70                  | 0.95         |
| LPS4414-123MR_           | 12                                   | 0.380                             | 38.0                             | 0.94                  | 0.97        | 1.0         | 0.66                  | 0.88         |
| LPS4414-153MR_           | 15                                   | 0.440                             | 36.0                             | 0.85                  | 0.89        | 0.92        | 0.63                  | 0.82         |
| LPS4414-183MR_           | 18                                   | 0.530                             | 31.0                             | 0.76                  | 0.80        | 0.82        | 0.56                  | 0.75         |
| LPS4414-223MR_           | 22                                   | 0.590                             | 27.0                             | 0.69                  | 0.72        | 0.74        | 0.53                  | 0.68         |
| LPS4414-333MR_           | 33                                   | 0.715                             | 23.0                             | 0.47                  | 0.49        | 0.51        | 0.49                  | 0.65         |
| LPS4414-473MR_           | 47                                   | 0.935                             | 18.0                             | 0.39                  | 0.42        | 0.43        | 0.44                  | 0.58         |
| LPS4414-563MR_           | 56                                   | 1.15                              | 16.0                             | 0.37                  | 0.39        | 0.40        | 0.42                  | 0.54         |
| LPS4414-683MR_           | 68                                   | 1.35                              | 14.6                             | 0.32                  | 0.33        | 0.34        | 0.36                  | 0.48         |
| LPS4414-104MR_           | 100                                  | 1.90                              | 11.0                             | 0.26                  | 0.28        | 0.285       | 0.31                  | 0.40         |
| LPS4414-124MR_           | 120                                  | 2.60                              | 10.0                             | 0.23                  | 0.24        | 0.25        | 0.27                  | 0.34         |
| LPS4414-154MR_           | 150                                  | 3.10                              | 9.0                              | 0.22                  | 0.23        | 0.24        | 0.24                  | 0.32         |
| LPS4414-224MR_           | 220                                  | 4.10                              | 6.7                              | 0.18                  | 0.20        | 0.20        | 0.22                  | 0.29         |
| LPS4414-334MR_           | 330                                  | 6.00                              | 5.6                              | 0.14                  | 0.16        | 0.165       | 0.17                  | 0.23         |
| LPS4414-474MR_           | 470                                  | 9.50                              | 4.3                              | 0.13                  | 0.14        | 0.145       | 0.14                  | 0.23         |
| LPS4414-564MR_           | 560                                  | 10.7                              | 4.0                              | 0.12                  | 0.13        | 0.14        | 0.13                  | 0.17         |
| LPS4414-684MR_           | 680                                  | 11.7                              | 3.5                              | 0.10                  | 0.11        | 0.12        | 0.13                  | 0.17         |
| LPS4414-824MR_           | 820                                  | 15.1                              | 3.0                              | 0.10                  | 0.105       | 0.11        | 0.11                  | 0.14         |
| LPS4414-105MR_           | 1000                                 | 16.3                              | 2.6                              | 0.10                  | 0.102       | 0.106       | 0.10                  | 0.13         |

1. Please specify **termination** and **packaging** codes:

**LPS4414-223MRC**

**Termination:** R= RoHS compliant matte tin over nickel over silver.

Special order, added cost:

**Q** = RoHS tin-silver-copper (95.5/4/0.5)  
or **P** = non-RoHS tin-lead (63/37).

**Packaging:** C= 7" machine-ready reel. EIA-481 embossed plastic tape (1000 parts per full reel).

**B**= Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

**D**= 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (3500 parts per full reel).

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc.

3. DCR measured on a micro-ohmmeter.

4. SRF measured using Agilent/HP 8753ES or equivalent.

5. DC current at which the inductance drops the specified amount from its value without current.

6. Current that causes the specified temperature rise from 25°C ambient.

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)

**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)

**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)

**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)

**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 548-1 Revised 08/01/13


© Coilcraft Inc. 2014

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.




# Shielded Power Inductors – LPS4414 Series


## Typical L vs Current



## Typical L vs Frequency





## Current Derating



**Packaging** 1000/7" reel; 3500/13" reel Plastic tape: 12 mm wide, 0.3 mm thick, 8 mm pocket spacing, 1.52 mm pocket depth

**NOTE NEW PART ORIENTATION** Parts are rotated 90° in the packaging tape compared to previous versions of this product.



\* Dimensions are of the case not including the termination. For maximum overall dimensions including the termination, add 0.005 in / 0.13 mm.

For optional tin-lead and tin-silver-copper terminations, dimensions are for the mounted part. Dimensions before mounting can be an additional 0.005 inch / 0.13 mm).

Dimensions are in  $\frac{\text{inches}}{\text{mm}}$



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com  
 UK +44-1236-730595 sales@coilcraft-europe.com  
 Taiwan +886-2-2264 3646 sales@coilcraft.com.tw  
 China +86-21-6218 8074 sales@coilcraft.com.cn  
 Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 548-2 Revised 08/01/13

© Coilcraft Inc. 2014

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.